

SAMSUNG

FJM

Technical Data Book

**Free Joint Multi for America
Capacity Table**



Model : Outdoor unit: JXH**S** (AJ****XS*CH/AA)

History

Version	Modification	Date	Remark
Ver.1.0	Released FJM Capacity for America (Low Ambi. 60Hz, HP) TDB	21.10.07	
Ver.1.1	Modified the unit error	21.12.31	
Ver.1.2	Modified the Ducted Capacity Table	22.06.03	
Ver.1.3	Modified the Ducted/Non Ducted Capacity Table	23.01.16	
Ver.1.4	Released 2023 FJM Capacity Table	23.09.26	

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Cooling (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9		18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18	
				70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20	
				73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22	
				77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25	
				81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28	
				84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31	
				88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34	
				91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37	
				95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40	
				99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44	
				102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47	
				108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52	
				111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56	
				115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59	
9	12		21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37	
				70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42	
				77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45	
				81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48	
				84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52	
				88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55	
				91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59	
				95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62	
				99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66	
				102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70	
				108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76	
				111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80	
				115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84	
12	12		24	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37	
				70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42	
				77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45	
				81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48	
				84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52	
				88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55	
				91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59	
				95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62	
				99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66	
				102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70	
				108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76	
				111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80	
				115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84	

Capacity Table

JXH20S3C (AJ020CXS3CH/AA)

Cooling (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9		27	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
					111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80
					115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 27.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0***BNHDCH/AA or ACO***BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7		14	68	12.37	0.91	15.27	0.93	15.72	0.95	15.98	0.96	16.89	0.98	17.61	1.00	
				70	12.37	0.92	15.08	0.94	15.54	0.96	15.81	0.97	16.74	0.99	17.47	1.01	
				73	12.37	0.94	14.71	0.96	15.20	0.98	15.48	0.99	16.44	1.02	17.20	1.03	
				77	12.37	0.97	14.37	0.99	14.88	1.01	15.17	1.01	16.17	1.04	16.95	1.06	
				81	12.37	0.99	14.04	1.01	14.57	1.03	14.87	1.04	15.91	1.07	16.72	1.08	
				84	12.37	1.02	13.73	1.04	14.29	1.05	14.60	1.06	15.67	1.09	16.50	1.11	
				88	12.37	1.04	13.44	1.06	14.02	1.08	14.35	1.09	15.46	1.12	16.31	1.13	
				91	12.37	1.07	13.17	1.09	13.77	1.11	14.11	1.12	15.26	1.14	16.14	1.16	
				95	12.37	1.10	12.92	1.12	13.55	1.13	14.00	1.14	15.08	1.17	15.98	1.19	
				99	12.37	1.12	12.68	1.14	13.34	1.16	13.70	1.17	14.92	1.20	15.85	1.21	
				102	12.37	1.15	12.47	1.17	13.15	1.19	13.53	1.20	14.78	1.22	15.73	1.24	
				108	12.37	1.20	12.19	1.21	12.91	1.23	13.30	1.24	14.61	1.27	15.59	1.28	
				111	12.37	1.23	12.03	1.24	12.77	1.26	13.17	1.27	14.52	1.30	15.53	1.31	
				115	12.37	1.26	11.88	1.27	12.65	1.29	13.06	1.30	14.45	1.33	15.48	1.34	
7	9		16	68	14.14	1.00	17.45	1.02	17.97	1.04	18.27	1.05	19.31	1.08	20.13	1.10	
				70	14.14	1.01	17.24	1.03	17.77	1.05	18.07	1.06	19.13	1.09	19.97	1.11	
				73	14.14	1.03	16.82	1.06	17.37	1.08	17.69	1.09	18.79	1.12	19.66	1.13	
				77	14.14	1.06	16.42	1.08	17.00	1.10	17.33	1.11	18.48	1.14	19.37	1.16	
				81	14.14	1.09	16.04	1.11	16.65	1.13	17.00	1.14	18.18	1.17	19.10	1.19	
				84	14.14	1.11	15.69	1.14	16.33	1.16	16.69	1.17	17.91	1.20	18.86	1.21	
				88	14.14	1.14	15.36	1.16	16.02	1.18	16.40	1.19	17.67	1.22	18.64	1.24	
				91	14.14	1.17	15.05	1.19	15.74	1.21	16.13	1.22	17.44	1.25	18.44	1.27	
				95	14.14	1.20	14.76	1.22	15.48	1.24	16.00	1.25	17.23	1.28	18.26	1.30	
				99	14.14	1.23	14.50	1.25	15.25	1.27	15.66	1.28	17.05	1.31	18.11	1.33	
				102	14.14	1.26	14.25	1.28	15.03	1.30	15.46	1.31	16.89	1.34	17.98	1.36	
				108	14.14	1.31	13.93	1.33	14.75	1.35	15.20	1.36	16.70	1.39	17.82	1.41	
				111	14.14	1.34	13.74	1.36	14.59	1.38	15.05	1.39	16.59	1.42	17.74	1.44	
				115	14.14	1.38	13.58	1.40	14.45	1.42	14.93	1.43	16.51	1.46	17.69	1.47	
7	12		19	68	16.79	1.16	20.73	1.19	21.34	1.21	21.69	1.22	22.93	1.26	23.90	1.28	
				70	16.79	1.18	20.47	1.20	21.10	1.23	21.46	1.24	22.72	1.27	23.71	1.30	
				73	16.79	1.21	19.97	1.23	20.63	1.26	21.01	1.27	22.32	1.30	23.34	1.32	
				77	16.79	1.24	19.50	1.26	20.19	1.29	20.58	1.30	21.94	1.33	23.00	1.36	
				81	16.79	1.27	19.05	1.29	19.78	1.32	20.19	1.33	21.59	1.36	22.69	1.39	
				84	16.79	1.30	18.63	1.33	19.39	1.35	19.81	1.36	21.27	1.40	22.40	1.42	
				88	16.79	1.33	18.24	1.36	19.03	1.38	19.47	1.40	20.98	1.43	22.13	1.45	
				91	16.79	1.37	17.87	1.39	18.69	1.42	19.15	1.43	20.71	1.46	21.90	1.48	
				95	16.79	1.40	17.53	1.43	18.39	1.45	19.00	1.46	20.47	1.50	21.69	1.52	
				99	16.79	1.44	17.21	1.46	18.10	1.49	18.60	1.50	20.25	1.53	21.51	1.55	
				102	16.79	1.48	16.93	1.50	17.85	1.52	18.36	1.53	20.06	1.57	21.35	1.59	
				108	16.79	1.53	16.54	1.56	17.52	1.58	18.05	1.59	19.83	1.62	21.16	1.64	
				111	16.79	1.57	16.32	1.59	17.33	1.62	17.88	1.63	19.70	1.66	21.07	1.68	
				115	16.79	1.61	16.13	1.63	17.16	1.66	17.73	1.67	19.61	1.70	21.01	1.72	

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15			22	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	24.40	1.32	25.34	1.35
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	24.15	1.34	25.11	1.36
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	23.67	1.37	24.67	1.39
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	23.22	1.40	24.25	1.42
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	22.80	1.43	23.87	1.46
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	22.40	1.47	23.51	1.49
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	22.04	1.50	23.19	1.53
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	21.71	1.54	22.89	1.56
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	21.40	1.58	22.62	1.60
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	21.13	1.61	22.38	1.64
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	20.88	1.65	22.17	1.68
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	20.57	1.71	21.91	1.73
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80					
115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84					

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15			24	68	18.56	1.10	26.18	1.12	26.67	1.15	26.97	1.16	27.30	1.18	28.07	1.20
					70	18.56	1.12	25.47	1.15	26.00	1.18	26.31	1.19	26.66	1.20	27.46	1.23
					73	18.56	1.15	24.78	1.18	25.35	1.21	25.69	1.22	26.05	1.23	26.89	1.26
					77	18.56	1.18	24.13	1.21	24.73	1.23	25.09	1.25	25.47	1.26	26.34	1.29
					81	18.56	1.21	23.50	1.24	24.15	1.26	24.52	1.28	24.92	1.29	25.83	1.31
					84	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	24.40	1.32	25.34	1.35
					88	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	24.15	1.34	25.11	1.36
					91	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	23.67	1.37	24.67	1.39
					95	18.56	1.32	21.55	1.35	22.32	1.38	21.00	1.56	23.22	1.40	24.25	1.42
					99	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	22.80	1.43	23.87	1.46
					102	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	22.40	1.47	23.51	1.49
					108	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	22.04	1.50	23.19	1.53
12	12			24	111	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	21.71	1.54	22.89	1.56
					115	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	21.40	1.58	22.62	1.60
					68	18.56	12.42	22.91	12.69	23.59	12.95	23.97	13.08	25.34	13.45	26.42	13.69
					70	18.56	12.58	22.62	12.85	23.32	13.11	23.71	13.24	25.11	13.61	26.21	13.84
					73	18.56	12.90	22.07	13.17	22.80	13.43	23.22	13.55	24.67	13.92	25.80	14.16
					77	18.56	13.23	21.55	13.49	22.32	13.75	22.75	13.88	24.25	14.25	25.42	14.48
					81	18.56	13.56	21.05	13.83	21.86	14.09	22.31	14.22	23.87	14.58	25.07	14.81
					84	18.56	13.91	20.59	14.18	21.43	14.43	21.90	14.56	23.51	14.92	24.75	15.15
					88	18.56	14.26	20.16	14.53	21.03	14.79	21.52	14.91	23.19	15.27	24.46	15.50
					91	18.56	14.62	19.75	14.89	20.66	15.15	21.17	15.27	22.89	15.63	24.20	15.86
					95	18.56	14.99	19.37	15.26	20.32	15.51	21.00	15.60	22.62	16.00	23.97	16.22
					99	18.56	15.37	19.03	15.64	20.01	15.89	20.55	16.01	22.38	16.37	23.77	16.60
12	15			27	102	18.56	15.76	18.71	16.02	19.73	16.28	20.29	16.40	22.17	16.75	23.60	16.98
					108	18.56	16.36	18.28	16.62	19.36	16.87	19.95	16.99	21.91	17.34	23.39	17.57
					111	18.56	16.76	18.04	17.02	19.15	17.27	19.76	17.40	21.78	17.75	23.29	17.97
					115	18.56	17.18	17.82	17.44	18.97	17.69	19.60	17.81	21.67	18.16	23.22	18.38
					68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	24.40	1.32	25.34	1.35
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	24.15	1.34	25.11	1.36
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	23.67	1.37	24.67	1.39
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	23.22	1.40	24.25	1.42
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	22.80	1.43	23.87	1.46
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	22.40	1.47	23.51	1.49
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	22.04	1.50	23.19	1.53
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	21.71	1.54	22.89	1.56

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7		21	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23
					70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24
					73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27
					77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30
					81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33
					84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36
					88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39
					91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42
					95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46
					99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49
					102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52
					108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58
7	7	9		23	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23
					70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24
					73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27
					77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30
					81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33
					84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36
					88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39
					91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42
					95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46
					99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49
					102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52
					108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58
7	7	12		26	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23
					70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24
					73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27
					77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30
					81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33
					84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36
					88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39
					91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42
					95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46
					99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49
					102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52
					108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58
111	18.56	1.50	18.04	1.53	19.15	1.55	19.76	1.56	21.78	1.59	23.29	1.61					
115	18.56	1.54	17.82	1.57	18.97	1.59	19.60	1.60	21.67	1.63	23.22	1.65					

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	25	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23	
				70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24	
				73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27	
				77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30	
				81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33	
				84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36	
				88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39	
				91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42	
				95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46	
				99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49	
				102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52	
				108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58	
				111	18.56	1.50	18.04	1.53	19.15	1.55	19.76	1.56	21.78	1.59	23.29	1.61	
				115	18.56	1.54	17.82	1.57	18.97	1.59	19.60	1.60	21.67	1.63	23.22	1.65	
9	9	9	27	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23	
				70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24	
				73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27	
				77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30	
				81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33	
				84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36	
				88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39	
				91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42	
				95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46	
				99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49	
				102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52	
				108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58	
				111	18.56	1.50	18.04	1.53	19.15	1.55	19.76	1.56	21.78	1.59	23.29	1.61	
				115	18.56	1.54	17.82	1.57	18.97	1.59	19.60	1.60	21.67	1.63	23.22	1.65	

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 27.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Heating (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		70.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	-13	24.54	6.86	20.52	5.44	19.69	5.52	15.24	4.02	13.51	3.35	9.63	2.17
					5	23.84	4.62	23.27	4.67	22.69	4.74	21.80	4.92	21.55	4.84	20.98	4.88
					17	23.23	4.00	22.83	4.04	22.43	4.08	21.80	4.23	21.63	4.17	21.22	4.21
					32	23.04	2.97	22.69	3.00	22.34	3.03	21.80	3.14	21.65	3.08	21.30	3.11
					47	23.10	2.09	22.83	2.11	22.53	2.13	21.80	2.21	21.92	2.17	21.62	2.19
					50	25.08	2.22	24.47	2.25	24.01	2.28	23.79	2.30	23.22	2.34	22.89	2.36
					59	27.46	2.31	26.94	2.34	26.45	2.38	26.23	2.39	25.62	2.43	25.26	2.45
9	12			21	-13	24.76	6.92	20.71	5.49	19.87	5.57	15.38	4.05	13.64	3.38	9.72	2.19
					5	24.06	4.67	23.48	4.71	22.90	4.78	22.00	4.96	21.75	4.88	21.17	4.93
					17	23.44	4.04	23.04	4.08	22.63	4.12	22.00	4.27	21.83	4.21	21.42	4.25
					32	23.25	3.00	22.90	3.03	22.55	3.06	22.00	3.17	21.85	3.11	21.49	3.14
					47	23.32	2.11	23.04	2.13	22.74	2.15	22.00	2.23	22.12	2.19	21.82	2.21
					50	25.31	2.24	24.69	2.27	24.23	2.30	24.01	2.32	23.43	2.36	23.10	2.38
					59	27.72	2.33	27.18	2.37	26.69	2.40	26.47	2.41	25.85	2.45	25.50	2.48
12	12			24	-13	24.76	6.92	20.71	5.49	19.87	5.57	15.38	4.05	13.64	3.38	9.72	2.19
					5	24.06	4.67	23.48	4.71	22.90	4.78	22.00	4.96	21.75	4.88	21.17	4.93
					17	23.44	4.04	23.04	4.08	22.63	4.12	22.00	4.27	21.83	4.21	21.42	4.25
					32	23.25	3.00	22.90	3.03	22.55	3.06	22.00	3.17	21.85	3.11	21.49	3.14
					47	23.32	2.11	23.04	2.13	22.74	2.15	22.00	2.23	22.12	2.19	21.82	2.21
					50	25.31	2.24	24.69	2.27	24.23	2.30	24.01	2.32	23.43	2.36	23.10	2.38
					59	27.72	2.33	27.18	2.37	26.69	2.40	26.47	2.41	25.85	2.45	25.50	2.48
9	9	9		27	-13	17.64	3.06	16.83	3.08	16.35	3.12	15.38	3.16	14.90	3.20	13.94	3.20
					5	23.76	3.74	23.25	3.78	22.58	3.83	22.00	3.87	21.50	3.91	21.09	3.94
					17	23.43	3.21	23.01	3.25	22.47	3.29	22.00	3.33	21.59	3.36	21.23	3.39
					32	23.33	2.38	22.93	2.41	22.44	2.44	22.00	2.47	21.61	2.50	21.28	2.52
					47	23.24	1.68	22.86	1.70	22.41	1.72	22.00	1.74	21.64	1.76	21.32	1.77
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 27.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)														
						57.2		60.8		64.4		69.98		71.6		75.2				
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)			
7	7		14	-13	16.88	3.91	14.12	3.10	13.55	3.15	10.49	2.29	9.30	1.91	6.63	1.24				
				5	16.40	2.64	16.01	2.66	15.61	2.70	15.00	2.80	14.83	2.76	14.43	2.78				
				17	15.98	2.28	15.71	2.30	15.43	2.33	15.00	2.41	14.88	2.38	14.60	2.40				
				32	15.85	1.70	15.62	1.71	15.37	1.73	15.00	1.79	14.90	1.76	14.66	1.77				
				47	15.90	1.19	15.71	1.20	15.50	1.21	15.00	1.26	15.08	1.23	14.87	1.25				
				50	17.26	1.27	16.84	1.29	16.52	1.30	16.37	1.31	15.97	1.33	15.75	1.34				
				59	18.90	1.32	18.53	1.34	18.20	1.35	18.05	1.36	17.63	1.39	17.38	1.40				
				7	9		16	-13	20.71	4.75	17.32	3.77	16.62	3.82	12.87	2.78	11.41	2.32	8.13	1.50
								5	20.12	3.20	19.64	3.23	19.15	3.28	18.40	3.40	18.19	3.35	17.71	3.38
								17	19.61	2.77	19.27	2.80	18.93	2.82	18.40	2.93	18.25	2.89	17.91	2.91
								32	19.45	2.06	19.16	2.08	18.86	2.10	18.40	2.17	18.27	2.14	17.98	2.15
								47	19.50	1.45	19.27	1.46	19.02	1.47	18.40	1.53	18.50	1.50	18.25	1.52
50	21.17	1.54	20.65					1.56	20.26	1.58	20.08	1.59	19.60	1.62	19.32	1.63				
				59	23.18	1.60	22.73	1.62	22.33	1.64	22.14	1.65	21.62	1.68	21.32	1.70				
				7	12		19	-13	24.20	5.19	20.24	4.11	19.42	4.17	15.03	3.04	13.33	2.53	9.50	1.64
								5	23.51	3.49	22.95	3.53	22.38	3.58	21.50	3.72	21.26	3.65	20.69	3.69
								17	22.91	3.02	22.51	3.05	22.12	3.08	21.50	3.20	21.33	3.15	20.93	3.18
								32	22.72	2.25	22.38	2.27	22.04	2.29	21.50	2.37	21.35	2.33	21.01	2.35
								47	22.79	1.58	22.52	1.59	22.22	1.61	21.50	1.67	21.62	1.64	21.32	1.66
50	24.74	1.68	24.13					1.70	23.68	1.73	23.47	1.74	22.90	1.77	22.57	1.78				
				59	27.09	1.75	26.56	1.77	26.09	1.80	25.86	1.81	25.26	1.84	24.92	1.85				
				7	15		22	-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
								5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
								17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
								32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
								47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
50	25.31	1.75	24.69					1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86				
				59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93				
				9	9		18	-13	24.54	5.31	20.52	4.21	19.69	4.27	15.24	3.11	13.51	2.59	9.63	1.68
								5	23.84	3.58	23.27	3.61	22.69	3.66	21.80	3.80	21.55	3.74	20.98	3.78
								17	23.23	3.09	22.83	3.13	22.43	3.16	21.80	3.27	21.63	3.23	21.22	3.26
								32	23.04	2.30	22.69	2.32	22.34	2.34	21.80	2.43	21.65	2.39	21.30	2.41
								47	23.10	1.62	22.83	1.63	22.53	1.65	21.80	1.71	21.92	1.68	21.62	1.69
50	25.08	1.72	24.47					1.74	24.01	1.77	23.79	1.78	23.22	1.81	22.89	1.82				
				59	27.46	1.79	26.94	1.81	26.45	1.84	26.23	1.85	25.62	1.88	25.26	1.90				
				9	12		21	-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
								5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
								17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
								32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
								47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
50	25.31	1.75	24.69					1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86				
				59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93				

Capacity Table

JXH20S3C (AJ020CX53CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15			22	-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
					5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
					17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
					32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
					47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93
					-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
					5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
					17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
					32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
					47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93
					-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
					5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
					17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
					32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
					47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93
					-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
					5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
					17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
					32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
					47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93
					-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
					5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
					17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
					32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
					47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93
					-13	24.76	5.40	20.71	4.28	19.87	4.35	15.38	3.16	13.64	2.64	9.72	1.71
					5	24.06	3.64	23.48	3.68	22.90	3.73	22.00	3.87	21.75	3.81	21.17	3.85
					17	23.44	3.15	23.04	3.18	22.63	3.21	22.00	3.33	21.83	3.28	21.42	3.31
					32	23.25	2.34	22.90	2.36	22.55	2.39	22.00	2.47	21.85	2.43	21.49	2.45
					47	23.32	1.65	23.04	1.66	22.74	1.68	22.00	1.74	22.12	1.71	21.82	1.72
					50	25.31	1.75	24.69	1.77	24.23	1.80	24.01	1.81	23.43	1.84	23.10	1.86
					59	27.72	1.82	27.18	1.85	26.69	1.87	26.47	1.88	25.85	1.91	25.50	1.93
					-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61
					-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61
					-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61
					-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61
					-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61
					-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67

Capacity Table

JXH20S3C (AJ020CXS3CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9		25	-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61
9	9	9		27	-13	17.64	2.55	16.83	2.57	16.35	2.60	15.38	2.64	14.90	2.67	13.94	2.67
					5	23.76	3.12	23.25	3.15	22.58	3.19	22.00	3.23	21.50	3.26	21.09	3.28
					17	23.43	2.68	23.01	2.71	22.47	2.74	22.00	2.78	21.59	2.80	21.23	2.83
					32	23.33	1.99	22.93	2.01	22.44	2.03	22.00	2.06	21.61	2.08	21.28	2.10
					47	23.24	1.40	22.86	1.41	22.41	1.43	22.00	1.45	21.64	1.47	21.32	1.48
					50	25.31	1.46	24.69	1.48	24.23	1.50	24.01	1.51	23.43	1.53	23.10	1.55
					59	27.72	1.52	27.18	1.54	26.69	1.56	26.47	1.57	25.85	1.59	25.50	1.61

- Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).
- Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).
- The above values are based on connection of non-ducted indoor units.
- Capacities are based on the following conditions:
- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)
- The total combination index of connected indoor units is up to 27.
- Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.
Single indoor unit connection is not allowed.
- This reference data is based on temperature and capacity trend.

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
9	15			24	68	21.21	1.36	26.18	1.39	26.96	1.42	27.40	1.43	27.88	1.45	28.96	1.47
					70	21.21	1.38	25.85	1.41	26.65	1.44	27.10	1.45	27.60	1.46	28.70	1.49
					73	21.21	1.41	25.22	1.44	26.06	1.47	26.53	1.49	27.05	1.50	28.19	1.53
					77	21.21	1.45	24.63	1.48	25.50	1.51	26.00	1.52	26.53	1.54	27.72	1.56
					81	21.21	1.49	24.06	1.52	24.98	1.54	25.50	1.56	26.05	1.57	27.28	1.60
					84	21.21	1.52	23.53	1.55	24.49	1.58	25.03	1.60	25.60	1.61	26.87	1.64
					88	21.21	1.56	23.03	1.59	24.04	1.62	24.59	1.63	25.19	1.65	26.50	1.67
					91	21.21	1.60	22.57	1.63	23.61	1.66	24.19	1.67	24.81	1.69	26.16	1.71
					95	21.21	1.64	22.14	1.67	23.22	1.70	24.00	1.71	24.46	1.73	25.85	1.75
					99	21.21	1.69	21.74	1.71	22.87	1.74	23.49	1.76	24.15	1.77	25.58	1.79
					102	21.21	1.73	21.38	1.76	22.55	1.78	23.19	1.80	23.87	1.81	25.34	1.84
					108	21.21	1.79	20.90	1.82	22.13	1.85	22.80	1.86	23.51	1.88	25.04	1.90
111	21.21	1.84	20.62	1.87	21.89	1.89	22.58	1.91	23.31	1.92	24.89	1.95					
115	21.21	1.88	20.37	1.91	21.68	1.94	22.39	1.95	23.15	1.97	24.76	1.99					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	22.09	1.50	27.27	1.53	28.08	1.56	28.54	1.58	30.17	1.62	31.45	1.65
					70	22.09	1.52	26.93	1.55	27.76	1.58	28.23	1.60	29.89	1.64	31.20	1.67
					73	22.09	1.55	26.27	1.59	27.14	1.62	27.64	1.63	29.36	1.68	30.71	1.71
					77	22.09	1.59	25.65	1.63	26.57	1.66	27.08	1.67	28.87	1.72	30.26	1.74
					81	22.09	1.63	25.07	1.67	26.02	1.70	26.56	1.71	28.41	1.76	29.85	1.78
					84	22.09	1.68	24.51	1.71	25.51	1.74	26.07	1.75	27.99	1.80	29.47	1.83
					88	22.09	1.72	23.99	1.75	25.04	1.78	25.62	1.80	27.60	1.84	29.12	1.87
					91	22.09	1.76	23.51	1.79	24.60	1.83	25.20	1.84	27.25	1.88	28.81	1.91
					95	22.09	1.81	23.06	1.84	24.19	1.87	25.00	1.88	26.93	1.93	28.54	1.96
					99	22.09	1.85	22.65	1.88	23.82	1.92	24.47	1.93	26.65	1.97	28.30	2.00
					102	22.09	1.90	22.27	1.93	23.49	1.96	24.15	1.98	26.40	2.02	28.09	2.05
					108	22.09	1.97	21.77	2.00	23.05	2.03	23.75	2.05	26.09	2.09	27.85	2.12
111	22.09	2.02	21.48	2.05	22.80	2.08	23.52	2.10	25.92	2.14	27.73	2.17					
115	22.09	2.07	21.22	2.10	22.58	2.13	23.33	2.15	25.80	2.19	27.64	2.22					
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04					
115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09					
12	15			27	68	22.09	1.50	27.27	1.53	28.08	1.56	28.54	1.58	29.04	1.59	30.17	1.62
					70	22.09	1.52	26.93	1.55	27.76	1.58	28.23	1.60	28.75	1.61	29.89	1.64
					73	22.09	1.55	26.27	1.59	27.14	1.62	27.64	1.63	28.17	1.65	29.36	1.68
					77	22.09	1.59	25.65	1.63	26.57	1.66	27.08	1.67	27.64	1.69	28.87	1.72
					81	22.09	1.63	25.07	1.67	26.02	1.70	26.56	1.71	27.14	1.73	28.41	1.76
					84	22.09	1.68	24.51	1.71	25.51	1.74	26.07	1.75	26.67	1.77	27.99	1.80
					88	22.09	1.72	23.99	1.75	25.04	1.78	25.62	1.80	26.24	1.81	27.60	1.84
					91	22.09	1.76	23.51	1.79	24.60	1.83	25.20	1.84	25.84	1.85	27.25	1.88
					95	22.09	1.81	23.06	1.84	24.19	1.87	25.00	1.88	25.48	1.90	26.93	1.93
					99	22.09	1.85	22.65	1.88	23.82	1.92	24.47	1.93	25.15	1.94	26.65	1.97
					102	22.09	1.90	22.27	1.93	23.49	1.96	24.15	1.98	24.86	1.99	26.40	2.02
					108	22.09	1.97	21.77	2.00	23.05	2.03	23.75	2.05	24.49	2.06	26.09	2.09
111	22.09	2.02	21.48	2.05	22.80	2.08	23.52	2.10	24.28	2.11	25.92	2.14					
115	22.09	2.07	21.22	2.10	22.58	2.13	23.33	2.15	24.11	2.16	25.80	2.19					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	18		30	68	22.09	1.50	27.27	1.53	28.08	1.56	28.54	1.58	30.17	1.62	31.45	1.65	
				70	22.09	1.52	26.93	1.55	27.76	1.58	28.23	1.60	29.89	1.64	31.20	1.67	
				73	22.09	1.55	26.27	1.59	27.14	1.62	27.64	1.63	29.36	1.68	30.71	1.71	
				77	22.09	1.59	25.65	1.63	26.57	1.66	27.08	1.67	28.87	1.72	30.26	1.74	
				81	22.09	1.63	25.07	1.67	26.02	1.70	26.56	1.71	28.41	1.76	29.85	1.78	
				84	22.09	1.68	24.51	1.71	25.51	1.74	26.07	1.75	27.99	1.80	29.47	1.83	
				88	22.09	1.72	23.99	1.75	25.04	1.78	25.62	1.80	27.60	1.84	29.12	1.87	
				91	22.09	1.76	23.51	1.79	24.60	1.83	25.20	1.84	27.25	1.88	28.81	1.91	
				95	22.09	1.81	23.06	1.84	24.19	1.87	25.00	1.88	26.93	1.93	28.54	1.96	
				99	22.09	1.85	22.65	1.88	23.82	1.92	24.47	1.93	26.65	1.97	28.30	2.00	
				102	22.09	1.90	22.27	1.93	23.49	1.96	24.15	1.98	26.40	2.02	28.09	2.05	
				108	22.09	1.97	21.77	2.00	23.05	2.03	23.75	2.05	26.09	2.09	27.85	2.12	
111	22.09	2.02	21.48	2.05	22.80	2.08	23.52	2.10	25.92	2.14	27.73	2.17					
115	22.09	2.07	21.22	2.10	22.58	2.13	23.33	2.15	25.80	2.19	27.64	2.22					
9	9	9	27	68	22.09	1.47	27.27	1.50	28.08	1.54	28.54	1.55	30.17	1.60	31.45	1.62	
				70	22.09	1.49	26.93	1.52	27.76	1.55	28.23	1.57	29.89	1.61	31.20	1.64	
				73	22.09	1.53	26.27	1.56	27.14	1.59	27.64	1.61	29.36	1.65	30.71	1.68	
				77	22.09	1.57	25.65	1.60	26.57	1.63	27.08	1.65	28.87	1.69	30.26	1.72	
				81	22.09	1.61	25.07	1.64	26.02	1.67	26.56	1.69	28.41	1.73	29.85	1.76	
				84	22.09	1.65	24.51	1.68	25.51	1.71	26.07	1.73	27.99	1.77	29.47	1.80	
				88	22.09	1.69	23.99	1.72	25.04	1.75	25.62	1.77	27.60	1.81	29.12	1.84	
				91	22.09	1.73	23.51	1.77	24.60	1.80	25.20	1.81	27.25	1.85	28.81	1.88	
				95	22.09	1.78	23.06	1.81	24.19	1.84	25.00	1.85	26.93	1.90	28.54	1.92	
				99	22.09	1.82	22.65	1.85	23.82	1.88	24.47	1.90	26.65	1.94	28.30	1.97	
				102	22.09	1.87	22.27	1.90	23.49	1.93	24.15	1.94	26.40	1.99	28.09	2.01	
				108	22.09	1.94	21.77	1.97	23.05	2.00	23.75	2.01	26.09	2.06	27.85	2.08	
111	22.09	1.99	21.48	2.02	22.80	2.05	23.52	2.06	25.92	2.10	27.73	2.13					
115	22.09	2.04	21.22	2.07	22.58	2.10	23.33	2.11	25.80	2.15	27.64	2.18					
9	9	12	30	68	22.09	1.47	27.27	1.50	28.08	1.54	28.54	1.55	30.17	1.60	31.45	1.62	
				70	22.09	1.49	26.93	1.52	27.76	1.55	28.23	1.57	29.89	1.61	31.20	1.64	
				73	22.09	1.53	26.27	1.56	27.14	1.59	27.64	1.61	29.36	1.65	30.71	1.68	
				77	22.09	1.57	25.65	1.60	26.57	1.63	27.08	1.65	28.87	1.69	30.26	1.72	
				81	22.09	1.61	25.07	1.64	26.02	1.67	26.56	1.69	28.41	1.73	29.85	1.76	
				84	22.09	1.65	24.51	1.68	25.51	1.71	26.07	1.73	27.99	1.77	29.47	1.80	
				88	22.09	1.69	23.99	1.72	25.04	1.75	25.62	1.77	27.60	1.81	29.12	1.84	
				91	22.09	1.73	23.51	1.77	24.60	1.80	25.20	1.81	27.25	1.85	28.81	1.88	
				95	22.09	1.78	23.06	1.81	24.19	1.84	25.00	1.85	26.93	1.90	28.54	1.92	
				99	22.09	1.82	22.65	1.85	23.82	1.88	24.47	1.90	26.65	1.94	28.30	1.97	
				102	22.09	1.87	22.27	1.90	23.49	1.93	24.15	1.94	26.40	1.99	28.09	2.01	
				108	22.09	1.94	21.77	1.97	23.05	2.00	23.75	2.01	26.09	2.06	27.85	2.08	
111	22.09	1.99	21.48	2.02	22.80	2.05	23.52	2.06	25.92	2.10	27.73	2.13					
115	22.09	2.04	21.22	2.07	22.58	2.10	23.33	2.11	25.80	2.15	27.64	2.18					

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 30.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7			14	68	12.37	0.91	15.27	0.93	15.72	0.95	15.98	0.96	16.89	0.98	17.61	1.00
					70	12.37	0.92	15.08	0.94	15.54	0.96	15.81	0.97	16.74	0.99	17.47	1.01
					73	12.37	0.94	14.71	0.96	15.20	0.98	15.48	0.99	16.44	1.02	17.20	1.03
					77	12.37	0.97	14.37	0.99	14.88	1.01	15.17	1.01	16.17	1.04	16.95	1.06
					81	12.37	0.99	14.04	1.01	14.57	1.03	14.87	1.04	15.91	1.07	16.72	1.08
					84	12.37	1.02	13.73	1.04	14.29	1.05	14.60	1.06	15.67	1.09	16.50	1.11
					88	12.37	1.04	13.44	1.06	14.02	1.08	14.35	1.09	15.46	1.12	16.31	1.13
					91	12.37	1.07	13.17	1.09	13.77	1.11	14.11	1.12	15.26	1.14	16.14	1.16
					95	12.37	1.10	12.92	1.12	13.55	1.13	14.00	1.14	15.08	1.17	15.98	1.19
					99	12.37	1.12	12.68	1.14	13.34	1.16	13.70	1.17	14.92	1.20	15.85	1.21
					102	12.37	1.15	12.47	1.17	13.15	1.19	13.53	1.20	14.78	1.22	15.73	1.24
					108	12.37	1.20	12.19	1.21	12.91	1.23	13.30	1.24	14.61	1.27	15.59	1.28
					111	12.37	1.23	12.03	1.24	12.77	1.26	13.17	1.27	14.52	1.30	15.53	1.31
					115	12.37	1.26	11.88	1.27	12.65	1.29	13.06	1.30	14.45	1.33	15.48	1.34
7	9			16	68	14.14	1.00	17.45	1.02	17.97	1.04	18.27	1.05	19.31	1.08	20.13	1.10
					70	14.14	1.01	17.24	1.03	17.77	1.05	18.07	1.06	19.13	1.09	19.97	1.11
					73	14.14	1.03	16.82	1.06	17.37	1.08	17.69	1.09	18.79	1.12	19.66	1.13
					77	14.14	1.06	16.42	1.08	17.00	1.10	17.33	1.11	18.48	1.14	19.37	1.16
					81	14.14	1.09	16.04	1.11	16.65	1.13	17.00	1.14	18.18	1.17	19.10	1.19
					84	14.14	1.11	15.69	1.14	16.33	1.16	16.69	1.17	17.91	1.20	18.86	1.21
					88	14.14	1.14	15.36	1.16	16.02	1.18	16.40	1.19	17.67	1.22	18.64	1.24
					91	14.14	1.17	15.05	1.19	15.74	1.21	16.13	1.22	17.44	1.25	18.44	1.27
					95	14.14	1.20	14.76	1.22	15.48	1.24	16.00	1.25	17.23	1.28	18.26	1.30
					99	14.14	1.23	14.50	1.25	15.25	1.27	15.66	1.28	17.05	1.31	18.11	1.33
					102	14.14	1.26	14.25	1.28	15.03	1.30	15.46	1.31	16.89	1.34	17.98	1.36
					108	14.14	1.31	13.93	1.33	14.75	1.35	15.20	1.36	16.70	1.39	17.82	1.41
					111	14.14	1.34	13.74	1.36	14.59	1.38	15.05	1.39	16.59	1.42	17.74	1.44
					115	14.14	1.38	13.58	1.40	14.45	1.42	14.93	1.43	16.51	1.46	17.69	1.47
7	12			19	68	16.79	1.16	20.73	1.19	21.34	1.21	21.69	1.22	22.93	1.26	23.90	1.28
					70	16.79	1.18	20.47	1.20	21.10	1.23	21.46	1.24	22.72	1.27	23.71	1.30
					73	16.79	1.21	19.97	1.23	20.63	1.26	21.01	1.27	22.32	1.30	23.34	1.32
					77	16.79	1.24	19.50	1.26	20.19	1.29	20.58	1.30	21.94	1.33	23.00	1.36
					81	16.79	1.27	19.05	1.29	19.78	1.32	20.19	1.33	21.59	1.36	22.69	1.39
					84	16.79	1.30	18.63	1.33	19.39	1.35	19.81	1.36	21.27	1.40	22.40	1.42
					88	16.79	1.33	18.24	1.36	19.03	1.38	19.47	1.40	20.98	1.43	22.13	1.45
					91	16.79	1.37	17.87	1.39	18.69	1.42	19.15	1.43	20.71	1.46	21.90	1.48
					95	16.79	1.40	17.53	1.43	18.39	1.45	19.00	1.46	20.47	1.50	21.69	1.52
					99	16.79	1.44	17.21	1.46	18.10	1.49	18.60	1.50	20.25	1.53	21.51	1.55
					102	16.79	1.48	16.93	1.50	17.85	1.52	18.36	1.53	20.06	1.57	21.35	1.59
					108	16.79	1.53	16.54	1.56	17.52	1.58	18.05	1.59	19.83	1.62	21.16	1.64
					111	16.79	1.57	16.32	1.59	17.33	1.62	17.88	1.63	19.70	1.66	21.07	1.68
					115	16.79	1.61	16.13	1.63	17.16	1.66	17.73	1.67	19.61	1.70	21.01	1.72

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15			22	68	19.44	1.33	24.00	1.36	24.71	1.39	25.12	1.40	25.56	1.41	26.55	1.44
					70	19.44	1.35	23.70	1.38	24.43	1.40	24.84	1.42	25.30	1.43	26.30	1.46
					73	19.44	1.38	23.12	1.41	23.89	1.44	24.32	1.45	24.79	1.46	25.84	1.49
					77	19.44	1.42	22.57	1.44	23.38	1.47	23.83	1.49	24.32	1.50	25.41	1.53
					81	19.44	1.45	22.06	1.48	22.90	1.51	23.37	1.52	23.88	1.54	25.00	1.56
					84	19.44	1.49	21.57	1.52	22.45	1.55	22.94	1.56	23.47	1.57	24.63	1.60
					88	19.44	1.53	21.12	1.56	22.03	1.58	22.54	1.60	23.09	1.61	24.29	1.63
					91	19.44	1.57	20.69	1.59	21.65	1.62	22.18	1.63	22.74	1.65	23.98	1.67
					95	19.44	1.61	20.30	1.63	21.29	1.66	22.00	1.67	22.42	1.69	23.70	1.71
					99	19.44	1.65	19.93	1.67	20.96	1.70	21.53	1.71	22.14	1.73	23.45	1.75
					102	19.44	1.69	19.60	1.72	20.67	1.74	21.26	1.76	21.88	1.77	23.23	1.79
					108	19.44	1.75	19.16	1.78	20.28	1.81	20.90	1.82	21.55	1.83	22.96	1.86
					111	19.44	1.79	18.90	1.82	20.06	1.85	20.70	1.86	21.37	1.88	22.81	1.90
					115	19.44	1.84	18.67	1.87	19.87	1.89	20.53	1.91	21.22	1.92	22.70	1.94
7	18			25	68	21.30	1.43	26.29	1.46	27.07	1.49	27.51	1.51	29.08	1.55	30.32	1.58
					70	21.30	1.45	25.96	1.48	26.76	1.51	27.22	1.53	28.82	1.57	30.07	1.60
					73	21.30	1.49	25.33	1.52	26.17	1.55	26.64	1.56	28.31	1.61	29.61	1.63
					77	21.30	1.53	24.73	1.56	25.61	1.59	26.11	1.60	27.83	1.64	29.17	1.67
					81	21.30	1.56	24.16	1.60	25.08	1.63	25.60	1.64	27.39	1.68	28.77	1.71
					84	21.30	1.60	23.63	1.64	24.59	1.67	25.13	1.68	26.98	1.72	28.41	1.75
					88	21.30	1.65	23.13	1.68	24.14	1.71	24.70	1.72	26.61	1.76	28.08	1.79
					91	21.30	1.69	22.67	1.72	23.71	1.75	24.29	1.76	26.27	1.80	27.78	1.83
					95	21.30	1.73	22.23	1.76	23.32	1.79	24.10	1.80	25.96	1.85	27.51	1.87
					99	21.30	1.77	21.83	1.80	22.96	1.83	23.59	1.85	25.69	1.89	27.28	1.91
					102	21.30	1.82	21.47	1.85	22.64	1.88	23.28	1.89	25.45	1.93	27.08	1.96
					108	21.30	1.89	20.98	1.92	22.22	1.95	22.89	1.96	25.15	2.00	26.84	2.03
					111	21.30	1.93	20.70	1.96	21.98	1.99	22.67	2.01	24.99	2.05	26.73	2.07
					115	21.30	1.98	20.45	2.01	21.77	2.04	22.49	2.05	24.87	2.10	26.65	2.12
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
					111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56
					115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59

Capacity Table

JXH24S4C (AJ024CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
					111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80
					115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84
9	15			24	68	21.21	1.24	29.92	1.27	30.49	1.31	30.83	1.32	31.20	1.33	32.08	1.36
					70	21.21	1.27	29.10	1.31	29.71	1.34	30.07	1.35	30.47	1.37	31.39	1.39
					73	21.21	1.31	28.32	1.34	28.97	1.37	29.36	1.38	29.78	1.40	30.73	1.43
					77	21.21	1.34	27.58	1.37	28.27	1.40	28.67	1.42	29.11	1.43	30.11	1.46
					81	21.21	1.37	26.86	1.40	27.59	1.43	28.02	1.45	28.48	1.46	29.52	1.49
					84	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	27.88	1.50	28.96	1.53
					88	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	27.60	1.52	28.70	1.54
					91	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	27.05	1.55	28.19	1.58
					95	21.21	1.50	24.63	1.53	25.50	1.56	24.00	1.77	26.53	1.59	27.72	1.62
					99	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	26.05	1.63	27.28	1.65
					102	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	25.60	1.67	26.87	1.69
					108	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	25.19	1.71	26.50	1.73
					111	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	24.81	1.75	26.16	1.77
					115	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	24.46	1.79	25.85	1.81
9	18			27	68	22.09	1.55	27.27	1.59	28.08	1.62	28.54	1.64	30.17	1.68	31.45	1.71
					70	22.09	1.57	26.93	1.61	27.76	1.64	28.23	1.65	29.89	1.70	31.20	1.73
					73	22.09	1.61	26.27	1.65	27.14	1.68	27.64	1.69	29.36	1.74	30.71	1.77
					77	22.09	1.65	25.65	1.69	26.57	1.72	27.08	1.74	28.87	1.78	30.26	1.81
					81	22.09	1.70	25.07	1.73	26.02	1.76	26.56	1.78	28.41	1.82	29.85	1.85
					84	22.09	1.74	24.51	1.77	25.51	1.80	26.07	1.82	27.99	1.87	29.47	1.89
					88	22.09	1.78	23.99	1.82	25.04	1.85	25.62	1.86	27.60	1.91	29.12	1.94
					91	22.09	1.83	23.51	1.86	24.60	1.89	25.20	1.91	27.25	1.95	28.81	1.98
					95	22.09	1.87	23.06	1.91	24.19	1.94	25.00	1.95	26.93	2.00	28.54	2.03
					99	22.09	1.92	22.65	1.95	23.82	1.99	24.47	2.00	26.65	2.05	28.30	2.07
					102	22.09	1.97	22.27	2.00	23.49	2.03	24.15	2.05	26.40	2.09	28.09	2.12
					108	22.09	2.04	21.77	2.08	23.05	2.11	23.75	2.12	26.09	2.17	27.85	2.20
					111	22.09	2.10	21.48	2.13	22.80	2.16	23.52	2.17	25.92	2.22	27.73	2.25
					115	22.09	2.15	21.22	2.18	22.58	2.21	23.33	2.23	25.80	2.27	27.64	2.30

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04					
115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09					
12	15			27	68	22.09	1.55	27.27	1.59	28.08	1.62	28.54	1.64	29.04	1.65	30.17	1.68
					70	22.09	1.57	26.93	1.61	27.76	1.64	28.23	1.65	28.75	1.67	29.89	1.70
					73	22.09	1.61	26.27	1.65	27.14	1.68	27.64	1.69	28.17	1.71	29.36	1.74
					77	22.09	1.65	25.65	1.69	26.57	1.72	27.08	1.74	27.64	1.75	28.87	1.78
					81	22.09	1.70	25.07	1.73	26.02	1.76	26.56	1.78	27.14	1.79	28.41	1.82
					84	22.09	1.74	24.51	1.77	25.51	1.80	26.07	1.82	26.67	1.84	27.99	1.87
					88	22.09	1.78	23.99	1.82	25.04	1.85	25.62	1.86	26.24	1.88	27.60	1.91
					91	22.09	1.83	23.51	1.86	24.60	1.89	25.20	1.91	25.84	1.92	27.25	1.95
					95	22.09	1.87	23.06	1.91	24.19	1.94	25.00	1.95	25.48	1.97	26.93	2.00
					99	22.09	1.92	22.65	1.95	23.82	1.99	24.47	2.00	25.15	2.02	26.65	2.05
					102	22.09	1.97	22.27	2.00	23.49	2.03	24.15	2.05	24.86	2.06	26.40	2.09
					108	22.09	2.04	21.77	2.08	23.05	2.11	23.75	2.12	24.49	2.14	26.09	2.17
111	22.09	2.10	21.48	2.13	22.80	2.16	23.52	2.17	24.28	2.19	25.92	2.22					
115	22.09	2.15	21.22	2.18	22.58	2.21	23.33	2.23	24.11	2.24	25.80	2.27					
12	18			30	68	22.09	1.55	27.27	1.59	28.08	1.62	28.54	1.64	30.17	1.68	31.45	1.71
					70	22.09	1.57	26.93	1.61	27.76	1.64	28.23	1.65	29.89	1.70	31.20	1.73
					73	22.09	1.61	26.27	1.65	27.14	1.68	27.64	1.69	29.36	1.74	30.71	1.77
					77	22.09	1.65	25.65	1.69	26.57	1.72	27.08	1.74	28.87	1.78	30.26	1.81
					81	22.09	1.70	25.07	1.73	26.02	1.76	26.56	1.78	28.41	1.82	29.85	1.85
					84	22.09	1.74	24.51	1.77	25.51	1.80	26.07	1.82	27.99	1.87	29.47	1.89
					88	22.09	1.78	23.99	1.82	25.04	1.85	25.62	1.86	27.60	1.91	29.12	1.94
					91	22.09	1.83	23.51	1.86	24.60	1.89	25.20	1.91	27.25	1.95	28.81	1.98
					95	22.09	1.87	23.06	1.91	24.19	1.94	25.00	1.95	26.93	2.00	28.54	2.03
					99	22.09	1.92	22.65	1.95	23.82	1.99	24.47	2.00	26.65	2.05	28.30	2.07
					102	22.09	1.97	22.27	2.00	23.49	2.03	24.15	2.05	26.40	2.09	28.09	2.12
					108	22.09	2.04	21.77	2.08	23.05	2.11	23.75	2.12	26.09	2.17	27.85	2.20
111	22.09	2.10	21.48	2.13	22.80	2.16	23.52	2.17	25.92	2.22	27.73	2.25					
115	22.09	2.15	21.22	2.18	22.58	2.21	23.33	2.23	25.80	2.27	27.64	2.30					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	68	22.09	1.55	27.27	1.59	28.08	1.62	28.54	1.64	29.04	1.65	30.17	1.68
					70	22.09	1.57	26.93	1.61	27.76	1.64	28.23	1.65	28.75	1.67	29.89	1.70
					73	22.09	1.61	26.27	1.65	27.14	1.68	27.64	1.69	28.17	1.71	29.36	1.74
					77	22.09	1.65	25.65	1.69	26.57	1.72	27.08	1.74	27.64	1.75	28.87	1.78
					81	22.09	1.70	25.07	1.73	26.02	1.76	26.56	1.78	27.14	1.79	28.41	1.82
					84	22.09	1.74	24.51	1.77	25.51	1.80	26.07	1.82	26.67	1.84	27.99	1.87
					88	22.09	1.78	23.99	1.82	25.04	1.85	25.62	1.86	26.24	1.88	27.60	1.91
					91	22.09	1.83	23.51	1.86	24.60	1.89	25.20	1.91	25.84	1.92	27.25	1.95
					95	22.09	1.87	23.06	1.91	24.19	1.94	25.00	1.95	25.48	1.97	26.93	2.00
					99	22.09	1.92	22.65	1.95	23.82	1.99	24.47	2.00	25.15	2.02	26.65	2.05
					102	22.09	1.97	22.27	2.00	23.49	2.03	24.15	2.05	24.86	2.06	26.40	2.09
					108	22.09	2.04	21.77	2.08	23.05	2.11	23.75	2.12	24.49	2.14	26.09	2.17
111	22.09	2.10	21.48	2.13	22.80	2.16	23.52	2.17	24.28	2.19	25.92	2.22					
115	22.09	2.15	21.22	2.18	22.58	2.21	23.33	2.23	24.11	2.24	25.80	2.27					
7	7	7		21	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23
					70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24
					73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27
					77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30
					81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33
					84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36
					88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39
					91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42
					95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46
					99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49
					102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52
					108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58
111	18.56	1.50	18.04	1.53	19.15	1.55	19.76	1.56	21.78	1.59	23.29	1.61					
115	18.56	1.54	17.82	1.57	18.97	1.59	19.60	1.60	21.67	1.63	23.22	1.65					
7	7	9		23	68	20.33	1.37	25.09	1.40	25.83	1.43	26.26	1.44	27.76	1.48	28.94	1.51
					70	20.33	1.39	24.78	1.42	25.54	1.45	25.97	1.46	27.50	1.50	28.70	1.53
					73	20.33	1.42	24.17	1.45	24.97	1.48	25.43	1.49	27.02	1.54	28.26	1.56
					77	20.33	1.46	23.60	1.49	24.44	1.52	24.92	1.53	26.56	1.57	27.84	1.60
					81	20.33	1.50	23.06	1.52	23.94	1.55	24.44	1.57	26.14	1.61	27.46	1.63
					84	20.33	1.53	22.55	1.56	23.47	1.59	23.99	1.61	25.75	1.65	27.11	1.67
					88	20.33	1.57	22.08	1.60	23.03	1.63	23.57	1.64	25.39	1.68	26.79	1.71
					91	20.33	1.61	21.63	1.64	22.63	1.67	23.18	1.68	25.07	1.72	26.51	1.75
					95	20.33	1.65	21.22	1.68	22.26	1.71	23.00	1.72	24.78	1.76	26.25	1.79
					99	20.33	1.70	20.84	1.72	21.92	1.75	22.51	1.77	24.51	1.80	26.03	1.83
					102	20.33	1.74	20.49	1.77	21.61	1.79	22.22	1.81	24.28	1.85	25.84	1.87
					108	20.33	1.80	20.03	1.83	21.20	1.86	21.85	1.87	24.00	1.91	25.62	1.94
111	20.33	1.85	19.76	1.88	20.98	1.90	21.64	1.92	23.85	1.96	25.51	1.98					
115	20.33	1.89	19.52	1.92	20.78	1.95	21.46	1.96	23.73	2.00	25.43	2.03					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	26	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25	
7	7	15	29	68	22.09	1.44	27.27	1.47	28.08	1.50	28.54	1.52	29.04	1.53	30.17	1.56	
				70	22.09	1.46	26.93	1.49	27.76	1.52	28.23	1.54	28.75	1.55	29.89	1.58	
				73	22.09	1.50	26.27	1.53	27.14	1.56	27.64	1.57	28.17	1.59	29.36	1.62	
				77	22.09	1.53	25.65	1.57	26.57	1.60	27.08	1.61	27.64	1.63	28.87	1.65	
				81	22.09	1.57	25.07	1.60	26.02	1.63	26.56	1.65	27.14	1.66	28.41	1.69	
				84	22.09	1.61	24.51	1.64	25.51	1.67	26.07	1.69	26.67	1.70	27.99	1.73	
				88	22.09	1.65	23.99	1.69	25.04	1.72	25.62	1.73	26.24	1.74	27.60	1.77	
				91	22.09	1.70	23.51	1.73	24.60	1.76	25.20	1.77	25.84	1.79	27.25	1.81	
				95	22.09	1.74	23.06	1.77	24.19	1.80	25.00	1.81	25.48	1.83	26.93	1.86	
				99	22.09	1.78	22.65	1.81	23.82	1.84	24.47	1.86	25.15	1.87	26.65	1.90	
				102	22.09	1.83	22.27	1.86	23.49	1.89	24.15	1.90	24.86	1.92	26.40	1.94	
				108	22.09	1.90	21.77	1.93	23.05	1.96	23.75	1.97	24.49	1.99	26.09	2.01	
7	7	18	32	68	22.09	1.44	27.27	1.47	28.08	1.50	28.54	1.52	30.17	1.56	31.45	1.59	
				70	22.09	1.46	26.93	1.49	27.76	1.52	28.23	1.54	29.89	1.58	31.20	1.61	
				73	22.09	1.50	26.27	1.53	27.14	1.56	27.64	1.57	29.36	1.62	30.71	1.64	
				77	22.09	1.53	25.65	1.57	26.57	1.60	27.08	1.61	28.87	1.65	30.26	1.68	
				81	22.09	1.57	25.07	1.60	26.02	1.63	26.56	1.65	28.41	1.69	29.85	1.72	
				84	22.09	1.61	24.51	1.64	25.51	1.67	26.07	1.69	27.99	1.73	29.47	1.76	
				88	22.09	1.65	23.99	1.69	25.04	1.72	25.62	1.73	27.60	1.77	29.12	1.80	
				91	22.09	1.70	23.51	1.73	24.60	1.76	25.20	1.77	27.25	1.81	28.81	1.84	
				95	22.09	1.74	23.06	1.77	24.19	1.80	25.00	1.81	26.93	1.86	28.54	1.88	
				99	22.09	1.78	22.65	1.81	23.82	1.84	24.47	1.86	26.65	1.90	28.30	1.93	
				102	22.09	1.83	22.27	1.86	23.49	1.89	24.15	1.90	26.40	1.94	28.09	1.97	
				108	22.09	1.90	21.77	1.93	23.05	1.96	23.75	1.97	26.09	2.01	27.85	2.04	
111	22.09	1.95	21.48	1.98	22.80	2.00	23.52	2.02	25.92	2.06	27.73	2.08					
115	22.09	1.99	21.22	2.02	22.58	2.05	23.33	2.07	25.80	2.11	27.64	2.13					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	25	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25	
7	9	12	28	68	22.09	1.44	27.27	1.47	28.08	1.50	28.54	1.52	30.17	1.56	31.45	1.59	
				70	22.09	1.46	26.93	1.49	27.76	1.52	28.23	1.54	29.89	1.58	31.20	1.61	
				73	22.09	1.50	26.27	1.53	27.14	1.56	27.64	1.57	29.36	1.62	30.71	1.64	
				77	22.09	1.53	25.65	1.57	26.57	1.60	27.08	1.61	28.87	1.65	30.26	1.68	
				81	22.09	1.57	25.07	1.60	26.02	1.63	26.56	1.65	28.41	1.69	29.85	1.72	
				84	22.09	1.61	24.51	1.64	25.51	1.67	26.07	1.69	27.99	1.73	29.47	1.76	
				88	22.09	1.65	23.99	1.69	25.04	1.72	25.62	1.73	27.60	1.77	29.12	1.80	
				91	22.09	1.70	23.51	1.73	24.60	1.76	25.20	1.77	27.25	1.81	28.81	1.84	
				95	22.09	1.74	23.06	1.77	24.19	1.80	25.00	1.81	26.93	1.86	28.54	1.88	
				99	22.09	1.78	22.65	1.81	23.82	1.84	24.47	1.86	26.65	1.90	28.30	1.93	
				102	22.09	1.83	22.27	1.86	23.49	1.89	24.15	1.90	26.40	1.94	28.09	1.97	
				108	22.09	1.90	21.77	1.93	23.05	1.96	23.75	1.97	26.09	2.01	27.85	2.04	
7	9	15	31	68	22.09	1.44	27.27	1.47	28.08	1.50	28.54	1.52	29.04	1.53	30.17	1.56	
				70	22.09	1.46	26.93	1.49	27.76	1.52	28.23	1.54	28.75	1.55	29.89	1.58	
				73	22.09	1.50	26.27	1.53	27.14	1.56	27.64	1.57	28.17	1.59	29.36	1.62	
				77	22.09	1.53	25.65	1.57	26.57	1.60	27.08	1.61	27.64	1.63	28.87	1.65	
				81	22.09	1.57	25.07	1.60	26.02	1.63	26.56	1.65	27.14	1.66	28.41	1.69	
				84	22.09	1.61	24.51	1.64	25.51	1.67	26.07	1.69	26.67	1.70	27.99	1.73	
				88	22.09	1.65	23.99	1.69	25.04	1.72	25.62	1.73	26.24	1.74	27.60	1.77	
				91	22.09	1.70	23.51	1.73	24.60	1.76	25.20	1.77	25.84	1.79	27.25	1.81	
				95	22.09	1.74	23.06	1.77	24.19	1.80	25.00	1.81	25.48	1.83	26.93	1.86	
				99	22.09	1.78	22.65	1.81	23.82	1.84	24.47	1.86	25.15	1.87	26.65	1.90	
				102	22.09	1.83	22.27	1.86	23.49	1.89	24.15	1.90	24.86	1.92	26.40	1.94	
				108	22.09	1.90	21.77	1.93	23.05	1.96	23.75	1.97	24.49	1.99	26.09	2.01	
111	22.09	1.95	21.48	1.98	22.80	2.00	23.52	2.02	24.28	2.03	25.92	2.06					
115	22.09	1.99	21.22	2.02	22.58	2.05	23.33	2.07	24.11	2.08	25.80	2.11					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	12	31	68	22.09	1.44	27.27	1.47	28.08	1.50	28.54	1.52	30.17	1.56	31.45	1.59	
				70	22.09	1.46	26.93	1.49	27.76	1.52	28.23	1.54	29.89	1.58	31.20	1.61	
				73	22.09	1.50	26.27	1.53	27.14	1.56	27.64	1.57	29.36	1.62	30.71	1.64	
				77	22.09	1.53	25.65	1.57	26.57	1.60	27.08	1.61	28.87	1.65	30.26	1.68	
				81	22.09	1.57	25.07	1.60	26.02	1.63	26.56	1.65	28.41	1.69	29.85	1.72	
				84	22.09	1.61	24.51	1.64	25.51	1.67	26.07	1.69	27.99	1.73	29.47	1.76	
				88	22.09	1.65	23.99	1.69	25.04	1.72	25.62	1.73	27.60	1.77	29.12	1.80	
				91	22.09	1.70	23.51	1.73	24.60	1.76	25.20	1.77	27.25	1.81	28.81	1.84	
				95	22.09	1.74	23.06	1.77	24.19	1.80	25.00	1.81	26.93	1.86	28.54	1.88	
				99	22.09	1.78	22.65	1.81	23.82	1.84	24.47	1.86	26.65	1.90	28.30	1.93	
				102	22.09	1.83	22.27	1.86	23.49	1.89	24.15	1.90	26.40	1.94	28.09	1.97	
				108	22.09	1.90	21.77	1.93	23.05	1.96	23.75	1.97	26.09	2.01	27.85	2.04	
9	9	9	27	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
9	9	12	30	68	22.09	1.44	27.27	1.47	28.08	1.50	28.54	1.52	30.17	1.56	31.45	1.59	
				70	22.09	1.46	26.93	1.49	27.76	1.52	28.23	1.54	29.89	1.58	31.20	1.61	
				73	22.09	1.50	26.27	1.53	27.14	1.56	27.64	1.57	29.36	1.62	30.71	1.64	
				77	22.09	1.53	25.65	1.57	26.57	1.60	27.08	1.61	28.87	1.65	30.26	1.68	
				81	22.09	1.57	25.07	1.60	26.02	1.63	26.56	1.65	28.41	1.69	29.85	1.72	
				84	22.09	1.61	24.51	1.64	25.51	1.67	26.07	1.69	27.99	1.73	29.47	1.76	
				88	22.09	1.65	23.99	1.69	25.04	1.72	25.62	1.73	27.60	1.77	29.12	1.80	
				91	22.09	1.70	23.51	1.73	24.60	1.76	25.20	1.77	27.25	1.81	28.81	1.84	
				95	22.09	1.74	23.06	1.77	24.19	1.80	25.00	1.81	26.93	1.86	28.54	1.88	
				99	22.09	1.78	22.65	1.81	23.82	1.84	24.47	1.86	26.65	1.90	28.30	1.93	
				102	22.09	1.83	22.27	1.86	23.49	1.89	24.15	1.90	26.40	1.94	28.09	1.97	
				108	22.09	1.90	21.77	1.93	23.05	1.96	23.75	1.97	26.09	2.01	27.85	2.04	
111	22.09	1.95	21.48	1.98	22.80	2.00	23.52	2.02	25.92	2.06	27.73	2.08					
115	22.09	1.99	21.22	2.02	22.58	2.05	23.33	2.07	25.80	2.11	27.64	2.13					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	7	28	68	22.09	1.37	27.27	1.40	28.08	1.43	28.54	1.44	30.17	1.48	31.45	1.51
					70	22.09	1.39	26.93	1.42	27.76	1.45	28.23	1.46	29.89	1.50	31.20	1.53
					73	22.09	1.42	26.27	1.45	27.14	1.48	27.64	1.49	29.36	1.54	30.71	1.56
					77	22.09	1.46	25.65	1.49	26.57	1.52	27.08	1.53	28.87	1.57	30.26	1.60
					81	22.09	1.50	25.07	1.52	26.02	1.55	26.56	1.57	28.41	1.61	29.85	1.63
					84	22.09	1.53	24.51	1.56	25.51	1.59	26.07	1.61	27.99	1.65	29.47	1.67
					88	22.09	1.57	23.99	1.60	25.04	1.63	25.62	1.64	27.60	1.68	29.12	1.71
					91	22.09	1.61	23.51	1.64	24.60	1.67	25.20	1.68	27.25	1.72	28.81	1.75
					95	22.09	1.65	23.06	1.68	24.19	1.71	25.00	1.72	26.93	1.76	28.54	1.79
					99	22.09	1.70	22.65	1.72	23.82	1.75	24.47	1.77	26.65	1.80	28.30	1.83
					102	22.09	1.74	22.27	1.77	23.49	1.79	24.15	1.81	26.40	1.85	28.09	1.87
					108	22.09	1.80	21.77	1.83	23.05	1.86	23.75	1.87	26.09	1.91	27.85	1.94
					111	22.09	1.85	21.48	1.88	22.80	1.90	23.52	1.92	25.92	1.96	27.73	1.98
					115	22.09	1.89	21.22	1.92	22.58	1.95	23.33	1.96	25.80	2.00	27.64	2.03
7	7	7	9	30	68	22.09	1.37	27.27	1.40	28.08	1.43	28.54	1.44	30.17	1.48	31.45	1.51
					70	22.09	1.39	26.93	1.42	27.76	1.45	28.23	1.46	29.89	1.50	31.20	1.53
					73	22.09	1.42	26.27	1.45	27.14	1.48	27.64	1.49	29.36	1.54	30.71	1.56
					77	22.09	1.46	25.65	1.49	26.57	1.52	27.08	1.53	28.87	1.57	30.26	1.60
					81	22.09	1.50	25.07	1.52	26.02	1.55	26.56	1.57	28.41	1.61	29.85	1.63
					84	22.09	1.53	24.51	1.56	25.51	1.59	26.07	1.61	27.99	1.65	29.47	1.67
					88	22.09	1.57	23.99	1.60	25.04	1.63	25.62	1.64	27.60	1.68	29.12	1.71
					91	22.09	1.61	23.51	1.64	24.60	1.67	25.20	1.68	27.25	1.72	28.81	1.75
					95	22.09	1.65	23.06	1.68	24.19	1.71	25.00	1.72	26.93	1.76	28.54	1.79
					99	22.09	1.70	22.65	1.72	23.82	1.75	24.47	1.77	26.65	1.80	28.30	1.83
					102	22.09	1.74	22.27	1.77	23.49	1.79	24.15	1.81	26.40	1.85	28.09	1.87
					108	22.09	1.80	21.77	1.83	23.05	1.86	23.75	1.87	26.09	1.91	27.85	1.94
					111	22.09	1.85	21.48	1.88	22.80	1.90	23.52	1.92	25.92	1.96	27.73	1.98
					115	22.09	1.89	21.22	1.92	22.58	1.95	23.33	1.96	25.80	2.00	27.64	2.03
7	7	9	9	32	68	22.09	1.37	27.27	1.40	28.08	1.43	28.54	1.44	30.17	1.48	31.45	1.51
					70	22.09	1.39	26.93	1.42	27.76	1.45	28.23	1.46	29.89	1.50	31.20	1.53
					73	22.09	1.42	26.27	1.45	27.14	1.48	27.64	1.49	29.36	1.54	30.71	1.56
					77	22.09	1.46	25.65	1.49	26.57	1.52	27.08	1.53	28.87	1.57	30.26	1.60
					81	22.09	1.50	25.07	1.52	26.02	1.55	26.56	1.57	28.41	1.61	29.85	1.63
					84	22.09	1.53	24.51	1.56	25.51	1.59	26.07	1.61	27.99	1.65	29.47	1.67
					88	22.09	1.57	23.99	1.60	25.04	1.63	25.62	1.64	27.60	1.68	29.12	1.71
					91	22.09	1.61	23.51	1.64	24.60	1.67	25.20	1.68	27.25	1.72	28.81	1.75
					95	22.09	1.65	23.06	1.68	24.19	1.71	25.00	1.72	26.93	1.76	28.54	1.79
					99	22.09	1.70	22.65	1.72	23.82	1.75	24.47	1.77	26.65	1.80	28.30	1.83
					102	22.09	1.74	22.27	1.77	23.49	1.79	24.15	1.81	26.40	1.85	28.09	1.87
					108	22.09	1.80	21.77	1.83	23.05	1.86	23.75	1.87	26.09	1.91	27.85	1.94
					111	22.09	1.85	21.48	1.88	22.80	1.90	23.52	1.92	25.92	1.96	27.73	1.98
					115	22.09	1.89	21.22	1.92	22.58	1.95	23.33	1.96	25.80	2.00	27.64	2.03

- Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).
- Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).
- The above values are based on connection of non-ducted indoor units.
- Capacities are based on the following conditions:
- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)
- The total combination index of connected indoor units is up to 32.
- Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.
Single indoor unit connection is not allowed.
- This reference data is based on temperature and capacity trend.

Capacity Table

JXH24S4C (AJ024CX54CH/AA)

Heating (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	-13	24.54	6.86	20.52	5.44	19.69	5.52	15.24	4.02	13.51	3.35	9.63	2.17
					5	23.84	4.62	23.27	4.67	22.69	4.74	21.80	4.92	21.55	4.84	20.98	4.88
					17	23.23	4.00	22.83	4.04	22.43	4.08	21.80	4.23	21.63	4.17	21.22	4.21
					32	23.04	2.97	22.69	3.00	22.34	3.03	21.80	3.14	21.65	3.08	21.30	3.11
					47	23.10	2.09	22.83	2.11	22.53	2.13	21.80	2.21	21.92	2.17	21.62	2.19
					50	25.08	2.22	24.47	2.25	24.01	2.28	23.79	2.30	23.22	2.34	22.89	2.36
					59	27.46	2.31	26.94	2.34	26.45	2.38	26.23	2.39	25.62	2.43	25.26	2.45
					-13	28.02	7.33	23.44	5.81	22.49	5.90	17.41	4.29	15.44	3.58	11.00	2.32
					5	27.23	4.94	26.58	4.99	25.92	5.06	24.90	5.25	24.62	5.16	23.96	5.22
					17	26.53	4.27	26.07	4.32	25.61	4.36	24.90	4.52	24.70	4.45	24.24	4.50
					32	26.32	3.18	25.92	3.21	25.52	3.24	24.90	3.35	24.73	3.29	24.33	3.32
					47	26.39	2.23	26.08	2.25	25.74	2.27	24.90	2.36	25.04	2.31	24.69	2.34
					50	28.65	2.37	27.95	2.41	27.42	2.44	27.18	2.45	26.52	2.50	26.14	2.52
					59	31.37	2.47	30.77	2.50	30.21	2.54	29.95	2.55	29.26	2.60	28.86	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08	2.55	29.38	2.60	28.97	2.62
					-13	28.14	7.33	23.54	5.81	22.58	5.90	17.48	4.29	15.50	3.58	11.05	2.32
					5	27.34	4.94	26.68	4.99	26.02	5.06	25.00	5.25	24.72	5.16	24.06	5.22
					17	26.64	4.27	26.18	4.32	25.72	4.36	25.00	4.52	24.80	4.45	24.34	4.50
					32	26.42	3.18	26.03	3.21	25.62	3.24	25.00	3.35	24.83	3.29	24.43	3.32
					47	26.50	2.23	26.18	2.25	25.84	2.27	25.00	2.36	25.14	2.31	24.79	2.34
					50	28.77	2.37	28.06	2.41	27.53	2.44	27.29	2.45	26.62	2.50	26.25	2.52
					59	31.50	2.47	30.89	2.50	30.33	2.54	30.08</					

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Heating (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9		27	-13	20.05	3.46	19.12	3.49	18.58	3.54	17.48	3.58	16.94	3.63	15.84	3.63
					5	27.00	4.23	26.42	4.28	25.66	4.33	25.00	4.38	24.43	4.43	23.96	4.46
					17	26.63	3.64	26.14	3.68	25.54	3.73	25.00	3.77	24.53	3.81	24.13	3.84
					32	26.51	2.70	26.06	2.73	25.50	2.76	25.00	2.80	24.56	2.83	24.18	2.85
					47	26.41	1.90	25.98	1.92	25.46	1.95	25.00	1.97	24.59	1.99	24.23	2.01
					50	28.77	1.98	28.06	2.01	27.53	2.04	27.29	2.05	26.62	2.08	26.25	2.10
9	9	12		30	59	31.50	2.06	30.89	2.09	30.33	2.12	30.08	2.13	29.38	2.17	28.97	2.19
					-13	20.05	3.46	19.12	3.49	18.58	3.54	17.48	3.58	16.94	3.63	15.84	3.63
					5	27.00	4.23	26.42	4.28	25.66	4.33	25.00	4.38	24.43	4.43	23.96	4.46
					17	26.63	3.64	26.14	3.68	25.54	3.73	25.00	3.77	24.53	3.81	24.13	3.84
					32	26.51	2.70	26.06	2.73	25.50	2.76	25.00	2.80	24.56	2.83	24.18	2.85
					47	26.41	1.90	25.98	1.92	25.46	1.95	25.00	1.97	24.59	1.99	24.23	2.01
9	9	12		30	50	28.77	1.98	28.06	2.01	27.53	2.04	27.29	2.05	26.62	2.08	26.25	2.10
					59	31.50	2.06	30.89	2.09	30.33	2.12	30.08	2.13	29.38	2.17	28.97	2.19

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 30.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH24S4C (AJ024CX54CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)														
						57.2		60.8		64.4		69.98		71.6		75.2				
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)			
7	7		14	-13	16.88	3.91	14.12	3.10	13.55	3.15	10.49	2.29	9.30	1.91	6.63	1.24				
				5	16.40	2.64	16.01	2.66	15.61	2.70	15.00	2.80	14.83	2.76	14.43	2.78				
				17	15.98	2.28	15.71	2.30	15.43	2.33	15.00	2.41	14.88	2.38	14.60	2.40				
				32	15.85	1.70	15.62	1.71	15.37	1.73	15.00	1.79	14.90	1.76	14.66	1.77				
				47	15.90	1.19	15.71	1.20	15.50	1.21	15.00	1.26	15.08	1.23	14.87	1.25				
				50	17.26	1.27	16.84	1.29	16.52	1.30	16.37	1.31	15.97	1.33	15.75	1.34				
				59	18.90	1.32	18.53	1.34	18.20	1.35	18.05	1.36	17.63	1.39	17.38	1.40				
				7	9		16	-13	20.71	4.75	17.32	3.77	16.62	3.82	12.87	2.78	11.41	2.32	8.13	1.50
								5	20.12	3.20	19.64	3.23	19.15	3.28	18.40	3.40	18.19	3.35	17.71	3.38
								17	19.61	2.77	19.27	2.80	18.93	2.82	18.40	2.93	18.25	2.89	17.91	2.91
								32	19.45	2.06	19.16	2.08	18.86	2.10	18.40	2.17	18.27	2.14	17.98	2.15
								47	19.50	1.45	19.27	1.46	19.02	1.47	18.40	1.53	18.50	1.50	18.25	1.52
50	21.17	1.54	20.65					1.56	20.26	1.58	20.08	1.59	19.60	1.62	19.32	1.63				
				59	23.18	1.60	22.73	1.62	22.33	1.64	22.14	1.65	21.62	1.68	21.32	1.70				
				7	12		19	-13	24.20	5.19	20.24	4.11	19.42	4.17	15.03	3.04	13.33	2.53	9.50	1.64
								5	23.51	3.49	22.95	3.53	22.38	3.58	21.50	3.72	21.26	3.65	20.69	3.69
								17	22.91	3.02	22.51	3.05	22.12	3.08	21.50	3.20	21.33	3.15	20.93	3.18
								32	22.72	2.25	22.38	2.27	22.04	2.29	21.50	2.37	21.35	2.33	21.01	2.35
								47	22.79	1.58	22.52	1.59	22.22	1.61	21.50	1.67	21.62	1.64	21.32	1.66
50	24.74	1.68	24.13					1.70	23.68	1.73	23.47	1.74	22.90	1.77	22.57	1.78				
				59	27.09	1.75	26.56	1.77	26.09	1.80	25.86	1.81	25.26	1.84	24.92	1.85				
				7	15		22	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85
								5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16
								17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58
								32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65
								47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86
50	28.77	1.89	28.06					1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01				
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09				
				7	18		25	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85
								5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16
								17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58
								32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65
								47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86
50	28.77	1.89	28.06					1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01				
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09				
				9	9		18	-13	24.54	5.31	20.52	4.21	19.69	4.27	15.24	3.11	13.51	2.59	9.63	1.68
								5	23.84	3.58	23.27	3.61	22.69	3.66	21.80	3.80	21.55	3.74	20.98	3.78
								17	23.23	3.09	22.83	3.13	22.43	3.16	21.80	3.27	21.63	3.23	21.22	3.26
								32	23.04	2.30	22.69	2.32	22.34	2.34	21.80	2.43	21.65	2.39	21.30	2.41
								47	23.10	1.62	22.83	1.63	22.53	1.65	21.80	1.71	21.92	1.68	21.62	1.69
50	25.08	1.72	24.47					1.74	24.01	1.77	23.79	1.78	23.22	1.81	22.89	1.82				
				59	27.46	1.79	26.94	1.81	26.45	1.84	26.23	1.85	25.62	1.88	25.26	1.90				
				9	12		21	-13	28.02	5.78	23.44	4.58	22.49	4.65	17.41	3.38	15.44	2.82	11.00	1.83
								5	27.23	3.89	26.58	3.93	25.92	3.99	24.90	4.14	24.62	4.07	23.96	4.11
								17	26.53	3.37	26.07	3.40	25.61	3.43	24.90	3.56	24.70	3.51	24.24	3.54
								32	26.32	2.50	25.92	2.53	25.52	2.55	24.90	2.64	24.73	2.60	24.33	2.62
								47	26.39	1.76	26.08	1.78	25.74	1.79	24.90	1.86	25.04	1.82	24.69	1.84
50	28.65	1.87	27.95					1.90	27.42	1.92	27.18	1.93	26.52	1.97	26.14	1.99				
				59	31.37	1.94	30.77	1.97	30.21	2.00	29.95	2.01	29.26	2.05	28.86	2.07				

Capacity Table

JXH24S4C (AJ024CX54CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15		24	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85	
				5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16	
				17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58	
				32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65	
				47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86	
				50	28.77	1.89	28.06	1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01	
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09	
9	18		27	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85	
				5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16	
				17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58	
				32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65	
				47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86	
				50	28.77	1.89	28.06	1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01	
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09	
12	12		24	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85	
				5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16	
				17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58	
				32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65	
				47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86	
				50	28.77	1.89	28.06	1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01	
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09	
12	15		27	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85	
				5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16	
				17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58	
				32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65	
				47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86	
				50	28.77	1.89	28.06	1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01	
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09	
12	18		30	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85	
				5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16	
				17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58	
				32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65	
				47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86	
				50	28.77	1.89	28.06	1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01	
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09	
15	15		30	-13	28.14	5.84	23.54	4.63	22.58	4.70	17.48	3.42	15.50	2.85	11.05	1.85	
				5	27.34	3.93	26.68	3.97	26.02	4.03	25.00	4.18	24.72	4.11	24.06	4.16	
				17	26.64	3.40	26.18	3.44	25.72	3.47	25.00	3.60	24.80	3.55	24.34	3.58	
				32	26.42	2.53	26.03	2.55	25.62	2.58	25.00	2.67	24.83	2.62	24.43	2.65	
				47	26.50	1.78	26.18	1.80	25.84	1.81	25.00	1.88	25.14	1.84	24.79	1.86	
				50	28.77	1.89	28.06	1.92	27.53	1.94	27.29	1.96	26.62	1.99	26.25	2.01	
				59	31.50	1.96	30.89	1.99	30.33	2.02	30.08	2.03	29.38	2.07	28.97	2.09	
7	7	7	21	-13	18.05	2.55	17.21	2.57	16.72	2.60	15.73	2.64	15.24	2.67	14.26	2.67	
				5	24.30	3.12	23.78	3.15	23.10	3.19	22.50	3.23	21.99	3.26	21.57	3.28	
				17	23.97	2.68	23.53	2.71	22.98	2.74	22.50	2.78	22.08	2.80	21.72	2.83	
				32	23.86	1.99	23.45	2.01	22.95	2.03	22.50	2.06	22.10	2.08	21.76	2.10	
				47	23.77	1.40	23.38	1.41	22.92	1.43	22.50	1.45	22.13	1.47	21.81	1.48	
				50	25.89	1.46	25.25	1.48	24.78	1.50	24.56	1.51	23.96	1.53	23.62	1.55	
				59	28.35	1.52	27.80	1.54	27.30	1.56	27.07	1.57	26.44	1.59	26.07	1.61	

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	23	-13	20.05	2.81	19.12	2.83	18.58	2.87	17.48	2.91	16.94	2.95	15.84	2.95	
				5	27.00	3.44	26.42	3.47	25.66	3.52	25.00	3.56	24.43	3.59	23.96	3.62	
				17	26.63	2.95	26.14	2.99	25.54	3.03	25.00	3.06	24.53	3.09	24.13	3.12	
				32	26.51	2.19	26.06	2.22	25.50	2.25	25.00	2.27	24.56	2.30	24.18	2.32	
				47	26.41	1.54	25.98	1.56	25.46	1.58	25.00	1.60	24.59	1.62	24.23	1.63	
				50	28.77	1.61	28.06	1.63	27.53	1.65	27.29	1.66	26.62	1.69	26.25	1.71	
				59	31.50	1.67	30.89	1.70	30.33	1.72	30.08	1.73	29.38	1.76	28.97	1.78	
7	7	12	26	-13	20.05	2.81	19.12	2.83	18.58	2.87	17.48	2.91	16.94	2.95	15.84	2.95	
				5	27.00	3.44	26.42	3.47	25.66	3.52	25.00	3.56	24.43	3.59	23.96	3.62	
				17	26.63	2.95	26.14	2.99	25.54	3.03	25.00	3.06	24.53	3.09	24.13	3.12	
				32	26.51	2.19	26.06	2.22	25.50	2.25	25.00	2.27	24.56	2.30	24.18	2.32	
				47	26.41	1.54	25.98	1.56	25.46	1.58	25.00	1.60	24.59	1.62	24.23	1.63	
				50	28.77	1.61	28.06	1.63	27.53	1.65	27.29	1.66	26.62	1.69	26.25	1.71	
				59	31.50	1.67	30.89	1.70	30.33	1.72	30.08	1.73	29.38	1.76	28.97	1.78	
7	7	15	29	-13	20.05	2.88	19.12	2.91	18.58	2.94	17.48	2.98	16.94	3.02	15.84	3.02	
				5	27.00	3.53	26.42	3.56	25.66	3.61	25.00	3.65	24.43	3.68	23.96	3.71	
				17	26.63	3.03	26.14	3.06	25.54	3.10	25.00	3.14	24.53	3.17	24.13	3.20	
				32	26.51	2.25	26.06	2.27	25.50	2.30	25.00	2.33	24.56	2.35	24.18	2.37	
				47	26.41	1.58	25.98	1.60	25.46	1.62	25.00	1.64	24.59	1.66	24.23	1.67	
				50	28.77	1.65	28.06	1.67	27.53	1.70	27.29	1.71	26.62	1.73	26.25	1.75	
				59	31.50	1.71	30.89	1.74	30.33	1.76	30.08	1.77	29.38	1.80	28.97	1.82	
7	7	18	32	-13	20.05	2.88	19.12	2.91	18.58	2.94	17.48	2.98	16.94	3.02	15.84	3.02	
				5	27.00	3.53	26.42	3.56	25.66	3.61	25.00	3.65	24.43	3.68	23.96	3.71	
				17	26.63	3.03	26.14	3.06	25.54	3.10	25.00	3.14	24.53	3.17	24.13	3.20	
				32	26.51	2.25	26.06	2.27	25.50	2.30	25.00	2.33	24.56	2.35	24.18	2.37	
				47	26.41	1.58	25.98	1.60	25.46	1.62	25.00	1.64	24.59	1.66	24.23	1.67	
				50	28.77	1.65	28.06	1.67	27.53	1.70	27.29	1.71	26.62	1.73	26.25	1.75	
				59	31.50	1.71	30.89	1.74	30.33	1.76	30.08	1.77	29.38	1.80	28.97	1.82	
7	9	9	25	-13	20.05	2.81	19.12	2.83	18.58	2.87	17.48	2.91	16.94	2.95	15.84	2.95	
				5	27.00	3.44	26.42	3.47	25.66	3.52	25.00	3.56	24.43	3.59	23.96	3.62	
				17	26.63	2.95	26.14	2.99	25.54	3.03	25.00	3.06	24.53	3.09	24.13	3.12	
				32	26.51	2.19	26.06	2.22	25.50	2.25	25.00	2.27	24.56	2.30	24.18	2.32	
				47	26.41	1.54	25.98	1.56	25.46	1.58	25.00	1.60	24.59	1.62	24.23	1.63	
				50	28.77	1.61	28.06	1.63	27.53	1.65	27.29	1.66	26.62	1.69	26.25	1.71	
				59	31.50	1.67	30.89	1.70	30.33	1.72	30.08	1.73	29.38	1.76	28.97	1.78	
7	9	12	28	-13	20.05	2.88	19.12	2.91	18.58	2.94	17.48	2.98	16.94	3.02	15.84	3.02	
				5	27.00	3.53	26.42	3.56	25.66	3.61	25.00	3.65	24.43	3.68	23.96	3.71	
				17	26.63	3.03	26.14	3.06	25.54	3.10	25.00	3.14	24.53	3.17	24.13	3.20	
				32	26.51	2.25	26.06	2.27	25.50	2.30	25.00	2.33	24.56	2.35	24.18	2.37	
				47	26.41	1.58	25.98	1.60	25.46	1.62	25.00	1.64	24.59	1.66	24.23	1.67	
				50	28.77	1.65	28.06	1.67	27.53	1.70	27.29	1.71	26.62	1.73	26.25	1.75	
				59	31.50	1.71	30.89	1.74	30.33	1.76	30.08	1.77	29.38	1.80	28.97	1.82	
7	9	15	31	-13	20.05	2.88	19.12	2.91	18.58	2.94	17.48	2.98	16.94	3.02	15.84	3.02	
				5	27.00	3.53	26.42	3.56	25.66	3.61	25.00	3.65	24.43	3.68	23.96	3.71	
				17	26.63	3.03	26.14	3.06	25.54	3.10	25.00	3.14	24.53	3.17	24.13	3.20	
				32	26.51	2.25	26.06	2.27	25.50	2.30	25.00	2.33	24.56	2.35	24.18	2.37	
				47	26.41	1.58	25.98	1.60	25.46	1.62	25.00	1.64	24.59	1.66	24.23	1.67	
				50	28.77	1.65	28.06	1.67	27.53	1.70	27.29	1.71	26.62	1.73	26.25	1.75	
				59	31.50	1.71	30.89	1.74	30.33	1.76	30.08	1.77	29.38	1.80	28.97	1.82	

Capacity Table

JXH24S4C (AJ024CXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	12	31	-13	20.05	2.88	19.12	2.91	18.58	2.94	17.48	2.98	16.94	3.02	15.84	3.02	
				5	27.00	3.53	26.42	3.56	25.66	3.61	25.00	3.65	24.43	3.68	23.96	3.71	
				17	26.63	3.03	26.14	3.06	25.54	3.10	25.00	3.14	24.53	3.17	24.13	3.20	
				32	26.51	2.25	26.06	2.27	25.50	2.30	25.00	2.33	24.56	2.35	24.18	2.37	
				47	26.41	1.58	25.98	1.60	25.46	1.62	25.00	1.64	24.59	1.66	24.23	1.67	
				50	28.77	1.65	28.06	1.67	27.53	1.70	27.29	1.71	26.62	1.73	26.25	1.75	
9	9	9	27	59	31.50	1.71	30.89	1.74	30.33	1.76	30.08	1.77	29.38	1.80	28.97	1.82	
				-13	20.05	2.81	19.12	2.83	18.58	2.87	17.48	2.91	16.94	2.95	15.84	2.95	
				5	27.00	3.44	26.42	3.47	25.66	3.52	25.00	3.56	24.43	3.59	23.96	3.62	
				17	26.63	2.95	26.14	2.99	25.54	3.03	25.00	3.06	24.53	3.09	24.13	3.12	
				32	26.51	2.19	26.06	2.22	25.50	2.25	25.00	2.27	24.56	2.30	24.18	2.32	
				47	26.41	1.54	25.98	1.56	25.46	1.58	25.00	1.60	24.59	1.62	24.23	1.63	
9	9	12	30	50	28.77	1.61	28.06	1.63	27.53	1.65	27.29	1.66	26.62	1.69	26.25	1.71	
				59	31.50	1.67	30.89	1.70	30.33	1.72	30.08	1.73	29.38	1.76	28.97	1.78	
				-13	20.05	2.88	19.12	2.91	18.58	2.94	17.48	2.98	16.94	3.02	15.84	3.02	
				5	27.00	3.53	26.42	3.56	25.66	3.61	25.00	3.65	24.43	3.68	23.96	3.71	
				17	26.63	3.03	26.14	3.06	25.54	3.10	25.00	3.14	24.53	3.17	24.13	3.20	
				32	26.51	2.25	26.06	2.27	25.50	2.30	25.00	2.33	24.56	2.35	24.18	2.37	
7	7	7	28	47	26.41	1.58	25.98	1.60	25.46	1.62	25.00	1.64	24.59	1.66	24.23	1.67	
				50	28.77	1.65	28.06	1.67	27.53	1.70	27.29	1.71	26.62	1.73	26.25	1.75	
				59	31.50	1.71	30.89	1.74	30.33	1.76	30.08	1.77	29.38	1.80	28.97	1.82	
				-13	20.05	2.74	19.12	2.76	18.58	2.80	17.48	2.84	16.94	2.87	15.84	2.87	
				5	27.00	3.35	26.42	3.39	25.66	3.43	25.00	3.47	24.43	3.50	23.96	3.53	
				17	26.63	2.88	26.14	2.91	25.54	2.95	25.00	2.99	24.53	3.02	24.13	3.04	
7	7	9	30	32	26.51	2.14	26.06	2.16	25.50	2.19	25.00	2.22	24.56	2.24	24.18	2.26	
				47	26.41	1.50	25.98	1.52	25.46	1.54	25.00	1.56	24.59	1.58	24.23	1.59	
				50	28.77	1.57	28.06	1.59	27.53	1.61	27.29	1.62	26.62	1.65	26.25	1.66	
				59	31.50	1.63	30.89	1.65	30.33	1.68	30.08	1.69	29.38	1.72	28.97	1.73	
				-13	20.05	2.74	19.12	2.76	18.58	2.80	17.48	2.84	16.94	2.87	15.84	2.87	
				5	27.00	3.35	26.42	3.39	25.66	3.43	25.00	3.47	24.43	3.50	23.96	3.53	
7	9	9	32	17	26.63	2.88	26.14	2.91	25.54	2.95	25.00	2.99	24.53	3.02	24.13	3.04	
				32	26.51	2.14	26.06	2.16	25.50	2.19	25.00	2.22	24.56	2.24	24.18	2.26	
				47	26.41	1.50	25.98	1.52	25.46	1.54	25.00	1.56	24.59	1.58	24.23	1.59	
				50	28.77	1.57	28.06	1.59	27.53	1.61	27.29	1.62	26.62	1.65	26.25	1.66	
				59	31.50	1.63	30.89	1.65	30.33	1.68	30.08	1.69	29.38	1.72	28.97	1.73	
				-13	20.05	2.74	19.12	2.76	18.58	2.80	17.48	2.84	16.94	2.87	15.84	2.87	
7	9	9	32	5	27.00	3.35	26.42	3.39	25.66	3.43	25.00	3.47	24.43	3.50	23.96	3.53	
				17	26.63	2.88	26.14	2.91	25.54	2.95	25.00	2.99	24.53	3.02	24.13	3.04	
				32	26.51	2.14	26.06	2.16	25.50	2.19	25.00	2.22	24.56	2.24	24.18	2.26	
				47	26.41	1.50	25.98	1.52	25.46	1.54	25.00	1.56	24.59	1.58	24.23	1.59	
				50	28.77	1.57	28.06	1.59	27.53	1.61	27.29	1.62	26.62	1.65	26.25	1.66	
				59	31.50	1.63	30.89	1.65	30.33	1.68	30.08	1.69	29.38	1.72	28.97	1.73	

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 32.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9		18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18	
				70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20	
				73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22	
				77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25	
				81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28	
				84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31	
				88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34	
				91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37	
				95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40	
				99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44	
				102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47	
				108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52	
9	12		21	111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56	
				115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59	
				68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37	
				70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42	
				77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45	
				81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48	
				84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52	
				88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55	
				91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59	
				95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62	
				99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66	
9	15		24	102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70	
				108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76	
				111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80	
				115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84	
				68	21.21	1.36	26.18	1.39	26.96	1.42	27.40	1.43	27.88	1.45	28.96	1.47	
				70	21.21	1.38	25.85	1.41	26.65	1.44	27.10	1.45	27.60	1.46	28.70	1.49	
				73	21.21	1.41	25.22	1.44	26.06	1.47	26.53	1.49	27.05	1.50	28.19	1.53	
				77	21.21	1.45	24.63	1.48	25.50	1.51	26.00	1.52	26.53	1.54	27.72	1.56	
				81	21.21	1.49	24.06	1.52	24.98	1.54	25.50	1.56	26.05	1.57	27.28	1.60	
				84	21.21	1.52	23.53	1.55	24.49	1.58	25.03	1.60	25.60	1.61	26.87	1.64	
				88	21.21	1.56	23.03	1.59	24.04	1.62	24.59	1.63	25.19	1.65	26.50	1.67	
				91	21.21	1.60	22.57	1.63	23.61	1.66	24.19	1.67	24.81	1.69	26.16	1.71	
95	21.21	1.64	22.14	1.67	23.22	1.70	24.00	1.71	24.46	1.73	25.85	1.75					
99	21.21	1.69	21.74	1.71	22.87	1.74	23.49	1.76	24.15	1.77	25.58	1.79					
102	21.21	1.73	21.38	1.76	22.55	1.78	23.19	1.80	23.87	1.81	25.34	1.84					
108	21.21	1.79	20.90	1.82	22.13	1.85	22.80	1.86	23.51	1.88	25.04	1.90					
111	21.21	1.84	20.62	1.87	21.89	1.89	22.58	1.91	23.31	1.92	24.89	1.95					
115	21.21	1.88	20.37	1.91	21.68	1.94	22.39	1.95	23.15	1.97	24.76	1.99					

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	23.07	1.80	28.47	1.84	29.31	1.88	29.80	1.90	31.50	1.95	32.84	1.98
					70	23.07	1.82	28.12	1.86	28.98	1.90	29.47	1.92	31.21	1.97	32.57	2.01
					73	23.07	1.87	27.43	1.91	28.34	1.95	28.86	1.96	30.66	2.02	32.06	2.05
					77	23.07	1.92	26.78	1.96	27.73	1.99	28.27	2.01	30.14	2.06	31.60	2.10
					81	23.07	1.96	26.17	2.00	27.17	2.04	27.73	2.06	29.66	2.11	31.16	2.15
					84	23.07	2.01	25.59	2.05	26.63	2.09	27.22	2.11	29.22	2.16	30.77	2.20
					88	23.07	2.07	25.05	2.10	26.14	2.14	26.75	2.16	28.82	2.21	30.41	2.25
					91	23.07	2.12	24.55	2.16	25.68	2.19	26.31	2.21	28.45	2.26	30.08	2.30
					95	23.07	2.17	24.08	2.21	25.26	2.25	26.10	2.26	28.11	2.32	29.79	2.35
					99	23.07	2.23	23.65	2.27	24.87	2.30	25.54	2.32	27.82	2.37	29.54	2.40
					102	23.07	2.28	23.25	2.32	24.52	2.36	25.22	2.38	27.56	2.43	29.33	2.46
					108	23.07	2.37	22.73	2.41	24.06	2.44	24.79	2.46	27.23	2.51	29.07	2.54
111	23.07	2.43	22.42	2.47	23.80	2.50	24.56	2.52	27.07	2.57	28.95	2.60					
115	23.07	2.49	22.15	2.53	23.58	2.56	24.35	2.58	26.93	2.63	28.86	2.66					
9	24			33	68	25.10	1.85	30.98	1.89	31.90	1.93	32.42	1.95	32.99	1.96	34.27	2.00
					70	25.10	1.87	30.59	1.91	31.53	1.95	32.07	1.97	32.65	1.99	33.96	2.02
					73	25.10	1.92	29.85	1.96	30.84	2.00	31.40	2.02	32.01	2.03	33.36	2.07
					77	25.10	1.97	29.14	2.01	30.18	2.05	30.77	2.06	31.40	2.08	32.80	2.12
					81	25.10	2.02	28.47	2.06	29.56	2.10	30.17	2.11	30.83	2.13	32.28	2.17
					84	25.10	2.07	27.85	2.11	28.98	2.15	29.62	2.17	30.30	2.18	31.80	2.22
					88	25.10	2.12	27.26	2.16	28.44	2.20	29.10	2.22	29.81	2.24	31.36	2.27
					91	25.10	2.17	26.71	2.21	27.94	2.25	28.63	2.27	29.36	2.29	30.95	2.32
					95	25.10	2.23	26.20	2.27	27.48	2.31	28.40	2.32	28.95	2.34	30.59	2.38
					99	25.10	2.29	25.73	2.33	27.06	2.36	27.80	2.38	28.57	2.40	30.27	2.43
					102	25.10	2.34	25.30	2.38	26.68	2.42	27.44	2.44	28.24	2.46	29.99	2.49
					108	25.10	2.43	24.73	2.47	26.18	2.51	26.98	2.53	27.82	2.54	29.63	2.58
111	25.10	2.49	24.40	2.53	25.90	2.57	26.72	2.59	27.58	2.60	29.45	2.64					
115	25.10	2.56	24.10	2.59	25.66	2.63	26.50	2.65	27.39	2.67	29.30	2.70					
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04					
115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09					

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	23.86	1.73	29.45	1.77	30.32	1.80	30.82	1.82	31.37	1.84	32.58	1.87
					70	23.86	1.75	29.09	1.79	29.98	1.82	30.49	1.84	31.05	1.86	32.28	1.89
					73	23.86	1.79	28.38	1.83	29.32	1.87	29.85	1.89	30.43	1.90	31.71	1.94
					77	23.86	1.84	27.70	1.88	28.69	1.91	29.25	1.93	29.85	1.95	31.18	1.98
					81	23.86	1.89	27.07	1.92	28.10	1.96	28.68	1.98	29.31	1.99	30.69	2.03
					84	23.86	1.93	26.47	1.97	27.55	2.01	28.16	2.03	28.81	2.04	30.23	2.08
					88	23.86	1.98	25.91	2.02	27.04	2.06	27.67	2.07	28.34	2.09	29.81	2.12
					91	23.86	2.03	25.39	2.07	26.57	2.11	27.22	2.12	27.91	2.14	29.43	2.17
					95	23.86	2.09	24.91	2.12	26.13	2.16	27.00	2.17	27.52	2.19	29.08	2.23
					99	23.86	2.14	24.46	2.18	25.73	2.21	26.43	2.23	27.17	2.24	28.78	2.28
					102	23.86	2.19	24.05	2.23	25.37	2.26	26.09	2.28	26.85	2.30	28.51	2.33
					108	23.86	2.28	23.51	2.31	24.89	2.35	25.65	2.36	26.45	2.38	28.17	2.41
					111	23.86	2.33	23.19	2.37	24.62	2.40	25.40	2.42	26.22	2.44	28.00	2.47
					115	23.86	2.39	22.92	2.43	24.39	2.46	25.19	2.48	26.04	2.49	27.86	2.53
12	18			30	68	25.10	1.93	30.98	1.98	31.90	2.02	32.42	2.04	34.27	2.10	35.73	2.13
					70	25.10	1.96	30.59	2.00	31.53	2.04	32.07	2.06	33.96	2.12	35.44	2.16
					73	25.10	2.01	29.85	2.05	30.84	2.09	31.40	2.11	33.36	2.17	34.89	2.20
					77	25.10	2.06	29.14	2.10	30.18	2.14	30.77	2.16	32.80	2.22	34.38	2.26
					81	25.10	2.11	28.47	2.15	29.56	2.19	30.17	2.21	32.28	2.27	33.91	2.31
					84	25.10	2.17	27.85	2.21	28.98	2.25	29.62	2.27	31.80	2.32	33.48	2.36
					88	25.10	2.22	27.26	2.26	28.44	2.30	29.10	2.32	31.36	2.38	33.08	2.41
					91	25.10	2.28	26.71	2.32	27.94	2.36	28.63	2.38	30.95	2.43	32.73	2.47
					95	25.10	2.34	26.20	2.38	27.48	2.42	28.40	2.43	30.59	2.49	32.42	2.53
					99	25.10	2.39	25.73	2.44	27.06	2.48	27.80	2.49	30.27	2.55	32.14	2.59
					102	25.10	2.46	25.30	2.50	26.68	2.54	27.44	2.55	29.99	2.61	31.91	2.64
					108	25.10	2.55	24.73	2.59	26.18	2.63	26.98	2.65	29.63	2.70	31.63	2.74
					111	25.10	2.61	24.40	2.65	25.90	2.69	26.72	2.71	29.45	2.76	31.50	2.80
					115	25.10	2.68	24.10	2.72	25.66	2.76	26.50	2.77	29.30	2.83	31.40	2.86
12	24			36	68	25.10	1.95	30.98	1.99	31.90	2.03	32.42	2.05	32.99	2.07	34.27	2.11
					70	25.10	1.97	30.59	2.02	31.53	2.06	32.07	2.08	32.65	2.10	33.96	2.14
					73	25.10	2.03	29.85	2.07	30.84	2.11	31.40	2.13	32.01	2.15	33.36	2.19
					77	25.10	2.08	29.14	2.12	30.18	2.16	30.77	2.18	31.40	2.20	32.80	2.24
					81	25.10	2.13	28.47	2.17	29.56	2.21	30.17	2.23	30.83	2.25	32.28	2.29
					84	25.10	2.18	27.85	2.23	28.98	2.27	29.62	2.29	30.30	2.31	31.80	2.34
					88	25.10	2.24	27.26	2.28	28.44	2.32	29.10	2.34	29.81	2.36	31.36	2.40
					91	25.10	2.30	26.71	2.34	27.94	2.38	28.63	2.40	29.36	2.42	30.95	2.45
					95	25.10	2.35	26.20	2.40	27.48	2.44	28.40	2.45	28.95	2.48	30.59	2.51
					99	25.10	2.41	25.73	2.46	27.06	2.50	27.80	2.52	28.57	2.53	30.27	2.57
					102	25.10	2.48	25.30	2.52	26.68	2.56	27.44	2.58	28.24	2.59	29.99	2.63
					108	25.10	2.57	24.73	2.61	26.18	2.65	26.98	2.67	27.82	2.69	29.63	2.72
					111	25.10	2.63	24.40	2.67	25.90	2.71	26.72	2.73	27.58	2.75	29.45	2.79
					115	25.10	2.70	24.10	2.74	25.66	2.78	26.50	2.80	27.39	2.82	29.30	2.85

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	18			33	68	25.10	1.85	30.98	1.89	31.90	1.93	32.42	1.95	32.99	1.96	34.27	2.00
					70	25.10	1.87	30.59	1.91	31.53	1.95	32.07	1.97	32.65	1.99	33.96	2.02
					73	25.10	1.92	29.85	1.96	30.84	2.00	31.40	2.02	32.01	2.03	33.36	2.07
					77	25.10	1.97	29.14	2.01	30.18	2.05	30.77	2.06	31.40	2.08	32.80	2.12
					81	25.10	2.02	28.47	2.06	29.56	2.10	30.17	2.11	30.83	2.13	32.28	2.17
					84	25.10	2.07	27.85	2.11	28.98	2.15	29.62	2.17	30.30	2.18	31.80	2.22
					88	25.10	2.12	27.26	2.16	28.44	2.20	29.10	2.22	29.81	2.24	31.36	2.27
					91	25.10	2.17	26.71	2.21	27.94	2.25	28.63	2.27	29.36	2.29	30.95	2.32
					95	25.10	2.23	26.20	2.27	27.48	2.31	28.40	2.32	28.95	2.34	30.59	2.38
					99	25.10	2.29	25.73	2.33	27.06	2.36	27.80	2.38	28.57	2.40	30.27	2.43
					102	25.10	2.34	25.30	2.38	26.68	2.42	27.44	2.44	28.24	2.46	29.99	2.49
					108	25.10	2.43	24.73	2.47	26.18	2.51	26.98	2.53	27.82	2.54	29.63	2.58
111	25.10	2.49	24.40	2.53	25.90	2.57	26.72	2.59	27.58	2.60	29.45	2.64					
115	25.10	2.56	24.10	2.59	25.66	2.63	26.50	2.65	27.39	2.67	29.30	2.70					
18	18			36	68	25.10	1.95	30.98	1.99	31.90	2.03	32.42	2.05	34.27	2.11	35.73	2.15
					70	25.10	1.97	30.59	2.02	31.53	2.06	32.07	2.08	33.96	2.14	35.44	2.17
					73	25.10	2.03	29.85	2.07	30.84	2.11	31.40	2.13	33.36	2.19	34.89	2.22
					77	25.10	2.08	29.14	2.12	30.18	2.16	30.77	2.18	32.80	2.24	34.38	2.27
					81	25.10	2.13	28.47	2.17	29.56	2.21	30.17	2.23	32.28	2.29	33.91	2.33
					84	25.10	2.18	27.85	2.23	28.98	2.27	29.62	2.29	31.80	2.34	33.48	2.38
					88	25.10	2.24	27.26	2.28	28.44	2.32	29.10	2.34	31.36	2.40	33.08	2.43
					91	25.10	2.30	26.71	2.34	27.94	2.38	28.63	2.40	30.95	2.45	32.73	2.49
					95	25.10	2.35	26.20	2.40	27.48	2.44	28.40	2.45	30.59	2.51	32.42	2.55
					99	25.10	2.41	25.73	2.46	27.06	2.50	27.80	2.52	30.27	2.57	32.14	2.61
					102	25.10	2.48	25.30	2.52	26.68	2.56	27.44	2.58	29.99	2.63	31.91	2.67
					108	25.10	2.57	24.73	2.61	26.18	2.65	26.98	2.67	29.63	2.72	31.63	2.76
					111	25.10	2.63	24.40	2.67	25.90	2.71	26.72	2.73	29.45	2.79	31.50	2.82
115	25.10	2.70	24.10	2.74	25.66	2.78	26.50	2.80	29.30	2.85	31.40	2.89					
9	9	9		27	68	23.86	2.01	29.45	2.06	30.32	2.10	30.82	2.12	32.58	2.18	33.97	2.22
					70	23.86	2.04	29.09	2.08	29.98	2.13	30.49	2.15	32.28	2.21	33.69	2.24
					73	23.86	2.09	28.38	2.14	29.32	2.18	29.85	2.20	31.71	2.26	33.17	2.30
					77	23.86	2.14	27.70	2.19	28.69	2.23	29.25	2.25	31.18	2.31	32.68	2.35
					81	23.86	2.20	27.07	2.24	28.10	2.29	28.68	2.31	30.69	2.36	32.24	2.40
					84	23.86	2.26	26.47	2.30	27.55	2.34	28.16	2.36	30.23	2.42	31.83	2.46
					88	23.86	2.31	25.91	2.36	27.04	2.40	27.67	2.42	29.81	2.48	31.45	2.51
					91	23.86	2.37	25.39	2.41	26.57	2.46	27.22	2.48	29.43	2.53	31.12	2.57
					95	23.86	2.43	24.91	2.47	26.13	2.52	27.00	2.53	29.08	2.59	30.82	2.63
					99	23.86	2.49	24.46	2.54	25.73	2.58	26.43	2.60	28.78	2.65	30.56	2.69
					102	23.86	2.56	24.05	2.60	25.37	2.64	26.09	2.66	28.51	2.72	30.34	2.75
					108	23.86	2.65	23.51	2.70	24.89	2.74	25.65	2.76	28.17	2.81	30.07	2.85
					111	23.86	2.72	23.19	2.76	24.62	2.80	25.40	2.82	28.00	2.88	29.94	2.91
115	23.86	2.79	22.92	2.83	24.39	2.87	25.19	2.89	27.86	2.94	29.85	2.98					

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	30	68	25.10	1.93	30.98	1.98	31.90	2.02	32.42	2.04	34.27	2.10	35.73	2.13	
				70	25.10	1.96	30.59	2.00	31.53	2.04	32.07	2.06	33.96	2.12	35.44	2.16	
				73	25.10	2.01	29.85	2.05	30.84	2.09	31.40	2.11	33.36	2.17	34.89	2.20	
				77	25.10	2.06	29.14	2.10	30.18	2.14	30.77	2.16	32.80	2.22	34.38	2.26	
				81	25.10	2.11	28.47	2.15	29.56	2.19	30.17	2.21	32.28	2.27	33.91	2.31	
				84	25.10	2.17	27.85	2.21	28.98	2.25	29.62	2.27	31.80	2.32	33.48	2.36	
				88	25.10	2.22	27.26	2.26	28.44	2.30	29.10	2.32	31.36	2.38	33.08	2.41	
				91	25.10	2.28	26.71	2.32	27.94	2.36	28.63	2.38	30.95	2.43	32.73	2.47	
				95	25.10	2.34	26.20	2.38	27.48	2.42	28.40	2.43	30.59	2.49	32.42	2.53	
				99	25.10	2.39	25.73	2.44	27.06	2.48	27.80	2.49	30.27	2.55	32.14	2.59	
				102	25.10	2.46	25.30	2.50	26.68	2.54	27.44	2.55	29.99	2.61	31.91	2.64	
				108	25.10	2.55	24.73	2.59	26.18	2.63	26.98	2.65	29.63	2.70	31.63	2.74	
9	9	15	33	111	25.10	2.61	24.40	2.65	25.90	2.69	26.72	2.71	29.45	2.76	31.50	2.80	
				115	25.10	2.68	24.10	2.72	25.66	2.76	26.50	2.77	29.30	2.83	31.40	2.86	
				68	25.10	1.85	30.98	1.89	31.90	1.93	32.42	1.95	32.99	1.96	34.27	2.00	
				70	25.10	1.87	30.59	1.91	31.53	1.95	32.07	1.97	32.65	1.99	33.96	2.02	
				73	25.10	1.92	29.85	1.96	30.84	2.00	31.40	2.02	32.01	2.03	33.36	2.07	
				77	25.10	1.97	29.14	2.01	30.18	2.05	30.77	2.06	31.40	2.08	32.80	2.12	
				81	25.10	2.02	28.47	2.06	29.56	2.10	30.17	2.11	30.83	2.13	32.28	2.17	
				84	25.10	2.07	27.85	2.11	28.98	2.15	29.62	2.17	30.30	2.18	31.80	2.22	
				88	25.10	2.12	27.26	2.16	28.44	2.20	29.10	2.22	29.81	2.24	31.36	2.27	
				91	25.10	2.17	26.71	2.21	27.94	2.25	28.63	2.27	29.36	2.29	30.95	2.32	
				95	25.10	2.23	26.20	2.27	27.48	2.31	28.40	2.32	28.95	2.34	30.59	2.38	
				99	25.10	2.29	25.73	2.33	27.06	2.36	27.80	2.38	28.57	2.40	30.27	2.43	
9	9	18	36	102	25.10	2.34	25.30	2.38	26.68	2.42	27.44	2.44	28.24	2.46	29.99	2.49	
				108	25.10	2.43	24.73	2.47	26.18	2.51	26.98	2.53	27.82	2.54	29.63	2.58	
				111	25.10	2.49	24.40	2.53	25.90	2.57	26.72	2.59	27.58	2.60	29.45	2.64	
				115	25.10	2.56	24.10	2.59	25.66	2.63	26.50	2.65	27.39	2.67	29.30	2.70	
				68	25.10	1.68	30.98	1.72	31.90	1.75	32.42	1.77	34.27	1.82	35.73	1.85	
				70	25.10	1.70	30.59	1.74	31.53	1.77	32.07	1.79	33.96	1.84	35.44	1.87	
				73	25.10	1.74	29.85	1.78	30.84	1.82	31.40	1.83	33.36	1.88	34.89	1.91	
				77	25.10	1.79	29.14	1.83	30.18	1.86	30.77	1.88	32.80	1.93	34.38	1.96	
				81	25.10	1.83	28.47	1.87	29.56	1.91	30.17	1.92	32.28	1.97	33.91	2.00	
				84	25.10	1.88	27.85	1.92	28.98	1.95	29.62	1.97	31.80	2.02	33.48	2.05	
				88	25.10	1.93	27.26	1.97	28.44	2.00	29.10	2.02	31.36	2.07	33.08	2.10	
				91	25.10	1.98	26.71	2.01	27.94	2.05	28.63	2.07	30.95	2.11	32.73	2.14	
95	25.10	2.03	26.20	2.06	27.48	2.10	28.40	2.11	30.59	2.16	32.42	2.19					
99	25.10	2.08	25.73	2.11	27.06	2.15	27.80	2.17	30.27	2.21	32.14	2.24					
102	25.10	2.13	25.30	2.17	26.68	2.20	27.44	2.22	29.99	2.27	31.91	2.30					
108	25.10	2.21	24.73	2.25	26.18	2.28	26.98	2.30	29.63	2.35	31.63	2.38					
111	25.10	2.27	24.40	2.30	25.90	2.34	26.72	2.35	29.45	2.40	31.50	2.43					
115	25.10	2.32	24.10	2.36	25.66	2.39	26.50	2.41	29.30	2.46	31.40	2.49					

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12		33	68	25.10	1.76	30.98	1.80	31.90	1.84	32.42	1.85	34.27	1.91	35.73	1.94
					70	25.10	1.78	30.59	1.82	31.53	1.86	32.07	1.88	33.96	1.93	35.44	1.96
					73	25.10	1.83	29.85	1.87	30.84	1.90	31.40	1.92	33.36	1.97	34.89	2.01
					77	25.10	1.87	29.14	1.91	30.18	1.95	30.77	1.97	32.80	2.02	34.38	2.05
					81	25.10	1.92	28.47	1.96	29.56	2.00	30.17	2.01	32.28	2.07	33.91	2.10
					84	25.10	1.97	27.85	2.01	28.98	2.04	29.62	2.06	31.80	2.11	33.48	2.15
					88	25.10	2.02	27.26	2.06	28.44	2.09	29.10	2.11	31.36	2.16	33.08	2.20
					91	25.10	2.07	26.71	2.11	27.94	2.15	28.63	2.16	30.95	2.21	32.73	2.25
					95	25.10	2.12	26.20	2.16	27.48	2.20	28.40	2.21	30.59	2.27	32.42	2.30
					99	25.10	2.18	25.73	2.22	27.06	2.25	27.80	2.27	30.27	2.32	32.14	2.35
					102	25.10	2.23	25.30	2.27	26.68	2.31	27.44	2.32	29.99	2.37	31.91	2.41
					108	25.10	2.32	24.73	2.35	26.18	2.39	26.98	2.41	29.63	2.46	31.63	2.49
9	12	15		36	111	25.10	2.38	24.40	2.41	25.90	2.45	26.72	2.46	29.45	2.51	31.50	2.55
					115	25.10	2.43	24.10	2.47	25.66	2.51	26.50	2.52	29.30	2.57	31.40	2.60
					68	25.10	1.68	30.98	1.72	31.90	1.75	32.42	1.77	32.99	1.79	34.27	1.82
					70	25.10	1.70	30.59	1.74	31.53	1.77	32.07	1.79	32.65	1.81	33.96	1.84
					73	25.10	1.74	29.85	1.78	30.84	1.82	31.40	1.83	32.01	1.85	33.36	1.88
					77	25.10	1.79	29.14	1.83	30.18	1.86	30.77	1.88	31.40	1.89	32.80	1.93
					81	25.10	1.83	28.47	1.87	29.56	1.91	30.17	1.92	30.83	1.94	32.28	1.97
					84	25.10	1.88	27.85	1.92	28.98	1.95	29.62	1.97	30.30	1.99	31.80	2.02
					88	25.10	1.93	27.26	1.97	28.44	2.00	29.10	2.02	29.81	2.03	31.36	2.07
					91	25.10	1.98	26.71	2.01	27.94	2.05	28.63	2.07	29.36	2.08	30.95	2.11
					95	25.10	2.03	26.20	2.06	27.48	2.10	28.40	2.11	28.95	2.13	30.59	2.16
					99	25.10	2.08	25.73	2.11	27.06	2.15	27.80	2.17	28.57	2.18	30.27	2.21
9	12	18	39	102	25.10	2.13	25.30	2.17	26.68	2.20	27.44	2.22	28.24	2.23	29.99	2.27	
				108	25.10	2.21	24.73	2.25	26.18	2.28	26.98	2.30	27.82	2.31	29.63	2.35	
				111	25.10	2.27	24.40	2.30	25.90	2.34	26.72	2.35	27.58	2.37	29.45	2.40	
				115	25.10	2.32	24.10	2.36	25.66	2.39	26.50	2.41	27.39	2.42	29.30	2.46	
				68	25.10	1.68	30.98	1.72	31.90	1.75	32.42	1.77	34.27	1.82	35.73	1.85	
				70	25.10	1.70	30.59	1.74	31.53	1.77	32.07	1.79	33.96	1.84	35.44	1.87	
				73	25.10	1.74	29.85	1.78	30.84	1.82	31.40	1.83	33.36	1.88	34.89	1.91	
				77	25.10	1.79	29.14	1.83	30.18	1.86	30.77	1.88	32.80	1.93	34.38	1.96	
				81	25.10	1.83	28.47	1.87	29.56	1.91	30.17	1.92	32.28	1.97	33.91	2.00	
				84	25.10	1.88	27.85	1.92	28.98	1.95	29.62	1.97	31.80	2.02	33.48	2.05	
				88	25.10	1.93	27.26	1.97	28.44	2.00	29.10	2.02	31.36	2.07	33.08	2.10	
				91	25.10	1.98	26.71	2.01	27.94	2.05	28.63	2.07	30.95	2.11	32.73	2.14	
				95	25.10	2.03	26.20	2.06	27.48	2.10	28.40	2.11	30.59	2.16	32.42	2.19	
				99	25.10	2.08	25.73	2.11	27.06	2.15	27.80	2.17	30.27	2.21	32.14	2.24	
				102	25.10	2.13	25.30	2.17	26.68	2.20	27.44	2.22	29.99	2.27	31.91	2.30	
				108	25.10	2.21	24.73	2.25	26.18	2.28	26.98	2.30	29.63	2.35	31.63	2.38	
				111	25.10	2.27	24.40	2.30	25.90	2.34	26.72	2.35	29.45	2.40	31.50	2.43	
				115	25.10	2.32	24.10	2.36	25.66	2.39	26.50	2.41	29.30	2.46	31.40	2.49	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	12		36	68	25.10	1.68	30.98	1.72	31.90	1.75	32.42	1.77	34.27	1.82	35.73	1.85
					70	25.10	1.70	30.59	1.74	31.53	1.77	32.07	1.79	33.96	1.84	35.44	1.87
					73	25.10	1.74	29.85	1.78	30.84	1.82	31.40	1.83	33.36	1.88	34.89	1.91
					77	25.10	1.79	29.14	1.83	30.18	1.86	30.77	1.88	32.80	1.93	34.38	1.96
					81	25.10	1.83	28.47	1.87	29.56	1.91	30.17	1.92	32.28	1.97	33.91	2.00
					84	25.10	1.88	27.85	1.92	28.98	1.95	29.62	1.97	31.80	2.02	33.48	2.05
					88	25.10	1.93	27.26	1.97	28.44	2.00	29.10	2.02	31.36	2.07	33.08	2.10
					91	25.10	1.98	26.71	2.01	27.94	2.05	28.63	2.07	30.95	2.11	32.73	2.14
					95	25.10	2.03	26.20	2.06	27.48	2.10	28.40	2.11	30.59	2.16	32.42	2.19
					99	25.10	2.08	25.73	2.11	27.06	2.15	27.80	2.17	30.27	2.21	32.14	2.24
					102	25.10	2.13	25.30	2.17	26.68	2.20	27.44	2.22	29.99	2.27	31.91	2.30
					108	25.10	2.21	24.73	2.25	26.18	2.28	26.98	2.30	29.63	2.35	31.63	2.38
					111	25.10	2.27	24.40	2.30	25.90	2.34	26.72	2.35	29.45	2.40	31.50	2.43
					115	25.10	2.32	24.10	2.36	25.66	2.39	26.50	2.41	29.30	2.46	31.40	2.49
9	9	9	9	36	68	25.10	1.74	30.98	1.77	31.90	1.81	32.42	1.83	34.27	1.88	35.73	1.91
					70	25.10	1.76	30.59	1.80	31.53	1.83	32.07	1.85	33.96	1.90	35.44	1.93
					73	25.10	1.80	29.85	1.84	30.84	1.88	31.40	1.89	33.36	1.95	34.89	1.98
					77	25.10	1.85	29.14	1.89	30.18	1.92	30.77	1.94	32.80	1.99	34.38	2.02
					81	25.10	1.90	28.47	1.93	29.56	1.97	30.17	1.99	32.28	2.04	33.91	2.07
					84	25.10	1.94	27.85	1.98	28.98	2.02	29.62	2.03	31.80	2.09	33.48	2.12
					88	25.10	1.99	27.26	2.03	28.44	2.07	29.10	2.08	31.36	2.13	33.08	2.17
					91	25.10	2.04	26.71	2.08	27.94	2.12	28.63	2.13	30.95	2.18	32.73	2.22
					95	25.10	2.10	26.20	2.13	27.48	2.17	28.40	2.18	30.59	2.24	32.42	2.27
					99	25.10	2.15	25.73	2.19	27.06	2.22	27.80	2.24	30.27	2.29	32.14	2.32
					102	25.10	2.20	25.30	2.24	26.68	2.27	27.44	2.29	29.99	2.34	31.91	2.37
					108	25.10	2.29	24.73	2.32	26.18	2.36	26.98	2.37	29.63	2.42	31.63	2.45
					111	25.10	2.34	24.40	2.38	25.90	2.41	26.72	2.43	29.45	2.48	31.50	2.51
					115	25.10	2.40	24.10	2.44	25.66	2.47	26.50	2.49	29.30	2.54	31.40	2.57
9	9	9	12	39	68	25.10	1.74	30.98	1.77	31.90	1.81	32.42	1.83	34.27	1.88	35.73	1.91
					70	25.10	1.76	30.59	1.80	31.53	1.83	32.07	1.85	33.96	1.90	35.44	1.93
					73	25.10	1.80	29.85	1.84	30.84	1.88	31.40	1.89	33.36	1.95	34.89	1.98
					77	25.10	1.85	29.14	1.89	30.18	1.92	30.77	1.94	32.80	1.99	34.38	2.02
					81	25.10	1.90	28.47	1.93	29.56	1.97	30.17	1.99	32.28	2.04	33.91	2.07
					84	25.10	1.94	27.85	1.98	28.98	2.02	29.62	2.03	31.80	2.09	33.48	2.12
					88	25.10	1.99	27.26	2.03	28.44	2.07	29.10	2.08	31.36	2.13	33.08	2.17
					91	25.10	2.04	26.71	2.08	27.94	2.12	28.63	2.13	30.95	2.18	32.73	2.22
					95	25.10	2.10	26.20	2.13	27.48	2.17	28.40	2.18	30.59	2.24	32.42	2.27
					99	25.10	2.15	25.73	2.19	27.06	2.22	27.80	2.24	30.27	2.29	32.14	2.32
					102	25.10	2.20	25.30	2.24	26.68	2.27	27.44	2.29	29.99	2.34	31.91	2.37
					108	25.10	2.29	24.73	2.32	26.18	2.36	26.98	2.37	29.63	2.42	31.63	2.45
					111	25.10	2.34	24.40	2.38	25.90	2.41	26.72	2.43	29.45	2.48	31.50	2.51
					115	25.10	2.40	24.10	2.44	25.66	2.47	26.50	2.49	29.30	2.54	31.40	2.57

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 39.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7			14	68	12.37	0.91	15.27	0.93	15.72	0.95	15.98	0.96	16.89	0.98	17.61	1.00
					70	12.37	0.92	15.08	0.94	15.54	0.96	15.81	0.97	16.74	0.99	17.47	1.01
					73	12.37	0.94	14.71	0.96	15.20	0.98	15.48	0.99	16.44	1.02	17.20	1.03
					77	12.37	0.97	14.37	0.99	14.88	1.01	15.17	1.01	16.17	1.04	16.95	1.06
					81	12.37	0.99	14.04	1.01	14.57	1.03	14.87	1.04	15.91	1.07	16.72	1.08
					84	12.37	1.02	13.73	1.04	14.29	1.05	14.60	1.06	15.67	1.09	16.50	1.11
					88	12.37	1.04	13.44	1.06	14.02	1.08	14.35	1.09	15.46	1.12	16.31	1.13
					91	12.37	1.07	13.17	1.09	13.77	1.11	14.11	1.12	15.26	1.14	16.14	1.16
					95	12.37	1.10	12.92	1.12	13.55	1.13	14.00	1.14	15.08	1.17	15.98	1.19
					99	12.37	1.12	12.68	1.14	13.34	1.16	13.70	1.17	14.92	1.20	15.85	1.21
					102	12.37	1.15	12.47	1.17	13.15	1.19	13.53	1.20	14.78	1.22	15.73	1.24
					108	12.37	1.20	12.19	1.21	12.91	1.23	13.30	1.24	14.61	1.27	15.59	1.28
					111	12.37	1.23	12.03	1.24	12.77	1.26	13.17	1.27	14.52	1.30	15.53	1.31
					115	12.37	1.26	11.88	1.27	12.65	1.29	13.06	1.30	14.45	1.33	15.48	1.34
7	9			16	68	14.14	1.00	17.45	1.02	17.97	1.04	18.27	1.05	19.31	1.08	20.13	1.10
					70	14.14	1.01	17.24	1.03	17.77	1.05	18.07	1.06	19.13	1.09	19.97	1.11
					73	14.14	1.03	16.82	1.06	17.37	1.08	17.69	1.09	18.79	1.12	19.66	1.13
					77	14.14	1.06	16.42	1.08	17.00	1.10	17.33	1.11	18.48	1.14	19.37	1.16
					81	14.14	1.09	16.04	1.11	16.65	1.13	17.00	1.14	18.18	1.17	19.10	1.19
					84	14.14	1.11	15.69	1.14	16.33	1.16	16.69	1.17	17.91	1.20	18.86	1.21
					88	14.14	1.14	15.36	1.16	16.02	1.18	16.40	1.19	17.67	1.22	18.64	1.24
					91	14.14	1.17	15.05	1.19	15.74	1.21	16.13	1.22	17.44	1.25	18.44	1.27
					95	14.14	1.20	14.76	1.22	15.48	1.24	16.00	1.25	17.23	1.28	18.26	1.30
					99	14.14	1.23	14.50	1.25	15.25	1.27	15.66	1.28	17.05	1.31	18.11	1.33
					102	14.14	1.26	14.25	1.28	15.03	1.30	15.46	1.31	16.89	1.34	17.98	1.36
					108	14.14	1.31	13.93	1.33	14.75	1.35	15.20	1.36	16.70	1.39	17.82	1.41
					111	14.14	1.34	13.74	1.36	14.59	1.38	15.05	1.39	16.59	1.42	17.74	1.44
					115	14.14	1.38	13.58	1.40	14.45	1.42	14.93	1.43	16.51	1.46	17.69	1.47
7	12			19	68	16.79	1.16	20.73	1.19	21.34	1.21	21.69	1.22	22.93	1.26	23.90	1.28
					70	16.79	1.18	20.47	1.20	21.10	1.23	21.46	1.24	22.72	1.27	23.71	1.30
					73	16.79	1.21	19.97	1.23	20.63	1.26	21.01	1.27	22.32	1.30	23.34	1.32
					77	16.79	1.24	19.50	1.26	20.19	1.29	20.58	1.30	21.94	1.33	23.00	1.36
					81	16.79	1.27	19.05	1.29	19.78	1.32	20.19	1.33	21.59	1.36	22.69	1.39
					84	16.79	1.30	18.63	1.33	19.39	1.35	19.81	1.36	21.27	1.40	22.40	1.42
					88	16.79	1.33	18.24	1.36	19.03	1.38	19.47	1.40	20.98	1.43	22.13	1.45
					91	16.79	1.37	17.87	1.39	18.69	1.42	19.15	1.43	20.71	1.46	21.90	1.48
					95	16.79	1.40	17.53	1.43	18.39	1.45	19.00	1.46	20.47	1.50	21.69	1.52
					99	16.79	1.44	17.21	1.46	18.10	1.49	18.60	1.50	20.25	1.53	21.51	1.55
					102	16.79	1.48	16.93	1.50	17.85	1.52	18.36	1.53	20.06	1.57	21.35	1.59
					108	16.79	1.53	16.54	1.56	17.52	1.58	18.05	1.59	19.83	1.62	21.16	1.64
					111	16.79	1.57	16.32	1.59	17.33	1.62	17.88	1.63	19.70	1.66	21.07	1.68
					115	16.79	1.61	16.13	1.63	17.16	1.66	17.73	1.67	19.61	1.70	21.01	1.72

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15			22	68	19.44	1.33	24.00	1.36	24.71	1.39	25.12	1.40	25.56	1.41	26.55	1.44
					70	19.44	1.35	23.70	1.38	24.43	1.40	24.84	1.42	25.30	1.43	26.30	1.46
					73	19.44	1.38	23.12	1.41	23.89	1.44	24.32	1.45	24.79	1.46	25.84	1.49
					77	19.44	1.42	22.57	1.44	23.38	1.47	23.83	1.49	24.32	1.50	25.41	1.53
					81	19.44	1.45	22.06	1.48	22.90	1.51	23.37	1.52	23.88	1.54	25.00	1.56
					84	19.44	1.49	21.57	1.52	22.45	1.55	22.94	1.56	23.47	1.57	24.63	1.60
					88	19.44	1.53	21.12	1.56	22.03	1.58	22.54	1.60	23.09	1.61	24.29	1.63
					91	19.44	1.57	20.69	1.59	21.65	1.62	22.18	1.63	22.74	1.65	23.98	1.67
					95	19.44	1.61	20.30	1.63	21.29	1.66	22.00	1.67	22.42	1.69	23.70	1.71
					99	19.44	1.65	19.93	1.67	20.96	1.70	21.53	1.71	22.14	1.73	23.45	1.75
					102	19.44	1.69	19.60	1.72	20.67	1.74	21.26	1.76	21.88	1.77	23.23	1.79
					108	19.44	1.75	19.16	1.78	20.28	1.81	20.90	1.82	21.55	1.83	22.96	1.86
					111	19.44	1.79	18.90	1.82	20.06	1.85	20.70	1.86	21.37	1.88	22.81	1.90
					115	19.44	1.84	18.67	1.87	19.87	1.89	20.53	1.91	21.22	1.92	22.70	1.94
7	18			25	68	21.30	1.43	26.29	1.46	27.07	1.49	27.51	1.51	29.08	1.55	30.32	1.58
					70	21.30	1.45	25.96	1.48	26.76	1.51	27.22	1.53	28.82	1.57	30.07	1.60
					73	21.30	1.49	25.33	1.52	26.17	1.55	26.64	1.56	28.31	1.61	29.61	1.63
					77	21.30	1.53	24.73	1.56	25.61	1.59	26.11	1.60	27.83	1.64	29.17	1.67
					81	21.30	1.56	24.16	1.60	25.08	1.63	25.60	1.64	27.39	1.68	28.77	1.71
					84	21.30	1.60	23.63	1.64	24.59	1.67	25.13	1.68	26.98	1.72	28.41	1.75
					88	21.30	1.65	23.13	1.68	24.14	1.71	24.70	1.72	26.61	1.76	28.08	1.79
					91	21.30	1.69	22.67	1.72	23.71	1.75	24.29	1.76	26.27	1.80	27.78	1.83
					95	21.30	1.73	22.23	1.76	23.32	1.79	24.10	1.80	25.96	1.85	27.51	1.87
					99	21.30	1.77	21.83	1.80	22.96	1.83	23.59	1.85	25.69	1.89	27.28	1.91
					102	21.30	1.82	21.47	1.85	22.64	1.88	23.28	1.89	25.45	1.93	27.08	1.96
					108	21.30	1.89	20.98	1.92	22.22	1.95	22.89	1.96	25.15	2.00	26.84	2.03
					111	21.30	1.93	20.70	1.96	21.98	1.99	22.67	2.01	24.99	2.05	26.73	2.07
					115	21.30	1.98	20.45	2.01	21.77	2.04	22.49	2.05	24.87	2.10	26.65	2.12
7	24			31	68	25.10	2.12	30.98	2.16	31.90	2.21	32.42	2.23	34.27	2.29	35.73	2.33
					70	25.10	2.14	30.59	2.19	31.53	2.24	32.07	2.26	33.96	2.32	35.44	2.36
					73	25.10	2.20	29.85	2.25	30.84	2.29	31.40	2.31	33.36	2.37	34.89	2.41
					77	25.10	2.26	29.14	2.30	30.18	2.35	30.77	2.37	32.80	2.43	34.38	2.47
					81	25.10	2.31	28.47	2.36	29.56	2.40	30.17	2.42	32.28	2.49	33.91	2.53
					84	25.10	2.37	27.85	2.42	28.98	2.46	29.62	2.48	31.80	2.54	33.48	2.58
					88	25.10	2.43	27.26	2.48	28.44	2.52	29.10	2.54	31.36	2.60	33.08	2.64
					91	25.10	2.49	26.71	2.54	27.94	2.58	28.63	2.60	30.95	2.67	32.73	2.70
					95	25.10	2.56	26.20	2.60	27.48	2.65	28.40	2.66	30.59	2.73	32.42	2.77
					99	25.10	2.62	25.73	2.67	27.06	2.71	27.80	2.73	30.27	2.79	32.14	2.83
					102	25.10	2.69	25.30	2.73	26.68	2.78	27.44	2.80	29.99	2.86	31.91	2.89
					108	25.10	2.79	24.73	2.83	26.18	2.88	26.98	2.90	29.63	2.96	31.63	3.00
					111	25.10	2.86	24.40	2.90	25.90	2.95	26.72	2.97	29.45	3.03	31.50	3.06
					115	25.10	2.93	24.10	2.97	25.66	3.02	26.50	3.04	29.30	3.10	31.40	3.13

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
					111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56
					115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
					111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80
					115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84
9	15			24	68	21.21	1.24	29.92	1.27	30.49	1.31	30.83	1.32	31.20	1.33	32.08	1.36
					70	21.21	1.27	29.10	1.31	29.71	1.34	30.07	1.35	30.47	1.37	31.39	1.39
					73	21.21	1.31	28.32	1.34	28.97	1.37	29.36	1.38	29.78	1.40	30.73	1.43
					77	21.21	1.34	27.58	1.37	28.27	1.40	28.67	1.42	29.11	1.43	30.11	1.46
					81	21.21	1.37	26.86	1.40	27.59	1.43	28.02	1.45	28.48	1.46	29.52	1.49
					84	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	27.88	1.50	28.96	1.53
					88	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	27.60	1.52	28.70	1.54
					91	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	27.05	1.55	28.19	1.58
					95	21.21	1.50	24.63	1.53	25.50	1.56	24.00	1.77	26.53	1.59	27.72	1.62
					99	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	26.05	1.63	27.28	1.65
					102	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	25.60	1.67	26.87	1.69
					108	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	25.19	1.71	26.50	1.73
					111	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	24.81	1.75	26.16	1.77
					115	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	24.46	1.79	25.85	1.81

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	23.07	1.80	28.47	1.84	29.31	1.88	29.80	1.90	31.50	1.95	32.84	1.98
					70	23.07	1.82	28.12	1.86	28.98	1.90	29.47	1.92	31.21	1.97	32.57	2.01
					73	23.07	1.87	27.43	1.91	28.34	1.95	28.86	1.96	30.66	2.02	32.06	2.05
					77	23.07	1.92	26.78	1.96	27.73	1.99	28.27	2.01	30.14	2.06	31.60	2.10
					81	23.07	1.96	26.17	2.00	27.17	2.04	27.73	2.06	29.66	2.11	31.16	2.15
					84	23.07	2.01	25.59	2.05	26.63	2.09	27.22	2.11	29.22	2.16	30.77	2.20
					88	23.07	2.07	25.05	2.10	26.14	2.14	26.75	2.16	28.82	2.21	30.41	2.25
					91	23.07	2.12	24.55	2.16	25.68	2.19	26.31	2.21	28.45	2.26	30.08	2.30
					95	23.07	2.17	24.08	2.21	25.26	2.25	26.10	2.26	28.11	2.32	29.79	2.35
					99	23.07	2.23	23.65	2.27	24.87	2.30	25.54	2.32	27.82	2.37	29.54	2.40
					102	23.07	2.28	23.25	2.32	24.52	2.36	25.22	2.38	27.56	2.43	29.33	2.46
					108	23.07	2.37	22.73	2.41	24.06	2.44	24.79	2.46	27.23	2.51	29.07	2.54
					111	23.07	2.43	22.42	2.47	23.80	2.50	24.56	2.52	27.07	2.57	28.95	2.60
					115	23.07	2.49	22.15	2.53	23.58	2.56	24.35	2.58	26.93	2.63	28.86	2.66
9	24			33	68	25.10	2.10	30.98	2.15	31.90	2.19	32.42	2.21	34.27	2.28	35.73	2.32
					70	25.10	2.13	30.59	2.17	31.53	2.22	32.07	2.24	33.96	2.30	35.44	2.34
					73	25.10	2.18	29.85	2.23	30.84	2.27	31.40	2.29	33.36	2.36	34.89	2.40
					77	25.10	2.24	29.14	2.28	30.18	2.33	30.77	2.35	32.80	2.41	34.38	2.45
					81	25.10	2.30	28.47	2.34	29.56	2.38	30.17	2.41	32.28	2.47	33.91	2.51
					84	25.10	2.35	27.85	2.40	28.98	2.44	29.62	2.46	31.80	2.53	33.48	2.56
					88	25.10	2.41	27.26	2.46	28.44	2.50	29.10	2.52	31.36	2.58	33.08	2.62
					91	25.10	2.47	26.71	2.52	27.94	2.56	28.63	2.58	30.95	2.64	32.73	2.68
					95	25.10	2.54	26.20	2.58	27.48	2.63	28.40	2.64	30.59	2.71	32.42	2.75
					99	25.10	2.60	25.73	2.65	27.06	2.69	27.80	2.71	30.27	2.77	32.14	2.81
					102	25.10	2.67	25.30	2.71	26.68	2.75	27.44	2.78	29.99	2.84	31.91	2.87
					108	25.10	2.77	24.73	2.81	26.18	2.85	26.98	2.88	29.63	2.94	31.63	2.97
					111	25.10	2.84	24.40	2.88	25.90	2.92	26.72	2.94	29.45	3.00	31.50	3.04
					115	25.10	2.91	24.10	2.95	25.66	2.99	26.50	3.01	29.30	3.07	31.40	3.11
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
					111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04
					115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15		27	68	23.86	1.89	29.45	1.94	30.32	1.98	30.82	2.00	31.37	2.01	32.58	2.05	
				70	23.86	1.92	29.09	1.96	29.98	2.00	30.49	2.02	31.05	2.04	32.28	2.08	
				73	23.86	1.97	28.38	2.01	29.32	2.05	29.85	2.07	30.43	2.09	31.71	2.12	
				77	23.86	2.02	27.70	2.06	28.69	2.10	29.25	2.12	29.85	2.14	31.18	2.17	
				81	23.86	2.07	27.07	2.11	28.10	2.15	28.68	2.17	29.31	2.19	30.69	2.22	
				84	23.86	2.12	26.47	2.16	27.55	2.20	28.16	2.22	28.81	2.24	30.23	2.28	
				88	23.86	2.18	25.91	2.22	27.04	2.26	27.67	2.27	28.34	2.29	29.81	2.33	
				91	23.86	2.23	25.39	2.27	26.57	2.31	27.22	2.33	27.91	2.35	29.43	2.38	
				95	23.86	2.29	24.91	2.33	26.13	2.37	27.00	2.38	27.52	2.40	29.08	2.44	
				99	23.86	2.35	24.46	2.39	25.73	2.42	26.43	2.44	27.17	2.46	28.78	2.50	
				102	23.86	2.40	24.05	2.44	25.37	2.48	26.09	2.50	26.85	2.52	28.51	2.56	
				108	23.86	2.50	23.51	2.54	24.89	2.57	25.65	2.59	26.45	2.61	28.17	2.65	
				111	23.86	2.56	23.19	2.60	24.62	2.64	25.40	2.65	26.22	2.67	28.00	2.71	
				115	23.86	2.62	22.92	2.66	24.39	2.70	25.19	2.72	26.04	2.74	27.86	2.77	
12	18		30	68	25.10	1.99	30.98	2.03	31.90	2.08	32.42	2.10	34.27	2.16	35.73	2.19	
				70	25.10	2.02	30.59	2.06	31.53	2.10	32.07	2.12	33.96	2.18	35.44	2.22	
				73	25.10	2.07	29.85	2.11	30.84	2.15	31.40	2.17	33.36	2.23	34.89	2.27	
				77	25.10	2.12	29.14	2.16	30.18	2.20	30.77	2.22	32.80	2.28	34.38	2.32	
				81	25.10	2.17	28.47	2.22	29.56	2.26	30.17	2.28	32.28	2.34	33.91	2.37	
				84	25.10	2.23	27.85	2.27	28.98	2.31	29.62	2.33	31.80	2.39	33.48	2.43	
				88	25.10	2.29	27.26	2.33	28.44	2.37	29.10	2.39	31.36	2.45	33.08	2.48	
				91	25.10	2.34	26.71	2.39	27.94	2.43	28.63	2.45	30.95	2.50	32.73	2.54	
				95	25.10	2.40	26.20	2.45	27.48	2.49	28.40	2.50	30.59	2.56	32.42	2.60	
				99	25.10	2.46	25.73	2.51	27.06	2.55	27.80	2.57	30.27	2.62	32.14	2.66	
				102	25.10	2.53	25.30	2.57	26.68	2.61	27.44	2.63	29.99	2.68	31.91	2.72	
				108	25.10	2.62	24.73	2.66	26.18	2.70	26.98	2.72	29.63	2.78	31.63	2.82	
				111	25.10	2.69	24.40	2.73	25.90	2.77	26.72	2.79	29.45	2.84	31.50	2.88	
				115	25.10	2.75	24.10	2.79	25.66	2.83	26.50	2.85	29.30	2.91	31.40	2.95	
12	24		36	68	25.10	2.28	30.98	2.33	31.90	2.37	32.42	2.40	34.27	2.47	35.73	2.51	
				70	25.10	2.31	30.59	2.36	31.53	2.40	32.07	2.43	33.96	2.49	35.44	2.54	
				73	25.10	2.36	29.85	2.41	30.84	2.46	31.40	2.49	33.36	2.55	34.89	2.60	
				77	25.10	2.42	29.14	2.47	30.18	2.52	30.77	2.54	32.80	2.61	34.38	2.65	
				81	25.10	2.49	28.47	2.54	29.56	2.58	30.17	2.61	32.28	2.67	33.91	2.72	
				84	25.10	2.55	27.85	2.60	28.98	2.65	29.62	2.67	31.80	2.74	33.48	2.78	
				88	25.10	2.61	27.26	2.66	28.44	2.71	29.10	2.73	31.36	2.80	33.08	2.84	
				91	25.10	2.68	26.71	2.73	27.94	2.78	28.63	2.80	30.95	2.87	32.73	2.91	
				95	25.10	2.75	26.20	2.80	27.48	2.84	28.40	2.86	30.59	2.93	32.42	2.97	
				99	25.10	2.82	25.73	2.87	27.06	2.91	27.80	2.94	30.27	3.00	32.14	3.04	
				102	25.10	2.89	25.30	2.94	26.68	2.98	27.44	3.01	29.99	3.07	31.91	3.11	
				108	25.10	3.00	24.73	3.05	26.18	3.09	26.98	3.12	29.63	3.18	31.63	3.22	
				111	25.10	3.07	24.40	3.12	25.90	3.17	26.72	3.19	29.45	3.25	31.50	3.29	
				115	25.10	3.15	24.10	3.20	25.66	3.24	26.50	3.27	29.30	3.33	31.40	3.37	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	68	25.10	2.05	30.98	2.10	31.90	2.14	32.42	2.16	32.99	2.18	34.27	2.22
					70	25.10	2.08	30.59	2.12	31.53	2.17	32.07	2.19	32.65	2.21	33.96	2.25
					73	25.10	2.13	29.85	2.18	30.84	2.22	31.40	2.24	32.01	2.26	33.36	2.30
					77	25.10	2.19	29.14	2.23	30.18	2.27	30.77	2.30	31.40	2.32	32.80	2.36
					81	25.10	2.24	28.47	2.29	29.56	2.33	30.17	2.35	30.83	2.37	32.28	2.41
					84	25.10	2.30	27.85	2.34	28.98	2.39	29.62	2.41	30.30	2.43	31.80	2.47
					88	25.10	2.36	27.26	2.40	28.44	2.45	29.10	2.47	29.81	2.49	31.36	2.53
					91	25.10	2.42	26.71	2.46	27.94	2.50	28.63	2.53	29.36	2.55	30.95	2.58
					95	25.10	2.48	26.20	2.52	27.48	2.57	28.40	2.58	28.95	2.61	30.59	2.65
					99	25.10	2.54	25.73	2.59	27.06	2.63	27.80	2.65	28.57	2.67	30.27	2.71
					102	25.10	2.61	25.30	2.65	26.68	2.69	27.44	2.71	28.24	2.73	29.99	2.77
					108	25.10	2.71	24.73	2.75	26.18	2.79	26.98	2.81	27.82	2.83	29.63	2.87
					111	25.10	2.77	24.40	2.82	25.90	2.86	26.72	2.88	27.58	2.90	29.45	2.94
					115	25.10	2.84	24.10	2.88	25.66	2.93	26.50	2.95	27.39	2.97	29.30	3.00
15	18			33	68	25.10	2.05	30.98	2.09	31.90	2.13	32.42	2.15	32.99	2.18	34.27	2.22
					70	25.10	2.07	30.59	2.12	31.53	2.16	32.07	2.18	32.65	2.20	33.96	2.24
					73	25.10	2.12	29.85	2.17	30.84	2.21	31.40	2.23	32.01	2.25	33.36	2.29
					77	25.10	2.18	29.14	2.22	30.18	2.27	30.77	2.29	31.40	2.31	32.80	2.35
					81	25.10	2.23	28.47	2.28	29.56	2.32	30.17	2.34	30.83	2.36	32.28	2.40
					84	25.10	2.29	27.85	2.34	28.98	2.38	29.62	2.40	30.30	2.42	31.80	2.46
					88	25.10	2.35	27.26	2.39	28.44	2.44	29.10	2.46	29.81	2.48	31.36	2.52
					91	25.10	2.41	26.71	2.45	27.94	2.50	28.63	2.52	29.36	2.54	30.95	2.57
					95	25.10	2.47	26.20	2.51	27.48	2.56	28.40	2.57	28.95	2.60	30.59	2.64
					99	25.10	2.53	25.73	2.58	27.06	2.62	27.80	2.64	28.57	2.66	30.27	2.70
					102	25.10	2.60	25.30	2.64	26.68	2.68	27.44	2.70	28.24	2.72	29.99	2.76
					108	25.10	2.69	24.73	2.74	26.18	2.78	26.98	2.80	27.82	2.82	29.63	2.86
					111	25.10	2.76	24.40	2.80	25.90	2.85	26.72	2.87	27.58	2.89	29.45	2.92
					115	25.10	2.83	24.10	2.87	25.66	2.91	26.50	2.93	27.39	2.95	29.30	2.99
15	24			39	68	25.10	2.01	35.40	2.06	36.07	2.11	36.48	2.13	36.93	2.16	37.96	2.20
					70	25.10	2.06	34.44	2.11	35.16	2.16	35.59	2.18	36.06	2.21	37.14	2.25
					73	25.10	2.11	33.52	2.16	34.29	2.21	34.74	2.23	35.23	2.26	36.37	2.30
					77	25.10	2.17	32.63	2.22	33.45	2.26	33.93	2.29	34.45	2.31	35.63	2.36
					81	25.10	2.22	31.79	2.27	32.65	2.32	33.15	2.34	33.70	2.37	34.93	2.41
					84	25.10	2.28	30.98	2.33	31.90	2.37	32.42	2.40	32.99	2.42	34.27	2.47
					88	25.10	2.31	30.59	2.36	31.53	2.40	32.07	2.43	32.65	2.45	33.96	2.49
					91	25.10	2.36	29.85	2.41	30.84	2.46	31.40	2.49	32.01	2.51	33.36	2.55
					95	25.10	2.42	29.14	2.47	30.18	2.52	28.40	2.86	31.40	2.57	32.80	2.61
					99	25.10	2.49	28.47	2.54	29.56	2.58	30.17	2.61	30.83	2.63	32.28	2.67
					102	25.10	2.55	27.85	2.60	28.98	2.65	29.62	2.67	30.30	2.69	31.80	2.74
					108	25.10	2.61	27.26	2.66	28.44	2.71	29.10	2.73	29.81	2.76	31.36	2.80
					111	25.10	2.68	26.71	2.73	27.94	2.78	28.63	2.80	29.36	2.82	30.95	2.87
					115	25.10	2.75	26.20	2.80	27.48	2.84	28.40	2.87	28.95	2.89	30.59	2.93

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18	18		36	68	25.10	2.28	30.98	2.33	31.90	2.37	32.42	2.40	34.27	2.47	35.73	2.51	
				70	25.10	2.31	30.59	2.36	31.53	2.40	32.07	2.43	33.96	2.49	35.44	2.54	
				73	25.10	2.36	29.85	2.41	30.84	2.46	31.40	2.49	33.36	2.55	34.89	2.60	
				77	25.10	2.42	29.14	2.47	30.18	2.52	30.77	2.54	32.80	2.61	34.38	2.65	
				81	25.10	2.49	28.47	2.54	29.56	2.58	30.17	2.61	32.28	2.67	33.91	2.72	
				84	25.10	2.55	27.85	2.60	28.98	2.65	29.62	2.67	31.80	2.74	33.48	2.78	
				88	25.10	2.61	27.26	2.66	28.44	2.71	29.10	2.73	31.36	2.80	33.08	2.84	
				91	25.10	2.68	26.71	2.73	27.94	2.78	28.63	2.80	30.95	2.87	32.73	2.91	
				95	25.10	2.75	26.20	2.80	27.48	2.84	28.40	2.86	30.59	2.93	32.42	2.97	
				99	25.10	2.82	25.73	2.87	27.06	2.91	27.80	2.94	30.27	3.00	32.14	3.04	
				102	25.10	2.89	25.30	2.94	26.68	2.98	27.44	3.01	29.99	3.07	31.91	3.11	
				108	25.10	3.00	24.73	3.05	26.18	3.09	26.98	3.12	29.63	3.18	31.63	3.22	
				111	25.10	3.07	24.40	3.12	25.90	3.17	26.72	3.19	29.45	3.25	31.50	3.29	
				115	25.10	3.15	24.10	3.20	25.66	3.24	26.50	3.27	29.30	3.33	31.40	3.37	
7	7	7	21	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23	
				70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24	
				73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27	
				77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30	
				81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33	
				84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36	
				88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39	
				91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42	
				95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46	
				99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49	
				102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52	
				108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58	
				111	18.56	1.50	18.04	1.53	19.15	1.55	19.76	1.56	21.78	1.59	23.29	1.61	
				115	18.56	1.54	17.82	1.57	18.97	1.59	19.60	1.60	21.67	1.63	23.22	1.65	
7	7	9	23	68	20.33	1.37	25.09	1.40	25.83	1.43	26.26	1.44	27.76	1.48	28.94	1.51	
				70	20.33	1.39	24.78	1.42	25.54	1.45	25.97	1.46	27.50	1.50	28.70	1.53	
				73	20.33	1.42	24.17	1.45	24.97	1.48	25.43	1.49	27.02	1.54	28.26	1.56	
				77	20.33	1.46	23.60	1.49	24.44	1.52	24.92	1.53	26.56	1.57	27.84	1.60	
				81	20.33	1.50	23.06	1.52	23.94	1.55	24.44	1.57	26.14	1.61	27.46	1.63	
				84	20.33	1.53	22.55	1.56	23.47	1.59	23.99	1.61	25.75	1.65	27.11	1.67	
				88	20.33	1.57	22.08	1.60	23.03	1.63	23.57	1.64	25.39	1.68	26.79	1.71	
				91	20.33	1.61	21.63	1.64	22.63	1.67	23.18	1.68	25.07	1.72	26.51	1.75	
				95	20.33	1.65	21.22	1.68	22.26	1.71	23.00	1.72	24.78	1.76	26.25	1.79	
				99	20.33	1.70	20.84	1.72	21.92	1.75	22.51	1.77	24.51	1.80	26.03	1.83	
				102	20.33	1.74	20.49	1.77	21.61	1.79	22.22	1.81	24.28	1.85	25.84	1.87	
				108	20.33	1.80	20.03	1.83	21.20	1.86	21.85	1.87	24.00	1.91	25.62	1.94	
				111	20.33	1.85	19.76	1.88	20.98	1.90	21.64	1.92	23.85	1.96	25.51	1.98	
				115	20.33	1.89	19.52	1.92	20.78	1.95	21.46	1.96	23.73	2.00	25.43	2.03	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	26	68	22.98	1.66	28.36	1.69	29.20	1.73	29.68	1.74	31.38	1.79	32.71	1.82	
				70	22.98	1.68	28.01	1.71	28.87	1.75	29.36	1.76	31.09	1.81	32.45	1.85	
				73	22.98	1.72	27.33	1.76	28.23	1.79	28.75	1.81	30.54	1.86	31.94	1.89	
				77	22.98	1.76	26.68	1.80	27.63	1.83	28.17	1.85	30.03	1.90	31.47	1.93	
				81	22.98	1.81	26.07	1.84	27.06	1.88	27.62	1.90	29.55	1.94	31.04	1.97	
				84	22.98	1.85	25.49	1.89	26.53	1.92	27.11	1.94	29.11	1.99	30.65	2.02	
				88	22.98	1.90	24.95	1.94	26.04	1.97	26.64	1.99	28.71	2.04	30.29	2.07	
				91	22.98	1.95	24.45	1.99	25.58	2.02	26.21	2.04	28.34	2.08	29.97	2.11	
				95	22.98	2.00	23.99	2.03	25.16	2.07	26.00	2.08	28.01	2.13	29.68	2.16	
				99	22.98	2.05	23.56	2.08	24.77	2.12	25.45	2.14	27.71	2.18	29.43	2.21	
				102	22.98	2.10	23.16	2.14	24.43	2.17	25.12	2.19	27.45	2.23	29.21	2.26	
				108	22.98	2.18	22.64	2.22	23.97	2.25	24.70	2.27	27.13	2.31	28.96	2.34	
				111	22.98	2.24	22.33	2.27	23.71	2.30	24.46	2.32	26.96	2.37	28.84	2.40	
				115	22.98	2.29	22.07	2.33	23.49	2.36	24.26	2.37	26.83	2.42	28.75	2.45	
7	7	15	29	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	
7	7	18	32	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	24	38	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	
7	9	9	25	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25	
				111	22.09	2.15	21.48	2.18	22.80	2.21	23.52	2.23	25.92	2.28	27.73	2.30	
				115	22.09	2.20	21.22	2.24	22.58	2.27	23.33	2.28	25.80	2.33	27.64	2.36	
7	9	12	28	68	24.74	1.78	30.55	1.82	31.45	1.86	31.97	1.88	33.79	1.93	35.23	1.97	
				70	24.74	1.81	30.16	1.84	31.09	1.88	31.62	1.90	33.48	1.95	34.94	1.99	
				73	24.74	1.85	29.43	1.89	30.40	1.93	30.96	1.95	32.89	2.00	34.40	2.03	
				77	24.74	1.90	28.73	1.94	29.75	1.98	30.33	1.99	32.34	2.05	33.90	2.08	
				81	24.74	1.95	28.07	1.99	29.14	2.02	29.75	2.04	31.82	2.09	33.43	2.13	
				84	24.74	2.00	27.45	2.04	28.57	2.07	29.20	2.09	31.35	2.14	33.01	2.18	
				88	24.74	2.05	26.87	2.09	28.04	2.12	28.69	2.14	30.91	2.19	32.62	2.23	
				91	24.74	2.10	26.33	2.14	27.55	2.17	28.22	2.19	30.52	2.24	32.27	2.28	
				95	24.74	2.15	25.83	2.19	27.10	2.23	28.00	2.24	30.16	2.30	31.96	2.33	
				99	24.74	2.21	25.37	2.25	26.68	2.28	27.40	2.30	29.84	2.35	31.69	2.38	
				102	24.74	2.26	24.94	2.30	26.30	2.34	27.05	2.35	29.56	2.41	31.46	2.44	
				108	24.74	2.35	24.38	2.39	25.81	2.42	26.60	2.44	29.22	2.49	31.19	2.52	
				111	24.74	2.41	24.05	2.44	25.53	2.48	26.34	2.50	29.04	2.55	31.05	2.58	
				115	24.74	2.47	23.76	2.50	25.30	2.54	26.13	2.56	28.89	2.61	30.96	2.64	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	15	31	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
7	9	18	34	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
7	9	24	40	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52					
115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58					

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	12	31	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	
7	12	15	34	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	
7	12	18	37	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15	15	37	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	
7	15	18	40	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	
9	9	9	27	68	23.86	1.72	29.45	1.76	30.32	1.79	30.82	1.81	32.58	1.86	33.97	1.89	
				70	23.86	1.74	29.09	1.78	29.98	1.82	30.49	1.83	32.28	1.88	33.69	1.92	
				73	23.86	1.79	28.38	1.82	29.32	1.86	29.85	1.88	31.71	1.93	33.17	1.96	
				77	23.86	1.83	27.70	1.87	28.69	1.90	29.25	1.92	31.18	1.97	32.68	2.00	
				81	23.86	1.88	27.07	1.92	28.10	1.95	28.68	1.97	30.69	2.02	32.24	2.05	
				84	23.86	1.93	26.47	1.96	27.55	2.00	28.16	2.02	30.23	2.07	31.83	2.10	
				88	23.86	1.97	25.91	2.01	27.04	2.05	27.67	2.06	29.81	2.11	31.45	2.15	
				91	23.86	2.02	25.39	2.06	26.57	2.10	27.22	2.11	29.43	2.16	31.12	2.20	
				95	23.86	2.08	24.91	2.11	26.13	2.15	27.00	2.16	29.08	2.21	30.82	2.25	
				99	23.86	2.13	24.46	2.17	25.73	2.20	26.43	2.22	28.78	2.27	30.56	2.30	
				102	23.86	2.18	24.05	2.22	25.37	2.25	26.09	2.27	28.51	2.32	30.34	2.35	
				108	23.86	2.26	23.51	2.30	24.89	2.34	25.65	2.35	28.17	2.40	30.07	2.43	
				111	23.86	2.32	23.19	2.36	24.62	2.39	25.40	2.41	28.00	2.46	29.94	2.49	
				115	23.86	2.38	22.92	2.41	24.39	2.45	25.19	2.47	27.86	2.51	29.85	2.54	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	30	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	
9	9	15	33	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	
9	9	18	36	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12		33	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58
9	12	15		36	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55
9	12	18		39	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15	15	39	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	
12	12	12	36	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58	
12	12	15	39	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89	
				70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91	
				73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95	
				77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00	
				81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05	
				84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09	
				88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14	
				91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19	
				95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25	
				99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30	
				102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35	
				108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43	
				111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49	
				115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	7	28	68	24.74	1.78	30.55	1.82	31.45	1.86	31.97	1.88	33.79	1.93	35.23	1.97
					70	24.74	1.81	30.16	1.84	31.09	1.88	31.62	1.90	33.48	1.95	34.94	1.99
					73	24.74	1.85	29.43	1.89	30.40	1.93	30.96	1.95	32.89	2.00	34.40	2.03
					77	24.74	1.90	28.73	1.94	29.75	1.98	30.33	1.99	32.34	2.05	33.90	2.08
					81	24.74	1.95	28.07	1.99	29.14	2.02	29.75	2.04	31.82	2.09	33.43	2.13
					84	24.74	2.00	27.45	2.04	28.57	2.07	29.20	2.09	31.35	2.14	33.01	2.18
					88	24.74	2.05	26.87	2.09	28.04	2.12	28.69	2.14	30.91	2.19	32.62	2.23
					91	24.74	2.10	26.33	2.14	27.55	2.17	28.22	2.19	30.52	2.24	32.27	2.28
					95	24.74	2.15	25.83	2.19	27.10	2.23	28.00	2.24	30.16	2.30	31.96	2.33
					99	24.74	2.21	25.37	2.25	26.68	2.28	27.40	2.30	29.84	2.35	31.69	2.38
					102	24.74	2.26	24.94	2.30	26.30	2.34	27.05	2.35	29.56	2.41	31.46	2.44
					108	24.74	2.35	24.38	2.39	25.81	2.42	26.60	2.44	29.22	2.49	31.19	2.52
111	24.74	2.41	24.05	2.44	25.53	2.48	26.34	2.50	29.04	2.55	31.05	2.58					
115	24.74	2.47	23.76	2.50	25.30	2.54	26.13	2.56	28.89	2.61	30.96	2.64					
7	7	7	9	30	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58
7	7	7	12	33	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	15	36	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	32.99	1.85	34.27	1.89
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	32.65	1.88	33.96	1.91
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	32.01	1.92	33.36	1.95
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	31.40	1.97	32.80	2.00
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	30.83	2.01	32.28	2.05
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	30.30	2.06	31.80	2.09
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	29.81	2.11	31.36	2.14
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	29.36	2.16	30.95	2.19
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	28.95	2.21	30.59	2.25
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	28.57	2.27	30.27	2.30
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	28.24	2.32	29.99	2.35
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	27.82	2.40	29.63	2.43
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	27.58	2.46	29.45	2.49
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	27.39	2.52	29.30	2.55
7	7	7	18	39	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	34.27	1.81	35.73	1.84
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	33.96	1.83	35.44	1.86
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	33.36	1.87	34.89	1.91
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	32.80	1.92	34.38	1.95
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	32.28	1.96	33.91	1.99
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	31.80	2.01	33.48	2.04
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	31.36	2.06	33.08	2.09
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	30.95	2.10	32.73	2.13
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	30.59	2.15	32.42	2.18
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	30.27	2.20	32.14	2.23
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	29.99	2.26	31.91	2.29
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	29.63	2.33	31.63	2.36
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	29.45	2.39	31.50	2.42
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	29.30	2.44	31.40	2.47
7	7	9	9	32	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	12	35	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58
7	7	9	15	38	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	32.99	1.78	34.27	1.81
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	32.65	1.80	33.96	1.83
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	32.01	1.84	33.36	1.87
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	31.40	1.89	32.80	1.92
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	30.83	1.93	32.28	1.96
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	30.30	1.98	31.80	2.01
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	29.81	2.02	31.36	2.06
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	29.36	2.07	30.95	2.10
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	28.95	2.12	30.59	2.15
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	28.57	2.17	30.27	2.20
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	28.24	2.22	29.99	2.26
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	27.82	2.30	29.63	2.33
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	27.58	2.36	29.45	2.39
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	27.39	2.41	29.30	2.44
7	7	12	12	38	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	34.27	1.81	35.73	1.84
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	33.96	1.83	35.44	1.86
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	33.36	1.87	34.89	1.91
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	32.80	1.92	34.38	1.95
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	32.28	1.96	33.91	1.99
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	31.80	2.01	33.48	2.04
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	31.36	2.06	33.08	2.09
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	30.95	2.10	32.73	2.13
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	30.59	2.15	32.42	2.18
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	30.27	2.20	32.14	2.23
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	29.99	2.26	31.91	2.29
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	29.63	2.33	31.63	2.36
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	29.45	2.39	31.50	2.42
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	29.30	2.44	31.40	2.47

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	9	34	68	25.10	1.74	30.98	1.78	31.90	1.82	32.42	1.84	34.27	1.89	35.73	1.92
					70	25.10	1.77	30.59	1.80	31.53	1.84	32.07	1.86	33.96	1.91	35.44	1.94
					73	25.10	1.81	29.85	1.85	30.84	1.89	31.40	1.90	33.36	1.95	34.89	1.99
					77	25.10	1.86	29.14	1.89	30.18	1.93	30.77	1.95	32.80	2.00	34.38	2.03
					81	25.10	1.90	28.47	1.94	29.56	1.98	30.17	2.00	32.28	2.05	33.91	2.08
					84	25.10	1.95	27.85	1.99	28.98	2.03	29.62	2.04	31.80	2.09	33.48	2.13
					88	25.10	2.00	27.26	2.04	28.44	2.08	29.10	2.09	31.36	2.14	33.08	2.18
					91	25.10	2.05	26.71	2.09	27.94	2.13	28.63	2.14	30.95	2.19	32.73	2.23
					95	25.10	2.11	26.20	2.14	27.48	2.18	28.40	2.19	30.59	2.25	32.42	2.28
					99	25.10	2.16	25.73	2.20	27.06	2.23	27.80	2.25	30.27	2.30	32.14	2.33
					102	25.10	2.21	25.30	2.25	26.68	2.28	27.44	2.30	29.99	2.35	31.91	2.38
					108	25.10	2.30	24.73	2.33	26.18	2.37	26.98	2.39	29.63	2.43	31.63	2.47
					111	25.10	2.35	24.40	2.39	25.90	2.43	26.72	2.44	29.45	2.49	31.50	2.52
					115	25.10	2.41	24.10	2.45	25.66	2.48	26.50	2.50	29.30	2.55	31.40	2.58
7	9	9	12	37	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	34.27	1.81	35.73	1.84
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	33.96	1.83	35.44	1.86
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	33.36	1.87	34.89	1.91
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	32.80	1.92	34.38	1.95
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	32.28	1.96	33.91	1.99
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	31.80	2.01	33.48	2.04
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	31.36	2.06	33.08	2.09
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	30.95	2.10	32.73	2.13
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	30.59	2.15	32.42	2.18
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	30.27	2.20	32.14	2.23
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	29.99	2.26	31.91	2.29
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	29.63	2.33	31.63	2.36
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	29.45	2.39	31.50	2.42
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	29.30	2.44	31.40	2.47
7	9	9	15	40	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	32.99	1.78	34.27	1.81
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	32.65	1.80	33.96	1.83
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	32.01	1.84	33.36	1.87
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	31.40	1.89	32.80	1.92
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	30.83	1.93	32.28	1.96
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	30.30	1.98	31.80	2.01
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	29.81	2.02	31.36	2.06
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	29.36	2.07	30.95	2.10
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	28.95	2.12	30.59	2.15
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	28.57	2.17	30.27	2.20
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	28.24	2.22	29.99	2.26
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	27.82	2.30	29.63	2.33
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	27.58	2.36	29.45	2.39
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	27.39	2.41	29.30	2.44

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12	12	40	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	34.27	1.81	35.73	1.84
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	33.96	1.83	35.44	1.86
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	33.36	1.87	34.89	1.91
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	32.80	1.92	34.38	1.95
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	32.28	1.96	33.91	1.99
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	31.80	2.01	33.48	2.04
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	31.36	2.06	33.08	2.09
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	30.95	2.10	32.73	2.13
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	30.59	2.15	32.42	2.18
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	30.27	2.20	32.14	2.23
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	29.99	2.26	31.91	2.29
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	29.63	2.33	31.63	2.36
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	29.45	2.39	31.50	2.42
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	29.30	2.44	31.40	2.47
9	9	9	9	36	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	34.27	1.81	35.73	1.84
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	33.96	1.83	35.44	1.86
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	33.36	1.87	34.89	1.91
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	32.80	1.92	34.38	1.95
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	32.28	1.96	33.91	1.99
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	31.80	2.01	33.48	2.04
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	31.36	2.06	33.08	2.09
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	30.95	2.10	32.73	2.13
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	30.59	2.15	32.42	2.18
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	30.27	2.20	32.14	2.23
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	29.99	2.26	31.91	2.29
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	29.63	2.33	31.63	2.36
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	29.45	2.39	31.50	2.42
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	29.30	2.44	31.40	2.47
9	9	9	12	39	68	25.10	1.67	30.98	1.71	31.90	1.74	32.42	1.76	34.27	1.81	35.73	1.84
					70	25.10	1.69	30.59	1.73	31.53	1.76	32.07	1.78	33.96	1.83	35.44	1.86
					73	25.10	1.74	29.85	1.77	30.84	1.81	31.40	1.82	33.36	1.87	34.89	1.91
					77	25.10	1.78	29.14	1.82	30.18	1.85	30.77	1.87	32.80	1.92	34.38	1.95
					81	25.10	1.83	28.47	1.86	29.56	1.90	30.17	1.91	32.28	1.96	33.91	1.99
					84	25.10	1.87	27.85	1.91	28.98	1.94	29.62	1.96	31.80	2.01	33.48	2.04
					88	25.10	1.92	27.26	1.96	28.44	1.99	29.10	2.01	31.36	2.06	33.08	2.09
					91	25.10	1.97	26.71	2.00	27.94	2.04	28.63	2.06	30.95	2.10	32.73	2.13
					95	25.10	2.02	26.20	2.05	27.48	2.09	28.40	2.10	30.59	2.15	32.42	2.18
					99	25.10	2.07	25.73	2.10	27.06	2.14	27.80	2.16	30.27	2.20	32.14	2.23
					102	25.10	2.12	25.30	2.16	26.68	2.19	27.44	2.21	29.99	2.26	31.91	2.29
					108	25.10	2.20	24.73	2.24	26.18	2.27	26.98	2.29	29.63	2.33	31.63	2.36
					111	25.10	2.26	24.40	2.29	25.90	2.33	26.72	2.34	29.45	2.39	31.50	2.42
					115	25.10	2.31	24.10	2.35	25.66	2.38	26.50	2.40	29.30	2.44	31.40	2.47

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 39.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9		18	-13	24.54	6.86	20.52	5.44	19.69	5.52	15.24	4.02	13.51	3.35	9.63	2.17	
				5	23.84	4.62	23.27	4.67	22.69	4.74	21.80	4.92	21.55	4.84	20.98	4.88	
				17	23.23	4.00	22.83	4.04	22.43	4.08	21.80	4.23	21.63	4.17	21.22	4.21	
				32	23.04	2.97	22.69	3.00	22.34	3.03	21.80	3.14	21.65	3.08	21.30	3.11	
				47	23.10	2.09	22.83	2.11	22.53	2.13	21.80	2.21	21.92	2.17	21.62	2.19	
				50	25.08	2.22	24.47	2.25	24.01	2.28	23.79	2.30	23.22	2.34	22.89	2.36	
9	12		21	59	27.46	2.31	26.94	2.34	26.45	2.38	26.23	2.39	25.62	2.43	25.26	2.45	
				-13	28.02	7.33	23.44	5.81	22.49	5.90	17.41	4.29	15.44	3.58	11.00	2.32	
				5	27.23	4.94	26.58	4.99	25.92	5.06	24.90	5.25	24.62	5.16	23.96	5.22	
				17	26.53	4.27	26.07	4.32	25.61	4.36	24.90	4.52	24.70	4.45	24.24	4.50	
				32	26.32	3.18	25.92	3.21	25.52	3.24	24.90	3.35	24.73	3.29	24.33	3.32	
				47	26.39	2.23	26.08	2.25	25.74	2.27	24.90	2.36	25.04	2.31	24.69	2.34	
9	15		24	50	28.65	2.37	27.95	2.41	27.42	2.44	27.18	2.45	26.52	2.50	26.14	2.52	
				59	31.37	2.47	30.77	2.50	30.21	2.54	29.95	2.55	29.26	2.60	28.86	2.62	
				-13	29.71	7.76	24.85	6.15	23.84	6.25	18.46	4.55	16.37	3.79	11.67	2.46	
				5	28.87	5.23	28.18	5.28	27.48	5.36	26.40	5.56	26.10	5.47	25.41	5.53	
				17	28.13	4.52	27.65	4.57	27.16	4.62	26.40	4.78	26.19	4.72	25.70	4.76	
				32	27.90	3.37	27.48	3.40	27.06	3.43	26.40	3.55	26.22	3.49	25.79	3.52	
9	18		27	47	27.98	2.37	27.65	2.39	27.29	2.41	26.40	2.50	26.54	2.45	26.18	2.48	
				50	30.38	2.51	29.63	2.55	29.07	2.58	28.81	2.60	28.12	2.64	27.72	2.67	
				59	33.26	2.61	32.62	2.65	32.03	2.69	31.76	2.70	31.02	2.75	30.59	2.78	
				-13	32.19	8.14	26.93	6.45	25.83	6.55	20.00	4.76	17.73	3.97	12.64	2.57	
				5	31.27	5.48	30.53	5.54	29.77	5.62	28.60	5.83	28.28	5.73	27.52	5.79	
				17	30.47	4.74	29.95	4.79	29.42	4.84	28.60	5.01	28.37	4.94	27.85	4.99	
9	24		33	32	30.23	3.53	29.77	3.56	29.31	3.59	28.60	3.72	28.40	3.66	27.94	3.69	
				47	30.31	2.48	29.96	2.50	29.56	2.52	28.60	2.62	28.76	2.57	28.36	2.60	
				50	32.91	2.63	32.10	2.67	31.50	2.71	31.21	2.72	30.46	2.77	30.03	2.80	
				59	36.03	2.74	35.34	2.78	34.70	2.82	34.41	2.83	33.61	2.88	33.14	2.91	
				-13	32.19	8.14	26.93	6.45	25.83	6.55	20.00	4.76	17.73	3.97	12.64	2.57	
				5	31.27	5.48	30.53	5.54	29.77	5.62	28.60	5.83	28.28	5.73	27.52	5.79	
12	12		24	17	30.47	4.74	29.95	4.79	29.42	4.84	28.60	5.01	28.37	4.94	27.85	4.99	
				32	30.23	3.53	29.77	3.56	29.31	3.59	28.60	3.72	28.40	3.66	27.94	3.69	
				47	30.31	2.48	29.96	2.50	29.56	2.52	28.60	2.62	28.76	2.57	28.36	2.60	
				50	32.91	2.63	32.10	2.67	31.50	2.71	31.21	2.72	30.46	2.77	30.03	2.80	
				59	36.03	2.74	35.34	2.78	34.70	2.82	34.41	2.83	33.61	2.88	33.14	2.91	
				-13	29.71	7.76	24.85	6.15	23.84	6.25	18.46	4.55	16.37	3.79	11.67	2.46	
12	15		27	5	28.87	5.23	28.18	5.28	27.48	5.36	26.40	5.56	26.10	5.47	25.41	5.53	
				17	28.13	4.52	27.65	4.57	27.16	4.62	26.40	4.78	26.19	4.72	25.70	4.76	
				32	27.90	3.37	27.48	3.40	27.06	3.43	26.40	3.55	26.22	3.49	25.79	3.52	
				47	27.98	2.37	27.65	2.39	27.29	2.41	26.40	2.50	26.54	2.45	26.18	2.48	
				50	30.38	2.51	29.63	2.55	29.07	2.58	28.81	2.60	28.12	2.64	27.72	2.67	
				59	33.26	2.61	32.62	2.65	32.03	2.69	31.76	2.70	31.02	2.75	30.59	2.78	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	18			30	-13	32.19	8.14	26.93	6.45	25.83	6.55	20.00	4.76	17.73	3.97	12.64	2.57
					5	31.27	5.48	30.53	5.54	29.77	5.62	28.60	5.83	28.28	5.73	27.52	5.79
					17	30.47	4.74	29.95	4.79	29.42	4.84	28.60	5.01	28.37	4.94	27.85	4.99
					32	30.23	3.53	29.77	3.56	29.31	3.59	28.60	3.72	28.40	3.66	27.94	3.69
					47	30.31	2.48	29.96	2.50	29.56	2.52	28.60	2.62	28.76	2.57	28.36	2.60
					50	32.91	2.63	32.10	2.67	31.50	2.71	31.21	2.72	30.46	2.77	30.03	2.80
12	24			36	59	36.03	2.74	35.34	2.78	34.70	2.82	34.41	2.83	33.61	2.88	33.14	2.91
					-13	32.19	8.14	26.93	6.45	25.83	6.55	20.00	4.76	17.73	3.97	12.64	2.57
					5	31.27	5.48	30.53	5.54	29.77	5.62	28.60	5.83	28.28	5.73	27.52	5.79
					17	30.47	4.74	29.95	4.79	29.42	4.84	28.60	5.01	28.37	4.94	27.85	4.99
					32	30.23	3.53	29.77	3.56	29.31	3.59	28.60	3.72	28.40	3.66	27.94	3.69
					47	30.31	2.48	29.96	2.50	29.56	2.52	28.60	2.62	28.76	2.57	28.36	2.60
15	18			33	50	32.91	2.63	32.10	2.67	31.50	2.71	31.21	2.72	30.46	2.77	30.03	2.80
					59	36.03	2.74	35.34	2.78	34.70	2.82	34.41	2.83	33.61	2.88	33.14	2.91
					-13	32.19	8.14	26.93	6.45	25.83	6.55	20.00	4.76	17.73	3.97	12.64	2.57
					5	31.27	5.48	30.53	5.54	29.77	5.62	28.60	5.83	28.28	5.73	27.52	5.79
					17	30.47	4.74	29.95	4.79	29.42	4.84	28.60	5.01	28.37	4.94	27.85	4.99
					32	30.23	3.53	29.77	3.56	29.31	3.59	28.60	3.72	28.40	3.66	27.94	3.69
18	18			36	47	30.31	2.48	29.96	2.50	29.56	2.52	28.60	2.62	28.76	2.57	28.36	2.60
					50	32.91	2.63	32.10	2.67	31.50	2.71	31.21	2.72	30.46	2.77	30.03	2.80
					59	36.03	2.74	35.34	2.78	34.70	2.82	34.41	2.83	33.61	2.88	33.14	2.91
					-13	32.19	8.14	26.93	6.45	25.83	6.55	20.00	4.76	17.73	3.97	12.64	2.57
					5	31.27	5.48	30.53	5.54	29.77	5.62	28.60	5.83	28.28	5.73	27.52	5.79
					17	30.47	4.74	29.95	4.79	29.42	4.84	28.60	5.01	28.37	4.94	27.85	4.99
9	9	9		27	32	30.23	3.53	29.77	3.56	29.31	3.59	28.60	3.72	28.40	3.66	27.94	3.69
					47	30.31	2.48	29.96	2.50	29.56	2.52	28.60	2.62	28.76	2.57	28.36	2.60
					50	32.91	2.63	32.10	2.67	31.50	2.71	31.21	2.72	30.46	2.77	30.03	2.80
					59	36.03	2.74	35.34	2.78	34.70	2.82	34.41	2.83	33.61	2.88	33.14	2.91
					-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22
					5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19
9	9	12		30	17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47
					32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31
					47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34
					50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44
					59	36.03	2.39	35.34	2.43	34.70	2.46	34.41	2.48	33.61	2.52	33.14	2.54
					-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22
9	9	15		33	5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19
					17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47
					32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31
					47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34
					50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44
					59	36.03	2.39	35.34	2.43	34.70	2.46	34.41	2.48	33.61	2.52	33.14	2.54

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	18	36	-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22	
				5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19	
				17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47	
				32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31	
				47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34	
				50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44	
			33	-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22	
				5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19	
				17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47	
				32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31	
				47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34	
				50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44	
			36	-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22	
				5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19	
				17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47	
				32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31	
				47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34	
				50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44	
			39	-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22	
				5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19	
				17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47	
				32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31	
				47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34	
				50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44	
			36	-13	22.94	4.02	21.88	4.06	21.25	4.11	20.00	4.16	19.38	4.22	18.13	4.22	
				5	30.89	4.92	30.23	4.97	29.36	5.04	28.60	5.09	27.95	5.14	27.41	5.19	
				17	30.46	4.23	29.91	4.28	29.21	4.33	28.60	4.38	28.06	4.43	27.60	4.47	
				32	30.33	3.14	29.81	3.17	29.17	3.21	28.60	3.25	28.10	3.29	27.66	3.31	
				47	30.21	2.21	29.72	2.23	29.13	2.26	28.60	2.29	28.13	2.31	27.72	2.34	
				50	32.91	2.30	32.10	2.34	31.50	2.37	31.21	2.38	30.46	2.42	30.03	2.44	
			36	-13	22.94	3.83	21.88	3.86	21.25	3.91	20.00	3.96	19.38	4.01	18.13	4.01	
				5	30.89	4.69	30.23	4.73	29.36	4.80	28.60	4.85	27.95	4.90	27.41	4.94	
				17	30.46	4.03	29.91	4.07	29.21	4.12	28.60	4.17	28.06	4.21	27.60	4.25	
				32	30.33	2.99	29.81	3.02	29.17	3.06	28.60	3.10	28.10	3.13	27.66	3.16	
				47	30.21	2.10	29.72	2.13	29.13	2.15	28.60	2.18	28.13	2.20	27.72	2.22	
				50	32.91	2.19	32.10	2.22	31.50	2.25	31.21	2.27	30.46	2.30	30.03	2.33	
			39	-13	22.94	3.83	21.88	3.86	21.25	3.91	20.00	3.96	19.38	4.01	18.13	4.01	
				5	30.89	4.69	30.23	4.73	29.36	4.80	28.60	4.85	27.95	4.90	27.41	4.94	
				17	30.46	4.03	29.91	4.07	29.21	4.12	28.60	4.17	28.06	4.21	27.60	4.25	
				32	30.33	2.99	29.81	3.02	29.17	3.06	28.60	3.10	28.10	3.13	27.66	3.16	
				47	30.21	2.10	29.72	2.13	29.13	2.15	28.60	2.18	28.13	2.20	27.72	2.22	
				50	32.91	2.19	32.10	2.22	31.50	2.25	31.21	2.27	30.46	2.30	30.03	2.33	

1. Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).

2. Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).

3. Capacities are based on the following conditions:

- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m

4. The total combination Index of connected a indoor unit is up to 39.

5. At least two indoor units must be connected for operation.

6. Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.

7. If AJ0**BNHDC/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.

8. This data is reference data for temperature capacity trend.

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7		14	-13	16.88	3.91	14.12	3.10	13.55	3.15	10.49	2.29	9.30	1.91	6.63	1.24	
				5	16.40	2.64	16.01	2.66	15.61	2.70	15.00	2.80	14.83	2.76	14.43	2.78	
				17	15.98	2.28	15.71	2.30	15.43	2.33	15.00	2.41	14.88	2.38	14.60	2.40	
				32	15.85	1.70	15.62	1.71	15.37	1.73	15.00	1.79	14.90	1.76	14.66	1.77	
				47	15.90	1.19	15.71	1.20	15.50	1.21	15.00	1.26	15.08	1.23	14.87	1.25	
				50	17.26	1.27	16.84	1.29	16.52	1.30	16.37	1.31	15.97	1.33	15.75	1.34	
				59	18.90	1.32	18.53	1.34	18.20	1.35	18.05	1.36	17.63	1.39	17.38	1.40	
7	9		16	-13	20.71	4.75	17.32	3.77	16.62	3.82	12.87	2.78	11.41	2.32	8.13	1.50	
				5	20.12	3.20	19.64	3.23	19.15	3.28	18.40	3.40	18.19	3.35	17.71	3.38	
				17	19.61	2.77	19.27	2.80	18.93	2.82	18.40	2.93	18.25	2.89	17.91	2.91	
				32	19.45	2.06	19.16	2.08	18.86	2.10	18.40	2.17	18.27	2.14	17.98	2.15	
				47	19.50	1.45	19.27	1.46	19.02	1.47	18.40	1.53	18.50	1.50	18.25	1.52	
				50	21.17	1.54	20.65	1.56	20.26	1.58	20.08	1.59	19.60	1.62	19.32	1.63	
				59	23.18	1.60	22.73	1.62	22.33	1.64	22.14	1.65	21.62	1.68	21.32	1.70	
7	12		19	-13	24.20	5.19	20.24	4.11	19.42	4.17	15.03	3.04	13.33	2.53	9.50	1.64	
				5	23.51	3.49	22.95	3.53	22.38	3.58	21.50	3.72	21.26	3.65	20.69	3.69	
				17	22.91	3.02	22.51	3.05	22.12	3.08	21.50	3.20	21.33	3.15	20.93	3.18	
				32	22.72	2.25	22.38	2.27	22.04	2.29	21.50	2.37	21.35	2.33	21.01	2.35	
				47	22.79	1.58	22.52	1.59	22.22	1.61	21.50	1.67	21.62	1.64	21.32	1.66	
				50	24.74	1.68	24.13	1.70	23.68	1.73	23.47	1.74	22.90	1.77	22.57	1.78	
				59	27.09	1.75	26.56	1.77	26.09	1.80	25.86	1.81	25.26	1.84	24.92	1.85	
7	15		22	-13	28.70	6.18	24.01	4.90	23.03	4.97	17.83	3.62	15.81	3.02	11.27	1.96	
				5	27.88	4.16	27.22	4.21	26.54	4.26	25.50	4.43	25.21	4.35	24.54	4.40	
				17	27.17	3.60	26.70	3.64	26.23	3.67	25.50	3.81	25.30	3.76	24.83	3.79	
				32	26.95	2.68	26.55	2.70	26.14	2.73	25.50	2.83	25.32	2.78	24.91	2.80	
				47	27.03	1.88	26.71	1.90	26.36	1.92	25.50	1.99	25.64	1.95	25.29	1.97	
				50	29.34	2.00	28.62	2.03	28.08	2.06	27.83	2.07	27.16	2.10	26.77	2.12	
				59	32.13	2.08	31.51	2.11	30.94	2.14	30.68	2.15	29.96	2.19	29.55	2.21	
7	18		25	-13	30.95	6.24	25.89	4.95	24.83	5.02	19.23	3.65	17.05	3.05	12.15	1.98	
				5	30.07	4.21	29.35	4.25	28.63	4.31	27.50	4.47	27.19	4.40	26.46	4.44	
				17	29.30	3.64	28.80	3.68	28.29	3.71	27.50	3.85	27.28	3.79	26.77	3.83	
				32	29.07	2.71	28.63	2.73	28.19	2.76	27.50	2.85	27.31	2.81	26.87	2.83	
				47	29.15	1.90	28.80	1.92	28.42	1.94	27.50	2.01	27.65	1.97	27.27	1.99	
				50	31.64	2.02	30.87	2.05	30.28	2.08	30.01	2.09	29.29	2.13	28.87	2.15	
				59	34.64	2.10	33.98	2.13	33.37	2.16	33.08	2.17	32.31	2.21	31.87	2.23	
7	24		31	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05	
				5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62	
				17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98	
				32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94	
				47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07	
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	
9	9		18	-13	24.54	5.31	20.52	4.21	19.69	4.27	15.24	3.11	13.51	2.59	9.63	1.68	
				5	23.84	3.58	23.27	3.61	22.69	3.66	21.80	3.80	21.55	3.74	20.98	3.78	
				17	23.23	3.09	22.83	3.13	22.43	3.16	21.80	3.27	21.63	3.23	21.22	3.26	
				32	23.04	2.30	22.69	2.32	22.34	2.34	21.80	2.43	21.65	2.39	21.30	2.41	
				47	23.10	1.62	22.83	1.63	22.53	1.65	21.80	1.71	21.92	1.68	21.62	1.69	
				50	25.08	1.72	24.47	1.74	24.01	1.77	23.79	1.78	23.22	1.81	22.89	1.82	
				59	27.46	1.79	26.94	1.81	26.45	1.84	26.23	1.85	25.62	1.88	25.26	1.90	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12			21	-13	28.02	5.78	23.44	4.58	22.49	4.65	17.41	3.38	15.44	2.82	11.00	1.83
					5	27.23	3.89	26.58	3.93	25.92	3.99	24.90	4.14	24.62	4.07	23.96	4.11
					17	26.53	3.37	26.07	3.40	25.61	3.43	24.90	3.56	24.70	3.51	24.24	3.54
					32	26.32	2.50	25.92	2.53	25.52	2.55	24.90	2.64	24.73	2.60	24.33	2.62
					47	26.39	1.76	26.08	1.78	25.74	1.79	24.90	1.86	25.04	1.82	24.69	1.84
					50	28.65	1.87	27.95	1.90	27.42	1.92	27.18	1.93	26.52	1.97	26.14	1.99
					59	31.37	1.94	30.77	1.97	30.21	2.00	29.95	2.01	29.26	2.05	28.86	2.07
					-13	29.83	6.37	24.95	5.05	23.93	5.12	18.53	3.73	16.43	3.11	11.71	2.01
					5	28.98	4.29	28.28	4.33	27.59	4.39	26.50	4.56	26.20	4.49	25.50	4.53
					17	28.24	3.71	27.75	3.75	27.26	3.79	26.50	3.92	26.29	3.87	25.80	3.90
					32	28.01	2.76	27.59	2.78	27.16	2.81	26.50	2.91	26.32	2.86	25.89	2.89
					47	28.09	1.94	27.76	1.96	27.39	1.97	26.50	2.05	26.64	2.01	26.28	2.03
					50	30.49	2.06	29.74	2.09	29.18	2.12	28.92	2.13	28.22	2.17	27.82	2.19
					59	33.38	2.14	32.74	2.17	32.15	2.20	31.88	2.22	31.14	2.25	30.71	2.28
					-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
					-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
					-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
					-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)														
						57.2		60.8		64.4		69.98		71.6		75.2				
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)			
12	24		36	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05				
				5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62				
				17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98				
				32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94				
				47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07				
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23				
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32				
				15	15	30	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05	
							5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62	
							17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98	
							32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94	
							47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07	
50	32.91	2.10	32.10				2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23					
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32				
				15	18	33	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05	
							5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62	
							17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98	
							32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94	
							47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07	
50	32.91	2.10	32.10				2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23					
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32				
				15	24	39	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05	
							5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62	
							17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98	
							32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94	
							47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07	
50	32.91	2.10	32.10				2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23					
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32				
				18	18	36	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05	
							5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62	
							17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98	
							32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94	
							47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07	
50	32.91	2.10	32.10				2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23					
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32				
				7	7	7	21	-13	18.05	2.55	17.21	2.57	16.72	2.60	15.73	2.64	15.24	2.67	14.26	2.67
								5	24.30	3.12	23.78	3.15	23.10	3.19	22.50	3.23	21.99	3.26	21.57	3.28
								17	23.97	2.68	23.53	2.71	22.98	2.74	22.50	2.78	22.08	2.80	21.72	2.83
								32	23.86	1.99	23.45	2.01	22.95	2.03	22.50	2.06	22.10	2.08	21.76	2.10
								47	23.77	1.40	23.38	1.41	22.92	1.43	22.50	1.45	22.13	1.47	21.81	1.48
50	25.89	1.46	25.25					1.48	24.78	1.50	24.56	1.51	23.96	1.53	23.62	1.55				
				59	28.35	1.52	27.80	1.54	27.30	1.56	27.07	1.57	26.44	1.59	26.07	1.61				
				7	7	9	23	-13	20.77	2.95	19.81	2.98	19.24	3.02	18.11	3.05	17.55	3.09	16.41	3.09
								5	27.98	3.61	27.37	3.65	26.59	3.70	25.90	3.74	25.31	3.77	24.83	3.80
								17	27.59	3.10	27.08	3.14	26.46	3.18	25.90	3.22	25.41	3.25	25.00	3.28
								32	27.47	2.30	26.99	2.33	26.42	2.36	25.90	2.39	25.45	2.41	25.05	2.43
								47	27.36	1.62	26.91	1.64	26.38	1.66	25.90	1.68	25.47	1.70	25.10	1.71
50	29.80	1.69	29.07					1.71	28.52	1.74	28.27	1.75	27.58	1.78	27.19	1.79				
				59	32.63	1.76	32.00	1.78	31.43	1.81	31.16	1.82	30.43	1.85	30.01	1.87				

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	26	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
7	7	15	29	59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
				-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
7	7	18	32	50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
				-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
7	7	24	38	47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
				-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
7	9	9	25	32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
				-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
7	9	12	28	17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
				-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
7	9	15	31	5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	18		34	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	9	24		40	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	12	12		31	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	12	15		34	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	12	18		37	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	15	15		37	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	15	18		40	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	27	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
9	9	12	30	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
9	9	15	33	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
9	9	18	36	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
9	12	12	33	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
9	12	15	36	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	
9	12	18	39	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59	
				5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42	
				17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80	
				32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82	
				47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99	
				50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08	
				59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17	

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15	15		39	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
12	12	12		36	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
12	12	15		39	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
12	12	15		39	-13	22.94	3.43	21.88	3.45	21.25	3.50	20.00	3.55	19.38	3.59	18.13	3.59
					5	30.89	4.19	30.23	4.23	29.36	4.29	28.60	4.34	27.95	4.38	27.41	4.42
					17	30.46	3.60	29.91	3.64	29.21	3.69	28.60	3.73	28.06	3.77	27.60	3.80
					32	30.33	2.67	29.81	2.70	29.17	2.74	28.60	2.77	28.10	2.80	27.66	2.82
					47	30.21	1.88	29.72	1.90	29.13	1.93	28.60	1.95	28.13	1.97	27.72	1.99
					50	32.91	1.96	32.10	1.99	31.50	2.02	31.21	2.03	30.46	2.06	30.03	2.08
					59	36.03	2.04	35.34	2.07	34.70	2.10	34.41	2.11	33.61	2.14	33.14	2.17
7	7	7	7	28	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	7	9	30	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	7	12	33	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	7	15	36	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	18	39	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	9	9	32	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	9	12	35	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	9	15	38	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	7	12	12	38	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	9	9	9	34	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
7	9	9	12	37	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07

Capacity Table

JXH30S4C (AJ030CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	15	40	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
7	9	12	12	40	-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
7	9	12	12	40	59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
					-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
9	9	9	9	36	50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
					-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
					32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
9	9	9	9	36	47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
					-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21
					17	30.46	3.44	29.91	3.47	29.21	3.52	28.60	3.56	28.06	3.60	27.60	3.63
9	9	9	12	39	32	30.33	2.55	29.81	2.58	29.17	2.61	28.60	2.64	28.10	2.67	27.66	2.69
					47	30.21	1.79	29.72	1.81	29.13	1.84	28.60	1.86	28.13	1.88	27.72	1.90
					50	32.91	1.87	32.10	1.90	31.50	1.92	31.21	1.93	30.46	1.97	30.03	1.99
					59	36.03	1.94	35.34	1.97	34.70	2.00	34.41	2.01	33.61	2.05	33.14	2.07
					-13	22.94	3.27	21.88	3.30	21.25	3.34	20.00	3.38	19.38	3.43	18.13	3.43
					5	30.89	4.00	30.23	4.04	29.36	4.09	28.60	4.14	27.95	4.18	27.41	4.21

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 39.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9		18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18	
				70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20	
				73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22	
				77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25	
				81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28	
				84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31	
				88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34	
				91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37	
				95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40	
				99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44	
				102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47	
				108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52	
				111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56	
115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59					
9	12		21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37	
				70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42	
				77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45	
				81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48	
				84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52	
				88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55	
				91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59	
				95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62	
				99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66	
				102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70	
				108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76	
				111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80	
115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84					
9	15		24	68	21.21	1.36	26.18	1.39	26.96	1.42	27.40	1.43	27.88	1.45	28.96	1.47	
				70	21.21	1.38	25.85	1.41	26.65	1.44	27.10	1.45	27.60	1.46	28.70	1.49	
				73	21.21	1.41	25.22	1.44	26.06	1.47	26.53	1.49	27.05	1.50	28.19	1.53	
				77	21.21	1.45	24.63	1.48	25.50	1.51	26.00	1.52	26.53	1.54	27.72	1.56	
				81	21.21	1.49	24.06	1.52	24.98	1.54	25.50	1.56	26.05	1.57	27.28	1.60	
				84	21.21	1.52	23.53	1.55	24.49	1.58	25.03	1.60	25.60	1.61	26.87	1.64	
				88	21.21	1.56	23.03	1.59	24.04	1.62	24.59	1.63	25.19	1.65	26.50	1.67	
				91	21.21	1.60	22.57	1.63	23.61	1.66	24.19	1.67	24.81	1.69	26.16	1.71	
				95	21.21	1.64	22.14	1.67	23.22	1.70	24.00	1.71	24.46	1.73	25.85	1.75	
				99	21.21	1.69	21.74	1.71	22.87	1.74	23.49	1.76	24.15	1.77	25.58	1.79	
				102	21.21	1.73	21.38	1.76	22.55	1.78	23.19	1.80	23.87	1.81	25.34	1.84	
				108	21.21	1.79	20.90	1.82	22.13	1.85	22.80	1.86	23.51	1.88	25.04	1.90	
				111	21.21	1.84	20.62	1.87	21.89	1.89	22.58	1.91	23.31	1.92	24.89	1.95	
115	21.21	1.88	20.37	1.91	21.68	1.94	22.39	1.95	23.15	1.97	24.76	1.99					

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	23.07	1.80	28.47	1.84	29.31	1.88	29.80	1.90	31.50	1.95	32.84	1.98
					70	23.07	1.82	28.12	1.86	28.98	1.90	29.47	1.92	31.21	1.97	32.57	2.01
					73	23.07	1.87	27.43	1.91	28.34	1.95	28.86	1.96	30.66	2.02	32.06	2.05
					77	23.07	1.92	26.78	1.96	27.73	1.99	28.27	2.01	30.14	2.06	31.60	2.10
					81	23.07	1.96	26.17	2.00	27.17	2.04	27.73	2.06	29.66	2.11	31.16	2.15
					84	23.07	2.01	25.59	2.05	26.63	2.09	27.22	2.11	29.22	2.16	30.77	2.20
					88	23.07	2.07	25.05	2.10	26.14	2.14	26.75	2.16	28.82	2.21	30.41	2.25
					91	23.07	2.12	24.55	2.16	25.68	2.19	26.31	2.21	28.45	2.26	30.08	2.30
					95	23.07	2.17	24.08	2.21	25.26	2.25	26.10	2.26	28.11	2.32	29.79	2.35
					99	23.07	2.23	23.65	2.27	24.87	2.30	25.54	2.32	27.82	2.37	29.54	2.40
					102	23.07	2.28	23.25	2.32	24.52	2.36	25.22	2.38	27.56	2.43	29.33	2.46
					108	23.07	2.37	22.73	2.41	24.06	2.44	24.79	2.46	27.23	2.51	29.07	2.54
111	23.07	2.43	22.42	2.47	23.80	2.50	24.56	2.52	27.07	2.57	28.95	2.60					
115	23.07	2.49	22.15	2.53	23.58	2.56	24.35	2.58	26.93	2.63	28.86	2.66					
9	24			33	68	27.40	2.21	33.82	2.26	34.82	2.31	35.39	2.33	36.01	2.35	37.41	2.40
					70	27.40	2.24	33.40	2.29	34.42	2.34	35.01	2.36	35.64	2.38	37.07	2.42
					73	27.40	2.30	32.58	2.35	33.66	2.39	34.27	2.42	34.94	2.44	36.41	2.48
					77	27.40	2.36	31.81	2.40	32.94	2.45	33.58	2.47	34.27	2.50	35.80	2.54
					81	27.40	2.42	31.08	2.46	32.27	2.51	32.93	2.53	33.65	2.56	35.23	2.60
					84	27.40	2.48	30.40	2.53	31.64	2.57	32.33	2.59	33.07	2.62	34.71	2.66
					88	27.40	2.54	29.75	2.59	31.05	2.63	31.77	2.66	32.54	2.68	34.23	2.72
					91	27.40	2.61	29.15	2.65	30.50	2.70	31.25	2.72	32.05	2.74	33.79	2.79
					95	27.40	2.67	28.60	2.72	30.00	2.76	31.00	2.78	31.60	2.81	33.39	2.85
					99	27.40	2.74	28.09	2.79	29.54	2.83	30.34	2.85	31.19	2.88	33.04	2.92
					102	27.40	2.81	27.62	2.86	29.12	2.90	29.95	2.92	30.83	2.94	32.73	2.99
					108	27.40	2.91	26.99	2.96	28.58	3.01	29.45	3.03	30.36	3.05	32.35	3.09
111	27.40	2.99	26.63	3.03	28.27	3.08	29.17	3.10	30.11	3.12	32.15	3.16					
115	27.40	3.06	26.31	3.11	28.01	3.15	28.93	3.17	29.90	3.19	31.99	3.24					
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04					
115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09					

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15		27	68	23.86	1.73	29.45	1.77	30.32	1.80	30.82	1.82	31.37	1.84	32.58	1.87	
				70	23.86	1.75	29.09	1.79	29.98	1.82	30.49	1.84	31.05	1.86	32.28	1.89	
				73	23.86	1.79	28.38	1.83	29.32	1.87	29.85	1.89	30.43	1.90	31.71	1.94	
				77	23.86	1.84	27.70	1.88	28.69	1.91	29.25	1.93	29.85	1.95	31.18	1.98	
				81	23.86	1.89	27.07	1.92	28.10	1.96	28.68	1.98	29.31	1.99	30.69	2.03	
				84	23.86	1.93	26.47	1.97	27.55	2.01	28.16	2.03	28.81	2.04	30.23	2.08	
				88	23.86	1.98	25.91	2.02	27.04	2.06	27.67	2.07	28.34	2.09	29.81	2.12	
				91	23.86	2.03	25.39	2.07	26.57	2.11	27.22	2.12	27.91	2.14	29.43	2.17	
				95	23.86	2.09	24.91	2.12	26.13	2.16	27.00	2.17	27.52	2.19	29.08	2.23	
				99	23.86	2.14	24.46	2.18	25.73	2.21	26.43	2.23	27.17	2.24	28.78	2.28	
				102	23.86	2.19	24.05	2.23	25.37	2.26	26.09	2.28	26.85	2.30	28.51	2.33	
				108	23.86	2.28	23.51	2.31	24.89	2.35	25.65	2.36	26.45	2.38	28.17	2.41	
				111	23.86	2.33	23.19	2.37	24.62	2.40	25.40	2.42	26.22	2.44	28.00	2.47	
				115	23.86	2.39	22.92	2.43	24.39	2.46	25.19	2.48	26.04	2.49	27.86	2.53	
12	18		30	68	25.72	2.04	31.75	2.08	32.68	2.13	33.22	2.15	35.12	2.21	36.61	2.25	
				70	25.72	2.06	31.35	2.11	32.31	2.15	32.86	2.17	34.79	2.23	36.31	2.27	
				73	25.72	2.12	30.58	2.16	31.60	2.20	32.17	2.22	34.18	2.28	35.75	2.32	
				77	25.72	2.17	29.86	2.21	30.92	2.26	31.52	2.28	33.61	2.34	35.23	2.38	
				81	25.72	2.23	29.18	2.27	30.29	2.31	30.92	2.33	33.07	2.39	34.74	2.43	
				84	25.72	2.28	28.53	2.33	29.70	2.37	30.35	2.39	32.58	2.45	34.30	2.49	
				88	25.72	2.34	27.93	2.38	29.14	2.43	29.82	2.45	32.13	2.51	33.90	2.54	
				91	25.72	2.40	27.37	2.44	28.63	2.49	29.33	2.51	31.72	2.56	33.54	2.60	
				95	25.72	2.46	26.85	2.50	28.16	2.55	29.10	2.56	31.35	2.62	33.22	2.66	
				99	25.72	2.52	26.36	2.57	27.73	2.61	28.48	2.63	31.02	2.69	32.94	2.72	
				102	25.72	2.59	25.92	2.63	27.34	2.67	28.11	2.69	30.72	2.75	32.70	2.79	
				108	25.72	2.68	25.34	2.73	26.83	2.77	27.64	2.79	30.37	2.85	32.41	2.88	
				111	25.72	2.75	25.00	2.79	26.54	2.83	27.38	2.85	30.18	2.91	32.27	2.95	
				115	25.72	2.82	24.70	2.86	26.29	2.90	27.15	2.92	30.03	2.98	32.18	3.02	
12	24		36	68	30.05	2.34	37.09	2.39	38.19	2.44	38.82	2.47	39.50	2.49	41.03	2.53	
				70	30.05	2.37	36.63	2.42	37.75	2.47	38.40	2.49	39.09	2.52	40.65	2.56	
				73	30.05	2.43	35.73	2.48	36.92	2.53	37.59	2.55	38.32	2.58	39.94	2.62	
				77	30.05	2.49	34.89	2.54	36.13	2.59	36.83	2.62	37.59	2.64	39.27	2.69	
				81	30.05	2.56	34.09	2.61	35.39	2.66	36.12	2.68	36.91	2.70	38.64	2.75	
				84	30.05	2.62	33.34	2.67	34.70	2.72	35.46	2.74	36.27	2.77	38.07	2.81	
				88	30.05	2.69	32.63	2.74	34.05	2.79	34.84	2.81	35.69	2.83	37.54	2.88	
				91	30.05	2.76	31.98	2.81	33.45	2.85	34.27	2.88	35.15	2.90	37.06	2.95	
				95	30.05	2.83	31.37	2.88	32.90	2.92	34.00	2.94	34.65	2.97	36.62	3.01	
				99	30.05	2.90	30.80	2.95	32.40	2.99	33.28	3.02	34.21	3.04	36.24	3.09	
				102	30.05	2.97	30.29	3.02	31.94	3.07	32.85	3.09	33.81	3.11	35.90	3.16	
				108	30.05	3.08	29.60	3.13	31.34	3.18	32.30	3.20	33.30	3.22	35.48	3.27	
				111	30.05	3.16	29.21	3.21	31.01	3.26	31.99	3.28	33.02	3.30	35.26	3.34	
				115	30.05	3.24	28.86	3.29	30.72	3.33	31.73	3.36	32.79	3.38	35.08	3.42	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	18		33	68	28.37	2.22	35.02	2.27	36.05	2.32	36.65	2.34	37.29	2.36	38.74	2.41	
				70	28.37	2.25	34.58	2.30	35.64	2.34	36.25	2.37	36.91	2.39	38.38	2.43	
				73	28.37	2.31	33.74	2.35	34.85	2.40	35.49	2.42	36.18	2.45	37.70	2.49	
				77	28.37	2.37	32.94	2.41	34.11	2.46	34.77	2.48	35.49	2.50	37.07	2.55	
				81	28.37	2.43	32.18	2.47	33.41	2.52	34.10	2.54	34.85	2.56	36.48	2.61	
				84	28.37	2.49	31.47	2.54	32.76	2.58	33.48	2.60	34.25	2.63	35.94	2.67	
				88	28.37	2.55	30.81	2.60	32.15	2.64	32.89	2.67	33.69	2.69	35.44	2.73	
				91	28.37	2.62	30.19	2.66	31.58	2.71	32.36	2.73	33.18	2.75	34.99	2.80	
				95	28.37	2.68	29.61	2.73	31.06	2.77	32.10	2.79	32.72	2.82	34.58	2.86	
				99	28.37	2.75	29.08	2.80	30.59	2.84	31.42	2.86	32.30	2.89	34.21	2.93	
				102	28.37	2.82	28.60	2.87	30.16	2.91	31.01	2.93	31.92	2.95	33.89	3.00	
				108	28.37	2.93	27.95	2.97	29.59	3.02	30.49	3.04	31.44	3.06	33.50	3.10	
18	18	36	111	28.37	3.00	27.57	3.04	29.27	3.09	30.20	3.11	31.18	3.13	33.29	3.17		
			115	28.37	3.07	27.24	3.12	29.00	3.16	29.95	3.19	30.96	3.21	33.12	3.25		
			68	30.22	2.47	37.31	2.52	38.41	2.57	39.04	2.60	41.27	2.67	43.03	2.72		
			70	30.22	2.50	36.84	2.55	37.97	2.61	38.62	2.63	40.89	2.70	42.68	2.75		
			73	30.22	2.56	35.94	2.62	37.13	2.67	37.81	2.69	40.17	2.77	42.02	2.81		
			77	30.22	2.63	35.09	2.68	36.34	2.73	37.05	2.76	39.50	2.83	41.40	2.88		
			81	30.22	2.70	34.29	2.75	35.60	2.80	36.33	2.82	38.87	2.90	40.83	2.94		
			84	30.22	2.76	33.53	2.82	34.90	2.87	35.67	2.89	38.29	2.97	40.31	3.01		
			88	30.22	2.83	32.82	2.89	34.25	2.94	35.05	2.96	37.76	3.03	39.84	3.08		
			91	30.22	2.91	32.16	2.96	33.65	3.01	34.47	3.03	37.28	3.11	39.42	3.15		
			95	30.22	2.98	31.55	3.03	33.10	3.08	34.20	3.10	36.84	3.18	39.04	3.22		
			99	30.22	3.06	30.98	3.11	32.59	3.16	33.47	3.18	36.45	3.25	38.71	3.30		
9	9	27	102	30.22	3.13	30.47	3.18	32.13	3.23	33.04	3.26	36.11	3.33	38.43	3.37		
			108	30.22	3.25	29.78	3.30	31.53	3.35	32.49	3.38	35.69	3.45	38.09	3.49		
			111	30.22	3.33	29.38	3.38	31.19	3.43	32.18	3.46	35.46	3.53	37.93	3.57		
			115	30.22	3.41	29.03	3.47	30.90	3.52	31.91	3.54	35.29	3.61	37.81	3.65		
			68	23.86	2.01	29.45	2.06	30.32	2.10	30.82	2.12	32.58	2.18	33.97	2.22		
			70	23.86	2.04	29.09	2.08	29.98	2.13	30.49	2.15	32.28	2.21	33.69	2.24		
			73	23.86	2.09	28.38	2.14	29.32	2.18	29.85	2.20	31.71	2.26	33.17	2.30		
			77	23.86	2.14	27.70	2.19	28.69	2.23	29.25	2.25	31.18	2.31	32.68	2.35		
			81	23.86	2.20	27.07	2.24	28.10	2.29	28.68	2.31	30.69	2.36	32.24	2.40		
			84	23.86	2.26	26.47	2.30	27.55	2.34	28.16	2.36	30.23	2.42	31.83	2.46		
			88	23.86	2.31	25.91	2.36	27.04	2.40	27.67	2.42	29.81	2.48	31.45	2.51		
			91	23.86	2.37	25.39	2.41	26.57	2.46	27.22	2.48	29.43	2.53	31.12	2.57		
95	23.86	2.43	24.91	2.47	26.13	2.52	27.00	2.53	29.08	2.59	30.82	2.63					
99	23.86	2.49	24.46	2.54	25.73	2.58	26.43	2.60	28.78	2.65	30.56	2.69					
102	23.86	2.56	24.05	2.60	25.37	2.64	26.09	2.66	28.51	2.72	30.34	2.75					
108	23.86	2.65	23.51	2.70	24.89	2.74	25.65	2.76	28.17	2.81	30.07	2.85					
111	23.86	2.72	23.19	2.76	24.62	2.80	25.40	2.82	28.00	2.88	29.94	2.91					
115	23.86	2.79	22.92	2.83	24.39	2.87	25.19	2.89	27.86	2.94	29.85	2.98					

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	30	68	26.51	2.21	32.73	2.25	33.69	2.30	34.25	2.32	36.20	2.39	37.74	2.43	
				70	26.51	2.23	32.32	2.28	33.31	2.33	33.88	2.35	35.87	2.42	37.44	2.46	
				73	26.51	2.29	31.53	2.34	32.57	2.38	33.17	2.41	35.24	2.47	36.86	2.51	
				77	26.51	2.35	30.78	2.40	31.88	2.44	32.50	2.46	34.65	2.53	36.32	2.57	
				81	26.51	2.41	30.08	2.46	31.23	2.50	31.87	2.52	34.10	2.59	35.82	2.63	
				84	26.51	2.47	29.42	2.52	30.61	2.56	31.29	2.59	33.59	2.65	35.36	2.69	
				88	26.51	2.53	28.79	2.58	30.05	2.63	30.74	2.65	33.12	2.71	34.95	2.75	
				91	26.51	2.60	28.21	2.64	29.52	2.69	30.24	2.71	32.70	2.78	34.58	2.82	
				95	26.51	2.66	27.68	2.71	29.03	2.75	30.00	2.77	32.32	2.84	34.24	2.88	
				99	26.51	2.73	27.18	2.78	28.59	2.82	29.36	2.84	31.97	2.91	33.96	2.95	
				102	26.51	2.80	26.72	2.85	28.18	2.89	28.98	2.91	31.68	2.97	33.71	3.01	
				108	26.51	2.90	26.12	2.95	27.66	3.00	28.50	3.02	31.30	3.08	33.42	3.12	
				111	26.51	2.98	25.77	3.02	27.36	3.07	28.22	3.09	31.11	3.15	33.27	3.19	
				115	26.51	3.05	25.46	3.10	27.10	3.14	27.99	3.16	30.96	3.22	33.17	3.26	
9	9	15	33	68	29.16	2.40	36.00	2.45	37.06	2.50	37.67	2.52	38.34	2.55	39.82	2.60	
				70	29.16	2.43	35.55	2.48	36.64	2.53	37.27	2.55	37.94	2.58	39.46	2.63	
				73	29.16	2.49	34.68	2.54	35.83	2.59	36.48	2.62	37.19	2.64	38.76	2.69	
				77	29.16	2.55	33.86	2.60	35.07	2.65	35.75	2.68	36.48	2.70	38.11	2.75	
				81	29.16	2.62	33.09	2.67	34.35	2.72	35.06	2.74	35.82	2.77	37.51	2.81	
				84	29.16	2.68	32.36	2.74	33.68	2.78	34.42	2.81	35.21	2.83	36.95	2.88	
				88	29.16	2.75	31.67	2.80	33.05	2.85	33.82	2.88	34.64	2.90	36.43	2.95	
				91	29.16	2.82	31.04	2.87	32.47	2.92	33.26	2.95	34.11	2.97	35.97	3.02	
				95	29.16	2.89	30.44	2.94	31.93	2.99	33.00	3.01	33.64	3.04	35.55	3.09	
				99	29.16	2.97	29.90	3.02	31.44	3.07	32.30	3.09	33.20	3.11	35.17	3.16	
				102	29.16	3.04	29.40	3.09	31.00	3.14	31.88	3.16	32.82	3.19	34.84	3.23	
				108	29.16	3.16	28.73	3.21	30.42	3.25	31.35	3.28	32.32	3.30	34.43	3.35	
				111	29.16	3.23	28.35	3.28	30.09	3.33	31.05	3.36	32.05	3.38	34.22	3.42	
				115	29.16	3.32	28.01	3.36	29.81	3.41	30.79	3.44	31.83	3.46	34.05	3.50	
9	9	18	36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71	
				70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74	
				73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80	
				77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87	
				81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93	
				84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00	
				88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07	
				91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14	
				95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21	
				99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29	
				102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36	
				108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48	
				111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56	
				115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12		33	68	29.16	2.40	36.00	2.45	37.06	2.50	37.67	2.52	39.82	2.60	41.52	2.64
					70	29.16	2.43	35.55	2.48	36.64	2.53	37.27	2.55	39.46	2.63	41.18	2.67
					73	29.16	2.49	34.68	2.54	35.83	2.59	36.48	2.62	38.76	2.69	40.54	2.73
					77	29.16	2.55	33.86	2.60	35.07	2.65	35.75	2.68	38.11	2.75	39.95	2.79
					81	29.16	2.62	33.09	2.67	34.35	2.72	35.06	2.74	37.51	2.81	39.40	2.86
					84	29.16	2.68	32.36	2.74	33.68	2.78	34.42	2.81	36.95	2.88	38.90	2.92
					88	29.16	2.75	31.67	2.80	33.05	2.85	33.82	2.88	36.43	2.95	38.44	2.99
					91	29.16	2.82	31.04	2.87	32.47	2.92	33.26	2.95	35.97	3.02	38.03	3.06
					95	29.16	2.89	30.44	2.94	31.93	2.99	33.00	3.01	35.55	3.09	37.67	3.13
					99	29.16	2.97	29.90	3.02	31.44	3.07	32.30	3.09	35.17	3.16	37.35	3.20
					102	29.16	3.04	29.40	3.09	31.00	3.14	31.88	3.16	34.84	3.23	37.08	3.28
					108	29.16	3.16	28.73	3.21	30.42	3.25	31.35	3.28	34.43	3.35	36.76	3.39
111	29.16	3.23	28.35	3.28	30.09	3.33	31.05	3.36	34.22	3.42	36.60	3.47					
115	29.16	3.32	28.01	3.36	29.81	3.41	30.79	3.44	34.05	3.50	36.49	3.55					
9	12	15		36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52					
115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60					
9	12	18		39	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56					
115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64					

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18	18	45	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66	
				70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69	
				73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76	
				77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82	
				81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89	
				84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96	
				88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02	
				91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10	
				95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17	
				99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24	
				102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32	
				108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44	
12	12	12	36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71	
				70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74	
				73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80	
				77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87	
				81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93	
				84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00	
				88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07	
				91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14	
				95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21	
				99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29	
				102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36	
				108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48	
111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56					
12	12	18	42	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66	
				70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69	
				73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76	
				77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82	
				81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89	
				84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96	
				88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02	
				91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10	
				95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17	
				99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24	
				102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32	
				108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44	
111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52					
115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60					

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	18	18		48	68	34.93	2.47	36.44	2.52	37.98	2.56	38.76	2.59	39.54	2.61	41.13	2.66
					70	34.60	2.50	36.12	2.55	37.66	2.60	38.44	2.62	39.22	2.64	40.80	2.69
					73	33.94	2.56	35.47	2.61	37.01	2.66	37.79	2.69	38.57	2.71	40.16	2.76
					77	33.29	2.63	34.81	2.68	36.36	2.73	37.14	2.75	37.93	2.78	39.52	2.82
					81	32.64	2.70	34.17	2.74	35.72	2.79	36.50	2.82	37.29	2.84	38.88	2.89
					84	31.99	2.76	33.52	2.81	35.07	2.86	35.86	2.89	36.65	2.91	38.24	2.96
					88	31.34	2.83	32.87	2.88	34.43	2.93	35.22	2.96	36.01	2.98	37.61	3.03
					91	30.70	2.90	32.23	2.95	33.79	3.00	34.58	3.03	35.37	3.05	36.97	3.10
					95	30.05	2.97	31.59	3.02	33.15	3.07	34.00	3.09	34.73	3.12	36.34	3.17
					99	29.41	3.04	30.95	3.09	32.51	3.14	33.30	3.17	34.10	3.19	35.71	3.24
					102	28.77	3.12	30.31	3.17	31.88	3.22	32.67	3.24	33.47	3.27	35.08	3.32
					108	27.81	3.23	29.36	3.28	30.93	3.33	31.72	3.35	32.52	3.38	34.14	3.43
					111	27.17	3.30	28.72	3.35	30.30	3.40	31.09	3.43	31.89	3.46	33.51	3.51
					115	26.54	3.38	28.09	3.43	29.67	3.48	30.46	3.51	31.26	3.53	32.89	3.59
9	9	9	9	36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64
9	9	9	12	39	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	18	45	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60
9	9	12	12	42	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60
9	9	12	18	48	68	34.93	2.47	36.44	2.52	37.98	2.56	38.76	2.59	39.54	2.61	41.13	2.66
					70	34.60	2.50	36.12	2.55	37.66	2.60	38.44	2.62	39.22	2.64	40.80	2.69
					73	33.94	2.56	35.47	2.61	37.01	2.66	37.79	2.69	38.57	2.71	40.16	2.76
					77	33.29	2.63	34.81	2.68	36.36	2.73	37.14	2.75	37.93	2.78	39.52	2.82
					81	32.64	2.70	34.17	2.74	35.72	2.79	36.50	2.82	37.29	2.84	38.88	2.89
					84	31.99	2.76	33.52	2.81	35.07	2.86	35.86	2.89	36.65	2.91	38.24	2.96
					88	31.34	2.83	32.87	2.88	34.43	2.93	35.22	2.96	36.01	2.98	37.61	3.03
					91	30.70	2.90	32.23	2.95	33.79	3.00	34.58	3.03	35.37	3.05	36.97	3.10
					95	30.05	2.97	31.59	3.02	33.15	3.07	34.00	3.09	34.73	3.12	36.34	3.17
					99	29.41	3.04	30.95	3.09	32.51	3.14	33.30	3.17	34.10	3.19	35.71	3.24
					102	28.77	3.12	30.31	3.17	31.88	3.22	32.67	3.24	33.47	3.27	35.08	3.32
					108	27.81	3.23	29.36	3.28	30.93	3.33	31.72	3.35	32.52	3.38	34.14	3.43
					111	27.17	3.30	28.72	3.35	30.30	3.40	31.09	3.43	31.89	3.46	33.51	3.51
					115	26.54	3.38	28.09	3.43	29.67	3.48	30.46	3.51	31.26	3.53	32.89	3.59

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12	12	45	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60
12	12	12	12	48	68	34.93	2.47	36.44	2.52	37.98	2.56	38.76	2.59	39.54	2.61	41.13	2.66
					70	34.60	2.50	36.12	2.55	37.66	2.60	38.44	2.62	39.22	2.64	40.80	2.69
					73	33.94	2.56	35.47	2.61	37.01	2.66	37.79	2.69	38.57	2.71	40.16	2.76
					77	33.29	2.63	34.81	2.68	36.36	2.73	37.14	2.75	37.93	2.78	39.52	2.82
					81	32.64	2.70	34.17	2.74	35.72	2.79	36.50	2.82	37.29	2.84	38.88	2.89
					84	31.99	2.76	33.52	2.81	35.07	2.86	35.86	2.89	36.65	2.91	38.24	2.96
					88	31.34	2.83	32.87	2.88	34.43	2.93	35.22	2.96	36.01	2.98	37.61	3.03
					91	30.70	2.90	32.23	2.95	33.79	3.00	34.58	3.03	35.37	3.05	36.97	3.10
					95	30.05	2.97	31.59	3.02	33.15	3.07	34.00	3.09	34.73	3.12	36.34	3.17
					99	29.41	3.04	30.95	3.09	32.51	3.14	33.30	3.17	34.10	3.19	35.71	3.24
					102	28.77	3.12	30.31	3.17	31.88	3.22	32.67	3.24	33.47	3.27	35.08	3.32
					108	27.81	3.23	29.36	3.28	30.93	3.33	31.72	3.35	32.52	3.38	34.14	3.43
					111	27.17	3.30	28.72	3.35	30.30	3.40	31.09	3.43	31.89	3.46	33.51	3.51
					115	26.54	3.38	28.09	3.43	29.67	3.48	30.46	3.51	31.26	3.53	32.89	3.59

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 48.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0***BNHDCH/AA or AC0***BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7			14	68	12.37	0.91	15.27	0.93	15.72	0.95	15.98	0.96	16.89	0.98	17.61	1.00
					70	12.37	0.92	15.08	0.94	15.54	0.96	15.81	0.97	16.74	0.99	17.47	1.01
					73	12.37	0.94	14.71	0.96	15.20	0.98	15.48	0.99	16.44	1.02	17.20	1.03
					77	12.37	0.97	14.37	0.99	14.88	1.01	15.17	1.01	16.17	1.04	16.95	1.06
					81	12.37	0.99	14.04	1.01	14.57	1.03	14.87	1.04	15.91	1.07	16.72	1.08
					84	12.37	1.02	13.73	1.04	14.29	1.05	14.60	1.06	15.67	1.09	16.50	1.11
					88	12.37	1.04	13.44	1.06	14.02	1.08	14.35	1.09	15.46	1.12	16.31	1.13
					91	12.37	1.07	13.17	1.09	13.77	1.11	14.11	1.12	15.26	1.14	16.14	1.16
					95	12.37	1.10	12.92	1.12	13.55	1.13	14.00	1.14	15.08	1.17	15.98	1.19
					99	12.37	1.12	12.68	1.14	13.34	1.16	13.70	1.17	14.92	1.20	15.85	1.21
					102	12.37	1.15	12.47	1.17	13.15	1.19	13.53	1.20	14.78	1.22	15.73	1.24
					108	12.37	1.20	12.19	1.21	12.91	1.23	13.30	1.24	14.61	1.27	15.59	1.28
					111	12.37	1.23	12.03	1.24	12.77	1.26	13.17	1.27	14.52	1.30	15.53	1.31
					115	12.37	1.26	11.88	1.27	12.65	1.29	13.06	1.30	14.45	1.33	15.48	1.34
7	9			16	68	14.14	1.00	17.45	1.02	17.97	1.04	18.27	1.05	19.31	1.08	20.13	1.10
					70	14.14	1.01	17.24	1.03	17.77	1.05	18.07	1.06	19.13	1.09	19.97	1.11
					73	14.14	1.03	16.82	1.06	17.37	1.08	17.69	1.09	18.79	1.12	19.66	1.13
					77	14.14	1.06	16.42	1.08	17.00	1.10	17.33	1.11	18.48	1.14	19.37	1.16
					81	14.14	1.09	16.04	1.11	16.65	1.13	17.00	1.14	18.18	1.17	19.10	1.19
					84	14.14	1.11	15.69	1.14	16.33	1.16	16.69	1.17	17.91	1.20	18.86	1.21
					88	14.14	1.14	15.36	1.16	16.02	1.18	16.40	1.19	17.67	1.22	18.64	1.24
					91	14.14	1.17	15.05	1.19	15.74	1.21	16.13	1.22	17.44	1.25	18.44	1.27
					95	14.14	1.20	14.76	1.22	15.48	1.24	16.00	1.25	17.23	1.28	18.26	1.30
					99	14.14	1.23	14.50	1.25	15.25	1.27	15.66	1.28	17.05	1.31	18.11	1.33
					102	14.14	1.26	14.25	1.28	15.03	1.30	15.46	1.31	16.89	1.34	17.98	1.36
					108	14.14	1.31	13.93	1.33	14.75	1.35	15.20	1.36	16.70	1.39	17.82	1.41
					111	14.14	1.34	13.74	1.36	14.59	1.38	15.05	1.39	16.59	1.42	17.74	1.44
					115	14.14	1.38	13.58	1.40	14.45	1.42	14.93	1.43	16.51	1.46	17.69	1.47
7	12			19	68	16.79	1.16	20.73	1.19	21.34	1.21	21.69	1.22	22.93	1.26	23.90	1.28
					70	16.79	1.18	20.47	1.20	21.10	1.23	21.46	1.24	22.72	1.27	23.71	1.30
					73	16.79	1.21	19.97	1.23	20.63	1.26	21.01	1.27	22.32	1.30	23.34	1.32
					77	16.79	1.24	19.50	1.26	20.19	1.29	20.58	1.30	21.94	1.33	23.00	1.36
					81	16.79	1.27	19.05	1.29	19.78	1.32	20.19	1.33	21.59	1.36	22.69	1.39
					84	16.79	1.30	18.63	1.33	19.39	1.35	19.81	1.36	21.27	1.40	22.40	1.42
					88	16.79	1.33	18.24	1.36	19.03	1.38	19.47	1.40	20.98	1.43	22.13	1.45
					91	16.79	1.37	17.87	1.39	18.69	1.42	19.15	1.43	20.71	1.46	21.90	1.48
					95	16.79	1.40	17.53	1.43	18.39	1.45	19.00	1.46	20.47	1.50	21.69	1.52
					99	16.79	1.44	17.21	1.46	18.10	1.49	18.60	1.50	20.25	1.53	21.51	1.55
					102	16.79	1.48	16.93	1.50	17.85	1.52	18.36	1.53	20.06	1.57	21.35	1.59
					108	16.79	1.53	16.54	1.56	17.52	1.58	18.05	1.59	19.83	1.62	21.16	1.64
					111	16.79	1.57	16.32	1.59	17.33	1.62	17.88	1.63	19.70	1.66	21.07	1.68
					115	16.79	1.61	16.13	1.63	17.16	1.66	17.73	1.67	19.61	1.70	21.01	1.72

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15			22	68	19.44	1.33	24.00	1.36	24.71	1.39	25.12	1.40	25.56	1.41	26.55	1.44
					70	19.44	1.35	23.70	1.38	24.43	1.40	24.84	1.42	25.30	1.43	26.30	1.46
					73	19.44	1.38	23.12	1.41	23.89	1.44	24.32	1.45	24.79	1.46	25.84	1.49
					77	19.44	1.42	22.57	1.44	23.38	1.47	23.83	1.49	24.32	1.50	25.41	1.53
					81	19.44	1.45	22.06	1.48	22.90	1.51	23.37	1.52	23.88	1.54	25.00	1.56
					84	19.44	1.49	21.57	1.52	22.45	1.55	22.94	1.56	23.47	1.57	24.63	1.60
					88	19.44	1.53	21.12	1.56	22.03	1.58	22.54	1.60	23.09	1.61	24.29	1.63
					91	19.44	1.57	20.69	1.59	21.65	1.62	22.18	1.63	22.74	1.65	23.98	1.67
					95	19.44	1.61	20.30	1.63	21.29	1.66	22.00	1.67	22.42	1.69	23.70	1.71
					99	19.44	1.65	19.93	1.67	20.96	1.70	21.53	1.71	22.14	1.73	23.45	1.75
					102	19.44	1.69	19.60	1.72	20.67	1.74	21.26	1.76	21.88	1.77	23.23	1.79
					108	19.44	1.75	19.16	1.78	20.28	1.81	20.90	1.82	21.55	1.83	22.96	1.86
					111	19.44	1.79	18.90	1.82	20.06	1.85	20.70	1.86	21.37	1.88	22.81	1.90
					115	19.44	1.84	18.67	1.87	19.87	1.89	20.53	1.91	21.22	1.92	22.70	1.94
7	18			25	68	21.30	1.43	26.29	1.46	27.07	1.49	27.51	1.51	29.08	1.55	30.32	1.58
					70	21.30	1.45	25.96	1.48	26.76	1.51	27.22	1.53	28.82	1.57	30.07	1.60
					73	21.30	1.49	25.33	1.52	26.17	1.55	26.64	1.56	28.31	1.61	29.61	1.63
					77	21.30	1.53	24.73	1.56	25.61	1.59	26.11	1.60	27.83	1.64	29.17	1.67
					81	21.30	1.56	24.16	1.60	25.08	1.63	25.60	1.64	27.39	1.68	28.77	1.71
					84	21.30	1.60	23.63	1.64	24.59	1.67	25.13	1.68	26.98	1.72	28.41	1.75
					88	21.30	1.65	23.13	1.68	24.14	1.71	24.70	1.72	26.61	1.76	28.08	1.79
					91	21.30	1.69	22.67	1.72	23.71	1.75	24.29	1.76	26.27	1.80	27.78	1.83
					95	21.30	1.73	22.23	1.76	23.32	1.79	24.10	1.80	25.96	1.85	27.51	1.87
					99	21.30	1.77	21.83	1.80	22.96	1.83	23.59	1.85	25.69	1.89	27.28	1.91
					102	21.30	1.82	21.47	1.85	22.64	1.88	23.28	1.89	25.45	1.93	27.08	1.96
					108	21.30	1.89	20.98	1.92	22.22	1.95	22.89	1.96	25.15	2.00	26.84	2.03
					111	21.30	1.93	20.70	1.96	21.98	1.99	22.67	2.01	24.99	2.05	26.73	2.07
					115	21.30	1.98	20.45	2.01	21.77	2.04	22.49	2.05	24.87	2.10	26.65	2.12
7	24			31	68	25.63	2.17	31.64	2.21	32.57	2.26	33.11	2.28	35.00	2.35	36.49	2.39
					70	25.63	2.19	31.24	2.24	32.20	2.29	32.75	2.31	34.67	2.37	36.19	2.41
					73	25.63	2.25	30.48	2.30	31.49	2.34	32.06	2.36	34.06	2.43	35.63	2.47
					77	25.63	2.31	29.76	2.35	30.82	2.40	31.42	2.42	33.49	2.48	35.11	2.52
					81	25.63	2.36	29.08	2.41	30.19	2.46	30.81	2.48	32.96	2.54	34.62	2.58
					84	25.63	2.43	28.43	2.47	29.59	2.52	30.24	2.54	32.47	2.60	34.18	2.64
					88	25.63	2.49	27.83	2.53	29.04	2.58	29.72	2.60	32.02	2.66	33.78	2.70
					91	25.63	2.55	27.27	2.60	28.53	2.64	29.23	2.66	31.61	2.73	33.42	2.76
					95	25.63	2.61	26.75	2.66	28.06	2.71	29.00	2.72	31.24	2.79	33.10	2.83
					99	25.63	2.68	26.27	2.73	27.63	2.77	28.38	2.79	30.91	2.85	32.82	2.89
					102	25.63	2.75	25.83	2.79	27.24	2.84	28.02	2.86	30.62	2.92	32.58	2.96
					108	25.63	2.85	25.25	2.90	26.74	2.94	27.55	2.96	30.26	3.02	32.30	3.06
					111	25.63	2.92	24.91	2.97	26.45	3.01	27.28	3.03	30.07	3.09	32.16	3.13
					115	25.63	3.00	24.61	3.04	26.20	3.08	27.06	3.11	29.92	3.17	32.06	3.20

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
					111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56
					115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
					111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80
					115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84
9	15			24	68	21.21	1.24	29.92	1.27	30.49	1.31	30.83	1.32	31.20	1.33	32.08	1.36
					70	21.21	1.27	29.10	1.31	29.71	1.34	30.07	1.35	30.47	1.37	31.39	1.39
					73	21.21	1.31	28.32	1.34	28.97	1.37	29.36	1.38	29.78	1.40	30.73	1.43
					77	21.21	1.34	27.58	1.37	28.27	1.40	28.67	1.42	29.11	1.43	30.11	1.46
					81	21.21	1.37	26.86	1.40	27.59	1.43	28.02	1.45	28.48	1.46	29.52	1.49
					84	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	27.88	1.50	28.96	1.53
					88	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	27.60	1.52	28.70	1.54
					91	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	27.05	1.55	28.19	1.58
					95	21.21	1.50	24.63	1.53	25.50	1.56	24.00	1.77	26.53	1.59	27.72	1.62
					99	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	26.05	1.63	27.28	1.65
					102	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	25.60	1.67	26.87	1.69
					108	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	25.19	1.71	26.50	1.73
					111	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	24.81	1.75	26.16	1.77
					115	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	24.46	1.79	25.85	1.81

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	23.07	1.80	28.47	1.84	29.31	1.88	29.80	1.90	31.50	1.95	32.84	1.98
					70	23.07	1.82	28.12	1.86	28.98	1.90	29.47	1.92	31.21	1.97	32.57	2.01
					73	23.07	1.87	27.43	1.91	28.34	1.95	28.86	1.96	30.66	2.02	32.06	2.05
					77	23.07	1.92	26.78	1.96	27.73	1.99	28.27	2.01	30.14	2.06	31.60	2.10
					81	23.07	1.96	26.17	2.00	27.17	2.04	27.73	2.06	29.66	2.11	31.16	2.15
					84	23.07	2.01	25.59	2.05	26.63	2.09	27.22	2.11	29.22	2.16	30.77	2.20
					88	23.07	2.07	25.05	2.10	26.14	2.14	26.75	2.16	28.82	2.21	30.41	2.25
					91	23.07	2.12	24.55	2.16	25.68	2.19	26.31	2.21	28.45	2.26	30.08	2.30
					95	23.07	2.17	24.08	2.21	25.26	2.25	26.10	2.26	28.11	2.32	29.79	2.35
					99	23.07	2.23	23.65	2.27	24.87	2.30	25.54	2.32	27.82	2.37	29.54	2.40
					102	23.07	2.28	23.25	2.32	24.52	2.36	25.22	2.38	27.56	2.43	29.33	2.46
					108	23.07	2.37	22.73	2.41	24.06	2.44	24.79	2.46	27.23	2.51	29.07	2.54
					111	23.07	2.43	22.42	2.47	23.80	2.50	24.56	2.52	27.07	2.57	28.95	2.60
					115	23.07	2.49	22.15	2.53	23.58	2.56	24.35	2.58	26.93	2.63	28.86	2.66
9	24			33	68	27.40	2.29	33.82	2.34	34.82	2.39	35.39	2.41	37.41	2.48	39.00	2.53
					70	27.40	2.32	33.40	2.37	34.42	2.42	35.01	2.44	37.07	2.51	38.69	2.56
					73	27.40	2.38	32.58	2.43	33.66	2.48	34.27	2.50	36.41	2.57	38.08	2.61
					77	27.40	2.44	31.81	2.49	32.94	2.54	33.58	2.56	35.80	2.63	37.53	2.67
					81	27.40	2.50	31.08	2.55	32.27	2.60	32.93	2.62	35.23	2.69	37.01	2.73
					84	27.40	2.57	30.40	2.62	31.64	2.66	32.33	2.69	34.71	2.75	36.54	2.80
					88	27.40	2.63	29.75	2.68	31.05	2.73	31.77	2.75	34.23	2.82	36.11	2.86
					91	27.40	2.70	29.15	2.75	30.50	2.80	31.25	2.82	33.79	2.89	35.73	2.93
					95	27.40	2.77	28.60	2.82	30.00	2.86	31.00	2.88	33.39	2.95	35.39	2.99
					99	27.40	2.84	28.09	2.89	29.54	2.93	30.34	2.96	33.04	3.02	35.09	3.06
					102	27.40	2.91	27.62	2.96	29.12	3.00	29.95	3.03	32.73	3.09	34.83	3.13
					108	27.40	3.02	26.99	3.07	28.58	3.11	29.45	3.14	32.35	3.20	34.53	3.24
					111	27.40	3.10	26.63	3.14	28.27	3.19	29.17	3.21	32.15	3.28	34.38	3.32
					115	27.40	3.17	26.31	3.22	28.01	3.27	28.93	3.29	31.99	3.35	34.28	3.39
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
					111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04
					115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09

Capacity Table

JXH36S4C (AJ036CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	23.86	1.89	29.45	1.94	30.32	1.98	30.82	2.00	31.37	2.01	32.58	2.05
					70	23.86	1.92	29.09	1.96	29.98	2.00	30.49	2.02	31.05	2.04	32.28	2.08
					73	23.86	1.97	28.38	2.01	29.32	2.05	29.85	2.07	30.43	2.09	31.71	2.12
					77	23.86	2.02	27.70	2.06	28.69	2.10	29.25	2.12	29.85	2.14	31.18	2.17
					81	23.86	2.07	27.07	2.11	28.10	2.15	28.68	2.17	29.31	2.19	30.69	2.22
					84	23.86	2.12	26.47	2.16	27.55	2.20	28.16	2.22	28.81	2.24	30.23	2.28
					88	23.86	2.18	25.91	2.22	27.04	2.26	27.67	2.27	28.34	2.29	29.81	2.33
					91	23.86	2.23	25.39	2.27	26.57	2.31	27.22	2.33	27.91	2.35	29.43	2.38
					95	23.86	2.29	24.91	2.33	26.13	2.37	27.00	2.38	27.52	2.40	29.08	2.44
					99	23.86	2.35	24.46	2.39	25.73	2.42	26.43	2.44	27.17	2.46	28.78	2.50
					102	23.86	2.40	24.05	2.44	25.37	2.48	26.09	2.50	26.85	2.52	28.51	2.56
					108	23.86	2.50	23.51	2.54	24.89	2.57	25.65	2.59	26.45	2.61	28.17	2.65
					111	23.86	2.56	23.19	2.60	24.62	2.64	25.40	2.65	26.22	2.67	28.00	2.71
					115	23.86	2.62	22.92	2.66	24.39	2.70	25.19	2.72	26.04	2.74	27.86	2.77
12	18			30	68	25.72	2.04	31.75	2.08	32.68	2.13	33.22	2.15	35.12	2.21	36.61	2.25
					70	25.72	2.06	31.35	2.11	32.31	2.15	32.86	2.17	34.79	2.23	36.31	2.27
					73	25.72	2.12	30.58	2.16	31.60	2.20	32.17	2.22	34.18	2.28	35.75	2.32
					77	25.72	2.17	29.86	2.21	30.92	2.26	31.52	2.28	33.61	2.34	35.23	2.38
					81	25.72	2.23	29.18	2.27	30.29	2.31	30.92	2.33	33.07	2.39	34.74	2.43
					84	25.72	2.28	28.53	2.33	29.70	2.37	30.35	2.39	32.58	2.45	34.30	2.49
					88	25.72	2.34	27.93	2.38	29.14	2.43	29.82	2.45	32.13	2.51	33.90	2.54
					91	25.72	2.40	27.37	2.44	28.63	2.49	29.33	2.51	31.72	2.56	33.54	2.60
					95	25.72	2.46	26.85	2.50	28.16	2.55	29.10	2.56	31.35	2.62	33.22	2.66
					99	25.72	2.52	26.36	2.57	27.73	2.61	28.48	2.63	31.02	2.69	32.94	2.72
					102	25.72	2.59	25.92	2.63	27.34	2.67	28.11	2.69	30.72	2.75	32.70	2.79
					108	25.72	2.68	25.34	2.73	26.83	2.77	27.64	2.79	30.37	2.85	32.41	2.88
					111	25.72	2.75	25.00	2.79	26.54	2.83	27.38	2.85	30.18	2.91	32.27	2.95
					115	25.72	2.82	24.70	2.86	26.29	2.90	27.15	2.92	30.03	2.98	32.18	3.02
12	24			36	68	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	41.03	2.95	42.78	3.00
					70	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	40.65	2.98	42.43	3.03
					73	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	39.94	3.05	41.77	3.10
					77	30.05	2.90	34.89	2.96	36.13	3.02	36.83	3.04	39.27	3.12	41.16	3.17
					81	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	38.64	3.20	40.59	3.25
					84	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	38.07	3.27	40.08	3.32
					88	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	37.54	3.35	39.61	3.40
					91	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	37.06	3.43	39.19	3.48
					95	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.42	36.62	3.51	38.81	3.56
					99	30.05	3.37	30.80	3.43	32.40	3.48	33.28	3.51	36.24	3.59	38.48	3.64
					102	30.05	3.46	30.29	3.51	31.94	3.57	32.85	3.60	35.90	3.67	38.20	3.72
					108	30.05	3.59	29.60	3.64	31.34	3.70	32.30	3.72	35.48	3.80	37.87	3.85
					111	30.05	3.68	29.21	3.73	31.01	3.79	31.99	3.81	35.26	3.89	37.71	3.94
					115	30.05	3.77	28.86	3.82	30.72	3.88	31.73	3.90	35.08	3.98	37.59	4.03

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	68	26.51	2.17	32.73	2.22	33.69	2.27	34.25	2.29	34.85	2.31	36.20	2.35
					70	26.51	2.20	32.32	2.25	33.31	2.29	33.88	2.32	34.49	2.34	35.87	2.38
					73	26.51	2.26	31.53	2.30	32.57	2.35	33.17	2.37	33.81	2.39	35.24	2.44
					77	26.51	2.31	30.78	2.36	31.88	2.41	32.50	2.43	33.17	2.45	34.65	2.49
					81	26.51	2.37	30.08	2.42	31.23	2.47	31.87	2.49	32.57	2.51	34.10	2.55
					84	26.51	2.43	29.42	2.48	30.61	2.53	31.29	2.55	32.01	2.57	33.59	2.61
					88	26.51	2.50	28.79	2.54	30.05	2.59	30.74	2.61	31.49	2.63	33.12	2.67
					91	26.51	2.56	28.21	2.61	29.52	2.65	30.24	2.67	31.01	2.69	32.70	2.74
					95	26.51	2.62	27.68	2.67	29.03	2.71	30.00	2.73	30.58	2.76	32.32	2.80
					99	26.51	2.69	27.18	2.74	28.59	2.78	29.36	2.80	30.18	2.82	31.97	2.86
					102	26.51	2.76	26.72	2.80	28.18	2.85	28.98	2.87	29.83	2.89	31.68	2.93
					108	26.51	2.86	26.12	2.91	27.66	2.95	28.50	2.97	29.39	2.99	31.30	3.04
					111	26.51	2.93	25.77	2.98	27.36	3.02	28.22	3.04	29.14	3.07	31.11	3.11
					115	26.51	3.01	25.46	3.05	27.10	3.10	27.99	3.12	28.93	3.14	30.96	3.18
15	18			33	68	28.37	2.32	35.02	2.37	36.05	2.42	36.65	2.44	37.29	2.46	38.74	2.51
					70	28.37	2.35	34.58	2.40	35.64	2.45	36.25	2.47	36.91	2.49	38.38	2.54
					73	28.37	2.41	33.74	2.46	34.85	2.50	35.49	2.53	36.18	2.55	37.70	2.60
					77	28.37	2.47	32.94	2.52	34.11	2.57	34.77	2.59	35.49	2.61	37.07	2.66
					81	28.37	2.53	32.18	2.58	33.41	2.63	34.10	2.65	34.85	2.67	36.48	2.72
					84	28.37	2.59	31.47	2.64	32.76	2.69	33.48	2.72	34.25	2.74	35.94	2.78
					88	28.37	2.66	30.81	2.71	32.15	2.76	32.89	2.78	33.69	2.80	35.44	2.85
					91	28.37	2.73	30.19	2.78	31.58	2.83	32.36	2.85	33.18	2.87	34.99	2.92
					95	28.37	2.80	29.61	2.85	31.06	2.89	32.10	2.91	32.72	2.94	34.58	2.98
					99	28.37	2.87	29.08	2.92	30.59	2.96	31.42	2.99	32.30	3.01	34.21	3.05
					102	28.37	2.94	28.60	2.99	30.16	3.04	31.01	3.06	31.92	3.08	33.89	3.13
					108	28.37	3.05	27.95	3.10	29.59	3.15	30.49	3.17	31.44	3.19	33.50	3.24
					111	28.37	3.13	27.57	3.18	29.27	3.22	30.20	3.25	31.18	3.27	33.29	3.31
					115	28.37	3.20	27.24	3.25	29.00	3.30	29.95	3.32	30.96	3.34	33.12	3.39
15	24			39	68	30.05	2.40	42.39	2.46	43.19	2.52	43.67	2.55	44.21	2.58	45.44	2.63
					70	30.05	2.46	41.23	2.52	42.09	2.58	42.60	2.61	43.17	2.64	44.47	2.69
					73	30.05	2.53	40.13	2.59	41.05	2.64	41.59	2.67	42.18	2.70	43.54	2.75
					77	30.05	2.59	39.07	2.65	40.05	2.71	40.62	2.74	41.24	2.76	42.65	2.82
					81	30.05	2.65	38.06	2.71	39.09	2.77	39.69	2.80	40.35	2.83	41.82	2.88
					84	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	39.50	2.90	41.03	2.95
					88	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	39.09	2.93	40.65	2.98
					91	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	38.32	3.00	39.94	3.05
					95	30.05	2.90	34.89	2.96	36.13	3.02	34.00	3.42	37.59	3.07	39.27	3.12
					99	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	36.91	3.14	38.64	3.20
					102	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	36.27	3.22	38.07	3.27
					108	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	35.69	3.30	37.54	3.35
					111	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	35.15	3.37	37.06	3.43
					115	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.43	34.65	3.45	36.62	3.51

Capacity Table

JXH36S4C (AJ036CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18	18			36	68	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	41.03	2.95	42.78	3.00
					70	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	40.65	2.98	42.43	3.03
					73	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	39.94	3.05	41.77	3.10
					77	30.05	2.90	34.89	2.96	36.13	3.02	36.83	3.04	39.27	3.12	41.16	3.17
					81	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	38.64	3.20	40.59	3.25
					84	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	38.07	3.27	40.08	3.32
					88	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	37.54	3.35	39.61	3.40
					91	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	37.06	3.43	39.19	3.48
					95	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.42	36.62	3.51	38.81	3.56
					99	30.05	3.37	30.80	3.43	32.40	3.48	33.28	3.51	36.24	3.59	38.48	3.64
					102	30.05	3.46	30.29	3.51	31.94	3.57	32.85	3.60	35.90	3.67	38.20	3.72
					108	30.05	3.59	29.60	3.64	31.34	3.70	32.30	3.72	35.48	3.80	37.87	3.85
					111	30.05	3.68	29.21	3.73	31.01	3.79	31.99	3.81	35.26	3.89	37.71	3.94
					115	30.05	3.77	28.86	3.82	30.72	3.88	31.73	3.90	35.08	3.98	37.59	4.03
18	24			42	68	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	39.50	2.90	41.03	2.95
					70	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	39.09	2.93	40.65	2.98
					73	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	38.32	3.00	39.94	3.05
					77	30.05	2.90	34.89	2.96	36.13	3.02	36.83	3.04	37.59	3.07	39.27	3.12
					81	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	36.91	3.14	38.64	3.20
					84	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	36.27	3.22	38.07	3.27
					88	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	35.69	3.30	37.54	3.35
					91	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	35.15	3.37	37.06	3.43
					95	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.42	34.65	3.45	36.62	3.51
					99	30.05	3.37	30.80	3.43	32.40	3.48	33.28	3.51	34.21	3.54	36.24	3.59
					102	30.05	3.46	30.29	3.51	31.94	3.57	32.85	3.60	33.81	3.62	35.90	3.67
					108	30.05	3.59	29.60	3.64	31.34	3.70	32.30	3.72	33.30	3.75	35.48	3.80
					111	30.05	3.68	29.21	3.73	31.01	3.79	31.99	3.81	33.02	3.84	35.26	3.89
					115	30.05	3.77	28.86	3.82	30.72	3.88	31.73	3.90	32.79	3.93	35.08	3.98
24	24			48	68	38.23	2.40	39.73	2.45	41.25	2.50	42.03	2.53	42.80	2.55	44.37	2.60
					70	37.57	2.46	39.07	2.52	40.60	2.57	41.37	2.59	42.15	2.62	43.72	2.67
					73	36.90	2.53	38.41	2.58	39.94	2.63	40.71	2.66	41.49	2.68	43.07	2.74
					77	36.24	2.60	37.75	2.65	39.29	2.70	40.06	2.73	40.84	2.75	42.42	2.80
					81	35.58	2.66	37.10	2.72	38.63	2.77	39.41	2.80	40.19	2.82	41.77	2.87
					84	34.93	2.73	36.44	2.79	37.98	2.84	38.76	2.87	39.54	2.89	41.13	2.94
					88	34.60	2.77	36.12	2.82	37.66	2.87	38.44	2.90	39.22	2.93	40.80	2.98
					91	33.94	2.84	35.47	2.89	37.01	2.95	37.79	2.97	38.57	3.00	40.16	3.05
					95	33.29	2.91	34.81	2.96	36.36	3.02	34.00	3.42	37.93	3.07	39.52	3.13
					99	32.64	2.98	34.17	3.04	35.72	3.09	36.50	3.12	37.29	3.15	38.88	3.20
					102	31.99	3.06	33.52	3.11	35.07	3.17	35.86	3.19	36.65	3.22	38.24	3.28
					108	31.34	3.13	32.87	3.19	34.43	3.24	35.22	3.27	36.01	3.30	37.61	3.35
					111	30.70	3.21	32.23	3.27	33.79	3.32	34.58	3.35	35.37	3.38	36.97	3.43
					115	30.05	3.29	31.59	3.34	33.15	3.40	33.94	3.43	34.73	3.46	36.34	3.51

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7		21	68	18.56	1.11	22.91	1.14	23.59	1.16	23.97	1.17	25.34	1.21	26.42	1.23
					70	18.56	1.13	22.62	1.15	23.32	1.18	23.71	1.19	25.11	1.22	26.21	1.24
					73	18.56	1.16	22.07	1.18	22.80	1.21	23.22	1.22	24.67	1.25	25.80	1.27
					77	18.56	1.19	21.55	1.21	22.32	1.23	22.75	1.25	24.25	1.28	25.42	1.30
					81	18.56	1.22	21.05	1.24	21.86	1.26	22.31	1.28	23.87	1.31	25.07	1.33
					84	18.56	1.25	20.59	1.27	21.43	1.30	21.90	1.31	23.51	1.34	24.75	1.36
					88	18.56	1.28	20.16	1.30	21.03	1.33	21.52	1.34	23.19	1.37	24.46	1.39
					91	18.56	1.31	19.75	1.34	20.66	1.36	21.17	1.37	22.89	1.40	24.20	1.42
					95	18.56	1.35	19.37	1.37	20.32	1.39	21.00	1.40	22.62	1.44	23.97	1.46
					99	18.56	1.38	19.03	1.40	20.01	1.43	20.55	1.44	22.38	1.47	23.77	1.49
					102	18.56	1.41	18.71	1.44	19.73	1.46	20.29	1.47	22.17	1.50	23.60	1.52
					108	18.56	1.47	18.28	1.49	19.36	1.51	19.95	1.52	21.91	1.56	23.39	1.58
					111	18.56	1.50	18.04	1.53	19.15	1.55	19.76	1.56	21.78	1.59	23.29	1.61
					115	18.56	1.54	17.82	1.57	18.97	1.59	19.60	1.60	21.67	1.63	23.22	1.65
7	7	9		23	68	20.33	1.37	25.09	1.40	25.83	1.43	26.26	1.44	27.76	1.48	28.94	1.51
					70	20.33	1.39	24.78	1.42	25.54	1.45	25.97	1.46	27.50	1.50	28.70	1.53
					73	20.33	1.42	24.17	1.45	24.97	1.48	25.43	1.49	27.02	1.54	28.26	1.56
					77	20.33	1.46	23.60	1.49	24.44	1.52	24.92	1.53	26.56	1.57	27.84	1.60
					81	20.33	1.50	23.06	1.52	23.94	1.55	24.44	1.57	26.14	1.61	27.46	1.63
					84	20.33	1.53	22.55	1.56	23.47	1.59	23.99	1.61	25.75	1.65	27.11	1.67
					88	20.33	1.57	22.08	1.60	23.03	1.63	23.57	1.64	25.39	1.68	26.79	1.71
					91	20.33	1.61	21.63	1.64	22.63	1.67	23.18	1.68	25.07	1.72	26.51	1.75
					95	20.33	1.65	21.22	1.68	22.26	1.71	23.00	1.72	24.78	1.76	26.25	1.79
					99	20.33	1.70	20.84	1.72	21.92	1.75	22.51	1.77	24.51	1.80	26.03	1.83
					102	20.33	1.74	20.49	1.77	21.61	1.79	22.22	1.81	24.28	1.85	25.84	1.87
					108	20.33	1.80	20.03	1.83	21.20	1.86	21.85	1.87	24.00	1.91	25.62	1.94
					111	20.33	1.85	19.76	1.88	20.98	1.90	21.64	1.92	23.85	1.96	25.51	1.98
					115	20.33	1.89	19.52	1.92	20.78	1.95	21.46	1.96	23.73	2.00	25.43	2.03
7	7	12		26	68	22.98	1.66	28.36	1.69	29.20	1.73	29.68	1.74	31.38	1.79	32.71	1.82
					70	22.98	1.68	28.01	1.71	28.87	1.75	29.36	1.76	31.09	1.81	32.45	1.85
					73	22.98	1.72	27.33	1.76	28.23	1.79	28.75	1.81	30.54	1.86	31.94	1.89
					77	22.98	1.76	26.68	1.80	27.63	1.83	28.17	1.85	30.03	1.90	31.47	1.93
					81	22.98	1.81	26.07	1.84	27.06	1.88	27.62	1.90	29.55	1.94	31.04	1.97
					84	22.98	1.85	25.49	1.89	26.53	1.92	27.11	1.94	29.11	1.99	30.65	2.02
					88	22.98	1.90	24.95	1.94	26.04	1.97	26.64	1.99	28.71	2.04	30.29	2.07
					91	22.98	1.95	24.45	1.99	25.58	2.02	26.21	2.04	28.34	2.08	29.97	2.11
					95	22.98	2.00	23.99	2.03	25.16	2.07	26.00	2.08	28.01	2.13	29.68	2.16
					99	22.98	2.05	23.56	2.08	24.77	2.12	25.45	2.14	27.71	2.18	29.43	2.21
					102	22.98	2.10	23.16	2.14	24.43	2.17	25.12	2.19	27.45	2.23	29.21	2.26
					108	22.98	2.18	22.64	2.22	23.97	2.25	24.70	2.27	27.13	2.31	28.96	2.34
					111	22.98	2.24	22.33	2.27	23.71	2.30	24.46	2.32	26.96	2.37	28.84	2.40
					115	22.98	2.29	22.07	2.33	23.49	2.36	24.26	2.37	26.83	2.42	28.75	2.45

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	15	29	68	25.63	1.85	31.64	1.89	32.57	1.93	33.11	1.95	33.69	1.96	35.00	2.00	
				70	25.63	1.87	31.24	1.91	32.20	1.95	32.75	1.97	33.34	1.99	34.67	2.02	
				73	25.63	1.92	30.48	1.96	31.49	2.00	32.06	2.02	32.68	2.03	34.06	2.07	
				77	25.63	1.97	29.76	2.01	30.82	2.05	31.42	2.06	32.06	2.08	33.49	2.12	
				81	25.63	2.02	29.08	2.06	30.19	2.10	30.81	2.11	31.48	2.13	32.96	2.17	
				84	25.63	2.07	28.43	2.11	29.59	2.15	30.24	2.17	30.94	2.18	32.47	2.22	
				88	25.63	2.12	27.83	2.16	29.04	2.20	29.72	2.22	30.44	2.24	32.02	2.27	
				91	25.63	2.17	27.27	2.21	28.53	2.25	29.23	2.27	29.98	2.29	31.61	2.32	
				95	25.63	2.23	26.75	2.27	28.06	2.31	29.00	2.32	29.56	2.34	31.24	2.38	
				99	25.63	2.29	26.27	2.33	27.63	2.36	28.38	2.38	29.18	2.40	30.91	2.43	
				102	25.63	2.34	25.83	2.38	27.24	2.42	28.02	2.44	28.84	2.46	30.62	2.49	
				108	25.63	2.43	25.25	2.47	26.74	2.51	27.55	2.53	28.41	2.54	30.26	2.58	
				111	25.63	2.49	24.91	2.53	26.45	2.57	27.28	2.59	28.17	2.60	30.07	2.64	
				115	25.63	2.56	24.61	2.59	26.20	2.63	27.06	2.65	27.97	2.67	29.92	2.70	
7	7	18	32	68	28.28	2.04	34.91	2.08	35.94	2.13	36.53	2.15	38.62	2.21	40.26	2.25	
				70	28.28	2.06	34.47	2.11	35.53	2.15	36.14	2.17	38.26	2.23	39.93	2.27	
				73	28.28	2.12	33.63	2.16	34.75	2.20	35.38	2.22	37.59	2.28	39.31	2.32	
				77	28.28	2.17	32.84	2.21	34.00	2.26	34.67	2.28	36.96	2.34	38.74	2.38	
				81	28.28	2.23	32.08	2.27	33.31	2.31	34.00	2.33	36.37	2.39	38.21	2.43	
				84	28.28	2.28	31.38	2.33	32.66	2.37	33.37	2.39	35.83	2.45	37.72	2.49	
				88	28.28	2.34	30.71	2.38	32.05	2.43	32.79	2.45	35.33	2.51	37.28	2.54	
				91	28.28	2.40	30.09	2.44	31.48	2.49	32.26	2.51	34.88	2.56	36.88	2.60	
				95	28.28	2.46	29.52	2.50	30.97	2.55	32.00	2.56	34.47	2.62	36.53	2.66	
				99	28.28	2.52	28.99	2.57	30.49	2.61	31.32	2.63	34.11	2.69	36.22	2.72	
				102	28.28	2.59	28.51	2.63	30.06	2.67	30.92	2.69	33.79	2.75	35.96	2.79	
				108	28.28	2.68	27.86	2.73	29.50	2.77	30.40	2.79	33.39	2.85	35.64	2.88	
				111	28.28	2.75	27.49	2.79	29.18	2.83	30.11	2.85	33.18	2.91	35.49	2.95	
				115	28.28	2.82	27.16	2.86	28.91	2.90	29.86	2.92	33.02	2.98	35.38	3.02	
7	7	24	38	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	25	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25	
				111	22.09	2.15	21.48	2.18	22.80	2.21	23.52	2.23	25.92	2.28	27.73	2.30	
				115	22.09	2.20	21.22	2.24	22.58	2.27	23.33	2.28	25.80	2.33	27.64	2.36	
7	9	12	28	68	24.74	1.78	30.55	1.82	31.45	1.86	31.97	1.88	33.79	1.93	35.23	1.97	
				70	24.74	1.81	30.16	1.84	31.09	1.88	31.62	1.90	33.48	1.95	34.94	1.99	
				73	24.74	1.85	29.43	1.89	30.40	1.93	30.96	1.95	32.89	2.00	34.40	2.03	
				77	24.74	1.90	28.73	1.94	29.75	1.98	30.33	1.99	32.34	2.05	33.90	2.08	
				81	24.74	1.95	28.07	1.99	29.14	2.02	29.75	2.04	31.82	2.09	33.43	2.13	
				84	24.74	2.00	27.45	2.04	28.57	2.07	29.20	2.09	31.35	2.14	33.01	2.18	
				88	24.74	2.05	26.87	2.09	28.04	2.12	28.69	2.14	30.91	2.19	32.62	2.23	
				91	24.74	2.10	26.33	2.14	27.55	2.17	28.22	2.19	30.52	2.24	32.27	2.28	
				95	24.74	2.15	25.83	2.19	27.10	2.23	28.00	2.24	30.16	2.30	31.96	2.33	
				99	24.74	2.21	25.37	2.25	26.68	2.28	27.40	2.30	29.84	2.35	31.69	2.38	
				102	24.74	2.26	24.94	2.30	26.30	2.34	27.05	2.35	29.56	2.41	31.46	2.44	
				108	24.74	2.35	24.38	2.39	25.81	2.42	26.60	2.44	29.22	2.49	31.19	2.52	
				111	24.74	2.41	24.05	2.44	25.53	2.48	26.34	2.50	29.04	2.55	31.05	2.58	
				115	24.74	2.47	23.76	2.50	25.30	2.54	26.13	2.56	28.89	2.61	30.96	2.64	
7	9	15	31	68	27.40	1.97	33.82	2.02	34.82	2.06	35.39	2.08	36.01	2.10	37.41	2.14	
				70	27.40	2.00	33.40	2.04	34.42	2.08	35.01	2.10	35.64	2.12	37.07	2.16	
				73	27.40	2.05	32.58	2.09	33.66	2.13	34.27	2.15	34.94	2.17	36.41	2.21	
				77	27.40	2.10	31.81	2.15	32.94	2.19	33.58	2.21	34.27	2.23	35.80	2.26	
				81	27.40	2.16	31.08	2.20	32.27	2.24	32.93	2.26	33.65	2.28	35.23	2.32	
				84	27.40	2.21	30.40	2.25	31.64	2.29	32.33	2.31	33.07	2.33	34.71	2.37	
				88	27.40	2.27	29.75	2.31	31.05	2.35	31.77	2.37	32.54	2.39	34.23	2.43	
				91	27.40	2.32	29.15	2.37	30.50	2.41	31.25	2.43	32.05	2.45	33.79	2.48	
				95	27.40	2.38	28.60	2.43	30.00	2.47	31.00	2.48	31.60	2.51	33.39	2.54	
				99	27.40	2.44	28.09	2.49	29.54	2.53	30.34	2.55	31.19	2.57	33.04	2.60	
				102	27.40	2.51	27.62	2.55	29.12	2.59	29.95	2.61	30.83	2.63	32.73	2.66	
				108	27.40	2.60	26.99	2.64	28.58	2.68	29.45	2.70	30.36	2.72	32.35	2.76	
				111	27.40	2.67	26.63	2.71	28.27	2.75	29.17	2.77	30.11	2.78	32.15	2.82	
				115	27.40	2.73	26.31	2.77	28.01	2.81	28.93	2.83	29.90	2.85	31.99	2.89	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	18	34	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	
7	9	24	40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	
7	12	12	31	68	27.40	1.97	33.82	2.02	34.82	2.06	35.39	2.08	37.41	2.14	39.00	2.18	
				70	27.40	2.00	33.40	2.04	34.42	2.08	35.01	2.10	37.07	2.16	38.69	2.20	
				73	27.40	2.05	32.58	2.09	33.66	2.13	34.27	2.15	36.41	2.21	38.08	2.25	
				77	27.40	2.10	31.81	2.15	32.94	2.19	33.58	2.21	35.80	2.26	37.53	2.30	
				81	27.40	2.16	31.08	2.20	32.27	2.24	32.93	2.26	35.23	2.32	37.01	2.35	
				84	27.40	2.21	30.40	2.25	31.64	2.29	32.33	2.31	34.71	2.37	36.54	2.41	
				88	27.40	2.27	29.75	2.31	31.05	2.35	31.77	2.37	34.23	2.43	36.11	2.46	
				91	27.40	2.32	29.15	2.37	30.50	2.41	31.25	2.43	33.79	2.48	35.73	2.52	
				95	27.40	2.38	28.60	2.43	30.00	2.47	31.00	2.48	33.39	2.54	35.39	2.58	
				99	27.40	2.44	28.09	2.49	29.54	2.53	30.34	2.55	33.04	2.60	35.09	2.64	
				102	27.40	2.51	27.62	2.55	29.12	2.59	29.95	2.61	32.73	2.66	34.83	2.70	
				108	27.40	2.60	26.99	2.64	28.58	2.68	29.45	2.70	32.35	2.76	34.53	2.79	
				111	27.40	2.67	26.63	2.71	28.27	2.75	29.17	2.77	32.15	2.82	34.38	2.86	
				115	27.40	2.73	26.31	2.77	28.01	2.81	28.93	2.83	31.99	2.89	34.28	2.92	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	15	34	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
7	12	18	37	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	
7	12	24	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15	15	37	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
7	15	18	40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
7	15	24	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	18	18	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
9	9	9	27	68	23.86	1.72	29.45	1.76	30.32	1.79	30.82	1.81	32.58	1.86	33.97	1.89	
				70	23.86	1.74	29.09	1.78	29.98	1.82	30.49	1.83	32.28	1.88	33.69	1.92	
				73	23.86	1.79	28.38	1.82	29.32	1.86	29.85	1.88	31.71	1.93	33.17	1.96	
				77	23.86	1.83	27.70	1.87	28.69	1.90	29.25	1.92	31.18	1.97	32.68	2.00	
				81	23.86	1.88	27.07	1.92	28.10	1.95	28.68	1.97	30.69	2.02	32.24	2.05	
				84	23.86	1.93	26.47	1.96	27.55	2.00	28.16	2.02	30.23	2.07	31.83	2.10	
				88	23.86	1.97	25.91	2.01	27.04	2.05	27.67	2.06	29.81	2.11	31.45	2.15	
				91	23.86	2.02	25.39	2.06	26.57	2.10	27.22	2.11	29.43	2.16	31.12	2.20	
				95	23.86	2.08	24.91	2.11	26.13	2.15	27.00	2.16	29.08	2.21	30.82	2.25	
				99	23.86	2.13	24.46	2.17	25.73	2.20	26.43	2.22	28.78	2.27	30.56	2.30	
				102	23.86	2.18	24.05	2.22	25.37	2.25	26.09	2.27	28.51	2.32	30.34	2.35	
				108	23.86	2.26	23.51	2.30	24.89	2.34	25.65	2.35	28.17	2.40	30.07	2.43	
				111	23.86	2.32	23.19	2.36	24.62	2.39	25.40	2.41	28.00	2.46	29.94	2.49	
				115	23.86	2.38	22.92	2.41	24.39	2.45	25.19	2.47	27.86	2.51	29.85	2.54	
9	9	12	30	68	26.51	1.91	32.73	1.95	33.69	1.99	34.25	2.01	36.20	2.07	37.74	2.11	
				70	26.51	1.93	32.32	1.98	33.31	2.02	33.88	2.04	35.87	2.09	37.44	2.13	
				73	26.51	1.98	31.53	2.03	32.57	2.07	33.17	2.09	35.24	2.14	36.86	2.18	
				77	26.51	2.03	30.78	2.08	31.88	2.12	32.50	2.14	34.65	2.19	36.32	2.23	
				81	26.51	2.09	30.08	2.13	31.23	2.17	31.87	2.19	34.10	2.24	35.82	2.28	
				84	26.51	2.14	29.42	2.18	30.61	2.22	31.29	2.24	33.59	2.30	35.36	2.33	
				88	26.51	2.19	28.79	2.24	30.05	2.27	30.74	2.29	33.12	2.35	34.95	2.38	
				91	26.51	2.25	28.21	2.29	29.52	2.33	30.24	2.35	32.70	2.40	34.58	2.44	
				95	26.51	2.31	27.68	2.35	29.03	2.39	30.00	2.40	32.32	2.46	34.24	2.50	
				99	26.51	2.37	27.18	2.41	28.59	2.44	29.36	2.46	31.97	2.52	33.96	2.55	
				102	26.51	2.42	26.72	2.47	28.18	2.50	28.98	2.52	31.68	2.58	33.71	2.61	
				108	26.51	2.52	26.12	2.56	27.66	2.60	28.50	2.61	31.30	2.67	33.42	2.70	
				111	26.51	2.58	25.77	2.62	27.36	2.66	28.22	2.68	31.11	2.73	33.27	2.76	
				115	26.51	2.64	25.46	2.68	27.10	2.72	27.99	2.74	30.96	2.79	33.17	2.83	

Capacity Table

JXH36S4C (AJ036CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	15	33	68	29.16	2.10	36.00	2.15	37.06	2.19	37.67	2.21	38.34	2.23	39.82	2.28	
				70	29.16	2.13	35.55	2.17	36.64	2.22	37.27	2.24	37.94	2.26	39.46	2.30	
				73	29.16	2.18	34.68	2.23	35.83	2.27	36.48	2.29	37.19	2.32	38.76	2.36	
				77	29.16	2.24	33.86	2.28	35.07	2.33	35.75	2.35	36.48	2.37	38.11	2.41	
				81	29.16	2.30	33.09	2.34	34.35	2.38	35.06	2.41	35.82	2.43	37.51	2.47	
				84	29.16	2.35	32.36	2.40	33.68	2.44	34.42	2.46	35.21	2.48	36.95	2.53	
				88	29.16	2.41	31.67	2.46	33.05	2.50	33.82	2.52	34.64	2.54	36.43	2.58	
				91	29.16	2.47	31.04	2.52	32.47	2.56	33.26	2.58	34.11	2.60	35.97	2.64	
				95	29.16	2.54	30.44	2.58	31.93	2.63	33.00	2.64	33.64	2.67	35.55	2.71	
				99	29.16	2.60	29.90	2.65	31.44	2.69	32.30	2.71	33.20	2.73	35.17	2.77	
				102	29.16	2.67	29.40	2.71	31.00	2.75	31.88	2.78	32.82	2.80	34.84	2.84	
				108	29.16	2.77	28.73	2.81	30.42	2.85	31.35	2.88	32.32	2.90	34.43	2.94	
				111	29.16	2.84	28.35	2.88	30.09	2.92	31.05	2.94	32.05	2.96	34.22	3.00	
				115	29.16	2.91	28.01	2.95	29.81	2.99	30.79	3.01	31.83	3.03	34.05	3.07	
9	9	18	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	
9	9	24	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12		33	68	29.16	2.10	36.00	2.15	37.06	2.19	37.67	2.21	39.82	2.28	41.52	2.32
					70	29.16	2.13	35.55	2.17	36.64	2.22	37.27	2.24	39.46	2.30	41.18	2.34
					73	29.16	2.18	34.68	2.23	35.83	2.27	36.48	2.29	38.76	2.36	40.54	2.40
					77	29.16	2.24	33.86	2.28	35.07	2.33	35.75	2.35	38.11	2.41	39.95	2.45
					81	29.16	2.30	33.09	2.34	34.35	2.38	35.06	2.41	37.51	2.47	39.40	2.51
					84	29.16	2.35	32.36	2.40	33.68	2.44	34.42	2.46	36.95	2.53	38.90	2.56
					88	29.16	2.41	31.67	2.46	33.05	2.50	33.82	2.52	36.43	2.58	38.44	2.62
					91	29.16	2.47	31.04	2.52	32.47	2.56	33.26	2.58	35.97	2.64	38.03	2.68
					95	29.16	2.54	30.44	2.58	31.93	2.63	33.00	2.64	35.55	2.71	37.67	2.75
					99	29.16	2.60	29.90	2.65	31.44	2.69	32.30	2.71	35.17	2.77	37.35	2.81
					102	29.16	2.67	29.40	2.71	31.00	2.75	31.88	2.78	34.84	2.84	37.08	2.87
					108	29.16	2.77	28.73	2.81	30.42	2.85	31.35	2.88	34.43	2.94	36.76	2.97
					111	29.16	2.84	28.35	2.88	30.09	2.92	31.05	2.94	34.22	3.00	36.60	3.04
					115	29.16	2.91	28.01	2.95	29.81	2.99	30.79	3.01	34.05	3.07	36.49	3.11
9	12	15		36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	12	18		39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	24	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
9	15	15	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
9	15	18	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15	24	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34	
				70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37	
				73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43	
				77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49	
				81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55	
				84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61	
				88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67	
				91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73	
				95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79	
				99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86	
				102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92	
				108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02	
				111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09	
				115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16	
9	18	18	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	12	12	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	15	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	12	18	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	12	24	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34	
				70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37	
				73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43	
				77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49	
				81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55	
				84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61	
				88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67	
				91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73	
				95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79	
				99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86	
				102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92	
				108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02	
				111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09	
				115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15	15	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	15	18	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	18	18	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34	
				70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37	
				73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43	
				77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49	
				81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55	
				84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61	
				88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67	
				91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73	
				95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79	
				99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86	
				102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92	
				108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02	
				111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09	
				115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15	15		45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
15	15	18		48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16
7	7	7	7	28	68	24.74	1.78	30.55	1.82	31.45	1.86	31.97	1.88	33.79	1.93	35.23	1.97
					70	24.74	1.81	30.16	1.84	31.09	1.88	31.62	1.90	33.48	1.95	34.94	1.99
					73	24.74	1.85	29.43	1.89	30.40	1.93	30.96	1.95	32.89	2.00	34.40	2.03
					77	24.74	1.90	28.73	1.94	29.75	1.98	30.33	1.99	32.34	2.05	33.90	2.08
					81	24.74	1.95	28.07	1.99	29.14	2.02	29.75	2.04	31.82	2.09	33.43	2.13
					84	24.74	2.00	27.45	2.04	28.57	2.07	29.20	2.09	31.35	2.14	33.01	2.18
					88	24.74	2.05	26.87	2.09	28.04	2.12	28.69	2.14	30.91	2.19	32.62	2.23
					91	24.74	2.10	26.33	2.14	27.55	2.17	28.22	2.19	30.52	2.24	32.27	2.28
					95	24.74	2.15	25.83	2.19	27.10	2.23	28.00	2.24	30.16	2.30	31.96	2.33
					99	24.74	2.21	25.37	2.25	26.68	2.28	27.40	2.30	29.84	2.35	31.69	2.38
					102	24.74	2.26	24.94	2.30	26.30	2.34	27.05	2.35	29.56	2.41	31.46	2.44
					108	24.74	2.35	24.38	2.39	25.81	2.42	26.60	2.44	29.22	2.49	31.19	2.52
					111	24.74	2.41	24.05	2.44	25.53	2.48	26.34	2.50	29.04	2.55	31.05	2.58
					115	24.74	2.47	23.76	2.50	25.30	2.54	26.13	2.56	28.89	2.61	30.96	2.64

Capacity Table

JXH36S4C (AJ036CXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	9	30	68	26.51	1.91	32.73	1.95	33.69	1.99	34.25	2.01	36.20	2.07	37.74	2.11
					70	26.51	1.93	32.32	1.98	33.31	2.02	33.88	2.04	35.87	2.09	37.44	2.13
					73	26.51	1.98	31.53	2.03	32.57	2.07	33.17	2.09	35.24	2.14	36.86	2.18
					77	26.51	2.03	30.78	2.08	31.88	2.12	32.50	2.14	34.65	2.19	36.32	2.23
					81	26.51	2.09	30.08	2.13	31.23	2.17	31.87	2.19	34.10	2.24	35.82	2.28
					84	26.51	2.14	29.42	2.18	30.61	2.22	31.29	2.24	33.59	2.30	35.36	2.33
					88	26.51	2.19	28.79	2.24	30.05	2.27	30.74	2.29	33.12	2.35	34.95	2.38
					91	26.51	2.25	28.21	2.29	29.52	2.33	30.24	2.35	32.70	2.40	34.58	2.44
					95	26.51	2.31	27.68	2.35	29.03	2.39	30.00	2.40	32.32	2.46	34.24	2.50
					99	26.51	2.37	27.18	2.41	28.59	2.44	29.36	2.46	31.97	2.52	33.96	2.55
					102	26.51	2.42	26.72	2.47	28.18	2.50	28.98	2.52	31.68	2.58	33.71	2.61
					108	26.51	2.52	26.12	2.56	27.66	2.60	28.50	2.61	31.30	2.67	33.42	2.70
					111	26.51	2.58	25.77	2.62	27.36	2.66	28.22	2.68	31.11	2.73	33.27	2.76
					115	26.51	2.64	25.46	2.68	27.10	2.72	27.99	2.74	30.96	2.79	33.17	2.83
7	7	7	12	33	68	29.16	2.10	36.00	2.15	37.06	2.19	37.67	2.21	39.82	2.28	41.52	2.32
					70	29.16	2.13	35.55	2.17	36.64	2.22	37.27	2.24	39.46	2.30	41.18	2.34
					73	29.16	2.18	34.68	2.23	35.83	2.27	36.48	2.29	38.76	2.36	40.54	2.40
					77	29.16	2.24	33.86	2.28	35.07	2.33	35.75	2.35	38.11	2.41	39.95	2.45
					81	29.16	2.30	33.09	2.34	34.35	2.38	35.06	2.41	37.51	2.47	39.40	2.51
					84	29.16	2.35	32.36	2.40	33.68	2.44	34.42	2.46	36.95	2.53	38.90	2.56
					88	29.16	2.41	31.67	2.46	33.05	2.50	33.82	2.52	36.43	2.58	38.44	2.62
					91	29.16	2.47	31.04	2.52	32.47	2.56	33.26	2.58	35.97	2.64	38.03	2.68
					95	29.16	2.54	30.44	2.58	31.93	2.63	33.00	2.64	35.55	2.71	37.67	2.75
					99	29.16	2.60	29.90	2.65	31.44	2.69	32.30	2.71	35.17	2.77	37.35	2.81
					102	29.16	2.67	29.40	2.71	31.00	2.75	31.88	2.78	34.84	2.84	37.08	2.87
					108	29.16	2.77	28.73	2.81	30.42	2.85	31.35	2.88	34.43	2.94	36.76	2.97
					111	29.16	2.84	28.35	2.88	30.09	2.92	31.05	2.94	34.22	3.00	36.60	3.04
					115	29.16	2.91	28.01	2.95	29.81	2.99	30.79	3.01	34.05	3.07	36.49	3.11
7	7	7	15	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	18	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	7	7	24	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	9	9	32	68	28.28	2.04	34.91	2.08	35.94	2.13	36.53	2.15	38.62	2.21	40.26	2.25
					70	28.28	2.06	34.47	2.11	35.53	2.15	36.14	2.17	38.26	2.23	39.93	2.27
					73	28.28	2.12	33.63	2.16	34.75	2.20	35.38	2.22	37.59	2.28	39.31	2.32
					77	28.28	2.17	32.84	2.21	34.00	2.26	34.67	2.28	36.96	2.34	38.74	2.38
					81	28.28	2.23	32.08	2.27	33.31	2.31	34.00	2.33	36.37	2.39	38.21	2.43
					84	28.28	2.28	31.38	2.33	32.66	2.37	33.37	2.39	35.83	2.45	37.72	2.49
					88	28.28	2.34	30.71	2.38	32.05	2.43	32.79	2.45	35.33	2.51	37.28	2.54
					91	28.28	2.40	30.09	2.44	31.48	2.49	32.26	2.51	34.88	2.56	36.88	2.60
					95	28.28	2.46	29.52	2.50	30.97	2.55	32.00	2.56	34.47	2.62	36.53	2.66
					99	28.28	2.52	28.99	2.57	30.49	2.61	31.32	2.63	34.11	2.69	36.22	2.72
					102	28.28	2.59	28.51	2.63	30.06	2.67	30.92	2.69	33.79	2.75	35.96	2.79
					108	28.28	2.68	27.86	2.73	29.50	2.77	30.40	2.79	33.39	2.85	35.64	2.88
					111	28.28	2.75	27.49	2.79	29.18	2.83	30.11	2.85	33.18	2.91	35.49	2.95
					115	28.28	2.82	27.16	2.86	28.91	2.90	29.86	2.92	33.02	2.98	35.38	3.02

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	12	35	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	7	9	15	38	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	9	18	41	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	24	47	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	12	12	38	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	7	12	15	41	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	18	44	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	15	15	44	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	15	18	47	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	9	34	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20					
7	9	9	12	37	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20					
7	9	9	15	40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17					

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	18	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	9	12	12	40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	9	12	15	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12	18	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	9	15	15	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	12	12	12	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	12	15	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	9	9	9	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
9	9	9	12	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	15	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	9	9	18	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	9	12	12	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	15	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	9	12	18	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16
9	9	15	15	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67.0		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12	12	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	12	12	15	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16
12	12	12	12	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 48.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9		18	-13	24.54	6.86	20.52	5.44	19.69	5.52	15.24	4.02	13.51	3.35	9.63	2.17	
				5	23.84	4.62	23.27	4.67	22.69	4.74	21.80	4.92	21.55	4.84	20.98	4.88	
				17	23.23	4.00	22.83	4.04	22.43	4.08	21.80	4.23	21.63	4.17	21.22	4.21	
				32	23.04	2.97	22.69	3.00	22.34	3.03	21.80	3.14	21.65	3.08	21.30	3.11	
				47	23.10	2.09	22.83	2.11	22.53	2.13	21.80	2.21	21.92	2.17	21.62	2.19	
				50	25.08	2.22	24.47	2.25	24.01	2.28	23.79	2.30	23.22	2.34	22.89	2.36	
9	12		21	59	27.46	2.31	26.94	2.34	26.45	2.38	26.23	2.39	25.62	2.43	25.26	2.45	
				-13	28.02	7.33	23.44	5.81	22.49	5.90	17.41	4.29	15.44	3.58	11.00	2.32	
				5	27.23	4.94	26.58	4.99	25.92	5.06	24.90	5.25	24.62	5.16	23.96	5.22	
				17	26.53	4.27	26.07	4.32	25.61	4.36	24.90	4.52	24.70	4.45	24.24	4.50	
				32	26.32	3.18	25.92	3.21	25.52	3.24	24.90	3.35	24.73	3.29	24.33	3.32	
				47	26.39	2.23	26.08	2.25	25.74	2.27	24.90	2.36	25.04	2.31	24.69	2.34	
9	15		24	50	28.65	2.37	27.95	2.41	27.42	2.44	27.18	2.45	26.52	2.50	26.14	2.52	
				59	31.37	2.47	30.77	2.50	30.21	2.54	29.95	2.55	29.26	2.60	28.86	2.62	
				-13	29.71	7.76	24.85	6.15	23.84	6.25	18.46	4.55	16.37	3.79	11.67	2.46	
				5	28.87	5.23	28.18	5.28	27.48	5.36	26.40	5.56	26.10	5.47	25.41	5.53	
				17	28.13	4.52	27.65	4.57	27.16	4.62	26.40	4.78	26.19	4.72	25.70	4.76	
				32	27.90	3.37	27.48	3.40	27.06	3.43	26.40	3.55	26.22	3.49	25.79	3.52	
9	18		27	47	27.98	2.37	27.65	2.39	27.29	2.41	26.40	2.50	26.54	2.45	26.18	2.48	
				50	30.38	2.51	29.63	2.55	29.07	2.58	28.81	2.60	28.12	2.64	27.72	2.67	
				59	33.26	2.61	32.62	2.65	32.03	2.69	31.76	2.70	31.02	2.75	30.59	2.78	
				-13	34.78	8.17	29.09	6.47	27.90	6.57	21.61	4.78	19.16	3.99	13.66	2.58	
				5	33.79	5.50	32.98	5.56	32.17	5.64	30.90	5.85	30.55	5.75	29.74	5.81	
				17	32.92	4.76	32.36	4.81	31.79	4.86	30.90	5.03	30.66	4.96	30.08	5.01	
9	24		33	32	32.66	3.54	32.17	3.57	31.67	3.61	30.90	3.73	30.69	3.67	30.19	3.70	
				47	32.75	2.49	32.36	2.51	31.94	2.53	30.90	2.63	31.07	2.58	30.64	2.61	
				50	35.55	2.64	34.68	2.68	34.03	2.72	33.72	2.74	32.91	2.78	32.44	2.81	
				59	38.93	2.75	38.18	2.79	37.49	2.83	37.17	2.84	36.31	2.89	35.81	2.92	
				-13	38.27	9.16	32.01	7.26	30.70	7.37	23.78	5.36	21.08	4.47	15.03	2.90	
				5	37.18	6.17	36.29	6.23	35.39	6.32	34.00	6.56	33.62	6.45	32.72	6.52	
12	12		24	17	36.23	5.34	35.60	5.40	34.98	5.45	34.00	5.65	33.73	5.57	33.10	5.62	
				32	35.94	3.97	35.40	4.01	34.85	4.04	34.00	4.19	33.77	4.12	33.22	4.15	
				47	36.03	2.79	35.61	2.82	35.14	2.84	34.00	2.95	34.19	2.89	33.72	2.92	
				50	39.12	2.96	38.16	3.01	37.44	3.05	37.11	3.07	36.21	3.12	35.70	3.15	
				59	42.83	3.08	42.01	3.13	41.25	3.17	40.90	3.19	39.95	3.24	39.40	3.28	
				-13	29.71	7.76	24.85	6.15	23.84	6.25	18.46	4.55	16.37	3.79	11.67	2.46	
12	15		27	5	28.87	5.23	28.18	5.28	27.48	5.36	26.40	5.56	26.10	5.47	25.41	5.53	
				17	28.13	4.52	27.65	4.57	27.16	4.62	26.40	4.78	26.19	4.72	25.70	4.76	
				32	27.90	3.37	27.48	3.40	27.06	3.43	26.40	3.55	26.22	3.49	25.79	3.52	
				47	27.98	2.37	27.65	2.39	27.29	2.41	26.40	2.50	26.54	2.45	26.18	2.48	
				50	30.38	2.51	29.63	2.55	29.07	2.58	28.81	2.60	28.12	2.64	27.72	2.67	
				59	33.26	2.61	32.62	2.65	32.03	2.69	31.76	2.70	31.02	2.75	30.59	2.78	
12	15		27	-13	36.02	9.35	30.13	7.41	28.90	7.52	22.38	5.47	19.84	4.56	14.14	2.96	
				5	34.99	6.30	34.16	6.36	33.31	6.45	32.00	6.70	31.64	6.59	30.79	6.65	
				17	34.10	5.45	33.51	5.50	32.92	5.56	32.00	5.76	31.75	5.68	31.16	5.73	
				32	33.82	4.05	33.31	4.09	32.80	4.13	32.00	4.27	31.78	4.20	31.27	4.24	
				47	33.91	2.85	33.52	2.87	33.07	2.90	32.00	3.01	32.17	2.95	31.73	2.98	
				50	36.82	3.02	35.92	3.07	35.24	3.11	34.93	3.13	34.08	3.18	33.60	3.21	
12	15		27	59	40.31	3.15	39.54	3.19	38.83	3.24	38.50	3.26	37.60	3.31	37.08	3.34	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)															
						57.2		60.8		64.4		69.98		71.6		75.2					
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)				
12	18			30	-13	38.27	9.16	32.01	7.26	30.70	7.37	23.78	5.36	21.08	4.47	15.03	2.90				
					5	37.18	6.17	36.29	6.23	35.39	6.32	34.00	6.56	33.62	6.45	32.72	6.52				
					17	36.23	5.34	35.60	5.40	34.98	5.45	34.00	5.65	33.73	5.57	33.10	5.62				
					32	35.94	3.97	35.40	4.01	34.85	4.04	34.00	4.19	33.77	4.12	33.22	4.15				
					47	36.03	2.79	35.61	2.82	35.14	2.84	34.00	2.95	34.19	2.89	33.72	2.92				
					50	39.12	2.96	38.16	3.01	37.44	3.05	37.11	3.07	36.21	3.12	35.70	3.15				
					59	42.83	3.08	42.01	3.13	41.25	3.17	40.90	3.19	39.95	3.24	39.40	3.28				
					12	24		36	-13	38.94	9.16	32.57	7.26	31.25	7.37	24.20	5.36	21.45	4.47	15.29	2.90
									5	37.84	6.17	36.93	6.23	36.02	6.32	34.60	6.56	34.21	6.45	33.30	6.52
									17	36.87	5.34	36.23	5.40	35.59	5.45	34.60	5.65	34.33	5.57	33.69	5.62
									32	36.57	3.97	36.02	4.01	35.46	4.04	34.60	4.19	34.36	4.12	33.81	4.15
									47	36.67	2.79	36.24	2.82	35.76	2.84	34.60	2.95	34.79	2.89	34.31	2.92
50	39.81	2.96	38.84	3.01					38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15					
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28				
					15	18		33	-13	38.27	9.16	32.01	7.26	30.70	7.37	23.78	5.36	21.08	4.47	15.03	2.90
									5	37.18	6.17	36.29	6.23	35.39	6.32	34.00	6.56	33.62	6.45	32.72	6.52
									17	36.23	5.34	35.60	5.40	34.98	5.45	34.00	5.65	33.73	5.57	33.10	5.62
									32	35.94	3.97	35.40	4.01	34.85	4.04	34.00	4.19	33.77	4.12	33.22	4.15
									47	36.03	2.79	35.61	2.82	35.14	2.84	34.00	2.95	34.19	2.89	33.72	2.92
50	39.12	2.96	38.16	3.01					37.44	3.05	37.11	3.07	36.21	3.12	35.70	3.15					
					59	42.83	3.08	42.01	3.13	41.25	3.17	40.90	3.19	39.95	3.24	39.40	3.28				
					18	18		36	-13	38.94	9.16	32.57	7.26	31.25	7.37	24.20	5.36	21.45	4.47	15.29	2.90
									5	37.84	6.17	36.93	6.23	36.02	6.32	34.60	6.56	34.21	6.45	33.30	6.52
									17	36.87	5.34	36.23	5.40	35.59	5.45	34.60	5.65	34.33	5.57	33.69	5.62
									32	36.57	3.97	36.02	4.01	35.46	4.04	34.60	4.19	34.36	4.12	33.81	4.15
									47	36.67	2.79	36.24	2.82	35.76	2.84	34.60	2.95	34.79	2.89	34.31	2.92
50	39.81	2.96	38.84	3.01					38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15					
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28				
					9	9	9	27	-13	26.23	4.90	25.01	4.94	24.30	5.01	22.87	5.07	22.15	5.14	20.72	5.14
									5	35.32	6.00	34.56	6.06	33.57	6.14	32.70	6.21	31.96	6.27	31.34	6.32
									17	34.83	5.15	34.19	5.21	33.40	5.28	32.70	5.34	32.09	5.39	31.56	5.44
									32	34.68	3.82	34.08	3.86	33.35	3.92	32.70	3.96	32.13	4.00	31.63	4.04
									47	34.54	2.69	33.98	2.72	33.31	2.76	32.70	2.79	32.16	2.82	31.69	2.85
50	37.63	2.80	36.70	2.85					36.01	2.88	35.69	2.90	34.83	2.95	34.33	2.98					
					59	41.20	2.92	40.40	2.96	39.68	3.00	39.34	3.02	38.42	3.07	37.90	3.10				
					9	9	12	30	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
									5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
									17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
									32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
									47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
50	39.81	2.96	38.84	3.01					38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15					
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28				
					9	9	15	33	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
									5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
									17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
									32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
									47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
50	39.81	2.96	38.84	3.01					38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15					
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28				

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	18	36	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
9	12	12	33	59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
9	12	15	36	50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
9	12	18	39	47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
9	18	18	45	32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
12	12	12	36	17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
12	12	18	42	5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	18	18		48	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	12	12	48	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 48.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0***BNHDCH/AA or AC0***BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7		14	-13	16.88	3.91	14.12	3.10	13.55	3.15	10.49	2.29	9.30	1.91	6.63	1.24	
				5	16.40	2.64	16.01	2.66	15.61	2.70	15.00	2.80	14.83	2.76	14.43	2.78	
				17	15.98	2.28	15.71	2.30	15.43	2.33	15.00	2.41	14.88	2.38	14.60	2.40	
				32	15.85	1.70	15.62	1.71	15.37	1.73	15.00	1.79	14.90	1.76	14.66	1.77	
				47	15.90	1.19	15.71	1.20	15.50	1.21	15.00	1.26	15.08	1.23	14.87	1.25	
				50	17.26	1.27	16.84	1.29	16.52	1.30	16.37	1.31	15.97	1.33	15.75	1.34	
7	9		16	59	18.90	1.32	18.53	1.34	18.20	1.35	18.05	1.36	17.63	1.39	17.38	1.40	
				-13	20.71	4.75	17.32	3.77	16.62	3.82	12.87	2.78	11.41	2.32	8.13	1.50	
				5	20.12	3.20	19.64	3.23	19.15	3.28	18.40	3.40	18.19	3.35	17.71	3.38	
				17	19.61	2.77	19.27	2.80	18.93	2.82	18.40	2.93	18.25	2.89	17.91	2.91	
				32	19.45	2.06	19.16	2.08	18.86	2.10	18.40	2.17	18.27	2.14	17.98	2.15	
				47	19.50	1.45	19.27	1.46	19.02	1.47	18.40	1.53	18.50	1.50	18.25	1.52	
7	12		19	50	21.17	1.54	20.65	1.56	20.26	1.58	20.08	1.59	19.60	1.62	19.32	1.63	
				59	23.18	1.60	22.73	1.62	22.33	1.64	22.14	1.65	21.62	1.68	21.32	1.70	
				-13	24.20	5.19	20.24	4.11	19.42	4.17	15.03	3.04	13.33	2.53	9.50	1.64	
				5	23.51	3.49	22.95	3.53	22.38	3.58	21.50	3.72	21.26	3.65	20.69	3.69	
				17	22.91	3.02	22.51	3.05	22.12	3.08	21.50	3.20	21.33	3.15	20.93	3.18	
				32	22.72	2.25	22.38	2.27	22.04	2.29	21.50	2.37	21.35	2.33	21.01	2.35	
7	15		22	47	22.79	1.58	22.52	1.59	22.22	1.61	21.50	1.67	21.62	1.64	21.32	1.66	
				50	24.74	1.68	24.13	1.70	23.68	1.73	23.47	1.74	22.90	1.77	22.57	1.78	
				59	27.09	1.75	26.56	1.77	26.09	1.80	25.86	1.81	25.26	1.84	24.92	1.85	
				-13	28.70	6.18	24.01	4.90	23.03	4.97	17.83	3.62	15.81	3.02	11.27	1.96	
				5	27.88	4.16	27.22	4.21	26.54	4.26	25.50	4.43	25.21	4.35	24.54	4.40	
				17	27.17	3.60	26.70	3.64	26.23	3.67	25.50	3.81	25.30	3.76	24.83	3.79	
7	18		25	32	26.95	2.68	26.55	2.70	26.14	2.73	25.50	2.83	25.32	2.78	24.91	2.80	
				47	27.03	1.88	26.71	1.90	26.36	1.92	25.50	1.99	25.64	1.95	25.29	1.97	
				50	29.34	2.00	28.62	2.03	28.08	2.06	27.83	2.07	27.16	2.10	26.77	2.12	
				59	32.13	2.08	31.51	2.11	30.94	2.14	30.68	2.15	29.96	2.19	29.55	2.21	
				-13	30.95	6.24	25.89	4.95	24.83	5.02	19.23	3.65	17.05	3.05	12.15	1.98	
				5	30.07	4.21	29.35	4.25	28.63	4.31	27.50	4.47	27.19	4.40	26.46	4.44	
7	24		31	17	29.30	3.64	28.80	3.68	28.29	3.71	27.50	3.85	27.28	3.79	26.77	3.83	
				32	29.07	2.71	28.63	2.73	28.19	2.76	27.50	2.85	27.31	2.81	26.87	2.83	
				47	29.15	1.90	28.80	1.92	28.42	1.94	27.50	2.01	27.65	1.97	27.27	1.99	
				50	31.64	2.02	30.87	2.05	30.28	2.08	30.01	2.09	29.29	2.13	28.87	2.15	
				59	34.64	2.10	33.98	2.13	33.37	2.16	33.08	2.17	32.31	2.21	31.87	2.23	
				-13	37.14	7.48	31.07	5.93	29.80	6.02	23.08	4.38	20.46	3.65	14.58	2.37	
9	9		18	5	36.09	5.04	35.22	5.09	34.35	5.17	33.00	5.36	32.63	5.27	31.76	5.33	
				17	35.16	4.36	34.56	4.41	33.95	4.45	33.00	4.61	32.74	4.55	32.13	4.59	
				32	34.88	3.24	34.35	3.27	33.82	3.30	33.00	3.42	32.77	3.36	32.24	3.39	
				47	34.97	2.28	34.56	2.30	34.11	2.32	33.00	2.41	33.18	2.36	32.72	2.39	
				50	37.97	2.42	37.04	2.46	36.34	2.49	36.02	2.51	35.14	2.55	34.65	2.57	
				59	41.57	2.52	40.77	2.56	40.04	2.59	39.70	2.61	38.78	2.65	38.24	2.68	
9	9		18	-13	24.54	5.31	20.52	4.21	19.69	4.27	15.24	3.11	13.51	2.59	9.63	1.68	
				5	23.84	3.58	23.27	3.61	22.69	3.66	21.80	3.80	21.55	3.74	20.98	3.78	
				17	23.23	3.09	22.83	3.13	22.43	3.16	21.80	3.27	21.63	3.23	21.22	3.26	
				32	23.04	2.30	22.69	2.32	22.34	2.34	21.80	2.43	21.65	2.39	21.30	2.41	
				47	23.10	1.62	22.83	1.63	22.53	1.65	21.80	1.71	21.92	1.68	21.62	1.69	
				50	25.08	1.72	24.47	1.74	24.01	1.77	23.79	1.78	23.22	1.81	22.89	1.82	
					59	27.46	1.79	26.94	1.81	26.45	1.84	26.23	1.85	25.62	1.88	25.26	1.90

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12			21	-13	28.02	5.78	23.44	4.58	22.49	4.65	17.41	3.38	15.44	2.82	11.00	1.83
					5	27.23	3.89	26.58	3.93	25.92	3.99	24.90	4.14	24.62	4.07	23.96	4.11
					17	26.53	3.37	26.07	3.40	25.61	3.43	24.90	3.56	24.70	3.51	24.24	3.54
					32	26.32	2.50	25.92	2.53	25.52	2.55	24.90	2.64	24.73	2.60	24.33	2.62
					47	26.39	1.76	26.08	1.78	25.74	1.79	24.90	1.86	25.04	1.82	24.69	1.84
					50	28.65	1.87	27.95	1.90	27.42	1.92	27.18	1.93	26.52	1.97	26.14	1.99
9	15			24	59	31.37	1.94	30.77	1.97	30.21	2.00	29.95	2.01	29.26	2.05	28.86	2.07
					-13	29.83	6.37	24.95	5.05	23.93	5.12	18.53	3.73	16.43	3.11	11.71	2.01
					5	28.98	4.29	28.28	4.33	27.59	4.39	26.50	4.56	26.20	4.49	25.50	4.53
					17	28.24	3.71	27.75	3.75	27.26	3.79	26.50	3.92	26.29	3.87	25.80	3.90
					32	28.01	2.76	27.59	2.78	27.16	2.81	26.50	2.91	26.32	2.86	25.89	2.89
					47	28.09	1.94	27.76	1.96	27.39	1.97	26.50	2.05	26.64	2.01	26.28	2.03
9	18			27	50	30.49	2.06	29.74	2.09	29.18	2.12	28.92	2.13	28.22	2.17	27.82	2.19
					59	33.38	2.14	32.74	2.17	32.15	2.20	31.88	2.22	31.14	2.25	30.71	2.28
					-13	34.78	7.02	29.09	5.56	27.90	5.65	21.61	4.11	19.16	3.42	13.66	2.22
					5	33.79	4.73	32.98	4.78	32.17	4.84	30.90	5.03	30.55	4.94	29.74	4.99
					17	32.92	4.09	32.36	4.13	31.79	4.17	30.90	4.33	30.66	4.27	30.08	4.30
					32	32.66	3.04	32.17	3.07	31.67	3.10	30.90	3.21	30.69	3.15	30.19	3.18
9	24			33	47	32.75	2.14	32.36	2.16	31.94	2.18	30.90	2.26	31.07	2.21	30.64	2.24
					50	35.55	2.27	34.68	2.30	34.03	2.34	33.72	2.35	32.91	2.39	32.44	2.41
					59	38.93	2.36	38.18	2.40	37.49	2.43	37.17	2.44	36.31	2.49	35.81	2.51
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
12	12			24	32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.83	6.37	24.95	5.05	23.93	5.12	18.53	3.73	16.43	3.11	11.71	2.01
					5	28.98	4.29	28.28	4.33	27.59	4.39	26.50	4.56	26.20	4.49	25.50	4.53
12	15			27	17	28.24	3.71	27.75	3.75	27.26	3.79	26.50	3.92	26.29	3.87	25.80	3.90
					32	28.01	2.76	27.59	2.78	27.16	2.81	26.50	2.91	26.32	2.86	25.89	2.89
					47	28.09	1.94	27.76	1.96	27.39	1.97	26.50	2.05	26.64	2.01	26.28	2.03
					50	30.49	2.06	29.74	2.09	29.18	2.12	28.92	2.13	28.22	2.17	27.82	2.19
					59	33.38	2.14	32.74	2.17	32.15	2.20	31.88	2.22	31.14	2.25	30.71	2.28
					-13	36.02	7.27	30.13	5.76	28.90	5.85	22.38	4.25	19.84	3.55	14.14	2.30
12	18			30	5	34.99	4.90	34.16	4.95	33.31	5.02	32.00	5.21	31.64	5.12	30.79	5.17
					17	34.10	4.23	33.51	4.28	32.92	4.32	32.00	4.48	31.75	4.42	31.16	4.46
					32	33.82	3.15	33.31	3.18	32.80	3.21	32.00	3.32	31.78	3.27	31.27	3.30
					47	33.91	2.22	33.52	2.23	33.07	2.25	32.00	2.34	32.17	2.29	31.73	2.32
					50	36.82	2.35	35.92	2.39	35.24	2.42	34.93	2.43	34.08	2.47	33.60	2.50
					59	40.31	2.45	39.54	2.48	38.83	2.52	38.50	2.53	37.60	2.57	37.08	2.60
12	18			30	-13	38.27	7.73	32.01	6.13	30.70	6.22	23.78	4.53	21.08	3.77	15.03	2.45
					5	37.18	5.21	36.29	5.26	35.39	5.34	34.00	5.54	33.62	5.45	32.72	5.50
					17	36.23	4.51	35.60	4.55	34.98	4.60	34.00	4.77	33.73	4.70	33.10	4.74
					32	35.94	3.35	35.40	3.38	34.85	3.41	34.00	3.54	33.77	3.48	33.22	3.51
					47	36.03	2.36	35.61	2.38	35.14	2.40	34.00	2.49	34.19	2.44	33.72	2.47
					50	39.12	2.50	38.16	2.54	37.44	2.57	37.11	2.59	36.21	2.63	35.70	2.66
12	18			30	59	42.83	2.60	42.01	2.64	41.25	2.68	40.90	2.69	39.95	2.74	39.40	2.77

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	24			36	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
15	15			30	-13	38.27	7.92	32.01	6.28	30.70	6.37	23.78	4.64	21.08	3.86	15.03	2.51
					5	37.18	5.34	36.29	5.39	35.39	5.47	34.00	5.67	33.62	5.58	32.72	5.64
					17	36.23	4.61	35.60	4.66	34.98	4.71	34.00	4.88	33.73	4.81	33.10	4.86
					32	35.94	3.43	35.40	3.46	34.85	3.50	34.00	3.62	33.77	3.56	33.22	3.59
					47	36.03	2.41	35.61	2.44	35.14	2.46	34.00	2.55	34.19	2.50	33.72	2.53
					50	39.12	2.56	38.16	2.60	37.44	2.64	37.11	2.65	36.21	2.70	35.70	2.72
					59	42.83	2.66	42.01	2.70	41.25	2.74	40.90	2.76	39.95	2.80	39.40	2.83
15	18			33	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
15	24			39	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
18	18			36	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
18	24			42	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
24	24			48	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	21	-13	18.05	2.55	17.21	2.57	16.72	2.60	15.73	2.64	15.24	2.67	14.26	2.67	
				5	24.30	3.12	23.78	3.15	23.10	3.19	22.50	3.23	21.99	3.26	21.57	3.28	
				17	23.97	2.68	23.53	2.71	22.98	2.74	22.50	2.78	22.08	2.80	21.72	2.83	
				32	23.86	1.99	23.45	2.01	22.95	2.03	22.50	2.06	22.10	2.08	21.76	2.10	
				47	23.77	1.40	23.38	1.41	22.92	1.43	22.50	1.45	22.13	1.47	21.81	1.48	
				50	25.89	1.46	25.25	1.48	24.78	1.50	24.56	1.51	23.96	1.53	23.62	1.55	
7	7	9	23	59	28.35	1.52	27.80	1.54	27.30	1.56	27.07	1.57	26.44	1.59	26.07	1.61	
				-13	20.77	2.95	19.81	2.98	19.24	3.02	18.11	3.05	17.55	3.09	16.41	3.09	
				5	27.98	3.61	27.37	3.65	26.59	3.70	25.90	3.74	25.31	3.77	24.83	3.80	
				17	27.59	3.10	27.08	3.14	26.46	3.18	25.90	3.22	25.41	3.25	25.00	3.28	
				32	27.47	2.30	26.99	2.33	26.42	2.36	25.90	2.39	25.45	2.41	25.05	2.43	
				47	27.36	1.62	26.91	1.64	26.38	1.66	25.90	1.68	25.47	1.70	25.10	1.71	
7	7	12	26	50	29.80	1.69	29.07	1.71	28.52	1.74	28.27	1.75	27.58	1.78	27.19	1.79	
				59	32.63	1.76	32.00	1.78	31.43	1.81	31.16	1.82	30.43	1.85	30.01	1.87	
				-13	23.26	3.55	22.18	3.58	21.55	3.63	20.28	3.67	19.65	3.72	18.38	3.72	
				5	31.33	4.34	30.65	4.39	29.77	4.44	29.00	4.49	28.34	4.54	27.80	4.57	
				17	30.89	3.73	30.32	3.77	29.62	3.82	29.00	3.87	28.46	3.91	27.99	3.94	
				32	30.76	2.77	30.22	2.80	29.58	2.83	29.00	2.87	28.49	2.90	28.05	2.92	
7	7	15	29	47	30.63	1.95	30.13	1.97	29.54	2.00	29.00	2.02	28.52	2.04	28.10	2.06	
				50	33.37	2.03	32.55	2.06	31.94	2.09	31.65	2.10	30.88	2.14	30.45	2.16	
				59	36.53	2.11	35.83	2.14	35.19	2.17	34.89	2.18	34.08	2.22	33.61	2.24	
				-13	26.47	4.04	25.24	4.07	24.52	4.13	23.08	4.18	22.36	4.24	20.91	4.24	
				5	35.65	4.94	34.88	4.99	33.88	5.06	33.00	5.12	32.25	5.17	31.63	5.21	
				17	35.15	4.25	34.51	4.29	33.71	4.35	33.00	4.40	32.38	4.45	31.85	4.49	
7	7	18	32	32	35.00	3.15	34.39	3.19	33.66	3.23	33.00	3.27	32.42	3.30	31.92	3.33	
				47	34.86	2.22	34.29	2.24	33.61	2.27	33.00	2.30	32.46	2.32	31.98	2.35	
				50	37.97	2.31	37.04	2.35	36.34	2.38	36.02	2.39	35.14	2.43	34.65	2.45	
				59	41.57	2.40	40.77	2.44	40.04	2.47	39.70	2.49	38.78	2.53	38.24	2.55	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
7	7	24	38	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
7	9	9	25	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
7	9	9	25	-13	23.50	3.59	22.41	3.61	21.77	3.66	20.49	3.71	19.85	3.76	18.57	3.76	
				5	31.65	4.38	30.97	4.43	30.08	4.49	29.30	4.54	28.64	4.58	28.09	4.62	
				17	31.21	3.77	30.64	3.81	29.93	3.86	29.30	3.90	28.75	3.94	28.28	3.98	
				32	31.07	2.79	30.54	2.83	29.88	2.86	29.30	2.90	28.79	2.93	28.34	2.95	
				47	30.95	1.97	30.45	1.99	29.84	2.02	29.30	2.04	28.82	2.06	28.40	2.08	
				50	33.71	2.05	32.89	2.08	32.27	2.11	31.98	2.12	31.20	2.16	30.76	2.18	
7	9	9	25	59	36.91	2.13	36.20	2.16	35.55	2.19	35.25	2.21	34.43	2.24	33.96	2.27	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12		28	-13	25.99	3.97	24.78	4.00	24.07	4.06	22.66	4.11	21.95	4.16	20.53	4.16
					5	35.00	4.86	34.24	4.91	33.26	4.97	32.40	5.03	31.67	5.08	31.06	5.12
					17	34.51	4.17	33.88	4.22	33.10	4.28	32.40	4.33	31.79	4.37	31.27	4.41
					32	34.36	3.10	33.77	3.13	33.05	3.17	32.40	3.21	31.83	3.24	31.34	3.27
					47	34.23	2.18	33.67	2.20	33.00	2.23	32.40	2.26	31.87	2.28	31.40	2.31
					50	37.28	2.27	36.37	2.30	35.68	2.34	35.36	2.35	34.51	2.39	34.02	2.41
					59	40.82	2.36	40.03	2.40	39.31	2.43	38.98	2.44	38.07	2.49	37.55	2.51
7	9	15		31	-13	29.19	4.46	27.84	4.50	27.05	4.56	25.45	4.62	24.66	4.68	23.07	4.68
					5	39.32	5.46	38.47	5.52	37.37	5.59	36.40	5.65	35.58	5.71	34.89	5.75
					17	38.77	4.69	38.06	4.74	37.18	4.81	36.40	4.86	35.72	4.91	35.13	4.95
					32	38.60	3.48	37.94	3.52	37.13	3.56	36.40	3.61	35.76	3.64	35.21	3.68
					47	38.45	2.45	37.82	2.48	37.07	2.51	36.40	2.54	35.80	2.57	35.28	2.59
					50	41.88	2.55	40.86	2.59	40.09	2.63	39.73	2.64	38.77	2.69	38.22	2.71
					59	45.86	2.65	44.97	2.69	44.17	2.73	43.79	2.75	42.77	2.79	42.18	2.82
7	9	18		34	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
7	9	24		40	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
7	12	12		31	-13	28.47	4.34	27.15	4.38	26.38	4.43	24.83	4.49	24.05	4.55	22.50	4.55
					5	38.35	5.31	37.52	5.36	36.44	5.43	35.50	5.50	34.70	5.55	34.03	5.59
					17	37.81	4.56	37.12	4.61	36.26	4.67	35.50	4.73	34.83	4.78	34.26	4.82
					32	37.65	3.38	37.00	3.42	36.21	3.47	35.50	3.51	34.88	3.54	34.34	3.58
					47	37.50	2.38	36.89	2.41	36.16	2.44	35.50	2.47	34.92	2.50	34.40	2.52
					50	40.85	2.48	39.85	2.52	39.09	2.55	38.75	2.57	37.81	2.61	37.27	2.64
					59	44.72	2.58	43.86	2.62	43.07	2.66	42.71	2.67	41.71	2.72	41.14	2.74
7	12	15		34	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
7	12	18		37	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

Capacity Table

JXH36S4C (AJ036CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	24	43	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
7	15	15	37	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
7	15	18	40	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
7	15	24	46	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
7	18	18	43	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
9	9	9	27	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	34.68	3.12	34.08	3.16	33.35	3.20	32.70	3.24	32.13	3.27	31.63	3.30	
				47	34.54	2.20	33.98	2.22	33.31	2.25	32.70	2.28	32.16	2.30	31.69	2.33	
				50	37.63	2.29	36.70	2.33	36.01	2.36	35.69	2.37	34.83	2.41	34.33	2.43	
				59	41.20	2.38	40.40	2.42	39.68	2.45	39.34	2.47	38.42	2.51	37.90	2.53	
				-13	26.23	4.01	25.01	4.04	24.30	4.09	22.87	4.15	22.15	4.20	20.72	4.20	
9	9	12	30	5	35.32	4.90	34.56	4.95	33.57	5.02	32.70	5.07	31.96	5.12	31.34	5.16	
				17	34.83	4.21	34.19	4.26	33.40	4.31	32.70	4.36	32.09	4.41	31.56	4.45	
				32	37.97	3.41	37.31	3.45	36.51	3.49	35.80	3.54	35.17	3.57	34.63	3.60	
				47	37.82	2.40	37.20	2.43	36.46	2.46	35.80	2.49	35.21	2.52	34.69	2.54	
				50	41.19	2.50	40.18	2.54	39.42	2.57	39.07	2.59	38.13	2.63	37.59	2.66	
				59	45.10	2.60	44.23	2.64	43.44	2.68	43.07	2.69	42.07	2.74	41.49	2.77	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	15	33	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
			36	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
			42	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
			33	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
			36	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
			39	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
			45	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15	15	39	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
9	15	18	42	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
9	15	24	48	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
9	18	18	45	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
12	12	12	36	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
12	12	15	39	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
12	12	18	42	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)																	
						57.2		60.8		64.4		69.98		71.6		75.2							
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)						
12	12	24		48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
12	15	15		42	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
12	15	18		45	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
12	18	18		48	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
15	15	15		45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
15	15	18		48	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69						
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60						
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72						
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83						
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70						
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77						
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97						
7	7	7	7	28	32	31.82	3.00	31.27	3.03	30.60	3.07	30.00	3.11	29.47	3.14	29.02	3.17						
					47	31.69	2.11	31.17	2.14	30.56	2.16	30.00	2.19	29.51	2.21	29.07	2.23						
					50	34.52	2.20	33.67	2.23	33.04	2.26	32.74	2.28	31.95	2.32	31.50	2.34						
					59	37.79	2.29	37.07	2.32	36.40	2.35	36.09	2.37	35.25	2.41	34.77	2.43						
											59	37.79	2.29	37.07	2.32	36.40	2.35	36.09	2.37	35.25	2.41	34.77	2.43

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	9	30	-13	26.79	4.29	25.55	4.32	24.82	4.38	23.36	4.44	22.63	4.49	21.17	4.49
					5	36.08	5.24	35.30	5.30	34.29	5.37	33.40	5.43	32.64	5.48	32.02	5.53
					17	35.58	4.51	34.93	4.56	34.12	4.62	33.40	4.67	32.77	4.72	32.24	4.76
					32	35.42	3.34	34.81	3.38	34.07	3.42	33.40	3.46	32.81	3.50	32.31	3.53
					47	35.28	2.35	34.71	2.38	34.02	2.41	33.40	2.44	32.85	2.47	32.37	2.49
					50	38.43	2.45	37.49	2.49	36.78	2.52	36.45	2.54	35.57	2.58	35.07	2.60
7	7	7	12	33	59	42.08	2.55	41.27	2.59	40.53	2.62	40.18	2.64	39.25	2.68	38.71	2.71
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
7	7	7	15	36	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
7	7	7	18	39	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
7	7	7	24	45	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
7	7	9	9	32	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
7	7	9	12	35	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	15	38	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	7	9	18	41	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
7	7	9	24	47	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
7	7	12	12	38	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
7	7	12	15	41	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
7	7	12	18	44	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
7	7	15	15	44	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	15	18	47	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	9	9	34	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
7	9	9	9	34	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
7	9	9	12	37	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
7	9	9	15	40	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
7	9	9	18	43	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
7	9	12	12	40	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
7	9	12	15	43	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	15	15	46	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
7	9	12	12	46	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
7	12	12	12	43	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
7	12	12	15	46	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
9	9	9	9	36	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
9	9	9	12	39	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	9	9	15	42	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72

Capacity Table

JXH36S4C (AJ036CX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	18	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
9	9	12	12	42	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
9	9	12	12	42	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
9	9	12	15	45	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
9	9	12	15	45	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
9	9	12	18	48	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
9	9	15	15	48	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	12	12	12	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
9	12	12	15	48	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
9	12	12	15	48	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69

Capacity Table

JXH36S4C (AJ036CXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57.2		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	12	12	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

- Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).
- Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).
- The above values are based on connection of non-ducted indoor units.
- Capacities are based on the following conditions:
 - Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)
- The total combination index of connected indoor units is up to 48.
- Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.
Single indoor unit connection is not allowed.
- This reference data is based on temperature and capacity trend.

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9				9	68	7.20	0.57	9.60	0.61	10.03	0.65	10.24	0.67	10.89	0.70	11.32	0.71
					70	7.20	0.58	9.52	0.62	9.95	0.66	10.16	0.67	10.80	0.71	11.23	0.72
					73	7.20	0.61	9.36	0.65	9.78	0.68	9.99	0.69	10.63	0.72	11.06	0.73
					77	7.20	0.63	9.20	0.67	9.61	0.70	9.82	0.71	10.46	0.74	10.89	0.75
					81	7.20	0.65	9.03	0.69	9.45	0.72	9.66	0.73	10.29	0.76	10.71	0.76
					84	7.20	0.68	8.87	0.71	9.28	0.74	9.49	0.75	10.12	0.77	10.54	0.78
					88	7.20	0.70	8.71	0.73	9.12	0.76	9.33	0.77	9.95	0.79	10.37	0.79
					91	7.20	0.72	8.55	0.76	8.96	0.78	9.16	0.79	9.78	0.81	10.20	0.81
					95	7.20	0.75	8.39	0.78	8.79	0.80	9.00	0.80	9.61	0.83	10.02	0.83
					99	7.20	0.77	8.23	0.80	8.63	0.82	8.83	0.83	9.44	0.84	9.85	0.84
					102	7.20	0.80	8.07	0.83	8.47	0.85	8.67	0.85	9.28	0.86	9.68	0.86
					108	7.11	0.84	7.83	0.86	8.23	0.88	8.42	0.88	9.03	0.89	9.43	0.88
					111	6.75	0.86	7.67	0.89	8.07	0.90	8.26	0.91	8.86	0.91	9.26	0.90
115	6.57	0.89	7.52	0.91	7.90	0.93	8.10	0.93	8.69	0.93	9.09	0.92					
12				12	68	9.60	0.84	12.81	0.90	13.37	0.95	13.66	0.97	14.52	1.02	15.09	1.04
					70	9.60	0.85	12.70	0.91	13.26	0.97	13.54	0.99	14.40	1.03	14.98	1.05
					73	9.60	0.88	12.48	0.94	13.04	0.99	13.32	1.01	14.17	1.06	14.75	1.07
					77	9.60	0.92	12.26	0.98	12.82	1.02	13.10	1.04	13.95	1.08	14.51	1.09
					81	9.60	0.95	12.04	1.01	12.60	1.05	12.88	1.07	13.72	1.11	14.28	1.12
					84	9.60	0.99	11.83	1.04	12.38	1.08	12.66	1.10	13.49	1.13	14.05	1.14
					88	9.60	1.02	11.61	1.07	12.16	1.11	12.43	1.13	13.27	1.16	13.82	1.16
					91	9.60	1.06	11.40	1.11	11.94	1.14	12.21	1.16	13.04	1.18	13.59	1.18
					95	9.60	1.09	11.19	1.14	11.72	1.17	12.00	1.17	12.81	1.21	13.37	1.21
					99	9.60	1.13	10.97	1.17	11.51	1.20	11.78	1.22	12.59	1.23	13.14	1.23
					102	9.60	1.17	10.76	1.21	11.29	1.24	11.56	1.25	12.37	1.26	12.91	1.26
					108	9.48	1.23	10.44	1.26	10.97	1.29	11.23	1.29	12.03	1.30	12.57	1.29
					111	9.00	1.26	10.23	1.30	10.75	1.32	11.02	1.33	11.81	1.33	12.35	1.32
115	8.76	1.30	10.02	1.33	10.54	1.35	10.80	1.36	11.59	1.36	12.12	1.35					
9	9			18	68	15.91	1.35	19.64	1.38	20.22	1.41	20.55	1.43	21.72	1.47	22.65	1.49
					70	15.91	1.37	19.39	1.40	19.99	1.43	20.33	1.44	21.52	1.48	22.46	1.51
					73	15.91	1.41	18.92	1.43	19.54	1.46	19.90	1.48	21.14	1.52	22.11	1.54
					77	15.91	1.44	18.47	1.47	19.13	1.50	19.50	1.51	20.79	1.55	21.79	1.58
					81	15.91	1.48	18.05	1.51	18.74	1.54	19.12	1.55	20.46	1.59	21.49	1.61
					84	15.91	1.52	17.65	1.54	18.37	1.57	18.77	1.59	20.15	1.63	21.22	1.65
					88	15.91	1.55	17.28	1.58	18.03	1.61	18.45	1.62	19.87	1.66	20.97	1.69
					91	15.91	1.59	16.93	1.62	17.71	1.65	18.14	1.66	19.62	1.70	20.75	1.73
					95	15.91	1.63	16.61	1.66	17.42	1.69	17.86	1.70	19.39	1.74	20.55	1.77
					99	15.91	1.68	16.31	1.70	17.15	1.73	17.62	1.75	19.18	1.78	20.37	1.81
					102	15.91	1.72	16.03	1.75	16.91	1.77	17.39	1.79	19.01	1.83	20.22	1.85
					108	15.91	1.78	15.67	1.81	16.59	1.84	17.10	1.85	18.78	1.89	20.05	1.91
					111	15.91	1.83	15.46	1.86	16.42	1.88	16.93	1.90	18.67	1.93	19.96	1.96
115	15.91	1.87	15.28	1.90	16.26	1.93	16.80	1.94	18.57	1.98	19.90	2.00					

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12		21	68	18.56	1.46	22.91	1.50	23.59	1.53	23.97	1.54	25.34	1.59	26.42	1.61	
				70	18.56	1.48	22.62	1.52	23.32	1.55	23.71	1.56	25.11	1.60	26.21	1.63	
				73	18.56	1.52	22.07	1.55	22.80	1.58	23.22	1.60	24.67	1.64	25.80	1.67	
				77	18.56	1.56	21.55	1.59	22.32	1.62	22.75	1.64	24.25	1.68	25.42	1.71	
				81	18.56	1.60	21.05	1.63	21.86	1.66	22.31	1.68	23.87	1.72	25.07	1.75	
				84	18.56	1.64	20.59	1.67	21.43	1.70	21.90	1.72	23.51	1.76	24.75	1.79	
				88	18.56	1.68	20.16	1.71	21.03	1.74	21.52	1.76	23.19	1.80	24.46	1.83	
				91	18.56	1.72	19.75	1.76	20.66	1.79	21.17	1.80	22.89	1.84	24.20	1.87	
				95	18.56	1.77	19.37	1.80	20.32	1.83	21.00	1.84	22.62	1.89	23.97	1.91	
				99	18.56	1.81	19.03	1.84	20.01	1.87	20.55	1.89	22.38	1.93	23.77	1.96	
				102	18.56	1.86	18.71	1.89	19.73	1.92	20.29	1.93	22.17	1.98	23.60	2.00	
				108	18.56	1.93	18.28	1.96	19.36	1.99	19.95	2.00	21.91	2.05	23.39	2.07	
				111	18.56	1.98	18.04	2.01	19.15	2.04	19.76	2.05	21.78	2.09	23.29	2.12	
				115	18.56	2.03	17.82	2.06	18.97	2.09	19.60	2.10	21.67	2.14	23.22	2.17	
12	12		24	68	18.56	1.46	22.91	1.50	23.59	1.53	23.97	1.54	25.34	1.59	26.42	1.61	
				70	18.56	1.48	22.62	1.52	23.32	1.55	23.71	1.56	25.11	1.60	26.21	1.63	
				73	18.56	1.52	22.07	1.55	22.80	1.58	23.22	1.60	24.67	1.64	25.80	1.67	
				77	18.56	1.56	21.55	1.59	22.32	1.62	22.75	1.64	24.25	1.68	25.42	1.71	
				81	18.56	1.60	21.05	1.63	21.86	1.66	22.31	1.68	23.87	1.72	25.07	1.75	
				84	18.56	1.64	20.59	1.67	21.43	1.70	21.90	1.72	23.51	1.76	24.75	1.79	
				88	18.56	1.68	20.16	1.71	21.03	1.74	21.52	1.76	23.19	1.80	24.46	1.83	
				91	18.56	1.72	19.75	1.76	20.66	1.79	21.17	1.80	22.89	1.84	24.20	1.87	
				95	18.56	1.77	19.37	1.80	20.32	1.83	21.00	1.84	22.62	1.89	23.97	1.91	
				99	18.56	1.81	19.03	1.84	20.01	1.87	20.55	1.89	22.38	1.93	23.77	1.96	
				102	18.56	1.86	18.71	1.89	19.73	1.92	20.29	1.93	22.17	1.98	23.60	2.00	
				108	18.56	1.93	18.28	1.96	19.36	1.99	19.95	2.00	21.91	2.05	23.39	2.07	
				111	18.56	1.98	18.04	2.01	19.15	2.04	19.76	2.05	21.78	2.09	23.29	2.12	
				115	18.56	2.03	17.82	2.06	18.97	2.09	19.60	2.10	21.67	2.14	23.22	2.17	
9	9	9	27	68	18.56	1.46	22.91	1.50	23.59	1.53	23.97	1.54	25.34	1.59	26.42	1.61	
				70	18.56	1.48	22.62	1.52	23.32	1.55	23.71	1.56	25.11	1.60	26.21	1.63	
				73	18.56	1.52	22.07	1.55	22.80	1.58	23.22	1.60	24.67	1.64	25.80	1.67	
				77	18.56	1.56	21.55	1.59	22.32	1.62	22.75	1.64	24.25	1.68	25.42	1.71	
				81	18.56	1.60	21.05	1.63	21.86	1.66	22.31	1.68	23.87	1.72	25.07	1.75	
				84	18.56	1.64	20.59	1.67	21.43	1.70	21.90	1.72	23.51	1.76	24.75	1.79	
				88	18.56	1.68	20.16	1.71	21.03	1.74	21.52	1.76	23.19	1.80	24.46	1.83	
				91	18.56	1.72	19.75	1.76	20.66	1.79	21.17	1.80	22.89	1.84	24.20	1.87	
				95	18.56	1.77	19.37	1.80	20.32	1.83	21.00	1.84	22.62	1.89	23.97	1.91	
				99	18.56	1.81	19.03	1.84	20.01	1.87	20.55	1.89	22.38	1.93	23.77	1.96	
				102	18.56	1.86	18.71	1.89	19.73	1.92	20.29	1.93	22.17	1.98	23.60	2.00	
				108	18.56	1.93	18.28	1.96	19.36	1.99	19.95	2.00	21.91	2.05	23.39	2.07	
				111	18.56	1.98	18.04	2.01	19.15	2.04	19.76	2.05	21.78	2.09	23.29	2.12	
				115	18.56	2.03	17.82	2.06	18.97	2.09	19.60	2.10	21.67	2.14	23.22	2.17	

1 Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).

2 Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).

3 Capacities are based on the following conditions:

- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m

4 The total combination Index of connected a indoor unit is up to 27.

5 At least two indoor units must be connected for operation.

6 Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.

7 If AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.

8. This data is reference data for temperature capacity trend.

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7				7	68	5.60	0.51	7.47	0.55	7.80	0.59	7.97	0.60	8.47	0.63	8.81	0.64
					70	5.60	0.52	7.41	0.56	7.74	0.59	7.90	0.61	8.40	0.64	8.74	0.65
					73	5.60	0.54	7.28	0.58	7.61	0.61	7.77	0.62	8.27	0.65	8.60	0.66
					77	5.60	0.57	7.15	0.60	7.48	0.63	7.64	0.64	8.13	0.67	8.47	0.67
					81	5.60	0.59	7.03	0.62	7.35	0.65	7.51	0.66	8.00	0.68	8.33	0.69
					84	5.60	0.61	6.90	0.64	7.22	0.67	7.38	0.68	7.87	0.70	8.20	0.70
					88	5.60	0.63	6.77	0.66	7.09	0.68	7.25	0.69	7.74	0.71	8.06	0.71
					91	5.60	0.65	6.65	0.68	6.97	0.70	7.13	0.71	7.61	0.73	7.93	0.73
					95	5.60	0.67	6.52	0.70	6.84	0.72	7.00	0.72	7.48	0.74	7.80	0.74
					99	5.60	0.70	6.40	0.72	6.71	0.74	6.87	0.75	7.34	0.76	7.66	0.76
					102	5.60	0.72	6.28	0.74	6.59	0.76	6.74	0.77	7.21	0.78	7.53	0.77
					108	5.53	0.75	6.09	0.78	6.40	0.79	6.55	0.80	7.02	0.80	7.33	0.80
					111	5.25	0.78	5.97	0.80	6.27	0.81	6.43	0.82	6.89	0.82	7.20	0.81
					115	5.11	0.80	5.85	0.82	6.15	0.83	6.30	0.84	6.76	0.84	7.07	0.83
9				9	68	7.20	0.57	9.60	0.61	10.03	0.65	10.24	0.67	10.89	0.70	11.32	0.71
					70	7.20	0.58	9.52	0.62	9.95	0.66	10.16	0.67	10.80	0.71	11.23	0.72
					73	7.20	0.61	9.36	0.65	9.78	0.68	9.99	0.69	10.63	0.72	11.06	0.73
					77	7.20	0.63	9.20	0.67	9.61	0.70	9.82	0.71	10.46	0.74	10.89	0.75
					81	7.20	0.65	9.03	0.69	9.45	0.72	9.66	0.73	10.29	0.76	10.71	0.76
					84	7.20	0.68	8.87	0.71	9.28	0.74	9.49	0.75	10.12	0.77	10.54	0.78
					88	7.20	0.70	8.71	0.73	9.12	0.76	9.33	0.77	9.95	0.79	10.37	0.79
					91	7.20	0.72	8.55	0.76	8.96	0.78	9.16	0.79	9.78	0.81	10.20	0.81
					95	7.20	0.75	8.39	0.78	8.79	0.80	9.00	0.80	9.61	0.83	10.02	0.83
					99	7.20	0.77	8.23	0.80	8.63	0.82	8.83	0.83	9.44	0.84	9.85	0.84
					102	7.20	0.80	8.07	0.83	8.47	0.85	8.67	0.85	9.28	0.86	9.68	0.86
					108	7.11	0.84	7.83	0.86	8.23	0.88	8.42	0.88	9.03	0.89	9.43	0.88
					111	6.75	0.86	7.67	0.89	8.07	0.90	8.26	0.91	8.86	0.91	9.26	0.90
					115	6.57	0.89	7.52	0.91	7.90	0.93	8.10	0.93	8.69	0.93	9.09	0.92
12				12	68	9.60	0.78	12.81	0.84	13.37	0.89	13.66	0.91	14.52	0.95	15.09	0.97
					70	9.60	0.79	12.70	0.85	13.26	0.90	13.54	0.92	14.40	0.96	14.98	0.98
					73	9.60	0.82	12.48	0.88	13.04	0.93	13.32	0.94	14.17	0.99	14.75	1.00
					77	9.60	0.86	12.26	0.91	12.82	0.95	13.10	0.97	13.95	1.01	14.51	1.02
					81	9.60	0.89	12.04	0.94	12.60	0.98	12.88	1.00	13.72	1.03	14.28	1.04
					84	9.60	0.92	11.83	0.97	12.38	1.01	12.66	1.02	13.49	1.05	14.05	1.06
					88	9.60	0.95	11.61	1.00	12.16	1.04	12.43	1.05	13.27	1.08	13.82	1.08
					91	9.60	0.99	11.40	1.03	11.94	1.06	12.21	1.08	13.04	1.10	13.59	1.10
					95	9.60	1.02	11.19	1.06	11.72	1.09	12.00	1.09	12.81	1.12	13.37	1.12
					99	9.60	1.05	10.97	1.09	11.51	1.12	11.78	1.13	12.59	1.15	13.14	1.15
					102	9.60	1.09	10.76	1.13	11.29	1.15	11.56	1.16	12.37	1.17	12.91	1.17
					108	9.48	1.14	10.44	1.17	10.97	1.20	11.23	1.21	12.03	1.21	12.57	1.21
					111	9.00	1.18	10.23	1.21	10.75	1.23	11.02	1.24	11.81	1.24	12.35	1.23
					115	8.76	1.21	10.02	1.24	10.54	1.26	10.80	1.27	11.59	1.27	12.12	1.25

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15			15	68	12.00	0.76	17.38	0.84	18.11	0.92	18.48	0.95	18.85	0.98	19.59	1.03	
				70	12.00	0.79	17.11	0.88	17.83	0.95	18.20	0.98	18.56	1.00	19.30	1.05	
				73	12.00	0.83	16.83	0.91	17.55	0.97	17.91	1.00	18.28	1.03	19.01	1.07	
				77	12.00	0.86	16.55	0.94	17.27	1.00	17.63	1.03	17.99	1.06	18.72	1.10	
				81	12.00	0.90	16.28	0.97	16.99	1.03	17.35	1.06	17.71	1.08	18.43	1.12	
				84	12.00	0.94	16.01	1.01	16.71	1.07	17.07	1.09	17.43	1.11	18.15	1.15	
				88	12.00	0.95	15.87	1.02	16.58	1.08	16.93	1.10	17.29	1.13	18.00	1.16	
				91	12.00	0.99	15.60	1.06	16.30	1.11	16.65	1.14	17.01	1.15	17.72	1.18	
				95	12.00	1.03	15.33	1.09	16.02	1.14	15.00	1.31	16.72	1.18	17.43	1.21	
				99	12.00	1.07	15.06	1.13	15.75	1.18	16.10	1.20	16.45	1.21	17.15	1.24	
				102	12.00	1.11	14.79	1.16	15.47	1.21	15.82	1.23	16.17	1.24	16.86	1.27	
				108	12.00	1.15	14.52	1.20	15.20	1.24	15.54	1.26	15.89	1.28	16.58	1.29	
				111	12.00	1.19	14.25	1.24	14.93	1.28	15.27	1.29	15.61	1.31	16.30	1.32	
				115	12.00	1.23	13.98	1.28	14.66	1.31	14.99	1.31	15.33	1.34	16.02	1.35	
7	7		14	68	12.37	0.89	15.27	0.91	15.72	0.93	15.98	0.94	16.89	0.97	17.61	0.98	
				70	12.37	0.90	15.08	0.92	15.54	0.94	15.81	0.95	16.74	0.98	17.47	0.99	
				73	12.37	0.93	14.71	0.95	15.20	0.96	15.48	0.97	16.44	1.00	17.20	1.02	
				77	12.37	0.95	14.37	0.97	14.88	0.99	15.17	1.00	16.17	1.02	16.95	1.04	
				81	12.37	0.97	14.04	0.99	14.57	1.01	14.87	1.02	15.91	1.05	16.72	1.06	
				84	12.37	1.00	13.73	1.02	14.29	1.04	14.60	1.05	15.67	1.07	16.50	1.09	
				88	12.37	1.02	13.44	1.04	14.02	1.06	14.35	1.07	15.46	1.10	16.31	1.11	
				91	12.37	1.05	13.17	1.07	13.77	1.09	14.11	1.10	15.26	1.12	16.14	1.14	
				95	12.37	1.08	12.92	1.10	13.55	1.11	14.00	1.12	15.08	1.15	15.98	1.16	
				99	12.37	1.10	12.68	1.12	13.34	1.14	13.70	1.15	14.92	1.18	15.85	1.19	
				102	12.37	1.13	12.47	1.15	13.15	1.17	13.53	1.18	14.78	1.20	15.73	1.22	
				108	12.37	1.17	12.19	1.19	12.91	1.21	13.30	1.22	14.61	1.25	15.59	1.26	
				111	12.37	1.20	12.03	1.22	12.77	1.24	13.17	1.25	14.52	1.27	15.53	1.29	
				115	12.37	1.23	11.88	1.25	12.65	1.27	13.06	1.28	14.45	1.30	15.48	1.32	
7	9		16	68	14.14	1.02	17.45	1.04	17.97	1.06	18.27	1.07	19.31	1.10	20.13	1.12	
				70	14.14	1.03	17.24	1.05	17.77	1.08	18.07	1.09	19.13	1.12	19.97	1.14	
				73	14.14	1.06	16.82	1.08	17.37	1.10	17.69	1.11	18.79	1.14	19.66	1.16	
				77	14.14	1.09	16.42	1.11	17.00	1.13	17.33	1.14	18.48	1.17	19.37	1.19	
				81	14.14	1.11	16.04	1.13	16.65	1.16	17.00	1.17	18.18	1.20	19.10	1.22	
				84	14.14	1.14	15.69	1.16	16.33	1.18	16.69	1.19	17.91	1.22	18.86	1.24	
				88	14.14	1.17	15.36	1.19	16.02	1.21	16.40	1.22	17.67	1.25	18.64	1.27	
				91	14.14	1.20	15.05	1.22	15.74	1.24	16.13	1.25	17.44	1.28	18.44	1.30	
				95	14.14	1.23	14.76	1.25	15.48	1.27	16.00	1.28	17.23	1.31	18.26	1.33	
				99	14.14	1.26	14.50	1.28	15.25	1.30	15.66	1.31	17.05	1.34	18.11	1.36	
				102	14.14	1.29	14.25	1.31	15.03	1.34	15.46	1.35	16.89	1.37	17.98	1.39	
				108	14.14	1.34	13.93	1.36	14.75	1.38	15.20	1.39	16.70	1.42	17.82	1.44	
				111	14.14	1.38	13.74	1.40	14.59	1.42	15.05	1.43	16.59	1.46	17.74	1.47	
				115	14.14	1.41	13.58	1.43	14.45	1.45	14.93	1.46	16.51	1.49	17.69	1.51	

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12			19	68	16.79	1.21	20.73	1.24	21.34	1.26	21.69	1.27	22.93	1.31	23.90	1.33
					70	16.79	1.23	20.47	1.25	21.10	1.28	21.46	1.29	22.72	1.33	23.71	1.35
					73	16.79	1.26	19.97	1.28	20.63	1.31	21.01	1.32	22.32	1.36	23.34	1.38
					77	16.79	1.29	19.50	1.31	20.19	1.34	20.58	1.35	21.94	1.39	23.00	1.41
					81	16.79	1.32	19.05	1.35	19.78	1.37	20.19	1.39	21.59	1.42	22.69	1.44
					84	16.79	1.36	18.63	1.38	19.39	1.41	19.81	1.42	21.27	1.45	22.40	1.48
					88	16.79	1.39	18.24	1.42	19.03	1.44	19.47	1.45	20.98	1.49	22.13	1.51
					91	16.79	1.42	17.87	1.45	18.69	1.48	19.15	1.49	20.71	1.52	21.90	1.55
					95	16.79	1.46	17.53	1.49	18.39	1.51	19.00	1.52	20.47	1.56	21.69	1.58
					99	16.79	1.50	17.21	1.52	18.10	1.55	18.60	1.56	20.25	1.60	21.51	1.62
					102	16.79	1.54	16.93	1.56	17.85	1.59	18.36	1.60	20.06	1.63	21.35	1.65
					108	16.79	1.59	16.54	1.62	17.52	1.64	18.05	1.66	19.83	1.69	21.16	1.71
					111	16.79	1.63	16.32	1.66	17.33	1.68	17.88	1.70	19.70	1.73	21.07	1.75
					115	16.79	1.67	16.13	1.70	17.16	1.72	17.73	1.74	19.61	1.77	21.01	1.79
7	15			22	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	24.40	1.32	25.34	1.34
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	24.15	1.33	25.11	1.36
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	23.67	1.36	24.67	1.39
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	23.22	1.40	24.25	1.42
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	22.80	1.43	23.87	1.45
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	22.40	1.46	23.51	1.49
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	22.04	1.50	23.19	1.52
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	21.71	1.53	22.89	1.56
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	21.40	1.57	22.62	1.59
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	21.13	1.61	22.38	1.63
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	20.88	1.65	22.17	1.67
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	20.57	1.71	21.91	1.73
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	20.40	1.75	21.78	1.77
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	20.25	1.79	21.67	1.81
9	9			18	68	15.91	1.15	19.64	1.17	20.22	1.20	20.55	1.21	21.72	1.24	22.65	1.26
					70	15.91	1.16	19.39	1.19	19.99	1.21	20.33	1.22	21.52	1.26	22.46	1.28
					73	15.91	1.19	18.92	1.22	19.54	1.24	19.90	1.25	21.14	1.29	22.11	1.31
					77	15.91	1.22	18.47	1.25	19.13	1.27	19.50	1.28	20.79	1.32	21.79	1.34
					81	15.91	1.25	18.05	1.28	18.74	1.30	19.12	1.31	20.46	1.35	21.49	1.37
					84	15.91	1.28	17.65	1.31	18.37	1.33	18.77	1.34	20.15	1.38	21.22	1.40
					88	15.91	1.32	17.28	1.34	18.03	1.36	18.45	1.38	19.87	1.41	20.97	1.43
					91	15.91	1.35	16.93	1.37	17.71	1.40	18.14	1.41	19.62	1.44	20.75	1.46
					95	15.91	1.38	16.61	1.41	17.42	1.43	18.00	1.44	19.39	1.48	20.55	1.50
					99	15.91	1.42	16.31	1.44	17.15	1.47	17.62	1.48	19.18	1.51	20.37	1.53
					102	15.91	1.45	16.03	1.48	16.91	1.50	17.39	1.51	19.01	1.55	20.22	1.57
					108	15.91	1.51	15.67	1.53	16.59	1.56	17.10	1.57	18.78	1.60	20.05	1.62
					111	15.91	1.55	15.46	1.57	16.42	1.59	16.93	1.61	18.67	1.64	19.96	1.66
					115	15.91	1.59	15.28	1.61	16.26	1.63	16.80	1.64	18.57	1.68	19.90	1.70

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12			21	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83
9	15			24	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	24.40	1.32	25.34	1.34
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	24.15	1.33	25.11	1.36
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	23.67	1.36	24.67	1.39
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	23.22	1.40	24.25	1.42
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	22.80	1.43	23.87	1.45
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	22.40	1.46	23.51	1.49
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	22.04	1.50	23.19	1.52
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	21.71	1.53	22.89	1.56
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	21.40	1.57	22.62	1.59
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	21.13	1.61	22.38	1.63
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	20.88	1.65	22.17	1.67
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	20.57	1.71	21.91	1.73
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	20.40	1.75	21.78	1.77
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	20.25	1.79	21.67	1.81
12	12			24	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	24.40	1.32	25.34	1.34
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	24.15	1.33	25.11	1.36
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	23.67	1.36	24.67	1.39
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	23.22	1.40	24.25	1.42
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	22.80	1.43	23.87	1.45
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	22.40	1.46	23.51	1.49
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	22.04	1.50	23.19	1.52
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	21.71	1.53	22.89	1.56
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	21.40	1.57	22.62	1.59
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	21.13	1.61	22.38	1.63
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	20.88	1.65	22.17	1.67
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	20.57	1.71	21.91	1.73
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	20.40	1.75	21.78	1.77
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	20.25	1.79	21.67	1.81
7	7	7		21	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83
7	7	9		23	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36
					70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41
					77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44
					81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48
					84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51
					88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55
					91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58
					95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62
					99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65
					102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69
					108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75
					111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79
					115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Cooling (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	26	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36	
				70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41	
				77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44	
				81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48	
				84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51	
				88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55	
				91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58	
				95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62	
				99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65	
				102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69	
				108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75	
				111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79	
				115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83	
7	9	9	25	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36	
				70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41	
				77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44	
				81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48	
				84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51	
				88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55	
				91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58	
				95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62	
				99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65	
				102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69	
				108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75	
				111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79	
				115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83	
9	9	9	27	68	18.56	1.24	22.91	1.26	23.59	1.29	23.97	1.30	25.34	1.34	26.42	1.36	
				70	18.56	1.25	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38	
				73	18.56	1.29	22.07	1.31	22.80	1.34	23.22	1.35	24.67	1.39	25.80	1.41	
				77	18.56	1.32	21.55	1.35	22.32	1.37	22.75	1.38	24.25	1.42	25.42	1.44	
				81	18.56	1.35	21.05	1.38	21.86	1.40	22.31	1.42	23.87	1.45	25.07	1.48	
				84	18.56	1.39	20.59	1.41	21.43	1.44	21.90	1.45	23.51	1.49	24.75	1.51	
				88	18.56	1.42	20.16	1.45	21.03	1.47	21.52	1.49	23.19	1.52	24.46	1.55	
				91	18.56	1.46	19.75	1.48	20.66	1.51	21.17	1.52	22.89	1.56	24.20	1.58	
				95	18.56	1.49	19.37	1.52	20.32	1.55	21.00	1.56	22.62	1.59	23.97	1.62	
				99	18.56	1.53	19.03	1.56	20.01	1.58	20.55	1.60	22.38	1.63	23.77	1.65	
				102	18.56	1.57	18.71	1.60	19.73	1.62	20.29	1.63	22.17	1.67	23.60	1.69	
				108	18.56	1.63	18.28	1.66	19.36	1.68	19.95	1.69	21.91	1.73	23.39	1.75	
				111	18.56	1.67	18.04	1.70	19.15	1.72	19.76	1.73	21.78	1.77	23.29	1.79	
				115	18.56	1.71	17.82	1.74	18.97	1.76	19.60	1.78	21.67	1.81	23.22	1.83	

- Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).
- Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).
- The above values are based on connection of non-ducted indoor units.
- Capacities are based on the following conditions:
- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)
- The total combination index of connected indoor units is up to 27.
- Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.
Single indoor unit connection is not allowed.
- This reference data is based on temperature and capacity trend.

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Heating (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9			9	-13	14.25	3.63	12.24	3.10	10.64	2.74	7.62	2.04	6.77	1.74	4.82	1.22	
				5	11.91	2.31	11.62	2.33	11.34	2.35	10.90	2.49	10.77	2.41	10.49	2.43	
				17	11.36	1.97	11.21	2.00	11.01	2.01	10.90	2.14	10.82	2.06	10.61	2.09	
				32	11.51	1.47	11.34	1.48	11.17	1.51	10.90	1.59	10.82	1.53	10.65	1.55	
				47	11.83	1.08	11.42	1.05	11.27	1.05	10.90	1.12	10.81	1.05	10.19	0.99	
				50	12.64	1.13	12.26	1.18	11.90	1.15	11.90	1.16	11.61	1.18	11.44	1.19	
				59	13.71	1.17	13.49	1.21	13.21	1.16	13.11	1.19	12.86	1.23	12.69	1.24	
12		12	-13	18.30	4.44	15.72	3.79	13.67	3.35	9.79	2.49	8.70	2.13	6.19	1.49		
			5	15.29	2.82	14.93	2.86	14.56	2.88	14.00	3.05	13.83	2.95	13.47	2.97		
			17	14.59	2.41	14.40	2.44	14.15	2.46	14.00	2.62	13.89	2.52	13.63	2.55		
			32	14.79	1.80	14.57	1.82	14.34	1.84	14.00	1.95	13.90	1.87	13.68	1.89		
			47	15.20	1.32	14.67	1.28	14.47	1.29	14.00	1.37	13.88	1.28	13.09	1.21		
			50	16.24	1.38	15.75	1.44	15.28	1.41	15.28	1.42	14.91	1.44	14.70	1.46		
			59	17.61	1.43	17.32	1.48	16.96	1.42	16.84	1.46	16.52	1.50	16.29	1.51		
9	9	18	-13	24.76	5.59	20.71	4.43	19.87	4.50	15.38	3.27	13.64	2.73	9.72	1.77		
			5	24.06	3.77	23.48	3.80	22.90	3.86	22.00	4.00	21.75	3.94	21.17	3.98		
			17	23.44	3.26	23.04	3.29	22.63	3.32	22.00	3.44	21.83	3.40	21.42	3.43		
			32	23.25	2.42	22.90	2.45	22.55	2.47	22.00	2.56	21.85	2.51	21.49	2.53		
			47	23.32	1.70	23.04	1.72	22.74	1.73	22.00	1.80	22.12	1.76	21.82	1.78		
			50	25.31	1.81	24.69	1.84	24.23	1.86	24.01	1.87	23.43	1.90	23.10	1.92		
			59	27.72	1.88	27.18	1.91	26.69	1.93	26.47	1.95	25.85	1.98	25.50	2.00		
9	12	21	-13	24.76	5.59	20.71	4.43	19.87	4.50	15.38	3.27	13.64	2.73	9.72	1.77		
			5	24.06	3.77	23.48	3.80	22.90	3.86	22.00	4.00	21.75	3.94	21.17	3.98		
			17	23.44	3.26	23.04	3.29	22.63	3.32	22.00	3.44	21.83	3.40	21.42	3.43		
			32	23.25	2.42	22.90	2.45	22.55	2.47	22.00	2.56	21.85	2.51	21.49	2.53		
			47	23.32	1.70	23.04	1.72	22.74	1.73	22.00	1.80	22.12	1.76	21.82	1.78		
			50	25.31	1.81	24.69	1.84	24.23	1.86	24.01	1.87	23.43	1.90	23.10	1.92		
			59	27.72	1.88	27.18	1.91	26.69	1.93	26.47	1.95	25.85	1.98	25.50	2.00		
12	12	24	-13	24.76	5.59	20.71	4.43	19.87	4.50	15.38	3.27	13.64	2.73	9.72	1.77		
			5	24.06	3.77	23.48	3.80	22.90	3.86	22.00	4.00	21.75	3.94	21.17	3.98		
			17	23.44	3.26	23.04	3.29	22.63	3.32	22.00	3.44	21.83	3.40	21.42	3.43		
			32	23.25	2.42	22.90	2.45	22.55	2.47	22.00	2.56	21.85	2.51	21.49	2.53		
			47	23.32	1.70	23.04	1.72	22.74	1.73	22.00	1.80	22.12	1.76	21.82	1.78		
			50	25.31	1.81	24.69	1.84	24.23	1.86	24.01	1.87	23.43	1.90	23.10	1.92		
			59	27.72	1.88	27.18	1.91	26.69	1.93	26.47	1.95	25.85	1.98	25.50	2.00		
9	9	27	-13	17.64	3.16	16.83	3.19	16.35	3.23	15.38	3.27	14.90	3.31	13.94	3.31		
			5	23.76	3.87	23.25	3.91	22.58	3.96	22.00	4.00	21.50	4.04	21.09	4.08		
			17	23.43	3.32	23.01	3.36	22.47	3.41	22.00	3.44	21.59	3.48	21.23	3.51		
			32	23.33	2.47	22.93	2.49	22.44	2.53	22.00	2.56	21.61	2.58	21.28	2.61		
			47	23.24	1.74	22.86	1.76	22.41	1.78	22.00	1.80	21.64	1.82	21.32	1.84		
			50	25.31	1.81	24.69	1.84	24.23	1.86	24.01	1.87	23.43	1.90	23.10	1.92		
			59	27.72	1.88	27.18	1.91	26.69	1.93	26.47	1.95	25.85	1.98	25.50	2.00		

1 Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).

2 Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).

3 Capacities are based on the following conditions:

- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m

4 The total combination Index of connected a indoor unit is up to 27.

5 At least two indoor units must be connected for operation.

6 Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.

7 If AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.

8. This data is reference data for temperature capacity trend.

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7			7	-13	9.80	2.72	8.42	2.32	7.32	2.06	5.24	1.53	4.66	1.30	3.32	0.92	
				5	8.19	1.73	8.00	1.75	7.80	1.77	7.50	1.87	7.41	1.81	7.22	1.82	
				17	7.81	1.48	7.72	1.50	7.58	1.51	7.50	1.61	7.44	1.54	7.30	1.57	
				32	7.92	1.10	7.80	1.11	7.68	1.13	7.50	1.19	7.45	1.15	7.33	1.16	
				47	8.14	0.81	7.86	0.78	7.75	0.79	7.50	0.84	7.44	0.78	7.01	0.74	
				50	8.70	0.84	8.44	0.89	8.19	0.87	8.19	0.87	7.99	0.88	7.87	0.89	
				59	9.43	0.88	9.28	0.91	9.09	0.87	9.02	0.90	8.85	0.92	8.73	0.93	
9			9	-13	14.25	3.47	12.24	2.96	10.64	2.62	7.62	1.95	6.77	1.66	4.82	1.17	
				5	11.91	2.21	11.62	2.23	11.34	2.25	10.90	2.38	10.77	2.30	10.49	2.32	
				17	11.36	1.88	11.21	1.91	11.01	1.92	10.90	2.05	10.82	1.97	10.61	1.99	
				32	11.51	1.41	11.34	1.42	11.17	1.44	10.90	1.52	10.82	1.46	10.65	1.48	
				47	11.83	1.03	11.42	1.00	11.27	1.01	10.90	1.07	10.81	1.00	10.19	0.95	
				50	12.64	1.08	12.26	1.13	11.90	1.10	11.90	1.11	11.61	1.13	11.44	1.14	
				59	13.71	1.12	13.49	1.16	13.21	1.11	13.11	1.14	12.86	1.17	12.69	1.18	
12			12	-13	18.30	4.18	15.72	3.57	13.67	3.16	9.79	2.35	8.70	2.00	6.19	1.41	
				5	15.29	2.66	14.93	2.69	14.56	2.71	14.00	2.87	13.83	2.78	13.47	2.80	
				17	14.59	2.27	14.40	2.30	14.15	2.32	14.00	2.47	13.89	2.37	13.63	2.40	
				32	14.79	1.69	14.57	1.71	14.34	1.73	14.00	1.83	13.90	1.76	13.68	1.78	
				47	15.20	1.24	14.67	1.20	14.47	1.21	14.00	1.29	13.88	1.20	13.09	1.14	
				50	16.24	1.30	15.75	1.36	15.28	1.33	15.28	1.34	14.91	1.36	14.70	1.37	
				59	17.61	1.35	17.32	1.39	16.96	1.34	16.84	1.38	16.52	1.41	16.29	1.43	
15			15	-13	23.53	5.77	20.22	4.92	17.57	4.36	12.59	3.24	11.18	2.76	7.96	1.94	
				5	19.66	3.67	19.20	3.71	18.73	3.74	18.00	3.96	17.79	3.83	17.32	3.86	
				17	18.75	3.13	18.52	3.17	18.19	3.20	18.00	3.41	17.86	3.27	17.52	3.32	
				32	19.01	2.34	18.73	2.36	18.44	2.39	18.00	2.53	17.87	2.43	17.58	2.46	
				47	19.54	1.71	18.86	1.66	18.61	1.67	18.00	1.78	17.85	1.66	16.83	1.57	
				50	20.88	1.79	20.25	1.88	19.65	1.83	19.65	1.84	19.17	1.87	18.90	1.89	
				59	22.64	1.86	22.27	1.92	21.81	1.85	21.65	1.90	21.24	1.95	20.95	1.97	
7	7		14	-13	17.78	4.32	14.87	3.42	14.27	3.47	11.05	2.53	9.79	2.11	6.98	1.37	
				5	17.28	2.91	16.86	2.94	16.45	2.98	15.80	3.09	15.62	3.04	15.20	3.07	
				17	16.83	2.52	16.55	2.54	16.25	2.57	15.80	2.66	15.67	2.62	15.38	2.65	
				32	16.70	1.87	16.45	1.89	16.19	1.91	15.80	1.97	15.69	1.94	15.44	1.96	
				47	16.75	1.32	16.55	1.33	16.33	1.34	15.80	1.39	15.89	1.36	15.67	1.38	
				50	18.18	1.40	17.73	1.42	17.40	1.44	17.24	1.45	16.83	1.47	16.59	1.48	
				59	19.90	1.45	19.52	1.47	19.17	1.49	19.01	1.50	18.57	1.53	18.31	1.54	
7	9		16	-13	21.27	5.00	17.79	3.96	17.07	4.02	13.22	2.93	11.72	2.44	8.35	1.58	
				5	20.67	3.37	20.17	3.40	19.67	3.45	18.90	3.58	18.69	3.52	18.19	3.56	
				17	20.14	2.91	19.79	2.94	19.44	2.97	18.90	3.08	18.75	3.04	18.40	3.07	
				32	19.98	2.17	19.68	2.19	19.37	2.21	18.90	2.29	18.77	2.25	18.47	2.27	
				47	20.03	1.52	19.80	1.54	19.53	1.55	18.90	1.61	19.00	1.58	18.74	1.60	
				50	21.75	1.62	21.21	1.64	20.81	1.66	20.63	1.67	20.13	1.70	19.84	1.72	
				59	23.81	1.68	23.35	1.71	22.93	1.73	22.74	1.74	22.21	1.77	21.90	1.79	
7	12		19	-13	24.09	5.00	20.15	3.96	19.33	4.02	14.97	2.93	13.27	2.44	9.46	1.58	
				5	23.40	3.37	22.84	3.40	22.28	3.45	21.40	3.58	21.16	3.52	20.59	3.56	
				17	22.80	2.91	22.41	2.94	22.01	2.97	21.40	3.08	21.23	3.04	20.84	3.07	
				32	22.62	2.17	22.28	2.19	21.93	2.21	21.40	2.29	21.25	2.25	20.91	2.27	
				47	22.68	1.52	22.41	1.54	22.12	1.55	21.40	1.61	21.52	1.58	21.22	1.60	
				50	24.62	1.62	24.02	1.64	23.57	1.66	23.36	1.67	22.79	1.70	22.47	1.72	
				59	26.96	1.68	26.44	1.71	25.97	1.73	25.74	1.74	25.15	1.77	24.80	1.79	

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)													
						57		60.8		64.4		69.98		71.6		75.2			
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)		
7	15		22	-13	24.76	5.00	20.71	3.96	19.87	4.02	15.38	2.93	13.64	2.44	9.72	1.58			
				5	24.06	3.37	23.48	3.40	22.90	3.45	22.00	3.58	21.75	3.52	21.17	3.56			
				17	23.44	2.91	23.04	2.94	22.63	2.97	22.00	3.08	21.83	3.04	21.42	3.07			
				32	23.25	2.17	22.90	2.19	22.55	2.21	22.00	2.29	21.85	2.25	21.49	2.27			
				47	23.32	1.52	23.04	1.54	22.74	1.55	22.00	1.61	22.12	1.58	21.82	1.60			
				50	25.31	1.62	24.69	1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72			
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			
				9	9	18	-13	24.76	5.00	20.71	3.96	19.87	4.02	15.38	2.93	13.64	2.44	9.72	1.58
							5	24.06	3.37	23.48	3.40	22.90	3.45	22.00	3.58	21.75	3.52	21.17	3.56
							17	23.44	2.91	23.04	2.94	22.63	2.97	22.00	3.08	21.83	3.04	21.42	3.07
							32	23.25	2.17	22.90	2.19	22.55	2.21	22.00	2.29	21.85	2.25	21.49	2.27
							47	23.32	1.52	23.04	1.54	22.74	1.55	22.00	1.61	22.12	1.58	21.82	1.60
50	25.31	1.62	24.69				1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72				
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			
				9	12	21	-13	24.76	5.00	20.71	3.96	19.87	4.02	15.38	2.93	13.64	2.44	9.72	1.58
							5	24.06	3.37	23.48	3.40	22.90	3.45	22.00	3.58	21.75	3.52	21.17	3.56
							17	23.44	2.91	23.04	2.94	22.63	2.97	22.00	3.08	21.83	3.04	21.42	3.07
							32	23.25	2.17	22.90	2.19	22.55	2.21	22.00	2.29	21.85	2.25	21.49	2.27
							47	23.32	1.52	23.04	1.54	22.74	1.55	22.00	1.61	22.12	1.58	21.82	1.60
50	25.31	1.62	24.69				1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72				
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			
				9	15	24	-13	24.76	5.00	20.71	3.96	19.87	4.02	15.38	2.93	13.64	2.44	9.72	1.58
							5	24.06	3.37	23.48	3.40	22.90	3.45	22.00	3.58	21.75	3.52	21.17	3.56
							17	23.44	2.91	23.04	2.94	22.63	2.97	22.00	3.08	21.83	3.04	21.42	3.07
							32	23.25	2.17	22.90	2.19	22.55	2.21	22.00	2.29	21.85	2.25	21.49	2.27
							47	23.32	1.52	23.04	1.54	22.74	1.55	22.00	1.61	22.12	1.58	21.82	1.60
50	25.31	1.62	24.69				1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72				
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			
				12	12	24	-13	24.76	5.00	20.71	3.96	19.87	4.02	15.38	2.93	13.64	2.44	9.72	1.58
							5	24.06	3.37	23.48	3.40	22.90	3.45	22.00	3.58	21.75	3.52	21.17	3.56
							17	23.44	2.91	23.04	2.94	22.63	2.97	22.00	3.08	21.83	3.04	21.42	3.07
							32	23.25	2.17	22.90	2.19	22.55	2.21	22.00	2.29	21.85	2.25	21.49	2.27
							47	23.32	1.52	23.04	1.54	22.74	1.55	22.00	1.61	22.12	1.58	21.82	1.60
50	25.31	1.62	24.69				1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72				
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			
				12	15	27	-13	24.76	5.00	20.71	3.96	19.87	4.02	15.38	2.93	13.64	2.44	9.72	1.58
							5	24.06	3.37	23.48	3.40	22.90	3.45	22.00	3.58	21.75	3.52	21.17	3.56
							17	23.44	2.91	23.04	2.94	22.63	2.97	22.00	3.08	21.83	3.04	21.42	3.07
							32	23.25	2.17	22.90	2.19	22.55	2.21	22.00	2.29	21.85	2.25	21.49	2.27
							47	23.32	1.52	23.04	1.54	22.74	1.55	22.00	1.61	22.12	1.58	21.82	1.60
50	25.31	1.62	24.69				1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72				
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			
				7	7	21	-13	17.64	2.83	16.83	2.85	16.35	2.89	15.38	2.93	14.90	2.96	13.94	2.96
							5	23.76	3.46	23.25	3.50	22.58	3.54	22.00	3.58	21.50	3.62	21.09	3.65
							17	23.43	2.97	23.01	3.01	22.47	3.05	22.00	3.08	21.59	3.11	21.23	3.14
							32	23.33	2.20	22.93	2.23	22.44	2.26	22.00	2.29	21.61	2.31	21.28	2.33
							47	23.24	1.55	22.86	1.57	22.41	1.59	22.00	1.61	21.64	1.63	21.32	1.64
50	25.31	1.62	24.69				1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72				
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79			

Capacity Table

JXH20S3B (AJ020BXS3CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	23	-13	17.64	2.83	16.83	2.85	16.35	2.89	15.38	2.93	14.90	2.96	13.94	2.96	
				5	23.76	3.46	23.25	3.50	22.58	3.54	22.00	3.58	21.50	3.62	21.09	3.65	
				17	23.43	2.97	23.01	3.01	22.47	3.05	22.00	3.08	21.59	3.11	21.23	3.14	
				32	23.33	2.20	22.93	2.23	22.44	2.26	22.00	2.29	21.61	2.31	21.28	2.33	
				47	23.24	1.55	22.86	1.57	22.41	1.59	22.00	1.61	21.64	1.63	21.32	1.64	
				50	25.31	1.62	24.69	1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72	
7	7	12	26	59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79	
				-13	17.64	2.83	16.83	2.85	16.35	2.89	15.38	2.93	14.90	2.96	13.94	2.96	
				5	23.76	3.46	23.25	3.50	22.58	3.54	22.00	3.58	21.50	3.62	21.09	3.65	
				17	23.43	2.97	23.01	3.01	22.47	3.05	22.00	3.08	21.59	3.11	21.23	3.14	
				32	23.33	2.20	22.93	2.23	22.44	2.26	22.00	2.29	21.61	2.31	21.28	2.33	
				47	23.24	1.55	22.86	1.57	22.41	1.59	22.00	1.61	21.64	1.63	21.32	1.64	
7	9	9	25	50	25.31	1.62	24.69	1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72	
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79	
				-13	17.64	2.83	16.83	2.85	16.35	2.89	15.38	2.93	14.90	2.96	13.94	2.96	
				5	23.76	3.46	23.25	3.50	22.58	3.54	22.00	3.58	21.50	3.62	21.09	3.65	
				17	23.43	2.97	23.01	3.01	22.47	3.05	22.00	3.08	21.59	3.11	21.23	3.14	
				32	23.33	2.20	22.93	2.23	22.44	2.26	22.00	2.29	21.61	2.31	21.28	2.33	
9	9	9	27	47	23.24	1.55	22.86	1.57	22.41	1.59	22.00	1.61	21.64	1.63	21.32	1.64	
				50	25.31	1.62	24.69	1.64	24.23	1.66	24.01	1.67	23.43	1.70	23.10	1.72	
				59	27.72	1.68	27.18	1.71	26.69	1.73	26.47	1.74	25.85	1.77	25.50	1.79	
				-13	17.64	2.83	16.83	2.85	16.35	2.89	15.38	2.93	14.90	2.96	13.94	2.96	
				5	23.76	3.46	23.25	3.50	22.58	3.54	22.00	3.58	21.50	3.62	21.09	3.65	
				17	23.43	2.97	23.01	3.01	22.47	3.05	22.00	3.08	21.59	3.11	21.23	3.14	

- Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).
- Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).
- The above values are based on connection of non-ducted indoor units.
- Capacities are based on the following conditions:
 - Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)
- The total combination index of connected indoor units is up to 27.
- Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.
Single indoor unit connection is not allowed.
- This reference data is based on temperature and capacity trend.

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9				9	68	7.20	0.59	9.60	0.63	10.03	0.67	10.24	0.68	10.89	0.72	11.32	0.73
					70	7.20	0.60	9.52	0.64	9.95	0.68	10.16	0.69	10.80	0.73	11.23	0.74
					73	7.20	0.62	9.36	0.66	9.78	0.70	9.99	0.71	10.63	0.74	11.06	0.75
					77	7.20	0.64	9.20	0.68	9.61	0.72	9.82	0.73	10.46	0.76	10.89	0.77
					81	7.20	0.67	9.03	0.71	9.45	0.74	9.66	0.75	10.29	0.77	10.71	0.78
					84	7.20	0.69	8.87	0.73	9.28	0.76	9.49	0.77	10.12	0.79	10.54	0.80
					88	7.20	0.72	8.71	0.75	9.12	0.78	9.33	0.79	9.95	0.81	10.37	0.81
					91	7.20	0.74	8.55	0.78	8.96	0.80	9.16	0.81	9.78	0.83	10.20	0.83
					95	7.20	0.77	8.39	0.80	8.79	0.82	9.00	0.82	9.61	0.85	10.02	0.85
					99	7.20	0.79	8.23	0.82	8.63	0.84	8.83	0.85	9.44	0.86	9.85	0.86
					102	7.20	0.82	8.07	0.85	8.47	0.87	8.67	0.87	9.28	0.88	9.68	0.88
					108	7.11	0.86	7.83	0.88	8.23	0.90	8.42	0.91	9.03	0.91	9.43	0.91
					111	6.75	0.89	7.67	0.91	8.07	0.92	8.26	0.93	8.86	0.93	9.26	0.92
					115	6.57	0.91	7.52	0.93	7.90	0.95	8.10	0.95	8.69	0.95	9.09	0.94
12				12	68	9.60	0.84	12.81	0.90	13.37	0.95	13.66	0.97	14.52	1.02	15.09	1.04
					70	9.60	0.85	12.70	0.91	13.26	0.97	13.54	0.99	14.40	1.03	14.98	1.05
					73	9.60	0.88	12.48	0.94	13.04	0.99	13.32	1.01	14.17	1.06	14.75	1.07
					77	9.60	0.92	12.26	0.98	12.82	1.02	13.10	1.04	13.95	1.08	14.51	1.09
					81	9.60	0.95	12.04	1.01	12.60	1.05	12.88	1.07	13.72	1.11	14.28	1.12
					84	9.60	0.99	11.83	1.04	12.38	1.08	12.66	1.10	13.49	1.13	14.05	1.14
					88	9.60	1.02	11.61	1.07	12.16	1.11	12.43	1.13	13.27	1.16	13.82	1.16
					91	9.60	1.06	11.40	1.11	11.94	1.14	12.21	1.16	13.04	1.18	13.59	1.18
					95	9.60	1.09	11.19	1.14	11.72	1.17	12.00	1.17	12.81	1.21	13.37	1.21
					99	9.60	1.13	10.97	1.17	11.51	1.20	11.78	1.22	12.59	1.23	13.14	1.23
					102	9.60	1.17	10.76	1.21	11.29	1.24	11.56	1.25	12.37	1.26	12.91	1.26
					108	9.48	1.23	10.44	1.26	10.97	1.29	11.23	1.29	12.03	1.30	12.57	1.29
					111	9.00	1.26	10.23	1.30	10.75	1.32	11.02	1.33	11.81	1.33	12.35	1.32
					115	8.76	1.30	10.02	1.33	10.54	1.35	10.80	1.36	11.59	1.36	12.12	1.35
15				15	68	12.00	0.94	16.01	1.01	16.71	1.07	17.07	1.09	17.43	1.11	18.15	1.15
					70	12.00	0.95	15.87	1.02	16.58	1.08	16.93	1.10	17.29	1.13	18.00	1.16
					73	12.00	0.99	15.60	1.06	16.30	1.11	16.65	1.14	17.01	1.15	17.72	1.18
					77	12.00	1.03	15.33	1.09	16.02	1.14	16.37	1.17	16.72	1.18	17.43	1.21
					81	12.00	1.07	15.06	1.13	15.75	1.18	16.10	1.20	16.45	1.21	17.15	1.24
					84	12.00	1.11	14.79	1.16	15.47	1.21	15.82	1.23	16.17	1.24	16.86	1.27
					88	12.00	1.15	14.52	1.20	15.20	1.24	15.54	1.26	15.89	1.28	16.58	1.29
					91	12.00	1.19	14.25	1.24	14.93	1.28	15.27	1.29	15.61	1.31	16.30	1.32
					95	12.00	1.23	13.98	1.28	14.66	1.31	15.00	1.31	15.33	1.34	16.02	1.35
					99	12.00	1.27	13.71	1.31	14.38	1.35	14.72	1.36	15.06	1.37	15.74	1.38
					102	12.00	1.31	13.45	1.35	14.11	1.38	14.45	1.40	14.78	1.40	15.46	1.41
					108	11.85	1.37	13.05	1.41	13.71	1.44	14.04	1.45	14.37	1.46	15.04	1.46
					111	11.25	1.41	12.79	1.45	13.44	1.48	13.77	1.48	14.10	1.49	14.76	1.49
					115	10.95	1.46	12.53	1.49	13.17	1.52	13.50	1.52	13.83	1.52	14.49	1.52

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18				18	68	14.40	1.08	19.21	1.16	20.06	1.23	20.48	1.26	21.77	1.32	22.64	1.35
					70	14.40	1.10	19.04	1.18	19.89	1.25	20.32	1.27	21.60	1.34	22.47	1.36
					73	14.40	1.14	18.72	1.22	19.56	1.28	19.98	1.31	21.26	1.37	22.12	1.39
					77	14.40	1.19	18.39	1.26	19.23	1.32	19.65	1.34	20.92	1.40	21.77	1.41
					81	14.40	1.23	18.07	1.30	18.90	1.36	19.31	1.38	20.58	1.43	21.43	1.44
					84	14.40	1.27	17.74	1.34	18.57	1.40	18.98	1.42	20.24	1.46	21.08	1.47
					88	14.40	1.32	17.42	1.38	18.24	1.43	18.65	1.45	19.90	1.49	20.74	1.50
					91	14.40	1.37	17.10	1.43	17.91	1.47	18.32	1.49	19.56	1.52	20.39	1.53
					95	14.40	1.41	16.78	1.47	17.59	1.51	18.00	1.51	19.22	1.56	20.05	1.56
					99	14.40	1.46	16.46	1.51	17.26	1.55	17.67	1.57	18.89	1.59	19.71	1.59
					102	14.40	1.51	16.14	1.56	16.94	1.60	17.34	1.61	18.55	1.63	19.37	1.62
					108	14.22	1.58	15.66	1.63	16.45	1.66	16.85	1.67	18.05	1.68	18.86	1.67
					111	13.50	1.63	15.35	1.67	16.13	1.70	16.53	1.71	17.72	1.72	18.52	1.70
					115	13.14	1.68	15.03	1.72	15.81	1.75	16.20	1.75	17.39	1.75	18.18	1.74
9	9			18	68	15.91	1.24	19.64	1.27	20.22	1.30	20.55	1.31	21.72	1.35	22.65	1.37
					70	15.91	1.26	19.39	1.28	19.99	1.31	20.33	1.32	21.52	1.36	22.46	1.38
					73	15.91	1.29	18.92	1.32	19.54	1.34	19.90	1.36	21.14	1.39	22.11	1.42
					77	15.91	1.32	18.47	1.35	19.13	1.38	19.50	1.39	20.79	1.42	21.79	1.45
					81	15.91	1.36	18.05	1.38	18.74	1.41	19.12	1.42	20.46	1.46	21.49	1.48
					84	15.91	1.39	17.65	1.42	18.37	1.44	18.77	1.46	20.15	1.49	21.22	1.52
					88	15.91	1.43	17.28	1.45	18.03	1.48	18.45	1.49	19.87	1.53	20.97	1.55
					91	15.91	1.46	16.93	1.49	17.71	1.51	18.14	1.53	19.62	1.56	20.75	1.59
					95	15.91	1.50	16.61	1.53	17.42	1.55	18.00	1.56	19.39	1.60	20.55	1.62
					99	15.91	1.54	16.31	1.56	17.15	1.59	17.62	1.60	19.18	1.64	20.37	1.66
					102	15.91	1.58	16.03	1.60	16.91	1.63	17.39	1.64	19.01	1.68	20.22	1.70
					108	15.91	1.64	15.67	1.66	16.59	1.69	17.10	1.70	18.78	1.73	20.05	1.76
					111	15.91	1.68	15.46	1.70	16.42	1.73	16.93	1.74	18.67	1.77	19.96	1.80
					115	15.91	1.72	15.28	1.74	16.26	1.77	16.80	1.78	18.57	1.82	19.90	1.84
9	12			21	68	18.56	1.43	22.91	1.46	23.59	1.49	23.97	1.51	25.34	1.55	26.42	1.58
					70	18.56	1.45	22.62	1.48	23.32	1.51	23.71	1.53	25.11	1.57	26.21	1.60
					73	18.56	1.49	22.07	1.52	22.80	1.55	23.22	1.56	24.67	1.61	25.80	1.63
					77	18.56	1.53	21.55	1.56	22.32	1.59	22.75	1.60	24.25	1.64	25.42	1.67
					81	18.56	1.56	21.05	1.60	21.86	1.63	22.31	1.64	23.87	1.68	25.07	1.71
					84	18.56	1.60	20.59	1.64	21.43	1.67	21.90	1.68	23.51	1.72	24.75	1.75
					88	18.56	1.65	20.16	1.68	21.03	1.71	21.52	1.72	23.19	1.76	24.46	1.79
					91	18.56	1.69	19.75	1.72	20.66	1.75	21.17	1.76	22.89	1.80	24.20	1.83
					95	18.56	1.73	19.37	1.76	20.32	1.79	21.00	1.80	22.62	1.85	23.97	1.87
					99	18.56	1.77	19.03	1.80	20.01	1.83	20.55	1.85	22.38	1.89	23.77	1.91
					102	18.56	1.82	18.71	1.85	19.73	1.88	20.29	1.89	22.17	1.93	23.60	1.96
					108	18.56	1.89	18.28	1.92	19.36	1.95	19.95	1.96	21.91	2.00	23.39	2.03
					111	18.56	1.93	18.04	1.96	19.15	1.99	19.76	2.01	21.78	2.05	23.29	2.07
					115	18.56	1.98	17.82	2.01	18.97	2.04	19.60	2.05	21.67	2.10	23.22	2.12

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15		24	68	21.21	1.74	26.18	1.77	26.96	1.81	27.40	1.83	27.88	1.85	28.96	1.88	
				70	21.21	1.76	25.85	1.80	26.65	1.83	27.10	1.85	27.60	1.87	28.70	1.90	
				73	21.21	1.80	25.22	1.84	26.06	1.88	26.53	1.89	27.05	1.91	28.19	1.95	
				77	21.21	1.85	24.63	1.89	25.50	1.92	26.00	1.94	26.53	1.96	27.72	1.99	
				81	21.21	1.90	24.06	1.93	24.98	1.97	25.50	1.99	26.05	2.00	27.28	2.04	
				84	21.21	1.94	23.53	1.98	24.49	2.02	25.03	2.03	25.60	2.05	26.87	2.09	
				88	21.21	1.99	23.03	2.03	24.04	2.07	24.59	2.08	25.19	2.10	26.50	2.13	
				91	21.21	2.04	22.57	2.08	23.61	2.12	24.19	2.13	24.81	2.15	26.16	2.18	
				95	21.21	2.10	22.14	2.13	23.22	2.17	24.00	2.18	24.46	2.20	25.85	2.24	
				99	21.21	2.15	21.74	2.19	22.87	2.22	23.49	2.24	24.15	2.25	25.58	2.29	
				102	21.21	2.20	21.38	2.24	22.55	2.27	23.19	2.29	23.87	2.31	25.34	2.34	
				108	21.21	2.29	20.90	2.32	22.13	2.36	22.80	2.37	23.51	2.39	25.04	2.42	
111	21.21	2.34	20.62	2.38	21.89	2.41	22.58	2.43	23.31	2.45	24.89	2.48					
115	21.21	2.40	20.37	2.44	21.68	2.47	22.39	2.49	23.15	2.51	24.76	2.54					
9	18		27	68	22.09	1.87	27.27	1.91	28.08	1.95	28.54	1.97	30.17	2.03	31.45	2.06	
				70	22.09	1.89	26.93	1.94	27.76	1.97	28.23	1.99	29.89	2.05	31.20	2.08	
				73	22.09	1.94	26.27	1.98	27.14	2.02	27.64	2.04	29.36	2.10	30.71	2.13	
				77	22.09	1.99	25.65	2.03	26.57	2.07	27.08	2.09	28.87	2.15	30.26	2.18	
				81	22.09	2.04	25.07	2.08	26.02	2.12	26.56	2.14	28.41	2.20	29.85	2.23	
				84	22.09	2.10	24.51	2.14	25.51	2.17	26.07	2.19	27.99	2.25	29.47	2.28	
				88	22.09	2.15	23.99	2.19	25.04	2.23	25.62	2.25	27.60	2.30	29.12	2.34	
				91	22.09	2.20	23.51	2.24	24.60	2.28	25.20	2.30	27.25	2.35	28.81	2.39	
				95	22.09	2.26	23.06	2.30	24.19	2.34	25.00	2.35	26.93	2.41	28.54	2.44	
				99	22.09	2.32	22.65	2.36	23.82	2.39	24.47	2.41	26.65	2.47	28.30	2.50	
				102	22.09	2.37	22.27	2.41	23.49	2.45	24.15	2.47	26.40	2.52	28.09	2.56	
				108	22.09	2.46	21.77	2.50	23.05	2.54	23.75	2.56	26.09	2.61	27.85	2.65	
111	22.09	2.53	21.48	2.56	22.80	2.60	23.52	2.62	25.92	2.67	27.73	2.71					
115	22.09	2.59	21.22	2.63	22.58	2.66	23.33	2.68	25.80	2.74	27.64	2.77					
12	12		24	68	21.21	1.74	26.18	1.77	26.96	1.81	27.40	1.83	28.96	1.88	30.19	1.91	
				70	21.21	1.76	25.85	1.80	26.65	1.83	27.10	1.85	28.70	1.90	29.95	1.93	
				73	21.21	1.80	25.22	1.84	26.06	1.88	26.53	1.89	28.19	1.95	29.48	1.98	
				77	21.21	1.85	24.63	1.89	25.50	1.92	26.00	1.94	27.72	1.99	29.05	2.02	
				81	21.21	1.90	24.06	1.93	24.98	1.97	25.50	1.99	27.28	2.04	28.66	2.07	
				84	21.21	1.94	23.53	1.98	24.49	2.02	25.03	2.03	26.87	2.09	28.29	2.12	
				88	21.21	1.99	23.03	2.03	24.04	2.07	24.59	2.08	26.50	2.13	27.96	2.17	
				91	21.21	2.04	22.57	2.08	23.61	2.12	24.19	2.13	26.16	2.18	27.66	2.22	
				95	21.21	2.10	22.14	2.13	23.22	2.17	24.00	2.18	25.85	2.24	27.40	2.27	
				99	21.21	2.15	21.74	2.19	22.87	2.22	23.49	2.24	25.58	2.29	27.16	2.32	
				102	21.21	2.20	21.38	2.24	22.55	2.27	23.19	2.29	25.34	2.34	26.97	2.37	
				108	21.21	2.29	20.90	2.32	22.13	2.36	22.80	2.37	25.04	2.42	26.73	2.45	
111	21.21	2.34	20.62	2.38	21.89	2.41	22.58	2.43	24.89	2.48	26.62	2.51					
115	21.21	2.40	20.37	2.44	21.68	2.47	22.39	2.49	24.76	2.54	26.54	2.57					

Capacity Table

JXH24S4B (AJ024BX54CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	18		30	68	22.09	1.87	27.27	1.91	28.08	1.95	28.54	1.97	30.17	2.03	31.45	2.06	
				70	22.09	1.89	26.93	1.94	27.76	1.97	28.23	1.99	29.89	2.05	31.20	2.08	
				73	22.09	1.94	26.27	1.98	27.14	2.02	27.64	2.04	29.36	2.10	30.71	2.13	
				77	22.09	1.99	25.65	2.03	26.57	2.07	27.08	2.09	28.87	2.15	30.26	2.18	
				81	22.09	2.04	25.07	2.08	26.02	2.12	26.56	2.14	28.41	2.20	29.85	2.23	
				84	22.09	2.10	24.51	2.14	25.51	2.17	26.07	2.19	27.99	2.25	29.47	2.28	
				88	22.09	2.15	23.99	2.19	25.04	2.23	25.62	2.25	27.60	2.30	29.12	2.34	
				91	22.09	2.20	23.51	2.24	24.60	2.28	25.20	2.30	27.25	2.35	28.81	2.39	
				95	22.09	2.26	23.06	2.30	24.19	2.34	25.00	2.35	26.93	2.41	28.54	2.44	
				99	22.09	2.32	22.65	2.36	23.82	2.39	24.47	2.41	26.65	2.47	28.30	2.50	
				102	22.09	2.37	22.27	2.41	23.49	2.45	24.15	2.47	26.40	2.52	28.09	2.56	
				108	22.09	2.46	21.77	2.50	23.05	2.54	23.75	2.56	26.09	2.61	27.85	2.65	
9	9	9	27	68	22.09	1.87	27.27	1.91	28.08	1.95	28.54	1.97	30.17	2.03	31.45	2.06	
				70	22.09	1.89	26.93	1.94	27.76	1.97	28.23	1.99	29.89	2.05	31.20	2.08	
				73	22.09	1.94	26.27	1.98	27.14	2.02	27.64	2.04	29.36	2.10	30.71	2.13	
				77	22.09	1.99	25.65	2.03	26.57	2.07	27.08	2.09	28.87	2.15	30.26	2.18	
				81	22.09	2.04	25.07	2.08	26.02	2.12	26.56	2.14	28.41	2.20	29.85	2.23	
				84	22.09	2.10	24.51	2.14	25.51	2.17	26.07	2.19	27.99	2.25	29.47	2.28	
				88	22.09	2.15	23.99	2.19	25.04	2.23	25.62	2.25	27.60	2.30	29.12	2.34	
				91	22.09	2.20	23.51	2.24	24.60	2.28	25.20	2.30	27.25	2.35	28.81	2.39	
				95	22.09	2.26	23.06	2.30	24.19	2.34	25.00	2.35	26.93	2.41	28.54	2.44	
				99	22.09	2.32	22.65	2.36	23.82	2.39	24.47	2.41	26.65	2.47	28.30	2.50	
				102	22.09	2.37	22.27	2.41	23.49	2.45	24.15	2.47	26.40	2.52	28.09	2.56	
				108	22.09	2.46	21.77	2.50	23.05	2.54	23.75	2.56	26.09	2.61	27.85	2.65	
9	9	12	30	68	22.09	1.87	27.27	1.91	28.08	1.95	28.54	1.97	30.17	2.03	31.45	2.06	
				70	22.09	1.89	26.93	1.94	27.76	1.97	28.23	1.99	29.89	2.05	31.20	2.08	
				73	22.09	1.94	26.27	1.98	27.14	2.02	27.64	2.04	29.36	2.10	30.71	2.13	
				77	22.09	1.99	25.65	2.03	26.57	2.07	27.08	2.09	28.87	2.15	30.26	2.18	
				81	22.09	2.04	25.07	2.08	26.02	2.12	26.56	2.14	28.41	2.20	29.85	2.23	
				84	22.09	2.10	24.51	2.14	25.51	2.17	26.07	2.19	27.99	2.25	29.47	2.28	
				88	22.09	2.15	23.99	2.19	25.04	2.23	25.62	2.25	27.60	2.30	29.12	2.34	
				91	22.09	2.20	23.51	2.24	24.60	2.28	25.20	2.30	27.25	2.35	28.81	2.39	
				95	22.09	2.26	23.06	2.30	24.19	2.34	25.00	2.35	26.93	2.41	28.54	2.44	
				99	22.09	2.32	22.65	2.36	23.82	2.39	24.47	2.41	26.65	2.47	28.30	2.50	
				102	22.09	2.37	22.27	2.41	23.49	2.45	24.15	2.47	26.40	2.52	28.09	2.56	
				108	22.09	2.46	21.77	2.50	23.05	2.54	23.75	2.56	26.09	2.61	27.85	2.65	
111	22.09	2.53	21.48	2.56	22.80	2.60	23.52	2.62	25.92	2.67	27.73	2.71					
115	22.09	2.59	21.22	2.63	22.58	2.66	23.33	2.68	25.80	2.74	27.64	2.77					

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 30.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or ACO**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7				7	68	5.60	0.51	7.47	0.55	7.80	0.59	7.97	0.60	8.47	0.63	8.81	0.64
					70	5.60	0.52	7.41	0.56	7.74	0.59	7.90	0.61	8.40	0.64	8.74	0.65
					73	5.60	0.54	7.28	0.58	7.61	0.61	7.77	0.62	8.27	0.65	8.60	0.66
					77	5.60	0.57	7.15	0.60	7.48	0.63	7.64	0.64	8.13	0.67	8.47	0.67
					81	5.60	0.59	7.03	0.62	7.35	0.65	7.51	0.66	8.00	0.68	8.33	0.69
					84	5.60	0.61	6.90	0.64	7.22	0.67	7.38	0.68	7.87	0.70	8.20	0.70
					88	5.60	0.63	6.77	0.66	7.09	0.68	7.25	0.69	7.74	0.71	8.06	0.71
					91	5.60	0.65	6.65	0.68	6.97	0.70	7.13	0.71	7.61	0.73	7.93	0.73
					95	5.60	0.67	6.52	0.70	6.84	0.72	7.00	0.72	7.48	0.74	7.80	0.74
					99	5.60	0.70	6.40	0.72	6.71	0.74	6.87		7.34	0.76	7.66	0.76
					102	5.60	0.72	6.28	0.74	6.59	0.76	6.74	0.77	7.21	0.78	7.53	0.77
					108	5.53	0.75	6.09	0.78	6.40	0.79	6.55	0.80	7.02	0.80	7.33	0.80
					111	5.25	0.78	5.97	0.80	6.27	0.81	6.43	0.82	6.89	0.82	7.20	0.81
					115	5.11	0.80	5.85	0.82	6.15	0.83	6.30	0.84	6.76	0.84	7.07	0.83
9				9	68	7.20	0.57	9.60	0.61	10.03	0.65	10.24	0.67	10.89	0.70	11.32	0.71
					70	7.20	0.58	9.52	0.62	9.95	0.66	10.16	0.67	10.80	0.71	11.23	0.72
					73	7.20	0.61	9.36	0.65	9.78	0.68	9.99	0.69	10.63	0.72	11.06	0.73
					77	7.20	0.63	9.20	0.67	9.61	0.70	9.82	0.71	10.46	0.74	10.89	0.75
					81	7.20	0.65	9.03	0.69	9.45	0.72	9.66	0.73	10.29	0.76	10.71	0.76
					84	7.20	0.68	8.87	0.71	9.28	0.74	9.49	0.75	10.12	0.77	10.54	0.78
					88	7.20	0.70	8.71	0.73	9.12	0.76	9.33	0.77	9.95	0.79	10.37	0.79
					91	7.20	0.72	8.55	0.76	8.96	0.78	9.16	0.79	9.78	0.81	10.20	0.81
					95	7.20	0.75	8.39	0.78	8.79	0.80	9.00	0.80	9.61	0.83	10.02	0.83
					99	7.20	0.77	8.23	0.80	8.63	0.82	8.83	0.83	9.44	0.84	9.85	0.84
					102	7.20	0.80	8.07	0.83	8.47	0.85	8.67	0.85	9.28	0.86	9.68	0.86
					108	7.11	0.84	7.83	0.86	8.23	0.88	8.42	0.88	9.03	0.89	9.43	0.88
					111	6.75	0.86	7.67	0.89	8.07	0.90	8.26	0.91	8.86	0.91	9.26	0.90
					115	6.57	0.89	7.52	0.91	7.90	0.93	8.10	0.93	8.69	0.93	9.09	0.92
12				12	68	9.60	0.78	12.81	0.84	13.37	0.89	13.66	0.91	14.52	0.95	15.09	0.97
					70	9.60	0.79	12.70	0.85	13.26	0.90	13.54	0.92	14.40	0.96	14.98	0.98
					73	9.60	0.82	12.48	0.88	13.04	0.93	13.32	0.94	14.17	0.99	14.75	1.00
					77	9.60	0.86	12.26	0.91	12.82	0.95	13.10	0.97	13.95	1.01	14.51	1.02
					81	9.60	0.89	12.04	0.94	12.60	0.98	12.88	1.00	13.72	1.03	14.28	1.04
					84	9.60	0.92	11.83	0.97	12.38	1.01	12.66	1.02	13.49	1.05	14.05	1.06
					88	9.60	0.95	11.61	1.00	12.16	1.04	12.43	1.05	13.27	1.08	13.82	1.08
					91	9.60	0.99	11.40	1.03	11.94	1.06	12.21	1.08	13.04	1.10	13.59	1.10
					95	9.60	1.02	11.19	1.06	11.72	1.09	12.00	1.09	12.81	1.12	13.37	1.12
					99	9.60	1.05	10.97	1.09	11.51	1.12	11.78	1.13	12.59	1.15	13.14	1.15
					102	9.60	1.09	10.76	1.13	11.29	1.15	11.56	1.16	12.37	1.17	12.91	1.17
					108	9.48	1.14	10.44	1.17	10.97	1.20	11.23	1.21	12.03	1.21	12.57	1.21
					111	9.00	1.18	10.23	1.21	10.75	1.23	11.02	1.24	11.81	1.24	12.35	1.23
					115	8.76	1.21	10.02	1.24	10.54	1.26	10.80	1.27	11.59	1.27	12.12	1.25

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15				15	68	12.00	0.94	16.01	1.01	16.71	1.07	17.07	1.09	17.43	1.11	18.15	1.15
					70	12.00	0.95	15.87	1.02	16.58	1.08	16.93	1.10	17.29	1.13	18.00	1.16
					73	12.00	0.99	15.60	1.06	16.30	1.11	16.65	1.14	17.01	1.15	17.72	1.18
					77	12.00	1.03	15.33	1.09	16.02	1.14	16.37	1.17	16.72	1.18	17.43	1.21
					81	12.00	1.07	15.06	1.13	15.75	1.18	16.10	1.20	16.45	1.21	17.15	1.24
					84	12.00	1.11	14.79	1.16	15.47	1.21	15.82	1.23	16.17	1.24	16.86	1.27
					88	12.00	1.15	14.52	1.20	15.20	1.24	15.54	1.26	15.89	1.28	16.58	1.29
					91	12.00	1.19	14.25	1.24	14.93	1.28	15.27	1.29	15.61	1.31	16.30	1.32
					95	12.00	1.23	13.98	1.28	14.66	1.31	15.00	1.31	15.33	1.34	16.02	1.35
					99	12.00	1.27	13.71	1.31	14.38	1.35	14.72	1.36	15.06	1.37	15.74	1.38
					102	12.00	1.31	13.45	1.35	14.11	1.38	14.45	1.40	14.78	1.40	15.46	1.41
					108	11.85	1.37	13.05	1.41	13.71	1.44	14.04	1.45	14.37	1.46	15.04	1.46
18				18	68	13.68	1.06	18.25	1.14	19.05	1.20	19.46	1.23	20.69	1.29	21.51	1.32
					70	13.68	1.08	18.09	1.16	18.90	1.22	19.30	1.25	20.52	1.31	21.34	1.33
					73	13.68	1.12	17.78	1.20	18.58	1.26	18.98	1.28	20.20	1.34	21.01	1.36
					77	13.68	1.16	17.47	1.23	18.27	1.29	18.67	1.32	19.87	1.37	20.68	1.38
					81	13.68	1.21	17.16	1.27	17.95	1.33	18.35	1.35	19.55	1.40	20.35	1.41
					84	13.68	1.25	16.86	1.32	17.64	1.37	18.03	1.39	19.22	1.43	20.03	1.44
					88	13.68	1.29	16.55	1.36	17.33	1.41	17.72	1.42	18.90	1.46	19.70	1.47
					91	13.68	1.34	16.24	1.40	17.02	1.44	17.41	1.46	18.58	1.49	19.37	1.50
					95	13.68	1.38	15.94	1.44	16.71	1.48	17.10	1.48	18.26	1.53	19.05	1.53
					99	13.68	1.43	15.63	1.48	16.40	1.52	16.78	1.54	17.94	1.56	18.72	1.56
					102	13.68	1.48	15.33	1.53	16.09	1.56	16.47	1.58	17.62	1.59	18.40	1.59
					108	13.51	1.55	14.88	1.60	15.63	1.63	16.01	1.64	17.15	1.65	17.92	1.64
7	7			14	68	12.37	0.89	15.27	0.91	15.72	0.93	15.98	0.94	16.89	0.97	17.61	0.98
					70	12.37	0.90	15.08	0.92	15.54	0.94	15.81	0.95	16.74	0.98	17.47	0.99
					73	12.37	0.93	14.71	0.95	15.20	0.96	15.48	0.97	16.44	1.00	17.20	1.02
					77	12.37	0.95	14.37	0.97	14.88	0.99	15.17	1.00	16.17	1.02	16.95	1.04
					81	12.37	0.97	14.04	0.99	14.57	1.01	14.87	1.02	15.91	1.05	16.72	1.06
					84	12.37	1.00	13.73	1.02	14.29	1.04	14.60	1.05	15.67	1.07	16.50	1.09
					88	12.37	1.02	13.44	1.04	14.02	1.06	14.35	1.07	15.46	1.10	16.31	1.11
					91	12.37	1.05	13.17	1.07	13.77	1.09	14.11	1.10	15.26	1.12	16.14	1.14
					95	12.37	1.08	12.92	1.10	13.55	1.11	14.00	1.12	15.08	1.15	15.98	1.16
					99	12.37	1.10	12.68	1.12	13.34	1.14	13.70	1.15	14.92	1.18	15.85	1.19
					102	12.37	1.13	12.47	1.15	13.15	1.17	13.53	1.18	14.78	1.20	15.73	1.22
					108	12.37	1.17	12.19	1.19	12.91	1.21	13.30	1.22	14.61	1.25	15.59	1.26
					111	12.37	1.20	12.03	1.22	12.77	1.24	13.17	1.25	14.52	1.27	15.53	1.29
					115	12.37	1.23	11.88	1.25	12.65	1.27	13.06	1.28	14.45	1.30	15.48	1.32

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9			16	68	14.14	1.02	17.45	1.04	17.97	1.06	18.27	1.07	19.31	1.10	20.13	1.12
					70	14.14	1.03	17.24	1.05	17.77	1.08	18.07	1.09	19.13	1.12	19.97	1.14
					73	14.14	1.06	16.82	1.08	17.37	1.10	17.69	1.11	18.79	1.14	19.66	1.16
					77	14.14	1.09	16.42	1.11	17.00	1.13	17.33	1.14	18.48	1.17	19.37	1.19
					81	14.14	1.11	16.04	1.13	16.65	1.16	17.00	1.17	18.18	1.20	19.10	1.22
					84	14.14	1.14	15.69	1.16	16.33	1.18	16.69	1.19	17.91	1.22	18.86	1.24
					88	14.14	1.17	15.36	1.19	16.02	1.21	16.40	1.22	17.67	1.25	18.64	1.27
					91	14.14	1.20	15.05	1.22	15.74	1.24	16.13	1.25	17.44	1.28	18.44	1.30
					95	14.14	1.23	14.76	1.25	15.48	1.27	16.00	1.28	17.23	1.31	18.26	1.33
					99	14.14	1.26	14.50	1.28	15.25	1.30	15.66	1.31	17.05	1.34	18.11	1.36
					102	14.14	1.29	14.25	1.31	15.03	1.34	15.46	1.35	16.89	1.37	17.98	1.39
					108	14.14	1.34	13.93	1.36	14.75	1.38	15.20	1.39	16.70	1.42	17.82	1.44
					111	14.14	1.38	13.74	1.40	14.59	1.42	15.05	1.43	16.59	1.46	17.74	1.47
					115	14.14	1.41	13.58	1.43	14.45	1.45	14.93	1.46	16.51	1.49	17.69	1.51
7	12			19	68	16.79	1.21	20.73	1.24	21.34	1.26	21.69	1.27	22.93	1.31	23.90	1.33
					70	16.79	1.23	20.47	1.25	21.10	1.28	21.46	1.29	22.72	1.33	23.71	1.35
					73	16.79	1.26	19.97	1.28	20.63	1.31	21.01	1.32	22.32	1.36	23.34	1.38
					77	16.79	1.29	19.50	1.31	20.19	1.34	20.58	1.35	21.94	1.39	23.00	1.41
					81	16.79	1.32	19.05	1.35	19.78	1.37	20.19	1.39	21.59	1.42	22.69	1.44
					84	16.79	1.36	18.63	1.38	19.39	1.41	19.81	1.42	21.27	1.45	22.40	1.48
					88	16.79	1.39	18.24	1.42	19.03	1.44	19.47	1.45	20.98	1.49	22.13	1.51
					91	16.79	1.42	17.87	1.45	18.69	1.48	19.15	1.49	20.71	1.52	21.90	1.55
					95	16.79	1.46	17.53	1.49	18.39	1.51	19.00	1.52	20.47	1.56	21.69	1.58
					99	16.79	1.50	17.21	1.52	18.10	1.55	18.60	1.56	20.25	1.60	21.51	1.62
					102	16.79	1.54	16.93	1.56	17.85	1.59	18.36	1.60	20.06	1.63	21.35	1.65
					108	16.79	1.59	16.54	1.62	17.52	1.64	18.05	1.66	19.83	1.69	21.16	1.71
					111	16.79	1.63	16.32	1.66	17.33	1.68	17.88	1.70	19.70	1.73	21.07	1.75
					115	16.79	1.67	16.13	1.70	17.16	1.72	17.73	1.74	19.61	1.77	21.01	1.79
7	15			22	68	19.44	1.40	24.00	1.43	24.71	1.46	25.12	1.48	25.56	1.49	26.55	1.52
					70	19.44	1.42	23.70	1.45	24.43	1.48	24.84	1.49	25.30	1.51	26.30	1.54
					73	19.44	1.45	23.12	1.49	23.89	1.51	24.32	1.53	24.79	1.54	25.84	1.57
					77	19.44	1.49	22.57	1.52	23.38	1.55	23.83	1.57	24.32	1.58	25.41	1.61
					81	19.44	1.53	22.06	1.56	22.90	1.59	23.37	1.60	23.88	1.62	25.00	1.64
					84	19.44	1.57	21.57	1.60	22.45	1.63	22.94	1.64	23.47	1.66	24.63	1.68
					88	19.44	1.61	21.12	1.64	22.03	1.67	22.54	1.68	23.09	1.70	24.29	1.72
					91	19.44	1.65	20.69	1.68	21.65	1.71	22.18	1.72	22.74	1.74	23.98	1.76
					95	19.44	1.69	20.30	1.72	21.29	1.75	22.00	1.76	22.42	1.78	23.70	1.80
					99	19.44	1.73	19.93	1.76	20.96	1.79	21.53	1.81	22.14	1.82	23.45	1.85
					102	19.44	1.78	19.60	1.81	20.67	1.84	21.26	1.85	21.88	1.86	23.23	1.89
					108	19.44	1.85	19.16	1.87	20.28	1.90	20.90	1.92	21.55	1.93	22.96	1.96
					111	19.44	1.89	18.90	1.92	20.06	1.95	20.70	1.96	21.37	1.98	22.81	2.00
					115	19.44	1.94	18.67	1.97	19.87	2.00	20.53	2.01	21.22	2.02	22.70	2.05

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	18			25	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75
					70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77
					73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81
					77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86
					81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90
					84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94
					88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99
					91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03
					95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08
					99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13
					102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18
					108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25
					111	22.09	2.15	21.48	2.18	22.80	2.21	23.52	2.23	25.92	2.28	27.73	2.30
					115	22.09	2.20	21.22	2.24	22.58	2.27	23.33	2.28	25.80	2.33	27.64	2.36
9	9			18	68	15.91	1.15	19.64	1.17	20.22	1.20	20.55	1.21	21.72	1.24	22.65	1.26
					70	15.91	1.16	19.39	1.19	19.99	1.21	20.33	1.22	21.52	1.26	22.46	1.28
					73	15.91	1.19	18.92	1.22	19.54	1.24	19.90	1.25	21.14	1.29	22.11	1.31
					77	15.91	1.22	18.47	1.25	19.13	1.27	19.50	1.28	20.79	1.32	21.79	1.34
					81	15.91	1.25	18.05	1.28	18.74	1.30	19.12	1.31	20.46	1.35	21.49	1.37
					84	15.91	1.28	17.65	1.31	18.37	1.33	18.77	1.34	20.15	1.38	21.22	1.40
					88	15.91	1.32	17.28	1.34	18.03	1.36	18.45	1.38	19.87	1.41	20.97	1.43
					91	15.91	1.35	16.93	1.37	17.71	1.40	18.14	1.41	19.62	1.44	20.75	1.46
					95	15.91	1.38	16.61	1.41	17.42	1.43	18.00	1.44	19.39	1.48	20.55	1.50
					99	15.91	1.42	16.31	1.44	17.15	1.47	17.62	1.48	19.18	1.51	20.37	1.53
					102	15.91	1.45	16.03	1.48	16.91	1.50	17.39	1.51	19.01	1.55	20.22	1.57
					108	15.91	1.51	15.67	1.53	16.59	1.56	17.10	1.57	18.78	1.60	20.05	1.62
					111	15.91	1.55	15.46	1.57	16.42	1.59	16.93	1.61	18.67	1.64	19.96	1.66
					115	15.91	1.59	15.28	1.61	16.26	1.63	16.80	1.64	18.57	1.68	19.90	1.70
9	12			21	68	18.56	1.34	22.91	1.37	23.59	1.39	23.97	1.41	25.34	1.45	26.42	1.47
					70	18.56	1.35	22.62	1.38	23.32	1.41	23.71	1.43	25.11	1.47	26.21	1.49
					73	18.56	1.39	22.07	1.42	22.80	1.45	23.22	1.46	24.67	1.50	25.80	1.52
					77	18.56	1.42	21.55	1.45	22.32	1.48	22.75	1.49	24.25	1.53	25.42	1.56
					81	18.56	1.46	21.05	1.49	21.86	1.52	22.31	1.53	23.87	1.57	25.07	1.60
					84	18.56	1.50	20.59	1.53	21.43	1.55	21.90	1.57	23.51	1.61	24.75	1.63
					88	18.56	1.54	20.16	1.56	21.03	1.59	21.52	1.61	23.19	1.64	24.46	1.67
					91	18.56	1.57	19.75	1.60	20.66	1.63	21.17	1.64	22.89	1.68	24.20	1.71
					95	18.56	1.61	19.37	1.64	20.32	1.67	21.00	1.68	22.62	1.72	23.97	1.75
					99	18.56	1.66	19.03	1.68	20.01	1.71	20.55	1.72	22.38	1.76	23.77	1.79
					102	18.56	1.70	18.71	1.73	19.73	1.75	20.29	1.77	22.17	1.80	23.60	1.83
					108	18.56	1.76	18.28	1.79	19.36	1.82	19.95	1.83	21.91	1.87	23.39	1.89
					111	18.56	1.81	18.04	1.83	19.15	1.86	19.76	1.87	21.78	1.91	23.29	1.94
					115	18.56	1.85	17.82	1.88	18.97	1.90	19.60	1.92	21.67	1.96	23.22	1.98

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15		24	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	29.04	1.69	30.17	1.72	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	28.75	1.71	29.89	1.74	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	28.17	1.75	29.36	1.78	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	27.64	1.80	28.87	1.83	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	27.14	1.84	28.41	1.87	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	26.67	1.88	27.99	1.91	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	26.24	1.93	27.60	1.96	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	25.84	1.97	27.25	2.00	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	25.48	2.02	26.93	2.05	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	25.15	2.07	26.65	2.10	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	24.86	2.12	26.40	2.15	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	24.49	2.19	26.09	2.22	
9	18		27	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25	
12	12		24	68	21.21	1.59	26.18	1.63	26.96	1.66	27.40	1.68	28.96	1.72	30.19	1.75	
				70	21.21	1.61	25.85	1.65	26.65	1.68	27.10	1.70	28.70	1.74	29.95	1.77	
				73	21.21	1.65	25.22	1.69	26.06	1.72	26.53	1.74	28.19	1.78	29.48	1.81	
				77	21.21	1.70	24.63	1.73	25.50	1.76	26.00	1.78	27.72	1.83	29.05	1.86	
				81	21.21	1.74	24.06	1.77	24.98	1.81	25.50	1.82	27.28	1.87	28.66	1.90	
				84	21.21	1.78	23.53	1.82	24.49	1.85	25.03	1.87	26.87	1.91	28.29	1.94	
				88	21.21	1.83	23.03	1.86	24.04	1.90	24.59	1.91	26.50	1.96	27.96	1.99	
				91	21.21	1.87	22.57	1.91	23.61	1.94	24.19	1.96	26.16	2.00	27.66	2.03	
				95	21.21	1.92	22.14	1.96	23.22	1.99	24.00	2.00	25.85	2.05	27.40	2.08	
				99	21.21	1.97	21.74	2.00	22.87	2.04	23.49	2.05	25.58	2.10	27.16	2.13	
				102	21.21	2.02	21.38	2.05	22.55	2.09	23.19	2.10	25.34	2.15	26.97	2.18	
				108	21.21	2.10	20.90	2.13	22.13	2.16	22.80	2.18	25.04	2.22	26.73	2.25	
111	21.21	2.15	20.62	2.18	21.89	2.21	22.58	2.23	24.89	2.28	26.62	2.30					
115	21.21	2.20	20.37	2.24	21.68	2.27	22.39	2.28	24.76	2.33	26.54	2.36					

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	29.04	1.69	30.17	1.72
					70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	28.75	1.71	29.89	1.74
					73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	28.17	1.75	29.36	1.78
					77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	27.64	1.80	28.87	1.83
					81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	27.14	1.84	28.41	1.87
					84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	26.67	1.88	27.99	1.91
					88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	26.24	1.93	27.60	1.96
					91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	25.84	1.97	27.25	2.00
					95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	25.48	2.02	26.93	2.05
					99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	25.15	2.07	26.65	2.10
					102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	24.86	2.12	26.40	2.15
					108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	24.49	2.19	26.09	2.22
12	18			30	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75
					70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77
					73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81
					77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86
					81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90
					84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94
					88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99
					91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03
					95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08
					99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13
					102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18
					108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25
15	15			30	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	29.04	1.69	30.17	1.72
					70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	28.75	1.71	29.89	1.74
					73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	28.17	1.75	29.36	1.78
					77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	27.64	1.80	28.87	1.83
					81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	27.14	1.84	28.41	1.87
					84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	26.67	1.88	27.99	1.91
					88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	26.24	1.93	27.60	1.96
					91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	25.84	1.97	27.25	2.00
					95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	25.48	2.02	26.93	2.05
					99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	25.15	2.07	26.65	2.10
					102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	24.86	2.12	26.40	2.15
					108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	24.49	2.19	26.09	2.22
111	22.09	2.15	21.48	2.18	22.80	2.21	23.52	2.23	24.28	2.25	25.92	2.28					
115	22.09	2.20	21.22	2.24	22.58	2.27	23.33	2.28	24.11	2.30	25.80	2.33					

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7		21	68	18.56	1.34	22.91	1.37	23.59	1.39	23.97	1.41	25.34	1.45	26.42	1.47
					70	18.56	1.35	22.62	1.38	23.32	1.41	23.71	1.43	25.11	1.47	26.21	1.49
					73	18.56	1.39	22.07	1.42	22.80	1.45	23.22	1.46	24.67	1.50	25.80	1.52
					77	18.56	1.42	21.55	1.45	22.32	1.48	22.75	1.49	24.25	1.53	25.42	1.56
					81	18.56	1.46	21.05	1.49	21.86	1.52	22.31	1.53	23.87	1.57	25.07	1.60
					84	18.56	1.50	20.59	1.53	21.43	1.55	21.90	1.57	23.51	1.61	24.75	1.63
					88	18.56	1.54	20.16	1.56	21.03	1.59	21.52	1.61	23.19	1.64	24.46	1.67
					91	18.56	1.57	19.75	1.60	20.66	1.63	21.17	1.64	22.89	1.68	24.20	1.71
					95	18.56	1.61	19.37	1.64	20.32	1.67	21.00	1.68	22.62	1.72	23.97	1.75
					99	18.56	1.66	19.03	1.68	20.01	1.71	20.55	1.72	22.38	1.76	23.77	1.79
					102	18.56	1.70	18.71	1.73	19.73	1.75	20.29	1.77	22.17	1.80	23.60	1.83
					108	18.56	1.76	18.28	1.79	19.36	1.82	19.95	1.83	21.91	1.87	23.39	1.89
					111	18.56	1.81	18.04	1.83	19.15	1.86	19.76	1.87	21.78	1.91	23.29	1.94
					115	18.56	1.85	17.82	1.88	18.97	1.90	19.60	1.92	21.67	1.96	23.22	1.98
7	7	9		23	68	20.33	1.46	25.09	1.50	25.83	1.53	26.26	1.54	27.76	1.59	28.94	1.61
					70	20.33	1.48	24.78	1.52	25.54	1.55	25.97	1.56	27.50	1.60	28.70	1.63
					73	20.33	1.52	24.17	1.55	24.97	1.58	25.43	1.60	27.02	1.64	28.26	1.67
					77	20.33	1.56	23.60	1.59	24.44	1.62	24.92	1.64	26.56	1.68	27.84	1.71
					81	20.33	1.60	23.06	1.63	23.94	1.66	24.44	1.68	26.14	1.72	27.46	1.75
					84	20.33	1.64	22.55	1.67	23.47	1.70	23.99	1.72	25.75	1.76	27.11	1.79
					88	20.33	1.68	22.08	1.71	23.03	1.74	23.57	1.76	25.39	1.80	26.79	1.83
					91	20.33	1.72	21.63	1.76	22.63	1.79	23.18	1.80	25.07	1.84	26.51	1.87
					95	20.33	1.77	21.22	1.80	22.26	1.83	23.00	1.84	24.78	1.89	26.25	1.91
					99	20.33	1.81	20.84	1.84	21.92	1.87	22.51	1.89	24.51	1.93	26.03	1.96
					102	20.33	1.86	20.49	1.89	21.61	1.92	22.22	1.93	24.28	1.98	25.84	2.00
					108	20.33	1.93	20.03	1.96	21.20	1.99	21.85	2.00	24.00	2.05	25.62	2.07
					111	20.33	1.98	19.76	2.01	20.98	2.04	21.64	2.05	23.85	2.09	25.51	2.12
					115	20.33	2.03	19.52	2.06	20.78	2.09	21.46	2.10	23.73	2.14	25.43	2.17
7	7	12		26	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75
					70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77
					73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81
					77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86
					81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90
					84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94
					88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99
					91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03
					95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08
					99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13
					102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18
					108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25
					111	22.09	2.15	21.48	2.18	22.80	2.21	23.52	2.23	25.92	2.28	27.73	2.30
					115	22.09	2.20	21.22	2.24	22.58	2.27	23.33	2.28	25.80	2.33	27.64	2.36

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	15	29	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	29.04	1.69	30.17	1.72	
				70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	28.75	1.71	29.89	1.74	
				73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	28.17	1.75	29.36	1.78	
				77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	27.64	1.80	28.87	1.83	
				81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	27.14	1.84	28.41	1.87	
				84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	26.67	1.88	27.99	1.91	
				88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	26.24	1.93	27.60	1.96	
				91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	25.84	1.97	27.25	2.00	
				95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	25.48	2.02	26.93	2.05	
				99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	25.15	2.07	26.65	2.10	
				102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	24.86	2.12	26.40	2.15	
				108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	24.49	2.19	26.09	2.22	
7	7	18	32	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
7	9	9	25	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
111	22.09	2.06	21.48	2.10	22.80	2.13	23.52	2.14	25.92	2.18	27.73	2.21					
115	22.09	2.11	21.22	2.15	22.58	2.18	23.33	2.19	25.80	2.23	27.64	2.26					

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12	28	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
7	9	15	31	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	29.04	1.63	30.17	1.66	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	28.75	1.64	29.89	1.67	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	28.17	1.68	29.36	1.71	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	27.64	1.72	28.87	1.75	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	27.14	1.76	28.41	1.79	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	26.67	1.81	27.99	1.84	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	26.24	1.85	27.60	1.88	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	25.84	1.89	27.25	1.92	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	25.48	1.94	26.93	1.97	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	25.15	1.99	26.65	2.01	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	24.86	2.03	26.40	2.06	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	24.49	2.11	26.09	2.13	
7	12	12	31	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
111	22.09	2.06	21.48	2.10	22.80	2.13	23.52	2.14	25.92	2.18	27.73	2.21					
115	22.09	2.11	21.22	2.15	22.58	2.18	23.33	2.19	25.80	2.23	27.64	2.26					

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	27	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
9	9	12	30	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
7	7	7	28	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68	
				70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70	
				73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74	
				77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78	
				81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82	
				84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86	
				88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91	
				91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95	
				95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00	
				99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04	
				102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09	
				108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16	
111	22.09	2.06	21.48	2.10	22.80	2.13	23.52	2.14	25.92	2.18	27.73	2.21					
115	22.09	2.11	21.22	2.15	22.58	2.18	23.33	2.19	25.80	2.23	27.64	2.26					

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	9	30	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68
					70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70
					73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74
					77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78
					81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82
					84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86
					88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91
					91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95
					95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00
					99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04
					102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09
					108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16
					111	22.09	2.06	21.48	2.10	22.80	2.13	23.52	2.14	25.92	2.18	27.73	2.21
					115	22.09	2.11	21.22	2.15	22.58	2.18	23.33	2.19	25.80	2.23	27.64	2.26
7	7	9	9	32	68	22.09	1.53	27.27	1.56	28.08	1.59	28.54	1.61	30.17	1.66	31.45	1.68
					70	22.09	1.55	26.93	1.58	27.76	1.61	28.23	1.63	29.89	1.67	31.20	1.70
					73	22.09	1.59	26.27	1.62	27.14	1.65	27.64	1.67	29.36	1.71	30.71	1.74
					77	22.09	1.63	25.65	1.66	26.57	1.69	27.08	1.71	28.87	1.75	30.26	1.78
					81	22.09	1.67	25.07	1.70	26.02	1.73	26.56	1.75	28.41	1.79	29.85	1.82
					84	22.09	1.71	24.51	1.74	25.51	1.78	26.07	1.79	27.99	1.84	29.47	1.86
					88	22.09	1.76	23.99	1.79	25.04	1.82	25.62	1.84	27.60	1.88	29.12	1.91
					91	22.09	1.80	23.51	1.83	24.60	1.86	25.20	1.88	27.25	1.92	28.81	1.95
					95	22.09	1.85	23.06	1.88	24.19	1.91	25.00	1.92	26.93	1.97	28.54	2.00
					99	22.09	1.89	22.65	1.92	23.82	1.96	24.47	1.97	26.65	2.01	28.30	2.04
					102	22.09	1.94	22.27	1.97	23.49	2.00	24.15	2.02	26.40	2.06	28.09	2.09
					108	22.09	2.01	21.77	2.05	23.05	2.08	23.75	2.09	26.09	2.13	27.85	2.16
					111	22.09	2.06	21.48	2.10	22.80	2.13	23.52	2.14	25.92	2.18	27.73	2.21
					115	22.09	2.11	21.22	2.15	22.58	2.18	23.33	2.19	25.80	2.23	27.64	2.26

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 32.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH24S4B (AJ024BX54CH/AA)

Heating (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9			9	-13	14.25	3.63	12.24	3.10	10.64	2.74	7.62	2.04	6.77	1.74	4.82	1.22	
				5	11.91	2.31	11.62	2.33	11.34	2.35	10.90	2.49	10.77	2.41	10.49	2.43	
				17	11.36	1.97	11.21	2.00	11.01	2.01	10.90	2.14	10.82	2.06	10.61	2.09	
				32	11.51	1.47	11.34	1.48	11.17	1.51	10.90	1.59	10.82	1.53	10.65	1.55	
				47	11.83	1.08	11.42	1.05	11.27	1.05	10.90	1.12	10.81	1.05	10.19	0.99	
				50	12.64	1.13	12.26	1.18	11.90	1.15	11.90	1.16	11.61	1.18	11.44	1.19	
			12	59	13.71	1.17	13.49	1.21	13.21	1.16	13.11	1.19	12.86	1.23	12.69	1.24	
				-13	18.30	4.44	15.72	3.79	13.67	3.35	9.79	2.49	8.70	2.13	6.19	1.49	
				5	15.29	2.82	14.93	2.86	14.56	2.88	14.00	3.05	13.83	2.95	13.47	2.97	
				17	14.59	2.41	14.40	2.44	14.15	2.46	14.00	2.62	13.89	2.52	13.63	2.55	
				32	14.79	1.80	14.57	1.82	14.34	1.84	14.00	1.95	13.90	1.87	13.68	1.89	
				47	15.20	1.32	14.67	1.28	14.47	1.29	14.00	1.37	13.88	1.28	13.09	1.21	
			15	50	16.24	1.38	15.75	1.44	15.28	1.41	15.28	1.42	14.91	1.44	14.70	1.46	
				59	17.61	1.43	17.32	1.48	16.96	1.42	16.84	1.46	16.52	1.50	16.29	1.51	
				-13	23.53	5.02	20.22	4.28	17.57	3.80	12.59	2.82	11.18	2.40	7.96	1.69	
				5	19.66	3.20	19.20	3.23	18.73	3.26	18.00	3.45	17.79	3.34	17.32	3.36	
				17	18.75	2.73	18.52	2.76	18.19	2.79	18.00	2.97	17.86	2.85	17.52	2.89	
				32	19.01	2.04	18.73	2.05	18.44	2.08	18.00	2.20	17.87	2.11	17.58	2.14	
			18	47	19.54	1.49	18.86	1.45	18.61	1.46	18.00	1.55	17.85	1.45	16.83	1.37	
				50	20.88	1.56	20.25	1.63	19.65	1.60	19.65	1.60	19.17	1.63	18.90	1.65	
				59	22.64	1.62	22.27	1.68	21.81	1.61	21.65	1.65	21.24	1.70	20.95	1.71	
				-13	26.14	6.19	22.46	5.28	19.52	4.68	13.99	3.47	12.42	2.96	8.85	2.08	
				5	21.85	3.94	21.33	3.98	20.81	4.01	20.00	4.25	19.76	4.11	19.24	4.15	
				17	20.84	3.36	20.58	3.41	20.21	3.43	20.00	3.66	19.84	3.51	19.47	3.56	
			21	32	21.13	2.51	20.81	2.53	20.49	2.57	20.00	2.71	19.86	2.60	19.54	2.64	
				47	21.71	1.83	20.95	1.78	20.67	1.80	20.00	1.91	19.83	1.78	18.70	1.69	
				50	23.20	1.92	22.50	2.01	21.83	1.97	21.83	1.98	21.30	2.01	21.00	2.03	
				59	25.16	2.00	24.74	2.06	24.23	1.98	24.06	2.04	23.60	2.09	23.28	2.11	
				-13	24.76	5.68	20.71	4.50	19.87	4.57	15.38	3.33	13.64	2.77	9.72	1.80	
				5	24.06	3.83	23.48	3.87	22.90	3.92	22.00	4.07	21.75	4.00	21.17	4.04	
			24	17	23.44	3.31	23.04	3.35	22.63	3.38	22.00	3.50	21.83	3.45	21.42	3.49	
				32	23.25	2.46	22.90	2.49	22.55	2.51	22.00	2.60	21.85	2.55	21.49	2.58	
				47	23.32	1.73	23.04	1.75	22.74	1.76	22.00	1.83	22.12	1.79	21.82	1.81	
				50	25.31	1.84	24.69	1.87	24.23	1.89	24.01	1.90	23.43	1.93	23.10	1.95	
				59	27.72	1.91	27.18	1.94	26.69	1.97	26.47	1.98	25.85	2.01	25.50	2.03	
				-13	27.57	6.30	23.07	5.00	22.13	5.07	17.13	3.69	15.19	3.08	10.83	1.99	
			27	5	26.79	4.25	26.15	4.29	25.50	4.35	24.50	4.52	24.22	4.44	23.58	4.49	
				17	26.10	3.67	25.66	3.71	25.20	3.75	24.50	3.89	24.31	3.83	23.85	3.87	
				32	25.90	2.73	25.51	2.76	25.11	2.78	24.50	2.88	24.33	2.83	23.94	2.86	
				47	25.97	1.92	25.66	1.94	25.32	1.96	24.50	2.03	24.63	1.99	24.30	2.01	
				50	28.19	2.04	27.50	2.07	26.98	2.10	26.74	2.11	26.09	2.15	25.72	2.17	
				59	30.87	2.12	30.27	2.15	29.73	2.18	29.47	2.20	28.79	2.23	28.39	2.25	
			30	-13	28.14	6.46	23.54	5.12	22.58	5.20	17.48	3.78	15.50	3.15	11.05	2.04	
				5	27.34	4.35	26.68	4.40	26.02	4.46	25.00	4.63	24.72	4.55	24.06	4.60	
				17	26.64	3.76	26.18	3.80	25.72	3.84	25.00	3.98	24.80	3.93	24.34	3.96	
				32	26.42	2.80	26.03	2.83	25.62	2.85	25.00	2.95	24.83	2.90	24.43	2.93	
				47	26.50	1.97	26.18	1.99	25.84	2.00	25.00	2.08	25.14	2.04	24.79	2.06	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
			33	59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Heating (Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18		27	-13	28.14	6.46	23.54	5.12	22.58	5.20	17.48	3.78	15.50	3.15	11.05	2.04	
				5	27.34	4.35	26.68	4.40	26.02	4.46	25.00	4.63	24.72	4.55	24.06	4.60	
				17	26.64	3.76	26.18	3.80	25.72	3.84	25.00	3.98	24.80	3.93	24.34	3.96	
				32	26.42	2.80	26.03	2.83	25.62	2.85	25.00	2.95	24.83	2.90	24.43	2.93	
				47	26.50	1.97	26.18	1.99	25.84	2.00	25.00	2.08	25.14	2.04	24.79	2.06	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
			24	59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
				-13	28.14	6.46	23.54	5.12	22.58	5.20	17.48	3.78	15.50	3.15	11.05	2.04	
				5	27.34	4.35	26.68	4.40	26.02	4.46	25.00	4.63	24.72	4.55	24.06	4.60	
				17	26.64	3.76	26.18	3.80	25.72	3.84	25.00	3.98	24.80	3.93	24.34	3.96	
				32	26.42	2.80	26.03	2.83	25.62	2.85	25.00	2.95	24.83	2.90	24.43	2.93	
				47	26.50	1.97	26.18	1.99	25.84	2.00	25.00	2.08	25.14	2.04	24.79	2.06	
			30	50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
				59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
				-13	28.14	6.46	23.54	5.12	22.58	5.20	17.48	3.78	15.50	3.15	11.05	2.04	
				5	27.34	4.35	26.68	4.40	26.02	4.46	25.00	4.63	24.72	4.55	24.06	4.60	
				17	26.64	3.76	26.18	3.80	25.72	3.84	25.00	3.98	24.80	3.93	24.34	3.96	
				32	26.42	2.80	26.03	2.83	25.62	2.85	25.00	2.95	24.83	2.90	24.43	2.93	
12	18		27	47	26.50	1.97	26.18	1.99	25.84	2.00	25.00	2.08	25.14	2.04	24.79	2.06	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
				59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
				-13	28.14	6.46	23.54	5.12	22.58	5.20	17.48	3.78	15.50	3.15	11.05	2.04	
				5	27.34	4.35	26.68	4.40	26.02	4.46	25.00	4.63	24.72	4.55	24.06	4.60	
				17	26.64	3.76	26.18	3.80	25.72	3.84	25.00	3.98	24.80	3.93	24.34	3.96	
			24	32	26.42	2.80	26.03	2.83	25.62	2.85	25.00	2.95	24.83	2.90	24.43	2.93	
				47	26.50	1.97	26.18	1.99	25.84	2.00	25.00	2.08	25.14	2.04	24.79	2.06	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
				59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
				-13	28.14	6.46	23.54	5.12	22.58	5.20	17.48	3.78	15.50	3.15	11.05	2.04	
				5	27.34	4.35	26.68	4.40	26.02	4.46	25.00	4.63	24.72	4.55	24.06	4.60	
9	9	9	27	17	26.64	3.76	26.18	3.80	25.72	3.84	25.00	3.98	24.80	3.93	24.34	3.96	
				32	26.42	2.80	26.03	2.83	25.62	2.85	25.00	2.95	24.83	2.90	24.43	2.93	
				47	26.50	1.97	26.18	1.99	25.84	2.00	25.00	2.08	25.14	2.04	24.79	2.06	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
				59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
				-13	20.05	3.66	19.12	3.68	18.58	3.73	17.48	3.78	16.94	3.83	15.84	3.83	
			24	5	27.00	4.47	26.42	4.52	25.66	4.58	25.00	4.63	24.43	4.67	23.96	4.71	
				17	26.63	3.84	26.14	3.88	25.54	3.93	25.00	3.98	24.53	4.02	24.13	4.06	
				32	26.51	2.85	26.06	2.88	25.50	2.92	25.00	2.95	24.56	2.98	24.18	3.01	
				47	26.41	2.00	25.98	2.03	25.46	2.06	25.00	2.08	24.59	2.10	24.23	2.12	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
				59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
			30	-13	20.05	3.66	19.12	3.68	18.58	3.73	17.48	3.78	16.94	3.83	15.84	3.83	
				5	27.00	4.47	26.42	4.52	25.66	4.58	25.00	4.63	24.43	4.67	23.96	4.71	
				17	26.63	3.84	26.14	3.88	25.54	3.93	25.00	3.98	24.53	4.02	24.13	4.06	
				32	26.51	2.85	26.06	2.88	25.50	2.92	25.00	2.95	24.56	2.98	24.18	3.01	
				47	26.41	2.00	25.98	2.03	25.46	2.06	25.00	2.08	24.59	2.10	24.23	2.12	
				50	28.77	2.09	28.06	2.12	27.53	2.15	27.29	2.16	26.62	2.20	26.25	2.22	
9	9	12	30	59	31.50	2.17	30.89	2.21	30.33	2.24	30.08	2.25	29.38	2.29	28.97	2.31	
				-13	20.05	3.66	19.12	3.68	18.58	3.73	17.48	3.78	16.94	3.83	15.84	3.83	
				5	27.00	4.47	26.42	4.52	25.66	4.58	25.00	4.63	24.43	4.67	23.96	4.71	
				17	26.63	3.84	26.14	3.88	25.54	3.93	25.00	3.98	24.53	4.02	24.13	4.06	
				32	26.51	2.85	26.06	2.88	25.50	2.92	25.00	2.95	24.56	2.98	24.18	3.01	
				47	26.41	2.00	25.98	2.03	25.46	2.06	25.00	2.08	24.59	2.10	24.23	2.12	

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 30.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0***BNHDCH/AA or AC0***BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7			7	-13	9.80	2.72	8.42	2.32	7.32	2.06	5.24	1.53	4.66	1.30	3.32	0.92	
				5	8.19	1.73	8.00	1.75	7.80	1.77	7.50	1.87	7.41	1.81	7.22	1.82	
				17	7.81	1.48	7.72	1.50	7.58	1.51	7.50	1.61	7.44	1.54	7.30	1.57	
				32	7.92	1.10	7.80	1.11	7.68	1.13	7.50	1.19	7.45	1.15	7.33	1.16	
				47	8.14	0.81	7.86	0.78	7.75	0.79	7.50	0.84	7.44	0.78	7.01	0.74	
				50	8.70	0.84	8.44	0.89	8.19	0.87	8.19	0.87	7.99	0.88	7.87	0.89	
				59	9.43	0.88	9.28	0.91	9.09	0.87	9.02	0.90	8.85	0.92	8.73	0.93	
				9	-13	14.25	3.47	12.24	2.96	10.64	2.62	7.62	1.95	6.77	1.66	4.82	1.17
					5	11.91	2.21	11.62	2.23	11.34	2.25	10.90	2.38	10.77	2.30	10.49	2.32
					17	11.36	1.88	11.21	1.91	11.01	1.92	10.90	2.05	10.82	1.97	10.61	1.99
					32	11.51	1.41	11.34	1.42	11.17	1.44	10.90	1.52	10.82	1.46	10.65	1.48
					47	11.83	1.03	11.42	1.00	11.27	1.01	10.90	1.07	10.81	1.00	10.19	0.95
			50		12.64	1.08	12.26	1.13	11.90	1.10	11.90	1.11	11.61	1.13	11.44	1.14	
			59	13.71	1.12	13.49	1.16	13.21	1.11	13.11	1.14	12.86	1.17	12.69	1.18		
			12	-13	18.30	4.18	15.72	3.57	13.67	3.16	9.79	2.35	8.70	2.00	6.19	1.41	
				5	15.29	2.66	14.93	2.69	14.56	2.71	14.00	2.87	13.83	2.78	13.47	2.80	
				17	14.59	2.27	14.40	2.30	14.15	2.32	14.00	2.47	13.89	2.37	13.63	2.40	
				32	14.79	1.69	14.57	1.71	14.34	1.73	14.00	1.83	13.90	1.76	13.68	1.78	
47	15.20	1.24		14.67	1.20	14.47	1.21	14.00	1.29	13.88	1.20	13.09	1.14				
50	16.24	1.30		15.75	1.36	15.28	1.33	15.28	1.34	14.91	1.36	14.70	1.37				
			59	17.61	1.35	17.32	1.39	16.96	1.34	16.84	1.38	16.52	1.41	16.29	1.43		
			15	-13	23.53	5.77	20.22	4.92	17.57	4.36	12.59	3.24	11.18	2.76	7.96	1.94	
				5	19.66	3.67	19.20	3.71	18.73	3.74	18.00	3.96	17.79	3.83	17.32	3.86	
				17	18.75	3.13	18.52	3.17	18.19	3.20	18.00	3.41	17.86	3.27	17.52	3.32	
				32	19.01	2.34	18.73	2.36	18.44	2.39	18.00	2.53	17.87	2.43	17.58	2.46	
				47	19.54	1.71	18.86	1.66	18.61	1.67	18.00	1.78	17.85	1.66	16.83	1.57	
				50	20.88	1.79	20.25	1.88	19.65	1.83	19.65	1.84	19.17	1.87	18.90	1.89	
			59	22.64	1.86	22.27	1.92	21.81	1.85	21.65	1.90	21.24	1.95	20.95	1.97		
			18	-13	26.14	6.03	22.46	5.14	19.52	4.55	13.99	3.38	12.42	2.89	8.85	2.03	
				5	21.85	3.83	21.33	3.88	20.81	3.91	20.00	4.14	19.76	4.00	19.24	4.04	
				17	20.84	3.28	20.58	3.32	20.21	3.34	20.00	3.56	19.84	3.42	19.47	3.47	
				32	21.13	2.44	20.81	2.46	20.49	2.50	20.00	2.64	19.86	2.54	19.54	2.57	
47	21.71	1.79		20.95	1.74	20.67	1.75	20.00	1.86	19.83	1.74	18.70	1.64				
50	23.20	1.87		22.50	1.96	21.83	1.92	21.83	1.93	21.30	1.96	21.00	1.98				
			59	25.16	1.94	24.74	2.01	24.23	1.93	24.06	1.98	23.60	2.04	23.28	2.06		
			14	-13	17.78	4.32	14.87	3.42	14.27	3.47	11.05	2.53	9.79	2.11	6.98	1.37	
				5	17.28	2.91	16.86	2.94	16.45	2.98	15.80	3.09	15.62	3.04	15.20	3.07	
				17	16.83	2.52	16.55	2.54	16.25	2.57	15.80	2.66	15.67	2.62	15.38	2.65	
				32	16.70	1.87	16.45	1.89	16.19	1.91	15.80	1.97	15.69	1.94	15.44	1.96	
				47	16.75	1.32	16.55	1.33	16.33	1.34	15.80	1.39	15.89	1.36	15.67	1.38	
50	18.18	1.40		17.73	1.42	17.40	1.44	17.24	1.45	16.83	1.47	16.59	1.48				
			59	19.90	1.45	19.52	1.47	19.17	1.49	19.01	1.50	18.57	1.53	18.31	1.54		
			16	-13	21.27	5.09	17.79	4.04	17.07	4.10	13.22	2.98	11.72	2.49	8.35	1.61	
				5	20.67	3.43	20.17	3.47	19.67	3.51	18.90	3.65	18.69	3.59	18.19	3.62	
				17	20.14	2.97	19.79	3.00	19.44	3.03	18.90	3.14	18.75	3.10	18.40	3.12	
				32	19.98	2.21	19.68	2.23	19.37	2.25	18.90	2.33	18.77	2.29	18.47	2.31	
				47	20.03	1.55	19.80	1.57	19.53	1.58	18.90	1.64	19.00	1.61	18.74	1.63	
50	21.75	1.65		21.21	1.67	20.81	1.70	20.63	1.71	20.13	1.73	19.84	1.75				
			59	23.81	1.71	23.35	1.74	22.93	1.76	22.74	1.77	22.21	1.80	21.90	1.82		

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)														
						57		60.8		64.4		69.98		71.6		75.2				
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)			
7	12		19	-13	24.09	5.68	20.15	4.50	19.33	4.57	14.97	3.33	13.27	2.77	9.46	1.80				
				5	23.40	3.83	22.84	3.87	22.28	3.92	21.40	4.07	21.16	4.00	20.59	4.04				
				17	22.80	3.31	22.41	3.35	22.01	3.38	21.40	3.50	21.23	3.45	20.84	3.49				
				32	22.62	2.46	22.28	2.49	21.93	2.51	21.40	2.60	21.25	2.55	20.91	2.58				
				47	22.68	1.73	22.41	1.75	22.12	1.76	21.40	1.83	21.52	1.79	21.22	1.81				
				50	24.62	1.84	24.02	1.87	23.57	1.89	23.36	1.90	22.79	1.93	22.47	1.95				
				59	26.96	1.91	26.44	1.94	25.97	1.97	25.74	1.98	25.15	2.01	24.80	2.03				
				7	15		22	-13	27.57	5.68	23.07	4.50	22.13	4.57	17.13	3.33	15.19	2.77	10.83	1.80
								5	26.79	3.83	26.15	3.87	25.50	3.92	24.50	4.07	24.22	4.00	23.58	4.04
								17	26.10	3.31	25.66	3.35	25.20	3.38	24.50	3.50	24.31	3.45	23.85	3.49
								32	25.90	2.46	25.51	2.49	25.11	2.51	24.50	2.60	24.33	2.55	23.94	2.58
								47	25.97	1.73	25.66	1.75	25.32	1.76	24.50	1.83	24.63	1.79	24.30	1.81
50	28.19	1.84	27.50					1.87	26.98	1.89	26.74	1.90	26.09	1.93	25.72	1.95				
				59	30.87	1.91	30.27	1.94	29.73	1.97	29.47	1.98	28.79	2.01	28.39	2.03				
				7	18		25	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80
								5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04
								17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49
								32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58
								47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81
50	28.77	1.84	28.06					1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95				
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03				
				9	9		18	-13	24.76	5.68	20.71	4.50	19.87	4.57	15.38	3.33	13.64	2.77	9.72	1.80
								5	24.06	3.83	23.48	3.87	22.90	3.92	22.00	4.07	21.75	4.00	21.17	4.04
								17	23.44	3.31	23.04	3.35	22.63	3.38	22.00	3.50	21.83	3.45	21.42	3.49
								32	23.25	2.46	22.90	2.49	22.55	2.51	22.00	2.60	21.85	2.55	21.49	2.58
								47	23.32	1.73	23.04	1.75	22.74	1.76	22.00	1.83	22.12	1.79	21.82	1.81
50	25.31	1.84	24.69					1.87	24.23	1.89	24.01	1.90	23.43	1.93	23.10	1.95				
				59	27.72	1.91	27.18	1.94	26.69	1.97	26.47	1.98	25.85	2.01	25.50	2.03				
				9	12		21	-13	27.57	5.68	23.07	4.50	22.13	4.57	17.13	3.33	15.19	2.77	10.83	1.80
								5	26.79	3.83	26.15	3.87	25.50	3.92	24.50	4.07	24.22	4.00	23.58	4.04
								17	26.10	3.31	25.66	3.35	25.20	3.38	24.50	3.50	24.31	3.45	23.85	3.49
								32	25.90	2.46	25.51	2.49	25.11	2.51	24.50	2.60	24.33	2.55	23.94	2.58
								47	25.97	1.73	25.66	1.75	25.32	1.76	24.50	1.83	24.63	1.79	24.30	1.81
50	28.19	1.84	27.50					1.87	26.98	1.89	26.74	1.90	26.09	1.93	25.72	1.95				
				59	30.87	1.91	30.27	1.94	29.73	1.97	29.47	1.98	28.79	2.01	28.39	2.03				
				9	15		24	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80
								5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04
								17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49
								32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58
								47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81
50	28.77	1.84	28.06					1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95				
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03				
				9	18		27	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80
								5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04
								17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49
								32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58
								47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81
50	28.77	1.84	28.06					1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95				
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03				

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12		24	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80	
				5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04	
				17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49	
				32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58	
				47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
12	15		27	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80	
				5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04	
				17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49	
				32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58	
				47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
12	18		30	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80	
				5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04	
				17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49	
				32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58	
				47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
15	15		30	-13	28.14	5.68	23.54	4.50	22.58	4.57	17.48	3.33	15.50	2.77	11.05	1.80	
				5	27.34	3.83	26.68	3.87	26.02	3.92	25.00	4.07	24.72	4.00	24.06	4.04	
				17	26.64	3.31	26.18	3.35	25.72	3.38	25.00	3.50	24.80	3.45	24.34	3.49	
				32	26.42	2.46	26.03	2.49	25.62	2.51	25.00	2.60	24.83	2.55	24.43	2.58	
				47	26.50	1.73	26.18	1.75	25.84	1.76	25.00	1.83	25.14	1.79	24.79	1.81	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	7	7	21	-13	18.13	3.46	17.29	3.49	16.79	3.54	15.80	3.58	15.31	3.63	14.32	3.63	
				5	24.41	4.23	23.89	4.28	23.20	4.33	22.60	4.38	22.09	4.43	21.66	4.46	
				17	24.07	3.64	23.63	3.68	23.09	3.73	22.60	3.77	22.18	3.81	21.81	3.84	
				32	23.97	2.70	23.55	2.73	23.05	2.76	22.60	2.80	22.20	2.83	21.86	2.85	
				47	23.87	1.90	23.48	1.92	23.02	1.95	22.60	1.97	22.23	1.99	21.90	2.01	
				50	26.00	1.98	25.37	2.01	24.89	2.04	24.67	2.05	24.07	2.08	23.73	2.10	
				59	28.47	2.06	27.92	2.09	27.42	2.12	27.19	2.13	26.56	2.17	26.19	2.19	
7	7	9	23	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	7	12	26	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	15	29	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	7	18	32	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	9	9	25	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	9	12	28	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	9	15	31	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
7	12	12	31	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	
9	9	9	27	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
				59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03	

Capacity Table

JXH24S4B (AJ024BXS4CH/AA)

Heating (Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	30	-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37	
				5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14	
				17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57	
				32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65	
				47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87	
				50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95	
7	7	7	7	28	59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03
					-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37
					5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14
					17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57
					32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65
					47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87
7	7	7	9	30	50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95
					59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03
					-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37
					5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14
					17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57
					32	26.51	2.51	26.06	2.53	25.50	2.57	25.00	2.60	24.56	2.63	24.18	2.65
7	7	9	9	32	47	26.41	1.76	25.98	1.78	25.46	1.81	25.00	1.83	24.59	1.85	24.23	1.87
					50	28.77	1.84	28.06	1.87	27.53	1.89	27.29	1.90	26.62	1.93	26.25	1.95
					59	31.50	1.91	30.89	1.94	30.33	1.97	30.08	1.98	29.38	2.01	28.97	2.03
					-13	20.05	3.22	19.12	3.24	18.58	3.28	17.48	3.33	16.94	3.37	15.84	3.37
					5	27.00	3.93	26.42	3.97	25.66	4.03	25.00	4.07	24.43	4.11	23.96	4.14
					17	26.63	3.38	26.14	3.42	25.54	3.46	25.00	3.50	24.53	3.54	24.13	3.57

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 32.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9				9	68	7.20	0.59	9.60	0.63	10.03	0.67	10.24	0.68	10.89	0.72	11.32	0.73
					70	7.20	0.60	9.52	0.64	9.95	0.68	10.16	0.69	10.80	0.73	11.23	0.74
					73	7.20	0.62	9.36	0.66	9.78	0.70	9.99	0.71	10.63	0.74	11.06	0.75
					77	7.20	0.64	9.20	0.68	9.61	0.72	9.82	0.73	10.46	0.76	10.89	0.77
					81	7.20	0.67	9.03	0.71	9.45	0.74	9.66	0.75	10.29	0.77	10.71	0.78
					84	7.20	0.69	8.87	0.73	9.28	0.76	9.49	0.77	10.12	0.79	10.54	0.80
					88	7.20	0.72	8.71	0.75	9.12	0.78	9.33	0.79	9.95	0.81	10.37	0.81
					91	7.20	0.74	8.55	0.78	8.96	0.80	9.16	0.81	9.78	0.83	10.20	0.83
					95	7.20	0.77	8.39	0.80	8.79	0.82	9.00	0.82	9.61	0.85	10.02	0.85
					99	7.20	0.79	8.23	0.82	8.63	0.84	8.83	0.85	9.44	0.86	9.85	0.86
					102	7.20	0.82	8.07	0.85	8.47	0.87	8.67	0.87	9.28	0.88	9.68	0.88
					108	7.11	0.86	7.83	0.88	8.23	0.90	8.42	0.91	9.03	0.91	9.43	0.91
					111	6.75	0.89	7.67	0.91	8.07	0.92	8.26	0.93	8.86	0.93	9.26	0.92
					115	6.57	0.91	7.52	0.93	7.90	0.95	8.10	0.95	8.69	0.95	9.09	0.94
12				12	68	9.60	0.84	12.81	0.90	13.37	0.95	13.66	0.97	14.52	1.02	15.09	1.04
					70	9.60	0.85	12.70	0.91	13.26	0.97	13.54	0.99	14.40	1.03	14.98	1.05
					73	9.60	0.88	12.48	0.94	13.04	0.99	13.32	1.01	14.17	1.06	14.75	1.07
					77	9.60	0.92	12.26	0.98	12.82	1.02	13.10	1.04	13.95	1.08	14.51	1.09
					81	9.60	0.95	12.04	1.01	12.60	1.05	12.88	1.07	13.72	1.11	14.28	1.12
					84	9.60	0.99	11.83	1.04	12.38	1.08	12.66	1.10	13.49	1.13	14.05	1.14
					88	9.60	1.02	11.61	1.07	12.16	1.11	12.43	1.13	13.27	1.16	13.82	1.16
					91	9.60	1.06	11.40	1.11	11.94	1.14	12.21	1.16	13.04	1.18	13.59	1.18
					95	9.60	1.09	11.19	1.14	11.72	1.17	12.00	1.17	12.81	1.21	13.37	1.21
					99	9.60	1.13	10.97	1.17	11.51	1.20	11.78	1.22	12.59	1.23	13.14	1.23
					102	9.60	1.17	10.76	1.21	11.29	1.24	11.56	1.25	12.37	1.26	12.91	1.26
					108	9.48	1.23	10.44	1.26	10.97	1.29	11.23	1.29	12.03	1.30	12.57	1.29
					111	9.00	1.26	10.23	1.30	10.75	1.32	11.02	1.33	11.81	1.33	12.35	1.32
					115	8.76	1.30	10.02	1.33	10.54	1.35	10.80	1.36	11.59	1.36	12.12	1.35
15				15	68	12.00	0.94	16.01	1.01	16.71	1.07	17.07	1.09	17.43	1.11	18.15	1.15
					70	12.00	0.95	15.87	1.02	16.58	1.08	16.93	1.10	17.29	1.13	18.00	1.16
					73	12.00	0.99	15.60	1.06	16.30	1.11	16.65	1.14	17.01	1.15	17.72	1.18
					77	12.00	1.03	15.33	1.09	16.02	1.14	16.37	1.17	16.72	1.18	17.43	1.21
					81	12.00	1.07	15.06	1.13	15.75	1.18	16.10	1.20	16.45	1.21	17.15	1.24
					84	12.00	1.11	14.79	1.16	15.47	1.21	15.82	1.23	16.17	1.24	16.86	1.27
					88	12.00	1.15	14.52	1.20	15.20	1.24	15.54	1.26	15.89	1.28	16.58	1.29
					91	12.00	1.19	14.25	1.24	14.93	1.28	15.27	1.29	15.61	1.31	16.30	1.32
					95	12.00	1.23	13.98	1.28	14.66	1.31	15.00	1.31	15.33	1.34	16.02	1.35
					99	12.00	1.27	13.71	1.31	14.38	1.35	14.72	1.36	15.06	1.37	15.74	1.38
					102	12.00	1.31	13.45	1.35	14.11	1.38	14.45	1.40	14.78	1.40	15.46	1.41
					108	11.85	1.37	13.05	1.41	13.71	1.44	14.04	1.45	14.37	1.46	15.04	1.46
					111	11.25	1.41	12.79	1.45	13.44	1.48	13.77	1.48	14.10	1.49	14.76	1.49
					115	10.95	1.46	12.53	1.49	13.17	1.52	13.50	1.52	13.83	1.52	14.49	1.52

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18				18	68	14.40	1.08	19.21	1.16	20.06	1.23	20.48	1.26	21.77	1.32	22.64	1.35
					70	14.40	1.10	19.04	1.18	19.89	1.25	20.32	1.27	21.60	1.34	22.47	1.36
					73	14.40	1.14	18.72	1.22	19.56	1.28	19.98	1.31	21.26	1.37	22.12	1.39
					77	14.40	1.19	18.39	1.26	19.23	1.32	19.65	1.34	20.92	1.40	21.77	1.41
					81	14.40	1.23	18.07	1.30	18.90	1.36	19.31	1.38	20.58	1.43	21.43	1.44
					84	14.40	1.27	17.74	1.34	18.57	1.40	18.98	1.42	20.24	1.46	21.08	1.47
					88	14.40	1.32	17.42	1.38	18.24	1.43	18.65	1.45	19.90	1.49	20.74	1.50
					91	14.40	1.37	17.10	1.43	17.91	1.47	18.32	1.49	19.56	1.52	20.39	1.53
					95	14.40	1.41	16.78	1.47	17.59	1.51	18.00	1.51	19.22	1.56	20.05	1.56
					99	14.40	1.46	16.46	1.51	17.26	1.55	17.67	1.57	18.89	1.59	19.71	1.59
					102	14.40	1.51	16.14	1.56	16.94	1.60	17.34	1.61	18.55	1.63	19.37	1.62
					108	14.22	1.58	15.66	1.63	16.45	1.66	16.85	1.67	18.05	1.68	18.86	1.67
					111	13.50	1.63	15.35	1.67	16.13	1.70	16.53	1.71	17.72	1.72	18.52	1.70
					115	13.14	1.68	15.03	1.72	15.81	1.75	16.20	1.75	17.39	1.75	18.18	1.74
9	9			18	68	15.91	1.24	19.64	1.27	20.22	1.30	20.55	1.31	21.72	1.35	22.65	1.37
					70	15.91	1.26	19.39	1.28	19.99	1.31	20.33	1.32	21.52	1.36	22.46	1.38
					73	15.91	1.29	18.92	1.32	19.54	1.34	19.90	1.36	21.14	1.39	22.11	1.42
					77	15.91	1.32	18.47	1.35	19.13	1.38	19.50	1.39	20.79	1.42	21.79	1.45
					81	15.91	1.36	18.05	1.38	18.74	1.41	19.12	1.42	20.46	1.46	21.49	1.48
					84	15.91	1.39	17.65	1.42	18.37	1.44	18.77	1.46	20.15	1.49	21.22	1.52
					88	15.91	1.43	17.28	1.45	18.03	1.48	18.45	1.49	19.87	1.53	20.97	1.55
					91	15.91	1.46	16.93	1.49	17.71	1.51	18.14	1.53	19.62	1.56	20.75	1.59
					95	15.91	1.50	16.61	1.53	17.42	1.55	17.80	1.56	19.39	1.60	20.55	1.62
					99	15.91	1.54	16.31	1.56	17.15	1.59	17.62	1.60	19.18	1.64	20.37	1.66
					102	15.91	1.58	16.03	1.60	16.91	1.63	17.39	1.64	19.01	1.68	20.22	1.70
					108	15.91	1.64	15.67	1.66	16.59	1.69	17.10	1.70	18.78	1.73	20.05	1.76
					111	15.91	1.68	15.46	1.70	16.42	1.73	16.93	1.74	18.67	1.77	19.96	1.80
					115	15.91	1.72	15.28	1.74	16.26	1.77	16.80	1.78	18.57	1.82	19.90	1.84
9	12			21	68	18.56	1.43	22.91	1.46	23.59	1.49	23.97	1.51	25.34	1.55	26.42	1.58
					70	18.56	1.45	22.62	1.48	23.32	1.51	23.71	1.53	25.11	1.57	26.21	1.60
					73	18.56	1.49	22.07	1.52	22.80	1.55	23.22	1.56	24.67	1.61	25.80	1.63
					77	18.56	1.53	21.55	1.56	22.32	1.59	22.75	1.60	24.25	1.64	25.42	1.67
					81	18.56	1.56	21.05	1.60	21.86	1.63	22.31	1.64	23.87	1.68	25.07	1.71
					84	18.56	1.60	20.59	1.64	21.43	1.67	21.90	1.68	23.51	1.72	24.75	1.75
					88	18.56	1.65	20.16	1.68	21.03	1.71	21.52	1.72	23.19	1.76	24.46	1.79
					91	18.56	1.69	19.75	1.72	20.66	1.75	21.17	1.76	22.89	1.80	24.20	1.83
					95	18.56	1.73	19.37	1.76	20.32	1.79	21.00	1.80	22.62	1.85	23.97	1.87
					99	18.56	1.77	19.03	1.80	20.01	1.83	20.55	1.85	22.38	1.89	23.77	1.91
					102	18.56	1.82	18.71	1.85	19.73	1.88	20.29	1.89	22.17	1.93	23.60	1.96
					108	18.56	1.89	18.28	1.92	19.36	1.95	19.95	1.96	21.91	2.00	23.39	2.03
					111	18.56	1.93	18.04	1.96	19.15	1.99	19.76	2.01	21.78	2.05	23.29	2.07
					115	18.56	1.98	17.82	2.01	18.97	2.04	19.60	2.05	21.67	2.10	23.22	2.12

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15			24	68	21.21	1.74	26.18	1.77	26.96	1.81	27.40	1.83	27.88	1.85	28.96	1.88
					70	21.21	1.76	25.85	1.80	26.65	1.83	27.10	1.85	27.60	1.87	28.70	1.90
					73	21.21	1.80	25.22	1.84	26.06	1.88	26.53	1.89	27.05	1.91	28.19	1.95
					77	21.21	1.85	24.63	1.89	25.50	1.92	26.00	1.94	26.53	1.96	27.72	1.99
					81	21.21	1.90	24.06	1.93	24.98	1.97	25.50	1.99	26.05	2.00	27.28	2.04
					84	21.21	1.94	23.53	1.98	24.49	2.02	25.03	2.03	25.60	2.05	26.87	2.09
					88	21.21	1.99	23.03	2.03	24.04	2.07	24.59	2.08	25.19	2.10	26.50	2.13
					91	21.21	2.04	22.57	2.08	23.61	2.12	24.19	2.13	24.81	2.15	26.16	2.18
					95	21.21	2.10	22.14	2.13	23.22	2.17	24.00	2.18	24.46	2.20	25.85	2.24
					99	21.21	2.15	21.74	2.19	22.87	2.22	23.49	2.24	24.15	2.25	25.58	2.29
					102	21.21	2.20	21.38	2.24	22.55	2.27	23.19	2.29	23.87	2.31	25.34	2.34
					108	21.21	2.29	20.90	2.32	22.13	2.36	22.80	2.37	23.51	2.39	25.04	2.42
					111	21.21	2.34	20.62	2.38	21.89	2.41	22.58	2.43	23.31	2.45	24.89	2.48
					115	21.21	2.40	20.37	2.44	21.68	2.47	22.39	2.49	23.15	2.51	24.76	2.54
9	18			27	68	22.09	2.09	27.27	2.13	28.08	2.18	28.54	2.20	30.17	2.26	31.45	2.30
					70	22.09	2.11	26.93	2.16	27.76	2.20	28.23	2.22	29.89	2.29	31.20	2.32
					73	22.09	2.17	26.27	2.21	27.14	2.26	27.64	2.28	29.36	2.34	30.71	2.38
					77	22.09	2.22	25.65	2.27	26.57	2.31	27.08	2.33	28.87	2.39	30.26	2.43
					81	22.09	2.28	25.07	2.32	26.02	2.37	26.56	2.39	28.41	2.45	29.85	2.49
					84	22.09	2.34	24.51	2.38	25.51	2.42	26.07	2.45	27.99	2.51	29.47	2.54
					88	22.09	2.40	23.99	2.44	25.04	2.48	25.62	2.50	27.60	2.56	29.12	2.60
					91	22.09	2.46	23.51	2.50	24.60	2.54	25.20	2.56	27.25	2.62	28.81	2.66
					95	22.09	2.52	23.06	2.56	24.19	2.61	25.00	2.62	26.93	2.69	28.54	2.72
					99	22.09	2.58	22.65	2.63	23.82	2.67	24.47	2.69	26.65	2.75	28.30	2.79
					102	22.09	2.65	22.27	2.69	23.49	2.73	24.15	2.75	26.40	2.81	28.09	2.85
					108	22.09	2.75	21.77	2.79	23.05	2.83	23.75	2.85	26.09	2.91	27.85	2.95
					111	22.09	2.82	21.48	2.86	22.80	2.90	23.52	2.92	25.92	2.98	27.73	3.02
					115	22.09	2.89	21.22	2.93	22.58	2.97	23.33	2.99	25.80	3.05	27.64	3.09
12	12			24	68	21.21	1.74	26.18	1.77	26.96	1.81	27.40	1.83	28.96	1.88	30.19	1.91
					70	21.21	1.76	25.85	1.80	26.65	1.83	27.10	1.85	28.70	1.90	29.95	1.93
					73	21.21	1.80	25.22	1.84	26.06	1.88	26.53	1.89	28.19	1.95	29.48	1.98
					77	21.21	1.85	24.63	1.89	25.50	1.92	26.00	1.94	27.72	1.99	29.05	2.02
					81	21.21	1.90	24.06	1.93	24.98	1.97	25.50	1.99	27.28	2.04	28.66	2.07
					84	21.21	1.94	23.53	1.98	24.49	2.02	25.03	2.03	26.87	2.09	28.29	2.12
					88	21.21	1.99	23.03	2.03	24.04	2.07	24.59	2.08	26.50	2.13	27.96	2.17
					91	21.21	2.04	22.57	2.08	23.61	2.12	24.19	2.13	26.16	2.18	27.66	2.22
					95	21.21	2.10	22.14	2.13	23.22	2.17	24.00	2.18	25.85	2.24	27.40	2.27
					99	21.21	2.15	21.74	2.19	22.87	2.22	23.49	2.24	25.58	2.29	27.16	2.32
					102	21.21	2.20	21.38	2.24	22.55	2.27	23.19	2.29	25.34	2.34	26.97	2.37
					108	21.21	2.29	20.90	2.32	22.13	2.36	22.80	2.37	25.04	2.42	26.73	2.45
					111	21.21	2.34	20.62	2.38	21.89	2.41	22.58	2.43	24.89	2.48	26.62	2.51
					115	21.21	2.40	20.37	2.44	21.68	2.47	22.39	2.49	24.76	2.54	26.54	2.57

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	23.86	2.09	29.45	2.13	30.32	2.18	30.82	2.20	31.37	2.22	32.58	2.26
					70	23.86	2.11	29.09	2.16	29.98	2.20	30.49	2.22	31.05	2.24	32.28	2.29
					73	23.86	2.17	28.38	2.21	29.32	2.26	29.85	2.28	30.43	2.30	31.71	2.34
					77	23.86	2.22	27.70	2.27	28.69	2.31	29.25	2.33	29.85	2.35	31.18	2.39
					81	23.86	2.28	27.07	2.32	28.10	2.37	28.68	2.39	29.31	2.41	30.69	2.45
					84	23.86	2.34	26.47	2.38	27.55	2.42	28.16	2.45	28.81	2.47	30.23	2.51
					88	23.86	2.40	25.91	2.44	27.04	2.48	27.67	2.50	28.34	2.52	29.81	2.56
					91	23.86	2.46	25.39	2.50	26.57	2.54	27.22	2.56	27.91	2.59	29.43	2.62
					95	23.86	2.52	24.91	2.56	26.13	2.61	27.00	2.62	27.52	2.65	29.08	2.69
					99	23.86	2.58	24.46	2.63	25.73	2.67	26.43	2.69	27.17	2.71	28.78	2.75
					102	23.86	2.65	24.05	2.69	25.37	2.73	26.09	2.75	26.85	2.77	28.51	2.81
					108	23.86	2.75	23.51	2.79	24.89	2.83	25.65	2.85	26.45	2.87	28.17	2.91
111	23.86	2.82	23.19	2.86	24.62	2.90	25.40	2.92	26.22	2.94	28.00	2.98					
115	23.86	2.89	22.92	2.93	24.39	2.97	25.19	2.99	26.04	3.01	27.86	3.05					
12	18			30	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11					
115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18					
18	18			36	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11					
115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9		27	68	23.42	1.89	28.91	1.93	29.76	1.97	30.25	1.99	31.98	2.04	33.34	2.08
					70	23.42	1.91	28.55	1.95	29.42	1.99	29.93	2.01	31.69	2.07	33.07	2.10
					73	23.42	1.96	27.85	2.00	28.77	2.04	29.30	2.06	31.13	2.12	32.56	2.15
					77	23.42	2.01	27.19	2.05	28.16	2.09	28.71	2.11	30.60	2.16	32.08	2.20
					81	23.42	2.06	26.57	2.10	27.58	2.14	28.15	2.16	30.12	2.22	31.64	2.25
					84	23.42	2.11	25.98	2.15	27.04	2.19	27.64	2.21	29.67	2.27	31.24	2.30
					88	23.42	2.17	25.43	2.21	26.54	2.25	27.16	2.27	29.26	2.32	30.87	2.35
					91	23.42	2.22	24.92	2.26	26.07	2.30	26.71	2.32	28.88	2.37	30.54	2.41
					95	23.42	2.28	24.45	2.32	25.64	2.36	26.50	2.37	28.55	2.43	30.25	2.46
					99	23.42	2.34	24.01	2.38	25.25	2.41	25.94	2.43	28.24	2.49	29.99	2.52
					102	23.42	2.39	23.61	2.43	24.90	2.47	25.60	2.49	27.98	2.55	29.78	2.58
					108	23.42	2.49	23.07	2.52	24.43	2.56	25.17	2.58	27.65	2.63	29.52	2.67
111	23.42	2.55	22.76	2.59	24.17	2.62	24.93	2.64	27.48	2.70	29.39	2.73					
115	23.42	2.61	22.49	2.65	23.94	2.69	24.73	2.71	27.34	2.76	29.30	2.79					
9	9	12		30	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11					
115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18					
9	9	18		36	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11					
115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12		33	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
					111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11
					115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18
9	12	18		39	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
					111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11
					115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18
12	12	12		36	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
					111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11
					115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	9	36	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
					111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11
					115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18
9	9	9	12	39	68	25.10	2.15	30.98	2.20	31.90	2.24	32.42	2.26	34.27	2.33	35.73	2.37
					70	25.10	2.18	30.59	2.22	31.53	2.27	32.07	2.29	33.96	2.35	35.44	2.40
					73	25.10	2.23	29.85	2.28	30.84	2.32	31.40	2.35	33.36	2.41	34.89	2.45
					77	25.10	2.29	29.14	2.34	30.18	2.38	30.77	2.40	32.80	2.47	34.38	2.51
					81	25.10	2.35	28.47	2.39	29.56	2.44	30.17	2.46	32.28	2.52	33.91	2.56
					84	25.10	2.41	27.85	2.45	28.98	2.50	29.62	2.52	31.80	2.58	33.48	2.62
					88	25.10	2.47	27.26	2.51	28.44	2.56	29.10	2.58	31.36	2.64	33.08	2.68
					91	25.10	2.53	26.71	2.58	27.94	2.62	28.63	2.64	30.95	2.71	32.73	2.74
					95	25.10	2.60	26.20	2.64	27.48	2.69	28.40	2.70	30.59	2.77	32.42	2.81
					99	25.10	2.66	25.73	2.71	27.06	2.75	27.80	2.77	30.27	2.83	32.14	2.87
					102	25.10	2.73	25.30	2.77	26.68	2.82	27.44	2.84	29.99	2.90	31.91	2.94
					108	25.10	2.83	24.73	2.88	26.18	2.92	26.98	2.94	29.63	3.00	31.63	3.04
					111	25.10	2.90	24.40	2.95	25.90	2.99	26.72	3.01	29.45	3.07	31.50	3.11
					115	25.10	2.97	24.10	3.02	25.66	3.06	26.50	3.08	29.30	3.14	31.40	3.18

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 39.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7				7	68	5.60	0.51	7.47	0.55	7.80	0.59	7.97	0.60	8.47	0.63	8.81	0.64
					70	5.60	0.52	7.41	0.56	7.74	0.59	7.90	0.61	8.40	0.64	8.74	0.65
					73	5.60	0.54	7.28	0.58	7.61	0.61	7.77	0.62	8.27	0.65	8.60	0.66
					77	5.60	0.57	7.15	0.60	7.48	0.63	7.64	0.64	8.13	0.67	8.47	0.67
					81	5.60	0.59	7.03	0.62	7.35	0.65	7.51	0.66	8.00	0.68	8.33	0.69
					84	5.60	0.61	6.90	0.64	7.22	0.67	7.38	0.68	7.87	0.70	8.20	0.70
					88	5.60	0.63	6.77	0.66	7.09	0.68	7.25	0.69	7.74	0.71	8.06	0.71
					91	5.60	0.65	6.65	0.68	6.97	0.70	7.13	0.71	7.61	0.73	7.93	0.73
					95	5.60	0.67	6.52	0.70	6.84	0.72	7.00	0.72	7.48	0.74	7.80	0.74
					99	5.60	0.70	6.40	0.72	6.71	0.74	6.87	0.75	7.34	0.76	7.66	0.76
					102	5.60	0.72	6.28	0.74	6.59	0.76	6.74	0.77	7.21	0.78	7.53	0.77
					108	5.53	0.75	6.09	0.78	6.40	0.79	6.55	0.80	7.02	0.80	7.33	0.80
					111	5.25	0.78	5.97	0.80	6.27	0.81	6.43	0.82	6.89	0.82	7.20	0.81
					115	5.11	0.80	5.85	0.82	6.15	0.83	6.30	0.84	6.76	0.84	7.07	0.83
9				9	68	7.20	0.57	9.60	0.61	10.03	0.65	10.24	0.67	10.89	0.70	11.32	0.71
					70	7.20	0.58	9.52	0.62	9.95	0.66	10.16	0.67	10.80	0.71	11.23	0.72
					73	7.20	0.61	9.36	0.65	9.78	0.68	9.99	0.69	10.63	0.72	11.06	0.73
					77	7.20	0.63	9.20	0.67	9.61	0.70	9.82	0.71	10.46	0.74	10.89	0.75
					81	7.20	0.65	9.03	0.69	9.45	0.72	9.66	0.73	10.29	0.76	10.71	0.76
					84	7.20	0.68	8.87	0.71	9.28	0.74	9.49	0.75	10.12	0.77	10.54	0.78
					88	7.20	0.70	8.71	0.73	9.12	0.76	9.33	0.77	9.95	0.79	10.37	0.79
					91	7.20	0.72	8.55	0.76	8.96	0.78	9.16	0.79	9.78	0.81	10.20	0.81
					95	7.20	0.75	8.39	0.78	8.79	0.80	9.00	0.80	9.61	0.83	10.02	0.83
					99	7.20	0.77	8.23	0.80	8.63	0.82	8.83	0.83	9.44	0.84	9.85	0.84
					102	7.20	0.80	8.07	0.83	8.47	0.85	8.67	0.85	9.28	0.86	9.68	0.86
					108	7.11	0.84	7.83	0.86	8.23	0.88	8.42	0.88	9.03	0.89	9.43	0.88
					111	6.75	0.86	7.67	0.89	8.07	0.90	8.26	0.91	8.86	0.91	9.26	0.90
					115	6.57	0.89	7.52	0.91	7.90	0.93	8.10	0.93	8.69	0.93	9.09	0.92
12				12	68	9.60	0.78	12.81	0.84	13.37	0.89	13.66	0.91	14.52	0.95	15.09	0.97
					70	9.60	0.79	12.70	0.85	13.26	0.90	13.54	0.92	14.40	0.96	14.98	0.98
					73	9.60	0.82	12.48	0.88	13.04	0.93	13.32	0.94	14.17	0.99	14.75	1.00
					77	9.60	0.86	12.26	0.91	12.82	0.95	13.10	0.97	13.95	1.01	14.51	1.02
					81	9.60	0.89	12.04	0.94	12.60	0.98	12.88	1.00	13.72	1.03	14.28	1.04
					84	9.60	0.92	11.83	0.97	12.38	1.01	12.66	1.02	13.49	1.05	14.05	1.06
					88	9.60	0.95	11.61	1.00	12.16	1.04	12.43	1.05	13.27	1.08	13.82	1.08
					91	9.60	0.99	11.40	1.03	11.94	1.06	12.21	1.08	13.04	1.10	13.59	1.10
					95	9.60	1.02	11.19	1.06	11.72	1.09	12.00	1.09	12.81	1.12	13.37	1.12
					99	9.60	1.05	10.97	1.09	11.51	1.12	11.78	1.13	12.59	1.15	13.14	1.15
					102	9.60	1.09	10.76	1.13	11.29	1.15	11.56	1.16	12.37	1.17	12.91	1.17
					108	9.48	1.14	10.44	1.17	10.97	1.20	11.23	1.21	12.03	1.21	12.57	1.21
					111	9.00	1.18	10.23	1.21	10.75	1.23	11.02	1.24	11.81	1.24	12.35	1.23
					115	8.76	1.21	10.02	1.24	10.54	1.26	10.80	1.27	11.59	1.27	12.12	1.25

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15				15	68	12.00	0.94	16.01	1.01	16.71	1.07	17.07	1.09	17.43	1.11	18.15	1.15
					70	12.00	0.95	15.87	1.02	16.58	1.08	16.93	1.10	17.29	1.13	18.00	1.16
					73	12.00	0.99	15.60	1.06	16.30	1.11	16.65	1.14	17.01	1.15	17.72	1.18
					77	12.00	1.03	15.33	1.09	16.02	1.14	16.37	1.17	16.72	1.18	17.43	1.21
					81	12.00	1.07	15.06	1.13	15.75	1.18	16.10	1.20	16.45	1.21	17.15	1.24
					84	12.00	1.11	14.79	1.16	15.47	1.21	15.82	1.23	16.17	1.24	16.86	1.27
					88	12.00	1.15	14.52	1.20	15.20	1.24	15.54	1.26	15.89	1.28	16.58	1.29
					91	12.00	1.19	14.25	1.24	14.93	1.28	15.27	1.29	15.61	1.31	16.30	1.32
					95	12.00	1.23	13.98	1.28	14.66	1.31	15.00	1.31	15.33	1.34	16.02	1.35
					99	12.00	1.27	13.71	1.31	14.38	1.35	14.72	1.36	15.06	1.37	15.74	1.38
					102	12.00	1.31	13.45	1.35	14.11	1.38	14.45	1.40	14.78	1.40	15.46	1.41
					108	11.85	1.37	13.05	1.41	13.71	1.44	14.04	1.45	14.37	1.46	15.04	1.46
111	11.25	1.41	12.79	1.45	13.44	1.48	13.77	1.48	14.10	1.49	14.76	1.49					
115	10.95	1.46	12.53	1.49	13.17	1.52	13.50	1.52	13.83	1.52	14.49	1.52					
18				18	68	13.68	1.06	18.25	1.14	19.05	1.20	19.46	1.23	20.69	1.29	21.51	1.32
					70	13.68	1.08	18.09	1.16	18.90	1.22	19.30	1.25	20.52	1.31	21.34	1.33
					73	13.68	1.12	17.78	1.20	18.58	1.26	18.98	1.28	20.20	1.34	21.01	1.36
					77	13.68	1.16	17.47	1.23	18.27	1.29	18.67	1.32	19.87	1.37	20.68	1.38
					81	13.68	1.21	17.16	1.27	17.95	1.33	18.35	1.35	19.55	1.40	20.35	1.41
					84	13.68	1.25	16.86	1.32	17.64	1.37	18.03	1.39	19.22	1.43	20.03	1.44
					88	13.68	1.29	16.55	1.36	17.33	1.41	17.72	1.42	18.90	1.46	19.70	1.47
					91	13.68	1.34	16.24	1.40	17.02	1.44	17.41	1.46	18.58	1.49	19.37	1.50
					95	13.68	1.38	15.94	1.44	16.71	1.48	17.10	1.48	18.26	1.53	19.05	1.53
					99	13.68	1.43	15.63	1.48	16.40	1.52	16.78	1.54	17.94	1.56	18.72	1.56
					102	13.68	1.48	15.33	1.53	16.09	1.56	16.47	1.58	17.62	1.59	18.40	1.59
					108	13.51	1.55	14.88	1.60	15.63	1.63	16.01	1.64	17.15	1.65	17.92	1.64
					111	12.83	1.60	14.58	1.64	15.32	1.67	15.70	1.68	16.83	1.68	17.59	1.67
					115	12.48	1.65	14.28	1.69	15.02	1.71	15.39	1.72	16.52	1.72	17.27	1.70
24				24	68	17.60	1.46	23.48	1.57	24.51	1.67	25.04	1.71	26.61	1.79	27.67	1.83
					70	17.60	1.49	23.28	1.60	24.31	1.69	24.83	1.73	26.40	1.81	27.46	1.84
					73	17.60	1.55	22.88	1.66	23.91	1.74	24.42	1.78	25.98	1.85	27.03	1.88
					77	17.60	1.61	22.48	1.71	23.50	1.79	24.01	1.82	25.57	1.89	26.61	1.92
					81	17.60	1.67	22.08	1.77	23.10	1.84	23.61	1.87	25.15	1.94	26.19	1.96
					84	17.60	1.73	21.69	1.82	22.69	1.89	23.20	1.92	24.73	1.98	25.76	1.99
					88	17.60	1.79	21.29	1.88	22.29	1.95	22.80	1.97	24.32	2.02	25.34	2.03
					91	17.60	1.85	20.90	1.94	21.89	2.00	22.39	2.03	23.91	2.07	24.92	2.07
					95	17.60	1.92	20.51	2.00	21.49	2.06	22.00	2.05	23.49	2.11	24.50	2.12
					99	17.60	1.98	20.12	2.06	21.10	2.11	21.59	2.13	23.08	2.16	24.09	2.16
					102	17.60	2.05	19.73	2.12	20.70	2.17	21.19	2.18	22.67	2.21	23.67	2.20
					108	17.38	2.15	19.14	2.21	20.11	2.25	20.59	2.27	22.06	2.28	23.05	2.27
					111	16.50	2.21	18.76	2.27	19.72	2.31	20.20	2.32	21.66	2.33	22.64	2.31
					115	16.06	2.28	18.37	2.34	19.32	2.37	19.80	2.38	21.25	2.38	22.22	2.36

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7			14	68	12.37	1.03	15.27	1.05	15.72	1.07	15.98	1.08	16.89	1.11	17.61	1.13
					70	12.37	1.04	15.08	1.06	15.54	1.08	15.81	1.09	16.74	1.13	17.47	1.14
					73	12.37	1.07	14.71	1.09	15.20	1.11	15.48	1.12	16.44	1.15	17.20	1.17
					77	12.37	1.09	14.37	1.12	14.88	1.14	15.17	1.15	16.17	1.18	16.95	1.20
					81	12.37	1.12	14.04	1.14	14.57	1.17	14.87	1.18	15.91	1.21	16.72	1.22
					84	12.37	1.15	13.73	1.17	14.29	1.19	14.60	1.20	15.67	1.23	16.50	1.25
					88	12.37	1.18	13.44	1.20	14.02	1.22	14.35	1.23	15.46	1.26	16.31	1.28
					91	12.37	1.21	13.17	1.23	13.77	1.25	14.11	1.26	15.26	1.29	16.14	1.31
					95	12.37	1.24	12.92	1.26	13.55	1.28	14.00	1.29	15.08	1.32	15.98	1.34
					99	12.37	1.27	12.68	1.29	13.34	1.31	13.70	1.32	14.92	1.35	15.85	1.37
					102	12.37	1.30	12.47	1.32	13.15	1.35	13.53	1.36	14.78	1.39	15.73	1.40
					108	12.37	1.35	12.19	1.37	12.91	1.39	13.30	1.41	14.61	1.43	15.59	1.45
					111	12.37	1.39	12.03	1.41	12.77	1.43	13.17	1.44	14.52	1.47	15.53	1.49
					115	12.37	1.42	11.88	1.44	12.65	1.46	13.06	1.47	14.45	1.50	15.48	1.52
7			16	68	14.14	1.12	17.45	1.15	17.97	1.17	18.27	1.18	19.31	1.22	20.13	1.24	
				70	14.14	1.14	17.24	1.16	17.77	1.18	18.07	1.20	19.13	1.23	19.97	1.25	
				73	14.14	1.17	16.82	1.19	17.37	1.21	17.69	1.23	18.79	1.26	19.66	1.28	
				77	14.14	1.20	16.42	1.22	17.00	1.24	17.33	1.25	18.48	1.29	19.37	1.31	
				81	14.14	1.23	16.04	1.25	16.65	1.27	17.00	1.28	18.18	1.32	19.10	1.34	
				84	14.14	1.26	15.69	1.28	16.33	1.30	16.69	1.32	17.91	1.35	18.86	1.37	
				88	14.14	1.29	15.36	1.31	16.02	1.34	16.40	1.35	17.67	1.38	18.64	1.40	
				91	14.14	1.32	15.05	1.35	15.74	1.37	16.13	1.38	17.44	1.41	18.44	1.43	
				95	14.14	1.36	14.76	1.38	15.48	1.40	16.00	1.41	17.23	1.45	18.26	1.47	
				99	14.14	1.39	14.50	1.41	15.25	1.44	15.66	1.45	17.05	1.48	18.11	1.50	
				102	14.14	1.42	14.25	1.45	15.03	1.47	15.46	1.48	16.89	1.51	17.98	1.53	
				108	14.14	1.48	13.93	1.50	14.75	1.52	15.20	1.54	16.70	1.57	17.82	1.59	
				111	14.14	1.52	13.74	1.54	14.59	1.56	15.05	1.57	16.59	1.60	17.74	1.62	
				115	14.14	1.55	13.58	1.58	14.45	1.60	14.93	1.61	16.51	1.64	17.69	1.66	
7			19	68	16.79	1.33	20.73	1.36	21.34	1.39	21.69	1.40	22.93	1.44	23.90	1.47	
				70	16.79	1.35	20.47	1.38	21.10	1.40	21.46	1.42	22.72	1.46	23.71	1.48	
				73	16.79	1.38	19.97	1.41	20.63	1.44	21.01	1.45	22.32	1.49	23.34	1.52	
				77	16.79	1.42	19.50	1.44	20.19	1.47	20.58	1.49	21.94	1.53	23.00	1.55	
				81	16.79	1.45	19.05	1.48	19.78	1.51	20.19	1.52	21.59	1.56	22.69	1.59	
				84	16.79	1.49	18.63	1.52	19.39	1.55	19.81	1.56	21.27	1.60	22.40	1.62	
				88	16.79	1.53	18.24	1.56	19.03	1.58	19.47	1.60	20.98	1.63	22.13	1.66	
				91	16.79	1.57	17.87	1.59	18.69	1.62	19.15	1.63	20.71	1.67	21.90	1.70	
				95	16.79	1.61	17.53	1.63	18.39	1.66	19.00	1.67	20.47	1.71	21.69	1.74	
				99	16.79	1.65	17.21	1.67	18.10	1.70	18.60	1.71	20.25	1.75	21.51	1.78	
				102	16.79	1.69	16.93	1.72	17.85	1.74	18.36	1.76	20.06	1.79	21.35	1.82	
				108	16.79	1.75	16.54	1.78	17.52	1.81	18.05	1.82	19.83	1.86	21.16	1.88	
				111	16.79	1.79	16.32	1.82	17.33	1.85	17.88	1.86	19.70	1.90	21.07	1.92	
				115	16.79	1.84	16.13	1.87	17.16	1.89	17.73	1.91	19.61	1.94	21.01	1.97	

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15			22	68	19.44	1.43	24.00	1.46	24.71	1.49	25.12	1.51	25.56	1.52	26.55	1.55
					70	19.44	1.45	23.70	1.48	24.43	1.51	24.84	1.53	25.30	1.54	26.30	1.57
					73	19.44	1.49	23.12	1.52	23.89	1.55	24.32	1.56	24.79	1.58	25.84	1.61
					77	19.44	1.53	22.57	1.56	23.38	1.59	23.83	1.60	24.32	1.62	25.41	1.64
					81	19.44	1.56	22.06	1.60	22.90	1.63	23.37	1.64	23.88	1.65	25.00	1.68
					84	19.44	1.60	21.57	1.64	22.45	1.67	22.94	1.68	23.47	1.69	24.63	1.72
					88	19.44	1.65	21.12	1.68	22.03	1.71	22.54	1.72	23.09	1.73	24.29	1.76
					91	19.44	1.69	20.69	1.72	21.65	1.75	22.18	1.76	22.74	1.78	23.98	1.80
					95	19.44	1.73	20.30	1.76	21.29	1.79	22.00	1.80	22.42	1.82	23.70	1.85
					99	19.44	1.77	19.93	1.80	20.96	1.83	21.53	1.85	22.14	1.86	23.45	1.89
					102	19.44	1.82	19.60	1.85	20.67	1.88	21.26	1.89	21.88	1.91	23.23	1.93
					108	19.44	1.89	19.16	1.92	20.28	1.95	20.90	1.96	21.55	1.97	22.96	2.00
111	19.44	1.93	18.90	1.96	20.06	1.99	20.70	2.01	21.37	2.02	22.81	2.05					
115	19.44	1.98	18.67	2.01	19.87	2.04	20.53	2.05	21.22	2.07	22.70	2.10					
7	18			25	68	22.09	1.65	27.27	1.68	28.08	1.72	28.54	1.74	30.17	1.78	31.45	1.82
					70	22.09	1.67	26.93	1.70	27.76	1.74	28.23	1.76	29.89	1.81	31.20	1.84
					73	22.09	1.71	26.27	1.75	27.14	1.78	27.64	1.80	29.36	1.85	30.71	1.88
					77	22.09	1.75	25.65	1.79	26.57	1.83	27.08	1.84	28.87	1.89	30.26	1.92
					81	22.09	1.80	25.07	1.84	26.02	1.87	26.56	1.89	28.41	1.93	29.85	1.97
					84	22.09	1.85	24.51	1.88	25.51	1.92	26.07	1.93	27.99	1.98	29.47	2.01
					88	22.09	1.89	23.99	1.93	25.04	1.96	25.62	1.98	27.60	2.03	29.12	2.06
					91	22.09	1.94	23.51	1.98	24.60	2.01	25.20	2.03	27.25	2.07	28.81	2.10
					95	22.09	1.99	23.06	2.02	24.19	2.06	25.00	2.07	26.93	2.12	28.54	2.15
					99	22.09	2.04	22.65	2.07	23.82	2.11	24.47	2.12	26.65	2.17	28.30	2.20
					102	22.09	2.09	22.27	2.13	23.49	2.16	24.15	2.18	26.40	2.22	28.09	2.25
					108	22.09	2.17	21.77	2.21	23.05	2.24	23.75	2.25	26.09	2.30	27.85	2.33
111	22.09	2.22	21.48	2.26	22.80	2.29	23.52	2.31	25.92	2.35	27.73	2.38					
115	22.09	2.28	21.22	2.31	22.58	2.35	23.33	2.36	25.80	2.41	27.64	2.44					
7	24			31	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	68	15.91	1.23	19.64	1.25	20.22	1.28	20.55	1.29	21.72	1.33	22.65	1.35
					70	15.91	1.24	19.39	1.27	19.99	1.29	20.33	1.31	21.52	1.34	22.46	1.37
					73	15.91	1.27	18.92	1.30	19.54	1.33	19.90	1.34	21.14	1.37	22.11	1.40
					77	15.91	1.31	18.47	1.33	19.13	1.36	19.50	1.37	20.79	1.41	21.79	1.43
					81	15.91	1.34	18.05	1.37	18.74	1.39	19.12	1.40	20.46	1.44	21.49	1.46
					84	15.91	1.37	17.65	1.40	18.37	1.42	18.77	1.44	20.15	1.47	21.22	1.50
					88	15.91	1.41	17.28	1.43	18.03	1.46	18.45	1.47	19.87	1.51	20.97	1.53
					91	15.91	1.44	16.93	1.47	17.71	1.50	18.14	1.51	19.62	1.54	20.75	1.57
					95	15.91	1.48	16.61	1.51	17.42	1.53	18.00	1.54	19.39	1.58	20.55	1.60
					99	15.91	1.52	16.31	1.54	17.15	1.57	17.62	1.58	19.18	1.62	20.37	1.64
					102	15.91	1.56	16.03	1.58	16.91	1.61	17.39	1.62	19.01	1.65	20.22	1.68
					108	15.91	1.61	15.67	1.64	16.59	1.67	17.10	1.68	18.78	1.71	20.05	1.73
					111	15.91	1.66	15.46	1.68	16.42	1.71	16.93	1.72	18.67	1.75	19.96	1.77
					115	15.91	1.70	15.28	1.72	16.26	1.75	16.80	1.76	18.57	1.79	19.90	1.81
9	12			21	68	18.56	1.43	22.91	1.46	23.59	1.49	23.97	1.51	25.34	1.55	26.42	1.58
					70	18.56	1.45	22.62	1.48	23.32	1.51	23.71	1.53	25.11	1.57	26.21	1.60
					73	18.56	1.49	22.07	1.52	22.80	1.55	23.22	1.56	24.67	1.61	25.80	1.63
					77	18.56	1.53	21.55	1.56	22.32	1.59	22.75	1.60	24.25	1.64	25.42	1.67
					81	18.56	1.56	21.05	1.60	21.86	1.63	22.31	1.64	23.87	1.68	25.07	1.71
					84	18.56	1.60	20.59	1.64	21.43	1.67	21.90	1.68	23.51	1.72	24.75	1.75
					88	18.56	1.65	20.16	1.68	21.03	1.71	21.52	1.72	23.19	1.76	24.46	1.79
					91	18.56	1.69	19.75	1.72	20.66	1.75	21.17	1.76	22.89	1.80	24.20	1.83
					95	18.56	1.73	19.37	1.76	20.32	1.79	21.00	1.80	22.62	1.85	23.97	1.87
					99	18.56	1.77	19.03	1.80	20.01	1.83	20.55	1.85	22.38	1.89	23.77	1.91
					102	18.56	1.82	18.71	1.85	19.73	1.88	20.29	1.89	22.17	1.93	23.60	1.96
					108	18.56	1.89	18.28	1.92	19.36	1.95	19.95	1.96	21.91	2.00	23.39	2.03
					111	18.56	1.93	18.04	1.96	19.15	1.99	19.76	2.01	21.78	2.05	23.29	2.07
					115	18.56	1.98	17.82	2.01	18.97	2.04	19.60	2.05	21.67	2.10	23.22	2.12
9	15			24	68	21.21	1.48	29.92	1.52	30.49	1.56	30.83	1.57	31.20	1.59	32.08	1.62
					70	21.21	1.52	29.10	1.56	29.71	1.59	30.07	1.61	30.47	1.63	31.39	1.66
					73	21.21	1.56	28.32	1.60	28.97	1.63	29.36	1.65	29.78	1.67	30.73	1.70
					77	21.21	1.60	27.58	1.63	28.27	1.67	28.67	1.69	29.11	1.70	30.11	1.74
					81	21.21	1.64	26.86	1.67	27.59	1.71	28.02	1.73	28.48	1.74	29.52	1.78
					84	21.21	1.68	26.18	1.72	26.96	1.75	27.40	1.77	27.88	1.79	28.96	1.82
					88	21.21	1.70	25.85	1.74	26.65	1.77	27.10	1.79	27.60	1.81	28.70	1.84
					91	21.21	1.74	25.22	1.78	26.06	1.82	26.53	1.83	27.05	1.85	28.19	1.88
					95	21.21	1.79	24.63	1.83	25.50	1.86	24.00	2.11	26.53	1.89	27.72	1.93
					99	21.21	1.83	24.06	1.87	24.98	1.91	25.50	1.92	26.05	1.94	27.28	1.97
					102	21.21	1.88	23.53	1.92	24.49	1.95	25.03	1.97	25.60	1.99	26.87	2.02
					108	21.21	1.93	23.03	1.97	24.04	2.00	24.59	2.02	25.19	2.03	26.50	2.07
					111	21.21	1.98	22.57	2.01	23.61	2.05	24.19	2.07	24.81	2.08	26.16	2.11
					115	21.21	2.03	22.14	2.06	23.22	2.10	24.00	2.12	24.46	2.13	25.85	2.16

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	23.86	1.81	29.45	1.85	30.32	1.88	30.82	1.90	32.58	1.96	33.97	1.99
					70	23.86	1.83	29.09	1.87	29.98	1.91	30.49	1.93	32.28	1.98	33.69	2.01
					73	23.86	1.88	28.38	1.92	29.32	1.95	29.85	1.97	31.71	2.03	33.17	2.06
					77	23.86	1.92	27.70	1.96	28.69	2.00	29.25	2.02	31.18	2.07	32.68	2.11
					81	23.86	1.97	27.07	2.01	28.10	2.05	28.68	2.07	30.69	2.12	32.24	2.16
					84	23.86	2.02	26.47	2.06	27.55	2.10	28.16	2.12	30.23	2.17	31.83	2.20
					88	23.86	2.08	25.91	2.11	27.04	2.15	27.67	2.17	29.81	2.22	31.45	2.26
					91	23.86	2.13	25.39	2.17	26.57	2.20	27.22	2.22	29.43	2.27	31.12	2.31
					95	23.86	2.18	24.91	2.22	26.13	2.26	27.00	2.27	29.08	2.33	30.82	2.36
					99	23.86	2.24	24.46	2.28	25.73	2.31	26.43	2.33	28.78	2.38	30.56	2.41
					102	23.86	2.29	24.05	2.33	25.37	2.37	26.09	2.39	28.51	2.44	30.34	2.47
					108	23.86	2.38	23.51	2.42	24.89	2.45	25.65	2.47	28.17	2.52	30.07	2.56
					111	23.86	2.44	23.19	2.48	24.62	2.51	25.40	2.53	28.00	2.58	29.94	2.61
					115	23.86	2.50	22.92	2.54	24.39	2.57	25.19	2.59	27.86	2.64	29.85	2.67
9	24		33	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56	
				111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61	
				115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67	
12	12		24	68	21.21	1.68	26.18	1.72	26.96	1.75	27.40	1.77	28.96	1.82	30.19	1.85	
				70	21.21	1.70	25.85	1.74	26.65	1.77	27.10	1.79	28.70	1.84	29.95	1.87	
				73	21.21	1.74	25.22	1.78	26.06	1.82	26.53	1.83	28.19	1.88	29.48	1.91	
				77	21.21	1.79	24.63	1.83	25.50	1.86	26.00	1.88	27.72	1.93	29.05	1.96	
				81	21.21	1.83	24.06	1.87	24.98	1.91	25.50	1.92	27.28	1.97	28.66	2.00	
				84	21.21	1.88	23.53	1.92	24.49	1.95	25.03	1.97	26.87	2.02	28.29	2.05	
				88	21.21	1.93	23.03	1.97	24.04	2.00	24.59	2.02	26.50	2.07	27.96	2.10	
				91	21.21	1.98	22.57	2.01	23.61	2.05	24.19	2.07	26.16	2.11	27.66	2.14	
				95	21.21	2.03	22.14	2.06	23.22	2.10	24.00	2.11	25.85	2.16	27.40	2.19	
				99	21.21	2.08	21.74	2.11	22.87	2.15	23.49	2.17	25.58	2.21	27.16	2.24	
				102	21.21	2.13	21.38	2.17	22.55	2.20	23.19	2.22	25.34	2.27	26.97	2.30	
				108	21.21	2.21	20.90	2.25	22.13	2.28	22.80	2.30	25.04	2.35	26.73	2.38	
				111	21.21	2.27	20.62	2.30	21.89	2.34	22.58	2.35	24.89	2.40	26.62	2.43	
				115	21.21	2.32	20.37	2.36	21.68	2.39	22.39	2.41	24.76	2.46	26.54	2.49	

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	23.86	1.81	29.45	1.85	30.32	1.88	30.82	1.90	31.37	1.92	32.58	1.96
					70	23.86	1.83	29.09	1.87	29.98	1.91	30.49	1.93	31.05	1.94	32.28	1.98
					73	23.86	1.88	28.38	1.92	29.32	1.95	29.85	1.97	30.43	1.99	31.71	2.03
					77	23.86	1.92	27.70	1.96	28.69	2.00	29.25	2.02	29.85	2.04	31.18	2.07
					81	23.86	1.97	27.07	2.01	28.10	2.05	28.68	2.07	29.31	2.09	30.69	2.12
					84	23.86	2.02	26.47	2.06	27.55	2.10	28.16	2.12	28.81	2.14	30.23	2.17
					88	23.86	2.08	25.91	2.11	27.04	2.15	27.67	2.17	28.34	2.19	29.81	2.22
					91	23.86	2.13	25.39	2.17	26.57	2.20	27.22	2.22	27.91	2.24	29.43	2.27
					95	23.86	2.18	24.91	2.22	26.13	2.26	27.00	2.27	27.52	2.29	29.08	2.33
					99	23.86	2.24	24.46	2.28	25.73	2.31	26.43	2.33	27.17	2.35	28.78	2.38
					102	23.86	2.29	24.05	2.33	25.37	2.37	26.09	2.39	26.85	2.40	28.51	2.44
					108	23.86	2.38	23.51	2.42	24.89	2.45	25.65	2.47	26.45	2.49	28.17	2.52
					111	23.86	2.44	23.19	2.48	24.62	2.51	25.40	2.53	26.22	2.55	28.00	2.58
					115	23.86	2.50	22.92	2.54	24.39	2.57	25.19	2.59	26.04	2.61	27.86	2.64
12	18			30	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67
12	24			36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64
15	18			33	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64
15	24			39	68	25.10	1.59	35.40	1.64	36.07	1.67	36.48	1.69	36.93	1.71	37.96	1.75
					70	25.10	1.63	34.44	1.67	35.16	1.71	35.59	1.73	36.06	1.75	37.14	1.79
					73	25.10	1.68	33.52	1.72	34.29	1.75	34.74	1.77	35.23	1.79	36.37	1.83
					77	25.10	1.72	32.63	1.76	33.45	1.80	33.93	1.82	34.45	1.83	35.63	1.87
					81	25.10	1.76	31.79	1.80	32.65	1.84	33.15	1.86	33.70	1.88	34.93	1.91
					84	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					88	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					91	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					95	25.10	1.92	29.14	1.96	30.18	2.00	28.40	2.27	31.40	2.04	32.80	2.07
					99	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					102	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					108	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					111	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					115	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.28	28.95	2.29	30.59	2.33

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18	18			36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67
7	7	7		21	68	18.56	1.46	22.91	1.49	23.59	1.52	23.97	1.53	25.34	1.58	26.42	1.61
					70	18.56	1.48	22.62	1.51	23.32	1.54	23.71	1.55	25.11	1.60	26.21	1.62
					73	18.56	1.51	22.07	1.54	22.80	1.58	23.22	1.59	24.67	1.63	25.80	1.66
					77	18.56	1.55	21.55	1.58	22.32	1.61	22.75	1.63	24.25	1.67	25.42	1.70
					81	18.56	1.59	21.05	1.62	21.86	1.65	22.31	1.67	23.87	1.71	25.07	1.74
					84	18.56	1.63	20.59	1.66	21.43	1.69	21.90	1.71	23.51	1.75	24.75	1.78
					88	18.56	1.67	20.16	1.70	21.03	1.73	21.52	1.75	23.19	1.79	24.46	1.82
					91	18.56	1.72	19.75	1.75	20.66	1.78	21.17	1.79	22.89	1.83	24.20	1.86
					95	18.56	1.76	19.37	1.79	20.32	1.82	21.00	1.83	22.62	1.88	23.97	1.90
					99	18.56	1.80	19.03	1.83	20.01	1.86	20.55	1.88	22.38	1.92	23.77	1.95
					102	18.56	1.85	18.71	1.88	19.73	1.91	20.29	1.92	22.17	1.97	23.60	1.99
					108	18.56	1.92	18.28	1.95	19.36	1.98	19.95	1.99	21.91	2.03	23.39	2.06
					111	18.56	1.97	18.04	2.00	19.15	2.03	19.76	2.04	21.78	2.08	23.29	2.11
					115	18.56	2.02	17.82	2.05	18.97	2.08	19.60	2.09	21.67	2.13	23.22	2.16
7	7	9		23	68	20.33	1.55	25.09	1.59	25.83	1.62	26.26	1.64	27.76	1.68	28.94	1.71
					70	20.33	1.57	24.78	1.61	25.54	1.64	25.97	1.65	27.50	1.70	28.70	1.73
					73	20.33	1.61	24.17	1.65	24.97	1.68	25.43	1.69	27.02	1.74	28.26	1.77
					77	20.33	1.65	23.60	1.69	24.44	1.72	24.92	1.74	26.56	1.78	27.84	1.81
					81	20.33	1.70	23.06	1.73	23.94	1.76	24.44	1.78	26.14	1.82	27.46	1.85
					84	20.33	1.74	22.55	1.77	23.47	1.80	23.99	1.82	25.75	1.87	27.11	1.89
					88	20.33	1.78	22.08	1.82	23.03	1.85	23.57	1.86	25.39	1.91	26.79	1.94
					91	20.33	1.83	21.63	1.86	22.63	1.89	23.18	1.91	25.07	1.95	26.51	1.98
					95	20.33	1.87	21.22	1.91	22.26	1.94	23.00	1.95	24.78	2.00	26.25	2.03
					99	20.33	1.92	20.84	1.95	21.92	1.99	22.51	2.00	24.51	2.05	26.03	2.07
					102	20.33	1.97	20.49	2.00	21.61	2.03	22.22	2.05	24.28	2.09	25.84	2.12
					108	20.33	2.04	20.03	2.08	21.20	2.11	21.85	2.12	24.00	2.17	25.62	2.20
					111	20.33	2.10	19.76	2.13	20.98	2.16	21.64	2.17	23.85	2.22	25.51	2.25
					115	20.33	2.15	19.52	2.18	20.78	2.21	21.46	2.23	23.73	2.27	25.43	2.30

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	26	68	22.98	1.81	28.36	1.85	29.20	1.88	29.68	1.90	31.38	1.96	32.71	1.99	
				70	22.98	1.83	28.01	1.87	28.87	1.91	29.36	1.93	31.09	1.98	32.45	2.01	
				73	22.98	1.88	27.33	1.92	28.23	1.95	28.75	1.97	30.54	2.03	31.94	2.06	
				77	22.98	1.92	26.68	1.96	27.63	2.00	28.17	2.02	30.03	2.07	31.47	2.11	
				81	22.98	1.97	26.07	2.01	27.06	2.05	27.62	2.07	29.55	2.12	31.04	2.16	
				84	22.98	2.02	25.49	2.06	26.53	2.10	27.11	2.12	29.11	2.17	30.65	2.20	
				88	22.98	2.08	24.95	2.11	26.04	2.15	26.64	2.17	28.71	2.22	30.29	2.26	
				91	22.98	2.13	24.45	2.17	25.58	2.20	26.21	2.22	28.34	2.27	29.97	2.31	
				95	22.98	2.18	23.99	2.22	25.16	2.26	26.00	2.27	28.01	2.33	29.68	2.36	
				99	22.98	2.24	23.56	2.28	24.77	2.31	25.45	2.33	27.71	2.38	29.43	2.41	
				102	22.98	2.29	23.16	2.33	24.43	2.37	25.12	2.39	27.45	2.44	29.21	2.47	
				108	22.98	2.38	22.64	2.42	23.97	2.45	24.70	2.47	27.13	2.52	28.96	2.56	
111	22.98	2.44	22.33	2.48	23.71	2.51	24.46	2.53	26.96	2.58	28.84	2.61					
115	22.98	2.50	22.07	2.54	23.49	2.57	24.26	2.59	26.83	2.64	28.75	2.67					
7	7	15	29	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52	
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64					
7	7	18	32	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56	
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	24	38	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56	
7	9	9	25	68	22.09	1.66	27.27	1.69	28.08	1.73	28.54	1.74	30.17	1.79	31.45	1.82	
				70	22.09	1.68	26.93	1.71	27.76	1.75	28.23	1.76	29.89	1.81	31.20	1.85	
				73	22.09	1.72	26.27	1.76	27.14	1.79	27.64	1.81	29.36	1.86	30.71	1.89	
				77	22.09	1.76	25.65	1.80	26.57	1.83	27.08	1.85	28.87	1.90	30.26	1.93	
				81	22.09	1.81	25.07	1.84	26.02	1.88	26.56	1.90	28.41	1.94	29.85	1.97	
				84	22.09	1.85	24.51	1.89	25.51	1.92	26.07	1.94	27.99	1.99	29.47	2.02	
				88	22.09	1.90	23.99	1.94	25.04	1.97	25.62	1.99	27.60	2.04	29.12	2.07	
				91	22.09	1.95	23.51	1.99	24.60	2.02	25.20	2.04	27.25	2.08	28.81	2.11	
				95	22.09	2.00	23.06	2.03	24.19	2.07	25.00	2.08	26.93	2.13	28.54	2.16	
				99	22.09	2.05	22.65	2.08	23.82	2.12	24.47	2.14	26.65	2.18	28.30	2.21	
				102	22.09	2.10	22.27	2.14	23.49	2.17	24.15	2.19	26.40	2.23	28.09	2.26	
				108	22.09	2.18	21.77	2.22	23.05	2.25	23.75	2.27	26.09	2.31	27.85	2.34	
7	9	12	28	68	24.74	1.81	30.55	1.85	31.45	1.88	31.97	1.90	33.79	1.96	35.23	1.99	
				70	24.74	1.83	30.16	1.87	31.09	1.91	31.62	1.93	33.48	1.98	34.94	2.01	
				73	24.74	1.88	29.43	1.92	30.40	1.95	30.96	1.97	32.89	2.03	34.40	2.06	
				77	24.74	1.92	28.73	1.96	29.75	2.00	30.33	2.02	32.34	2.07	33.90	2.11	
				81	24.74	1.97	28.07	2.01	29.14	2.05	29.75	2.07	31.82	2.12	33.43	2.16	
				84	24.74	2.02	27.45	2.06	28.57	2.10	29.20	2.12	31.35	2.17	33.01	2.20	
				88	24.74	2.08	26.87	2.11	28.04	2.15	28.69	2.17	30.91	2.22	32.62	2.26	
				91	24.74	2.13	26.33	2.17	27.55	2.20	28.22	2.22	30.52	2.27	32.27	2.31	
				95	24.74	2.18	25.83	2.22	27.10	2.26	28.00	2.27	30.16	2.33	31.96	2.36	
				99	24.74	2.24	25.37	2.28	26.68	2.31	27.40	2.33	29.84	2.38	31.69	2.41	
				102	24.74	2.29	24.94	2.33	26.30	2.37	27.05	2.39	29.56	2.44	31.46	2.47	
				108	24.74	2.38	24.38	2.42	25.81	2.45	26.60	2.47	29.22	2.52	31.19	2.56	
111	24.74	2.44	24.05	2.48	25.53	2.51	26.34	2.53	29.04	2.58	31.05	2.61					
115	24.74	2.50	23.76	2.54	25.30	2.57	26.13	2.59	28.89	2.64	30.96	2.67					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	15	31	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52	
7	9	18	34	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58		
				115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64	
				68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41	
7	9	24	40	102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56	
				111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61	
				115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67	
				68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36					
99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41					
102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47					
108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56					
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	12		31	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					
7	12	15		34	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64					
7	12	18		37	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9		27	68	23.86	1.81	29.45	1.85	30.32	1.88	30.82	1.90	32.58	1.96	33.97	1.99
					70	23.86	1.83	29.09	1.87	29.98	1.91	30.49	1.93	32.28	1.98	33.69	2.01
					73	23.86	1.88	28.38	1.92	29.32	1.95	29.85	1.97	31.71	2.03	33.17	2.06
					77	23.86	1.92	27.70	1.96	28.69	2.00	29.25	2.02	31.18	2.07	32.68	2.11
					81	23.86	1.97	27.07	2.01	28.10	2.05	28.68	2.07	30.69	2.12	32.24	2.16
					84	23.86	2.02	26.47	2.06	27.55	2.10	28.16	2.12	30.23	2.17	31.83	2.20
					88	23.86	2.08	25.91	2.11	27.04	2.15	27.67	2.17	29.81	2.22	31.45	2.26
					91	23.86	2.13	25.39	2.17	26.57	2.20	27.22	2.22	29.43	2.27	31.12	2.31
					95	23.86	2.18	24.91	2.22	26.13	2.26	27.00	2.27	29.08	2.33	30.82	2.36
					99	23.86	2.24	24.46	2.28	25.73	2.31	26.43	2.33	28.78	2.38	30.56	2.41
					102	23.86	2.29	24.05	2.33	25.37	2.37	26.09	2.39	28.51	2.44	30.34	2.47
					108	23.86	2.38	23.51	2.42	24.89	2.45	25.65	2.47	28.17	2.52	30.07	2.56
9	9	12		30	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
9	9	15		33	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64					

Capacity Table

JXH30S4B(AJ030BX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	18	36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56	
9	12	12	33	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99	
				70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01	
				73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06	
				77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11	
				81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16	
				84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20	
				88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26	
				91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31	
				95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36	
				99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41	
				102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47	
				108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56	
9	15	36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96		
			70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98		
			73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03		
			77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07		
			81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12		
			84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17		
			88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22		
			91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27		
			95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33		
			99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38		
			102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44		
			108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52		
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	18		39	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
12	12	12		36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
12	12	15		39	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	7	28	68	24.74	1.81	30.55	1.85	31.45	1.88	31.97	1.90	33.79	1.96	35.23	1.99
					70	24.74	1.83	30.16	1.87	31.09	1.91	31.62	1.93	33.48	1.98	34.94	2.01
					73	24.74	1.88	29.43	1.92	30.40	1.95	30.96	1.97	32.89	2.03	34.40	2.06
					77	24.74	1.92	28.73	1.96	29.75	2.00	30.33	2.02	32.34	2.07	33.90	2.11
					81	24.74	1.97	28.07	2.01	29.14	2.05	29.75	2.07	31.82	2.12	33.43	2.16
					84	24.74	2.02	27.45	2.06	28.57	2.10	29.20	2.12	31.35	2.17	33.01	2.20
					88	24.74	2.08	26.87	2.11	28.04	2.15	28.69	2.17	30.91	2.22	32.62	2.26
					91	24.74	2.13	26.33	2.17	27.55	2.20	28.22	2.22	30.52	2.27	32.27	2.31
					95	24.74	2.18	25.83	2.22	27.10	2.26	28.00	2.27	30.16	2.33	31.96	2.36
					99	24.74	2.24	25.37	2.28	26.68	2.31	27.40	2.33	29.84	2.38	31.69	2.41
					102	24.74	2.29	24.94	2.33	26.30	2.37	27.05	2.39	29.56	2.44	31.46	2.47
					108	24.74	2.38	24.38	2.42	25.81	2.45	26.60	2.47	29.22	2.52	31.19	2.56
7	7	7	9	30	111	24.74	2.44	24.05	2.48	25.53	2.51	26.34	2.53	29.04	2.58	31.05	2.61
					115	24.74	2.50	23.76	2.54	25.30	2.57	26.13	2.59	28.89	2.64	30.96	2.67
					68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
7	7	7	12	33	102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67
					68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
7	7	7	12	33	95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	15	36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	27.58	2.55	29.45	2.58					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	27.39	2.61	29.30	2.64					
7	7	7	18	39	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					
7	7	9	9	32	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	12	35	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
7	7	9	15	38	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	32.99	1.92	34.27	1.96
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	32.65	1.94	33.96	1.98
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	32.01	1.99	33.36	2.03
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	31.40	2.04	32.80	2.07
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	30.83	2.09	32.28	2.12
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	30.30	2.14	31.80	2.17
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	29.81	2.19	31.36	2.22
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	29.36	2.24	30.95	2.27
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	28.95	2.29	30.59	2.33
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	28.57	2.35	30.27	2.38
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	28.24	2.40	29.99	2.44
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	27.82	2.49	29.63	2.52
7	7	12	12	38	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61					
115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67					

Capacity Table

JXH30S4B(AJ030BX54CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	9	34	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
7	9	9	12	37	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
7	9	9	15	40	68	25.10	1.68	30.98	1.72	31.90	1.75	32.42	1.77	32.99	1.79	34.27	1.83
					70	25.10	1.72	30.59	1.76	31.53	1.80	32.07	1.82	32.65	1.83	33.96	1.87
					73	25.10	1.76	29.85	1.80	30.84	1.84	31.40	1.86	32.01	1.88	33.36	1.91
					77	25.10	1.81	29.14	1.85	30.18	1.88	30.77	1.90	31.40	1.92	32.80	1.96
					81	25.10	1.83	28.47	1.87	29.56	1.91	30.17	1.93	30.83	1.94	32.28	1.98
					84	25.10	1.88	27.85	1.92	28.98	1.95	29.62	1.97	30.30	1.99	31.80	2.03
					88	25.10	1.92	27.26	1.96	28.44	2.00	29.10	2.02	29.81	2.04	31.36	2.07
					91	25.10	1.97	26.71	2.01	27.94	2.05	28.63	2.07	29.36	2.09	30.95	2.12
					95	25.10	2.02	26.20	2.06	27.48	2.10	28.40	2.27	28.95	2.14	30.59	2.17
					99	25.10	2.08	25.73	2.11	27.06	2.15	27.80	2.17	28.57	2.19	30.27	2.22
					102	25.10	2.13	25.30	2.17	26.68	2.20	27.44	2.22	28.24	2.24	29.99	2.27
					108	25.10	2.18	24.73	2.22	26.18	2.26	26.98	2.28	27.82	2.29	29.63	2.33
111	25.10	2.24	24.40	2.28	25.90	2.31	26.72	2.33	27.58	2.35	29.45	2.38					
115	25.10	2.29	24.10	2.33	25.66	2.37	26.50	2.39	27.39	2.40	29.30	2.44					

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12	12	40	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67
9	9	9	9	36	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67
9	9	9	12	39	68	25.10	1.81	30.98	1.85	31.90	1.88	32.42	1.90	34.27	1.96	35.73	1.99
					70	25.10	1.83	30.59	1.87	31.53	1.91	32.07	1.93	33.96	1.98	35.44	2.01
					73	25.10	1.88	29.85	1.92	30.84	1.95	31.40	1.97	33.36	2.03	34.89	2.06
					77	25.10	1.92	29.14	1.96	30.18	2.00	30.77	2.02	32.80	2.07	34.38	2.11
					81	25.10	1.97	28.47	2.01	29.56	2.05	30.17	2.07	32.28	2.12	33.91	2.16
					84	25.10	2.02	27.85	2.06	28.98	2.10	29.62	2.12	31.80	2.17	33.48	2.20
					88	25.10	2.08	27.26	2.11	28.44	2.15	29.10	2.17	31.36	2.22	33.08	2.26
					91	25.10	2.13	26.71	2.17	27.94	2.20	28.63	2.22	30.95	2.27	32.73	2.31
					95	25.10	2.18	26.20	2.22	27.48	2.26	28.40	2.27	30.59	2.33	32.42	2.36
					99	25.10	2.24	25.73	2.28	27.06	2.31	27.80	2.33	30.27	2.38	32.14	2.41
					102	25.10	2.29	25.30	2.33	26.68	2.37	27.44	2.39	29.99	2.44	31.91	2.47
					108	25.10	2.38	24.73	2.42	26.18	2.45	26.98	2.47	29.63	2.52	31.63	2.56
					111	25.10	2.44	24.40	2.48	25.90	2.51	26.72	2.53	29.45	2.58	31.50	2.61
					115	25.10	2.50	24.10	2.54	25.66	2.57	26.50	2.59	29.30	2.64	31.40	2.67

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 39.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.
Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)												
						57		60.8		64.4		69.98		71.6		75.2		
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	
9				9	-13	14.25	3.63	12.24	3.10	10.64	2.74	7.62	2.04	6.77	1.74	4.82	1.22	
					5	11.91	2.31	11.62	2.33	11.34	2.35	10.90	2.49	10.77	2.41	10.49	2.43	
					17	11.36	1.97	11.21	2.00	11.01	2.01	10.90	2.14	10.82	2.06	10.61	2.09	
					32	11.51	1.47	11.34	1.48	11.17	1.51	10.90	1.59	10.82	1.53	10.65	1.55	
					47	11.83	1.08	11.42	1.05	11.27	1.05	10.90	1.12	10.81	1.05	10.19	0.99	
					50	12.64	1.13	12.26	1.18	11.90	1.15	11.90	1.16	11.61	1.18	11.44	1.19	
				12	59	13.71	1.17	13.49	1.21	13.21	1.16	13.11	1.19	12.86	1.23	12.69	1.24	
					-13	18.30	4.44	15.72	3.79	13.67	3.35	9.79	2.49	8.70	2.13	6.19	1.49	
					5	15.29	2.82	14.93	2.86	14.56	2.88	14.00	3.05	13.83	2.95	13.47	2.97	
					17	14.59	2.41	14.40	2.44	14.15	2.46	14.00	2.62	13.89	2.52	13.63	2.55	
					32	14.79	1.80	14.57	1.82	14.34	1.84	14.00	1.95	13.90	1.87	13.68	1.89	
					47	15.20	1.32	14.67	1.28	14.47	1.29	14.00	1.37	13.88	1.28	13.09	1.21	
				15	50	16.24	1.38	15.75	1.44	15.28	1.41	15.28	1.42	14.91	1.44	14.70	1.46	
					59	17.61	1.43	17.32	1.48	16.96	1.42	16.84	1.46	16.52	1.50	16.29	1.51	
					-13	23.53	5.02	20.22	4.28	17.57	3.80	12.59	2.82	11.18	2.40	7.96	1.69	
					5	19.66	3.20	19.20	3.23	18.73	3.26	18.00	3.45	17.79	3.34	17.32	3.36	
					17	18.75	2.73	18.52	2.76	18.19	2.79	18.00	2.97	17.86	2.85	17.52	2.89	
					32	19.01	2.04	18.73	2.05	18.44	2.08	18.00	2.20	17.87	2.11	17.58	2.14	
				18	47	19.54	1.49	18.86	1.45	18.61	1.46	18.00	1.55	17.85	1.45	16.83	1.37	
					50	20.88	1.56	20.25	1.63	19.65	1.60	19.65	1.60	19.17	1.63	18.90	1.65	
					59	22.64	1.62	22.27	1.68	21.81	1.61	21.65	1.65	21.24	1.70	20.95	1.71	
					-13	26.14	6.19	22.46	5.28	19.52	4.68	13.99	3.47	12.42	2.96	8.85	2.08	
					5	21.85	3.94	21.33	3.98	20.81	4.01	20.00	4.25	19.76	4.11	19.24	4.15	
					17	20.84	3.36	20.58	3.41	20.21	3.43	20.00	3.66	19.84	3.51	19.47	3.56	
				9	32	21.13	2.51	20.81	2.53	20.49	2.57	20.00	2.71	19.86	2.60	19.54	2.64	
					47	21.71	1.83	20.95	1.78	20.67	1.80	20.00	1.91	19.83	1.78	18.70	1.69	
					50	23.20	1.92	22.50	2.01	21.83	1.97	21.83	1.98	21.30	2.01	21.00	2.03	
					59	25.16	2.00	24.74	2.06	24.23	1.98	24.06	2.04	23.60	2.09	23.28	2.11	
					-13	24.76	5.68	20.71	4.50	19.87	4.57	15.38	3.33	13.64	2.77	9.72	1.80	
					5	24.06	3.83	23.48	3.87	22.90	3.92	22.00	4.07	21.75	4.00	21.17	4.04	
				12	17	23.44	3.31	23.04	3.35	22.63	3.38	22.00	3.50	21.83	3.45	21.42	3.49	
					32	23.25	2.46	22.90	2.49	22.55	2.51	22.00	2.60	21.85	2.55	21.49	2.58	
					47	23.32	1.73	23.04	1.75	22.74	1.76	22.00	1.83	22.12	1.79	21.82	1.81	
					50	25.31	1.84	24.69	1.87	24.23	1.89	24.01	1.90	23.43	1.93	23.10	1.95	
					59	27.72	1.91	27.18	1.94	26.69	1.97	26.47	1.98	25.85	2.01	25.50	2.03	
				15	-13	27.57	6.30	23.07	5.00	22.13	5.07	17.13	3.69	15.19	3.08	10.83	1.99	
					5	26.79	4.25	26.15	4.29	25.50	4.35	24.50	4.52	24.22	4.44	23.58	4.49	
					17	26.10	3.67	25.66	3.71	25.20	3.75	24.50	3.89	24.31	3.83	23.85	3.87	
					32	25.90	2.73	25.51	2.76	25.11	2.78	24.50	2.88	24.33	2.83	23.94	2.86	
					47	25.97	1.92	25.66	1.94	25.32	1.96	24.50	2.03	24.63	1.99	24.30	2.01	
					50	28.19	2.04	27.50	2.07	26.98	2.10	26.74	2.11	26.09	2.15	25.72	2.17	
				18	59	30.87	2.12	30.27	2.15	29.73	2.18	29.47	2.20	28.79	2.23	28.39	2.25	
					-13	30.39	6.77	25.42	5.37	24.38	5.45	18.88	3.96	16.74	3.30	11.93	2.14	
					5	29.52	4.56	28.82	4.61	28.11	4.67	27.00	4.85	26.69	4.77	25.98	4.82	
					17	28.77	3.94	28.27	3.99	27.77	4.03	27.00	4.17	26.79	4.11	26.29	4.15	
					32	28.54	2.93	28.11	2.96	27.67	2.99	27.00	3.10	26.81	3.04	26.38	3.07	
					47	28.62	2.06	28.28	2.08	27.91	2.10	27.00	2.18	27.15	2.14	26.77	2.16	
				9	50	31.07	2.19	30.31	2.22	29.73	2.25	29.47	2.27	28.75	2.30	28.35	2.33	
					59	34.01	2.28	33.36	2.31	32.76	2.34	32.48	2.36	31.73	2.40	31.29	2.42	

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	-13	32.19	7.24	26.93	5.74	25.83	5.82	20.00	4.24	17.73	3.53	12.64	2.29
					5	31.27	4.88	30.53	4.92	29.77	4.99	28.60	5.18	28.28	5.10	27.52	5.15
					17	30.47	4.22	29.95	4.26	29.42	4.30	28.60	4.46	28.37	4.40	27.85	4.44
					32	30.23	3.14	29.77	3.17	29.31	3.19	28.60	3.31	28.40	3.25	27.94	3.28
					47	30.31	2.21	29.96	2.23	29.56	2.24	28.60	2.33	28.76	2.28	28.36	2.31
					50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49
				24	59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59
					-13	30.39	6.77	25.42	5.37	24.38	5.45	18.88	3.96	16.74	3.30	11.93	2.14
					5	29.52	4.56	28.82	4.61	28.11	4.67	27.00	4.85	26.69	4.77	25.98	4.82
					17	28.77	3.94	28.27	3.99	27.77	4.03	27.00	4.17	26.79	4.11	26.29	4.15
					32	28.54	2.93	28.11	2.96	27.67	2.99	27.00	3.10	26.81	3.04	26.38	3.07
					47	28.62	2.06	28.28	2.08	27.91	2.10	27.00	2.18	27.15	2.14	26.77	2.16
				27	50	31.07	2.19	30.31	2.22	29.73	2.25	29.47	2.27	28.75	2.30	28.35	2.33
					59	34.01	2.28	33.36	2.31	32.76	2.34	32.48	2.36	31.73	2.40	31.29	2.42
				30	-13	32.19	7.24	26.93	5.74	25.83	5.82	20.00	4.24	17.73	3.53	12.64	2.29
					5	31.27	4.88	30.53	4.92	29.77	4.99	28.60	5.18	28.28	5.10	27.52	5.15
					17	30.47	4.22	29.95	4.26	29.42	4.30	28.60	4.46	28.37	4.40	27.85	4.44
					32	30.23	3.14	29.77	3.17	29.31	3.19	28.60	3.31	28.40	3.25	27.94	3.28
				36	47	30.31	2.21	29.96	2.23	29.56	2.24	28.60	2.33	28.76	2.28	28.36	2.31
					50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49
				27	59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59
					-13	32.19	7.24	26.93	5.74	25.83	5.82	20.00	4.24	17.73	3.53	12.64	2.29
					5	31.27	4.88	30.53	4.92	29.77	4.99	28.60	5.18	28.28	5.10	27.52	5.15
					17	30.47	4.22	29.95	4.26	29.42	4.30	28.60	4.46	28.37	4.40	27.85	4.44
				30	32	30.23	3.14	29.77	3.17	29.31	3.19	28.60	3.31	28.40	3.25	27.94	3.28
					47	30.31	2.21	29.96	2.23	29.56	2.24	28.60	2.33	28.76	2.28	28.36	2.31
				36	50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49
					59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59
				27	-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29
					5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28
					17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54
					32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37
					47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38
					50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49
				30	59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59
					-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29
					5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28
					17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54
					32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37
					47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38
				30	50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49
					59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	18	36	-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29	
				5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28	
				17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54	
				32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37	
				47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38	
				50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49	
9	12	12	33	59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59	
				-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29	
				5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28	
				17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54	
				32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37	
				47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38	
9	12	18	39	50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49	
				59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59	
				-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29	
				5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28	
				17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54	
				32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37	
12	12	12	36	47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38	
				50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49	
				59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59	
				-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29	
				5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28	
				17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54	
9	9	9	36	32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37	
				47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38	
				50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49	
				59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59	
				-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29	
				5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28	
9	9	9	36	17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54	
				32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37	
				47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38	
				50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49	
				59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59	
				-13	22.94	4.10	21.88	4.13	21.25	4.18	20.00	4.24	19.38	4.29	18.13	4.29	
9	9	12	39	5	30.89	5.01	30.23	5.06	29.36	5.13	28.60	5.18	27.95	5.23	27.41	5.28	
				17	30.46	4.30	29.91	4.35	29.21	4.41	28.60	4.46	28.06	4.50	27.60	4.54	
				32	30.33	3.19	29.81	3.23	29.17	3.27	28.60	3.31	28.10	3.34	27.66	3.37	
				47	30.21	2.25	29.72	2.27	29.13	2.30	28.60	2.33	28.13	2.35	27.72	2.38	
				50	32.91	2.34	32.10	2.38	31.50	2.41	31.21	2.42	30.46	2.46	30.03	2.49	
				59	36.03	2.43	35.34	2.47	34.70	2.50	34.41	2.52	33.61	2.56	33.14	2.59	

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 39.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7				7	-13	9.80	2.72	8.42	2.32	7.32	2.06	5.24	1.53	4.66	1.30	3.32	0.92
					5	8.19	1.73	8.00	1.75	7.80	1.77	7.50	1.87	7.41	1.81	7.22	1.82
					17	7.81	1.48	7.72	1.50	7.58	1.51	7.50	1.61	7.44	1.54	7.30	1.57
					32	7.92	1.10	7.80	1.11	7.68	1.13	7.50	1.19	7.45	1.15	7.33	1.16
					47	8.14	0.81	7.86	0.78	7.75	0.79	7.50	0.84	7.44	0.78	7.01	0.74
					50	8.70	0.84	8.44	0.89	8.19	0.87	8.19	0.87	7.99	0.88	7.87	0.89
					59	9.43	0.88	9.28	0.91	9.09	0.87	9.02	0.90	8.85	0.92	8.73	0.93
9				9	-13	14.25	3.47	12.24	2.96	10.64	2.62	7.62	1.95	6.77	1.66	4.82	1.17
					5	11.91	2.21	11.62	2.23	11.34	2.25	10.90	2.38	10.77	2.30	10.49	2.32
					17	11.36	1.88	11.21	1.91	11.01	1.92	10.90	2.05	10.82	1.97	10.61	1.99
					32	11.51	1.41	11.34	1.42	11.17	1.44	10.90	1.52	10.82	1.46	10.65	1.48
					47	11.83	1.03	11.42	1.00	11.27	1.01	10.90	1.07	10.81	1.00	10.19	0.95
					50	12.64	1.08	12.26	1.13	11.90	1.10	11.90	1.11	11.61	1.13	11.44	1.14
					59	13.71	1.12	13.49	1.16	13.21	1.11	13.11	1.14	12.86	1.17	12.69	1.18
12				12	-13	18.30	4.18	15.72	3.57	13.67	3.16	9.79	2.35	8.70	2.00	6.19	1.41
					5	15.29	2.66	14.93	2.69	14.56	2.71	14.00	2.87	13.83	2.78	13.47	2.80
					17	14.59	2.27	14.40	2.30	14.15	2.32	14.00	2.47	13.89	2.37	13.63	2.40
					32	14.79	1.69	14.57	1.71	14.34	1.73	14.00	1.83	13.90	1.76	13.68	1.78
					47	15.20	1.24	14.67	1.20	14.47	1.21	14.00	1.29	13.88	1.20	13.09	1.14
					50	16.24	1.30	15.75	1.36	15.28	1.33	15.28	1.34	14.91	1.36	14.70	1.37
					59	17.61	1.35	17.32	1.39	16.96	1.34	16.84	1.38	16.52	1.41	16.29	1.43
15				15	-13	23.53	5.77	20.22	4.92	17.57	4.36	12.59	3.24	11.18	2.76	7.96	1.94
					5	19.66	3.67	19.20	3.71	18.73	3.74	18.00	3.96	17.79	3.83	17.32	3.86
					17	18.75	3.13	18.52	3.17	18.19	3.20	18.00	3.41	17.86	3.27	17.52	3.32
					32	19.01	2.34	18.73	2.36	18.44	2.39	18.00	2.53	17.87	2.43	17.58	2.46
					47	19.54	1.71	18.86	1.66	18.61	1.67	18.00	1.78	17.85	1.66	16.83	1.57
					50	20.88	1.79	20.25	1.88	19.65	1.83	19.65	1.84	19.17	1.87	18.90	1.89
					59	22.64	1.86	22.27	1.92	21.81	1.85	21.65	1.90	21.24	1.95	20.95	1.97
18				18	-13	26.14	6.03	22.46	5.14	19.52	4.55	13.99	3.38	12.42	2.89	8.85	2.03
					5	21.85	3.83	21.33	3.88	20.81	3.91	20.00	4.14	19.76	4.00	19.24	4.04
					17	20.84	3.28	20.58	3.32	20.21	3.34	20.00	3.56	19.84	3.42	19.47	3.47
					32	21.13	2.44	20.81	2.46	20.49	2.50	20.00	2.64	19.86	2.54	19.54	2.57
					47	21.71	1.79	20.95	1.74	20.67	1.75	20.00	1.86	19.83	1.74	18.70	1.64
					50	23.20	1.87	22.50	1.96	21.83	1.92	21.83	1.93	21.30	1.96	21.00	1.98
					59	25.16	1.94	24.74	2.01	24.23	1.93	24.06	1.98	23.60	2.04	23.28	2.06
24				24	-13	33.33	7.71	28.64	6.58	24.89	5.83	17.83	4.33	15.84	3.69	11.28	2.60
					5	27.86	4.91	27.19	4.96	26.53	5.00	25.50	5.30	25.20	5.12	24.53	5.17
					17	26.57	4.19	26.23	4.25	25.77	4.28	25.50	4.56	25.30	4.37	24.82	4.44
					32	26.94	3.13	26.53	3.15	26.13	3.20	25.50	3.38	25.32	3.24	24.91	3.29
					47	27.68	2.28	26.71	2.22	26.36	2.24	25.50	2.38	25.28	2.22	23.84	2.10
					50	29.58	2.39	28.68	2.51	27.84	2.45	27.83	2.46	27.16	2.50	26.77	2.53
					59	32.08	2.49	31.55	2.57	30.90	2.47	30.68	2.54	30.09	2.61	29.68	2.63
7	7			14	-13	17.78	4.32	14.87	3.42	14.27	3.47	11.05	2.53	9.79	2.11	6.98	1.37
					5	17.28	2.91	16.86	2.94	16.45	2.98	15.80	3.09	15.62	3.04	15.20	3.07
					17	16.83	2.52	16.55	2.54	16.25	2.57	15.80	2.66	15.67	2.62	15.38	2.65
					32	16.70	1.87	16.45	1.89	16.19	1.91	15.80	1.97	15.69	1.94	15.44	1.96
					47	16.75	1.32	16.55	1.33	16.33	1.34	15.80	1.39	15.89	1.36	15.67	1.38
					50	18.18	1.40	17.73	1.42	17.40	1.44	17.24	1.45	16.83	1.47	16.59	1.48
					59	19.90	1.45	19.52	1.47	19.17	1.49	19.01	1.50	18.57	1.53	18.31	1.54

Capacity Table

JXH30S4B(AJ030BX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9			16	-13	21.27	5.09	17.79	4.04	17.07	4.10	13.22	2.98	11.72	2.49	8.35	1.61
					5	20.67	3.43	20.17	3.47	19.67	3.51	18.90	3.65	18.69	3.59	18.19	3.62
					17	20.14	2.97	19.79	3.00	19.44	3.03	18.90	3.14	18.75	3.10	18.40	3.12
					32	19.98	2.21	19.68	2.23	19.37	2.25	18.90	2.33	18.77	2.29	18.47	2.31
					47	20.03	1.55	19.80	1.57	19.53	1.58	18.90	1.64	19.00	1.61	18.74	1.63
					50	21.75	1.65	21.21	1.67	20.81	1.70	20.63	1.71	20.13	1.73	19.84	1.75
					59	23.81	1.71	23.35	1.74	22.93	1.76	22.74	1.77	22.21	1.80	21.90	1.82
7	12			19	-13	24.09	5.78	20.15	4.58	19.33	4.65	14.97	3.38	13.27	2.82	9.46	1.83
					5	23.40	3.89	22.84	3.93	22.28	3.99	21.40	4.14	21.16	4.07	20.59	4.11
					17	22.80	3.37	22.41	3.40	22.01	3.43	21.40	3.56	21.23	3.51	20.84	3.54
					32	22.62	2.50	22.28	2.53	21.93	2.55	21.40	2.64	21.25	2.60	20.91	2.62
					47	22.68	1.76	22.41	1.78	22.12	1.79	21.40	1.86	21.52	1.82	21.22	1.84
					50	24.62	1.87	24.02	1.90	23.57	1.92	23.36	1.93	22.79	1.97	22.47	1.99
					59	26.96	1.94	26.44	1.97	25.97	2.00	25.74	2.01	25.15	2.05	24.80	2.07
7	15			22	-13	27.57	6.49	23.07	5.14	22.13	5.22	17.13	3.80	15.19	3.17	10.83	2.05
					5	26.79	4.37	26.15	4.42	25.50	4.48	24.50	4.65	24.22	4.57	23.58	4.62
					17	26.10	3.78	25.66	3.82	25.20	3.86	24.50	4.00	24.31	3.94	23.85	3.98
					32	25.90	2.81	25.51	2.84	25.11	2.87	24.50	2.97	24.33	2.92	23.94	2.94
					47	25.97	1.98	25.66	2.00	25.32	2.01	24.50	2.09	24.63	2.05	24.30	2.07
					50	28.19	2.10	27.50	2.13	26.98	2.16	26.74	2.17	26.09	2.21	25.72	2.23
					59	30.87	2.18	30.27	2.22	29.73	2.25	29.47	2.26	28.79	2.30	28.39	2.32
7	18			25	-13	31.06	6.49	25.98	5.14	24.92	5.22	19.30	3.80	17.11	3.17	12.20	2.05
					5	30.18	4.37	29.46	4.42	28.73	4.48	27.60	4.65	27.29	4.57	26.56	4.62
					17	29.41	3.78	28.90	3.82	28.39	3.86	27.60	4.00	27.38	3.94	26.87	3.98
					32	29.17	2.81	28.73	2.84	28.29	2.87	27.60	2.97	27.41	2.92	26.97	2.94
					47	29.25	1.98	28.91	2.00	28.53	2.01	27.60	2.09	27.75	2.05	27.37	2.07
					50	31.76	2.10	30.98	2.13	30.39	2.16	30.12	2.17	29.39	2.21	28.98	2.23
					59	34.77	2.18	34.10	2.22	33.49	2.25	33.20	2.26	32.43	2.30	31.99	2.32
7	24			31	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	9			18	-13	24.76	5.90	20.71	4.68	19.87	4.75	15.38	3.45	13.64	2.88	9.72	1.87
					5	24.06	3.98	23.48	4.02	22.90	4.07	22.00	4.23	21.75	4.16	21.17	4.20
					17	23.44	3.44	23.04	3.47	22.63	3.51	22.00	3.64	21.83	3.59	21.42	3.62
					32	23.25	2.56	22.90	2.58	22.55	2.60	22.00	2.70	21.85	2.65	21.49	2.68
					47	23.32	1.80	23.04	1.81	22.74	1.83	22.00	1.90	22.12	1.86	21.82	1.88
					50	25.31	1.91	24.69	1.94	24.23	1.96	24.01	1.98	23.43	2.01	23.10	2.03
					59	27.72	1.99	27.18	2.02	26.69	2.04	26.47	2.06	25.85	2.09	25.50	2.11
9	12			21	-13	27.57	6.49	23.07	5.14	22.13	5.22	17.13	3.80	15.19	3.17	10.83	2.05
					5	26.79	4.37	26.15	4.42	25.50	4.48	24.50	4.65	24.22	4.57	23.58	4.62
					17	26.10	3.78	25.66	3.82	25.20	3.86	24.50	4.00	24.31	3.94	23.85	3.98
					32	25.90	2.81	25.51	2.84	25.11	2.87	24.50	2.97	24.33	2.92	23.94	2.94
					47	25.97	1.98	25.66	2.00	25.32	2.01	24.50	2.09	24.63	2.05	24.30	2.07
					50	28.19	2.10	27.50	2.13	26.98	2.16	26.74	2.17	26.09	2.21	25.72	2.23
					59	30.87	2.18	30.27	2.22	29.73	2.25	29.47	2.26	28.79	2.30	28.39	2.32

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15			24	-13	30.39	6.49	25.42	5.14	24.38	5.22	18.88	3.80	16.74	3.17	11.93	2.05
					5	29.52	4.37	28.82	4.42	28.11	4.48	27.00	4.65	26.69	4.57	25.98	4.62
					17	28.77	3.78	28.27	3.82	27.77	3.86	27.00	4.00	26.79	3.94	26.29	3.98
					32	28.54	2.81	28.11	2.84	27.67	2.87	27.00	2.97	26.81	2.92	26.38	2.94
					47	28.62	1.98	28.28	2.00	27.91	2.01	27.00	2.09	27.15	2.05	26.77	2.07
					50	31.07	2.10	30.31	2.13	29.73	2.16	29.47	2.17	28.75	2.21	28.35	2.23
					59	34.01	2.18	33.36	2.22	32.76	2.25	32.48	2.26	31.73	2.30	31.29	2.32
9	18			27	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	24			33	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
12	12			24	-13	30.39	6.49	25.42	5.14	24.38	5.22	18.88	3.80	16.74	3.17	11.93	2.05
					5	29.52	4.37	28.82	4.42	28.11	4.48	27.00	4.65	26.69	4.57	25.98	4.62
					17	28.77	3.78	28.27	3.82	27.77	3.86	27.00	4.00	26.79	3.94	26.29	3.98
					32	28.54	2.81	28.11	2.84	27.67	2.87	27.00	2.97	26.81	2.92	26.38	2.94
					47	28.62	1.98	28.28	2.00	27.91	2.01	27.00	2.09	27.15	2.05	26.77	2.07
					50	31.07	2.10	30.31	2.13	29.73	2.16	29.47	2.17	28.75	2.21	28.35	2.23
					59	34.01	2.18	33.36	2.22	32.76	2.25	32.48	2.26	31.73	2.30	31.29	2.32
12	15			27	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
12	18			30	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
12	24			36	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
15	18			33	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
15	24			39	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
18	18			36	-13	32.19	6.49	26.93	5.14	25.83	5.22	20.00	3.80	17.73	3.17	12.64	2.05
					5	31.27	4.37	30.53	4.42	29.77	4.48	28.60	4.65	28.28	4.57	27.52	4.62
					17	30.47	3.78	29.95	3.82	29.42	3.86	28.60	4.00	28.37	3.94	27.85	3.98
					32	30.23	2.81	29.77	2.84	29.31	2.87	28.60	2.97	28.40	2.92	27.94	2.94
					47	30.31	1.98	29.96	2.00	29.56	2.01	28.60	2.09	28.76	2.05	28.36	2.07
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	7		21	-13	18.13	3.46	17.29	3.49	16.79	3.54	15.80	3.58	15.31	3.63	14.32	3.63
					5	24.41	4.23	23.89	4.28	23.20	4.33	22.60	4.38	22.09	4.43	21.66	4.46
					17	24.07	3.64	23.63	3.68	23.09	3.73	22.60	3.77	22.18	3.81	21.81	3.84
					32	23.97	2.70	23.55	2.73	23.05	2.76	22.60	2.80	22.20	2.83	21.86	2.85
					47	23.87	1.90	23.48	1.92	23.02	1.95	22.60	1.97	22.23	1.99	21.90	2.01
					50	26.00	1.98	25.37	2.01	24.89	2.04	24.67	2.05	24.07	2.08	23.73	2.10
					59	28.47	2.06	27.92	2.09	27.42	2.12	27.19	2.13	26.56	2.17	26.19	2.19
7	7	9		23	-13	20.69	3.67	19.73	3.70	19.17	3.75	18.04	3.80	17.48	3.85	16.35	3.85
					5	27.87	4.49	27.27	4.54	26.48	4.60	25.80	4.65	25.22	4.69	24.73	4.73
					17	27.48	3.86	26.98	3.90	26.35	3.95	25.80	4.00	25.32	4.04	24.90	4.08
					32	27.36	2.86	26.89	2.89	26.31	2.93	25.80	2.97	25.35	3.00	24.96	3.03
					47	27.25	2.01	26.81	2.04	26.28	2.07	25.80	2.09	25.38	2.11	25.00	2.13
					50	29.69	2.10	28.96	2.13	28.41	2.16	28.16	2.17	27.48	2.21	27.09	2.23
					59	32.50	2.18	31.88	2.22	31.30	2.25	31.04	2.26	30.32	2.30	29.90	2.32
7	7	12		26	-13	22.70	3.67	21.65	3.70	21.03	3.75	19.79	3.80	19.17	3.85	17.93	3.85
					5	30.57	4.49	29.91	4.54	29.05	4.60	28.30	4.65	27.66	4.69	27.13	4.73
					17	30.14	3.86	29.59	3.90	28.91	3.95	28.30	4.00	27.77	4.04	27.32	4.08
					32	30.01	2.86	29.50	2.89	28.86	2.93	28.30	2.97	27.80	3.00	27.37	3.03
					47	29.89	2.01	29.41	2.04	28.82	2.07	28.30	2.09	27.83	2.11	27.43	2.13
					50	32.56	2.10	31.76	2.13	31.17	2.16	30.89	2.17	30.14	2.21	29.71	2.23
					59	35.65	2.18	34.97	2.22	34.34	2.25	34.04	2.26	33.25	2.30	32.80	2.32

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	15		29	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	18		32	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	24		38	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	9		25	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	12		28	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	15		31	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	18		34	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	24	40	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85	
				5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73	
				17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08	
				32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03	
				47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13	
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
7	12	12	31	59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	
				-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85	
				5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73	
				17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08	
				32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03	
				47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13	
7	12	15	34	50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	
				-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85	
				5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73	
				17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08	
				32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03	
7	12	18	37	47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13	
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	
				-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85	
				5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73	
				17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08	
9	9	9	27	32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03	
				47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13	
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	
				-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85	
				5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73	
9	9	12	30	17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08	
				32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03	
				47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13	
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	
				-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85	
9	9	15	33	5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73	
				17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08	
				32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03	
				47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13	
				50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23	
				59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32	

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	18		36	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	12	12		33	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	12	15		36	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	12	18		39	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
12	12	12		36	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
12	12	15		39	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	7	7	28	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32

Capacity Table

JXH30S4B(AJ030BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	9	30	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	7	12	33	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	7	15	36	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	7	18	39	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	9	9	32	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	9	12	35	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	7	9	15	38	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32

Capacity Table

JXH30S4B(AJ030BX54CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	12	38	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	9	9	34	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	9	12	37	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	9	15	40	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
7	9	12	12	40	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	9	9	9	36	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32
9	9	9	12	39	-13	22.94	3.67	21.88	3.70	21.25	3.75	20.00	3.80	19.38	3.85	18.13	3.85
					5	30.89	4.49	30.23	4.54	29.36	4.60	28.60	4.65	27.95	4.69	27.41	4.73
					17	30.46	3.86	29.91	3.90	29.21	3.95	28.60	4.00	28.06	4.04	27.60	4.08
					32	30.33	2.86	29.81	2.89	29.17	2.93	28.60	2.97	28.10	3.00	27.66	3.03
					47	30.21	2.01	29.72	2.04	29.13	2.07	28.60	2.09	28.13	2.11	27.72	2.13
					50	32.91	2.10	32.10	2.13	31.50	2.16	31.21	2.17	30.46	2.21	30.03	2.23
					59	36.03	2.18	35.34	2.22	34.70	2.25	34.41	2.26	33.61	2.30	33.14	2.32

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 39.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9				9	68	7.20	0.57	9.60	0.61	10.03	0.65	10.24	0.67	10.89	0.70	11.32	0.71
					70	7.20	0.58	9.52	0.62	9.95	0.66	10.16	0.67	10.80	0.71	11.23	0.72
					73	7.20	0.61	9.36	0.65	9.78	0.68	9.99	0.69	10.63	0.72	11.06	0.73
					77	7.20	0.63	9.20	0.67	9.61	0.70	9.82	0.71	10.46	0.74	10.89	0.75
					81	7.20	0.65	9.03	0.69	9.45	0.72	9.66	0.73	10.29	0.76	10.71	0.76
					84	7.20	0.68	8.87	0.71	9.28	0.74	9.49	0.75	10.12	0.77	10.54	0.78
					88	7.20	0.70	8.71	0.73	9.12	0.76	9.33	0.77	9.95	0.79	10.37	0.79
					91	7.20	0.72	8.55	0.76	8.96	0.78	9.16	0.79	9.78	0.81	10.20	0.81
					95	7.20	0.75	8.39	0.78	8.79	0.80	9.00	0.80	9.61	0.83	10.02	0.83
					99	7.20	0.77	8.23	0.80	8.63	0.82	8.83	0.83	9.44	0.84	9.85	0.84
					102	7.20	0.80	8.07	0.83	8.47	0.85	8.67	0.85	9.28	0.86	9.68	0.86
					108	7.11	0.84	7.83	0.86	8.23	0.88	8.42	0.88	9.03	0.89	9.43	0.88
					111	6.75	0.86	7.67	0.89	8.07	0.90	8.26	0.91	8.86	0.91	9.26	0.90
115	6.57	0.89	7.52	0.91	7.90	0.93	8.10	0.93	8.69	0.93	9.09	0.92					
12				12	68	9.60	0.78	12.81	0.84	13.37	0.89	13.66	0.91	14.52	0.95	15.09	0.97
					70	9.60	0.79	12.70	0.85	13.26	0.90	13.54	0.92	14.40	0.96	14.98	0.98
					73	9.60	0.82	12.48	0.88	13.04	0.93	13.32	0.94	14.17	0.99	14.75	1.00
					77	9.60	0.86	12.26	0.91	12.82	0.95	13.10	0.97	13.95	1.01	14.51	1.02
					81	9.60	0.89	12.04	0.94	12.60	0.98	12.88	1.00	13.72	1.03	14.28	1.04
					84	9.60	0.92	11.83	0.97	12.38	1.01	12.66	1.02	13.49	1.05	14.05	1.06
					88	9.60	0.95	11.61	1.00	12.16	1.04	12.43	1.05	13.27	1.08	13.82	1.08
					91	9.60	0.99	11.40	1.03	11.94	1.06	12.21	1.08	13.04	1.10	13.59	1.10
					95	9.60	1.02	11.19	1.06	11.72	1.09	12.00	1.09	12.81	1.12	13.37	1.12
					99	9.60	1.05	10.97	1.09	11.51	1.12	11.78	1.13	12.59	1.15	13.14	1.15
					102	9.60	1.09	10.76	1.13	11.29	1.15	11.56	1.16	12.37	1.17	12.91	1.17
					108	9.48	1.14	10.44	1.17	10.97	1.20	11.23	1.21	12.03	1.21	12.57	1.21
					111	9.00	1.18	10.23	1.21	10.75	1.23	11.02	1.24	11.81	1.24	12.35	1.23
115	8.76	1.21	10.02	1.24	10.54	1.26	10.80	1.27	11.59	1.27	12.12	1.25					
15				15	68	12.00	1.01	16.01	1.08	16.71	1.15	17.07	1.17	17.43	1.20	18.15	1.23
					70	12.00	1.03	15.87	1.10	16.58	1.16	16.93	1.19	17.29	1.21	18.00	1.25
					73	12.00	1.07	15.60	1.14	16.30	1.20	16.65	1.22	17.01	1.24	17.72	1.27
					77	12.00	1.11	15.33	1.18	16.02	1.23	16.37	1.25	16.72	1.27	17.43	1.30
					81	12.00	1.15	15.06	1.21	15.75	1.27	16.10	1.29	16.45	1.31	17.15	1.33
					84	12.00	1.19	14.79	1.25	15.47	1.30	15.82	1.32	16.17	1.34	16.86	1.36
					88	12.00	1.23	14.52	1.29	15.20	1.34	15.54	1.36	15.89	1.37	16.58	1.39
					91	12.00	1.28	14.25	1.33	14.93	1.38	15.27	1.39	15.61	1.41	16.30	1.42
					95	12.00	1.32	13.98	1.37	14.66	1.41	15.00	1.41	15.33	1.44	16.02	1.45
					99	12.00	1.36	13.71	1.41	14.38	1.45	14.72	1.47	15.06	1.48	15.74	1.49
					102	12.00	1.41	13.45	1.46	14.11	1.49	14.45	1.50	14.78	1.51	15.46	1.52
					108	11.85	1.48	13.05	1.52	13.71	1.55	14.04	1.56	14.37	1.57	15.04	1.57
					111	11.25	1.52	12.79	1.56	13.44	1.59	13.77	1.60	14.10	1.60	14.76	1.60
115	10.95	1.57	12.53	1.61	13.17	1.63	13.50	1.64	13.83	1.64	14.49	1.64					

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18				18	68	14.40	1.06	19.21	1.14	20.06	1.20	20.48	1.23	21.77	1.29	22.64	1.32
					70	14.40	1.08	19.04	1.16	19.89	1.22	20.32	1.25	21.60	1.31	22.47	1.33
					73	14.40	1.12	18.72	1.20	19.56	1.26	19.98	1.28	21.26	1.34	22.12	1.36
					77	14.40	1.16	18.39	1.23	19.23	1.29	19.65	1.32	20.92	1.37	21.77	1.38
					81	14.40	1.21	18.07	1.27	18.90	1.33	19.31	1.35	20.58	1.40	21.43	1.41
					84	14.40	1.25	17.74	1.32	18.57	1.37	18.98	1.39	20.24	1.43	21.08	1.44
					88	14.40	1.29	17.42	1.36	18.24	1.41	18.65	1.42	19.90	1.46	20.74	1.47
					91	14.40	1.34	17.10	1.40	17.91	1.44	18.32	1.46	19.56	1.49	20.39	1.50
					95	14.40	1.38	16.78	1.44	17.59	1.48	18.00	1.48	19.22	1.53	20.05	1.53
					99	14.40	1.43	16.46	1.48	17.26	1.52	17.67	1.54	18.89	1.56	19.71	1.56
					102	14.40	1.48	16.14	1.53	16.94	1.56	17.34	1.58	18.55	1.59	19.37	1.59
					108	14.22	1.55	15.66	1.60	16.45	1.63	16.85	1.64	18.05	1.65	18.86	1.64
					111	13.50	1.60	15.35	1.64	16.13	1.67	16.53	1.68	17.72	1.68	18.52	1.67
					115	13.14	1.65	15.03	1.69	15.81	1.71	16.20	1.72	17.39	1.72	18.18	1.70
24				24	68	19.20	1.46	25.61	1.57	26.74	1.67	27.31	1.71	27.88	1.74	29.03	1.79
					70	19.20	1.49	25.39	1.60	26.52	1.69	27.09	1.73	27.66	1.76	28.80	1.81
					73	19.20	1.55	24.96	1.66	26.08	1.74	26.64	1.78	27.21	1.81	28.35	1.85
					77	19.20	1.61	24.52	1.71	25.64	1.79	26.20	1.82	26.76	1.85	27.89	1.89
					81	19.20	1.67	24.09	1.77	25.20	1.84	25.75	1.87	26.31	1.90	27.44	1.94
					84	19.20	1.73	23.66	1.82	24.76	1.89	25.31	1.92	25.87	1.95	26.98	1.98
					88	19.20	1.79	23.23	1.88	24.32	1.95	24.87	1.97	25.42	2.00	26.53	2.02
					91	19.20	1.85	22.80	1.94	23.88	2.00	24.43	2.03	24.98	2.04	26.08	2.07
					95	19.20	1.92	22.37	2.00	23.45	2.06	24.00	2.05	24.54	2.09	25.63	2.11
					99	19.20	1.98	21.94	2.06	23.02	2.11	23.55	2.13	24.09	2.15	25.18	2.16
					102	19.20	2.05	21.52	2.12	22.58	2.17	23.12	2.18	23.65	2.20	24.73	2.21
					108	18.96	2.15	20.88	2.21	21.94	2.25	22.47	2.27	23.00	2.28	24.07	2.28
					111	18.00	2.21	20.46	2.27	21.51	2.31	22.03	2.32	22.56	2.33	23.62	2.33
					115	17.52	2.28	20.04	2.34	21.08	2.37	21.60	2.38	22.13	2.39	23.18	2.38
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	17.85	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
					111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56
					115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
					111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80
9	15			24	68	21.21	1.36	26.18	1.39	26.96	1.42	27.40	1.43	27.88	1.45	28.96	1.47
					70	21.21	1.38	25.85	1.41	26.65	1.44	27.10	1.45	27.60	1.46	28.70	1.49
					73	21.21	1.41	25.22	1.44	26.06	1.47	26.53	1.49	27.05	1.50	28.19	1.53
					77	21.21	1.45	24.63	1.48	25.50	1.51	26.00	1.52	26.53	1.54	27.72	1.56
					81	21.21	1.49	24.06	1.52	24.98	1.54	25.50	1.56	26.05	1.57	27.28	1.60
					84	21.21	1.52	23.53	1.55	24.49	1.58	25.03	1.60	25.60	1.61	26.87	1.64
					88	21.21	1.56	23.03	1.59	24.04	1.62	24.59	1.63	25.19	1.65	26.50	1.67
					91	21.21	1.60	22.57	1.63	23.61	1.66	24.19	1.67	24.81	1.69	26.16	1.71
					95	21.21	1.64	22.14	1.67	23.22	1.70	24.00	1.71	24.46	1.73	25.85	1.75
					99	21.21	1.69	21.74	1.71	22.87	1.74	23.49	1.76	24.15	1.77	25.58	1.79
					102	21.21	1.73	21.38	1.76	22.55	1.78	23.19	1.80	23.87	1.81	25.34	1.84
					108	21.21	1.79	20.90	1.82	22.13	1.85	22.80	1.86	23.51	1.88	25.04	1.90
					111	21.21	1.84	20.62	1.87	21.89	1.89	22.58	1.91	23.31	1.92	24.89	1.95
					115	21.21	1.88	20.37	1.91	21.68	1.94	22.39	1.95	23.15	1.97	24.76	1.99
9	18			27	68	23.07	1.80	28.47	1.84	29.31	1.88	29.80	1.90	31.50	1.95	32.84	1.98
					70	23.07	1.82	28.12	1.86	28.98	1.90	29.47	1.92	31.21	1.97	32.57	2.01
					73	23.07	1.87	27.43	1.91	28.34	1.95	28.86	1.96	30.66	2.02	32.06	2.05
					77	23.07	1.92	26.78	1.96	27.73	1.99	28.27	2.01	30.14	2.06	31.60	2.10
					81	23.07	1.96	26.17	2.00	27.17	2.04	27.73	2.06	29.66	2.11	31.16	2.15
					84	23.07	2.01	25.59	2.05	26.63	2.09	27.22	2.11	29.22	2.16	30.77	2.20
					88	23.07	2.07	25.05	2.10	26.14	2.14	26.75	2.16	28.82	2.21	30.41	2.25
					91	23.07	2.12	24.55	2.16	25.68	2.19	26.31	2.21	28.45	2.26	30.08	2.30
					95	23.07	2.17	24.08	2.21	25.26	2.25	26.10	2.26	28.11	2.32	29.79	2.35
					99	23.07	2.23	23.65	2.27	24.87	2.30	25.54	2.32	27.82	2.37	29.54	2.40
					102	23.07	2.28	23.25	2.32	24.52	2.36	25.22	2.38	27.56	2.43	29.33	2.46
					108	23.07	2.37	22.73	2.41	24.06	2.44	24.79	2.46	27.23	2.51	29.07	2.54
					111	23.07	2.43	22.42	2.47	23.80	2.50	24.56	2.52	27.07	2.57	28.95	2.60
					115	23.07	2.49	22.15	2.53	23.58	2.56	24.35	2.58	26.93	2.63	28.86	2.66

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	24			33	68	27.40	2.21	33.82	2.26	34.82	2.31	35.39	2.33	36.01	2.35	37.41	2.40
					70	27.40	2.24	33.40	2.29	34.42	2.34	35.01	2.36	35.64	2.38	37.07	2.42
					73	27.40	2.30	32.58	2.35	33.66	2.39	34.27	2.42	34.94	2.44	36.41	2.48
					77	27.40	2.36	31.81	2.40	32.94	2.45	33.58	2.47	34.27	2.50	35.80	2.54
					81	27.40	2.42	31.08	2.46	32.27	2.51	32.93	2.53	33.65	2.56	35.23	2.60
					84	27.40	2.48	30.40	2.53	31.64	2.57	32.33	2.59	33.07	2.62	34.71	2.66
					88	27.40	2.54	29.75	2.59	31.05	2.63	31.77	2.66	32.54	2.68	34.23	2.72
					91	27.40	2.61	29.15	2.65	30.50	2.70	31.25	2.72	32.05	2.74	33.79	2.79
					95	27.40	2.67	28.60	2.72	30.00	2.76	31.00	2.78	31.60	2.81	33.39	2.85
					99	27.40	2.74	28.09	2.79	29.54	2.83	30.34	2.85	31.19	2.88	33.04	2.92
					102	27.40	2.81	27.62	2.86	29.12	2.90	29.95	2.92	30.83	2.94	32.73	2.99
					108	27.40	2.91	26.99	2.96	28.58	3.01	29.45	3.03	30.36	3.05	32.35	3.09
					111	27.40	2.99	26.63	3.03	28.27	3.08	29.17	3.10	30.11	3.12	32.15	3.16
					115	27.40	3.06	26.31	3.11	28.01	3.15	28.93	3.17	29.90	3.19	31.99	3.24
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
					111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04
					115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09
12	15			27	68	23.86	1.73	29.45	1.77	30.32	1.80	30.82	1.82	31.37	1.84	32.58	1.87
					70	23.86	1.75	29.09	1.79	29.98	1.82	30.49	1.84	31.05	1.86	32.28	1.89
					73	23.86	1.79	28.38	1.83	29.32	1.87	29.85	1.89	30.43	1.90	31.71	1.94
					77	23.86	1.84	27.70	1.88	28.69	1.91	29.25	1.93	29.85	1.95	31.18	1.98
					81	23.86	1.89	27.07	1.92	28.10	1.96	28.68	1.98	29.31	1.99	30.69	2.03
					84	23.86	1.93	26.47	1.97	27.55	2.01	28.16	2.03	28.81	2.04	30.23	2.08
					88	23.86	1.98	25.91	2.02	27.04	2.06	27.67	2.07	28.34	2.09	29.81	2.12
					91	23.86	2.03	25.39	2.07	26.57	2.11	27.22	2.12	27.91	2.14	29.43	2.17
					95	23.86	2.09	24.91	2.12	26.13	2.16	27.00	2.17	27.52	2.19	29.08	2.23
					99	23.86	2.14	24.46	2.18	25.73	2.21	26.43	2.23	27.17	2.24	28.78	2.28
					102	23.86	2.19	24.05	2.23	25.37	2.26	26.09	2.28	26.85	2.30	28.51	2.33
					108	23.86	2.28	23.51	2.31	24.89	2.35	25.65	2.36	26.45	2.38	28.17	2.41
					111	23.86	2.33	23.19	2.37	24.62	2.40	25.40	2.42	26.22	2.44	28.00	2.47
					115	23.86	2.39	22.92	2.43	24.39	2.46	25.19	2.48	26.04	2.49	27.86	2.53

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F, DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	18			30	68	25.72	2.04	31.75	2.08	32.68	2.13	33.22	2.15	35.12	2.21	36.61	2.25
					70	25.72	2.06	31.35	2.11	32.31	2.15	32.86	2.17	34.79	2.23	36.31	2.27
					73	25.72	2.12	30.58	2.16	31.60	2.20	32.17	2.22	34.18	2.28	35.75	2.32
					77	25.72	2.17	29.86	2.21	30.92	2.26	31.52	2.28	33.61	2.34	35.23	2.38
					81	25.72	2.23	29.18	2.27	30.29	2.31	30.92	2.33	33.07	2.39	34.74	2.43
					84	25.72	2.28	28.53	2.33	29.70	2.37	30.35	2.39	32.58	2.45	34.30	2.49
					88	25.72	2.34	27.93	2.38	29.14	2.43	29.82	2.45	32.13	2.51	33.90	2.54
					91	25.72	2.40	27.37	2.44	28.63	2.49	29.33	2.51	31.72	2.56	33.54	2.60
					95	25.72	2.46	26.85	2.50	28.16	2.55	29.10	2.56	31.35	2.62	33.22	2.66
					99	25.72	2.52	26.36	2.57	27.73	2.61	28.48	2.63	31.02	2.69	32.94	2.72
					102	25.72	2.59	25.92	2.63	27.34	2.67	28.11	2.69	30.72	2.75	32.70	2.79
					108	25.72	2.68	25.34	2.73	26.83	2.77	27.64	2.79	30.37	2.85	32.41	2.88
					111	25.72	2.75	25.00	2.79	26.54	2.83	27.38	2.85	30.18	2.91	32.27	2.95
					115	25.72	2.82	24.70	2.86	26.29	2.90	27.15	2.92	30.03	2.98	32.18	3.02
12	24			36	68	30.05	2.34	37.09	2.39	38.19	2.44	38.82	2.47	39.50	2.49	41.03	2.53
					70	30.05	2.37	36.63	2.42	37.75	2.47	38.40	2.49	39.09	2.52	40.65	2.56
					73	30.05	2.43	35.73	2.48	36.92	2.53	37.59	2.55	38.32	2.58	39.94	2.62
					77	30.05	2.49	34.89	2.54	36.13	2.59	36.83	2.62	37.59	2.64	39.27	2.69
					81	30.05	2.56	34.09	2.61	35.39	2.66	36.12	2.68	36.91	2.70	38.64	2.75
					84	30.05	2.62	33.34	2.67	34.70	2.72	35.46	2.74	36.27	2.77	38.07	2.81
					88	30.05	2.69	32.63	2.74	34.05	2.79	34.84	2.81	35.69	2.83	37.54	2.88
					91	30.05	2.76	31.98	2.81	33.45	2.85	34.27	2.88	35.15	2.90	37.06	2.95
					95	30.05	2.83	31.37	2.88	32.90	2.92	34.00	2.94	34.65	2.97	36.62	3.01
					99	30.05	2.90	30.80	2.95	32.40	2.99	33.28	3.02	34.21	3.04	36.24	3.09
					102	30.05	2.97	30.29	3.02	31.94	3.07	32.85	3.09	33.81	3.11	35.90	3.16
					108	30.05	3.08	29.60	3.13	31.34	3.18	32.30	3.20	33.30	3.22	35.48	3.27
					111	30.05	3.16	29.21	3.21	31.01	3.26	31.99	3.28	33.02	3.30	35.26	3.34
					115	30.05	3.24	28.86	3.29	30.72	3.33	31.73	3.36	32.79	3.38	35.08	3.42
15	18			33	68	28.37	2.22	35.02	2.27	36.05	2.32	36.65	2.34	37.29	2.36	38.74	2.41
					70	28.37	2.25	34.58	2.30	35.64	2.34	36.25	2.37	36.91	2.39	38.38	2.43
					73	28.37	2.31	33.74	2.35	34.85	2.40	35.49	2.42	36.18	2.45	37.70	2.49
					77	28.37	2.37	32.94	2.41	34.11	2.46	34.77	2.48	35.49	2.50	37.07	2.55
					81	28.37	2.43	32.18	2.47	33.41	2.52	34.10	2.54	34.85	2.56	36.48	2.61
					84	28.37	2.49	31.47	2.54	32.76	2.58	33.48	2.60	34.25	2.63	35.94	2.67
					88	28.37	2.55	30.81	2.60	32.15	2.64	32.89	2.67	33.69	2.69	35.44	2.73
					91	28.37	2.62	30.19	2.66	31.58	2.71	32.36	2.73	33.18	2.75	34.99	2.80
					95	28.37	2.68	29.61	2.73	31.06	2.77	32.10	2.79	32.72	2.82	34.58	2.86
					99	28.37	2.75	29.08	2.80	30.59	2.84	31.42	2.86	32.30	2.89	34.21	2.93
					102	28.37	2.82	28.60	2.87	30.16	2.91	31.01	2.93	31.92	2.95	33.89	3.00
					108	28.37	2.93	27.95	2.97	29.59	3.02	30.49	3.04	31.44	3.06	33.50	3.10
					111	28.37	3.00	27.57	3.04	29.27	3.09	30.20	3.11	31.18	3.13	33.29	3.17
					115	28.37	3.07	27.24	3.12	29.00	3.16	29.95	3.19	30.96	3.21	33.12	3.25

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18	18			36	68	30.22	2.47	37.31	2.52	38.41	2.57	39.04	2.60	41.27	2.67	43.03	2.72
					70	30.22	2.50	36.84	2.55	37.97	2.61	38.62	2.63	40.89	2.70	42.68	2.75
					73	30.22	2.56	35.94	2.62	37.13	2.67	37.81	2.69	40.17	2.77	42.02	2.81
					77	30.22	2.63	35.09	2.68	36.34	2.73	37.05	2.76	39.50	2.83	41.40	2.88
					81	30.22	2.70	34.29	2.75	35.60	2.80	36.33	2.82	38.87	2.90	40.83	2.94
					84	30.22	2.76	33.53	2.82	34.90	2.87	35.67	2.89	38.29	2.97	40.31	3.01
					88	30.22	2.83	32.82	2.89	34.25	2.94	35.05	2.96	37.76	3.03	39.84	3.08
					91	30.22	2.91	32.16	2.96	33.65	3.01	34.47	3.03	37.28	3.11	39.42	3.15
					95	30.22	2.98	31.55	3.03	33.10	3.08	34.20	3.10	36.84	3.18	39.04	3.22
					99	30.22	3.06	30.98	3.11	32.59	3.16	33.47	3.18	36.45	3.25	38.71	3.30
					102	30.22	3.13	30.47	3.18	32.13	3.23	33.04	3.26	36.11	3.33	38.43	3.37
					108	30.22	3.25	29.78	3.30	31.53	3.35	32.49	3.38	35.69	3.45	38.09	3.49
					111	30.22	3.33	29.38	3.38	31.19	3.43	32.18	3.46	35.46	3.53	37.93	3.57
					115	30.22	3.41	29.03	3.47	30.90	3.52	31.91	3.54	35.29	3.61	37.81	3.65
9	9	9		27	68	23.86	2.01	29.45	2.06	30.32	2.10	30.82	2.12	32.58	2.18	33.97	2.22
					70	23.86	2.04	29.09	2.08	29.98	2.13	30.49	2.15	32.28	2.21	33.69	2.24
					73	23.86	2.09	28.38	2.14	29.32	2.18	29.85	2.20	31.71	2.26	33.17	2.30
					77	23.86	2.14	27.70	2.19	28.69	2.23	29.25	2.25	31.18	2.31	32.68	2.35
					81	23.86	2.20	27.07	2.24	28.10	2.29	28.68	2.31	30.69	2.36	32.24	2.40
					84	23.86	2.26	26.47	2.30	27.55	2.34	28.16	2.36	30.23	2.42	31.83	2.46
					88	23.86	2.31	25.91	2.36	27.04	2.40	27.67	2.42	29.81	2.48	31.45	2.51
					91	23.86	2.37	25.39	2.41	26.57	2.46	27.22	2.48	29.43	2.53	31.12	2.57
					95	23.86	2.43	24.91	2.47	26.13	2.52	27.00	2.53	29.08	2.59	30.82	2.63
					99	23.86	2.49	24.46	2.54	25.73	2.58	26.43	2.60	28.78	2.65	30.56	2.69
					102	23.86	2.56	24.05	2.60	25.37	2.64	26.09	2.66	28.51	2.72	30.34	2.75
					108	23.86	2.65	23.51	2.70	24.89	2.74	25.65	2.76	28.17	2.81	30.07	2.85
					111	23.86	2.72	23.19	2.76	24.62	2.80	25.40	2.82	28.00	2.88	29.94	2.91
					115	23.86	2.79	22.92	2.83	24.39	2.87	25.19	2.89	27.86	2.94	29.85	2.98
9	9	12		30	68	26.51	2.21	32.73	2.25	33.69	2.30	34.25	2.32	36.20	2.39	37.74	2.43
					70	26.51	2.23	32.32	2.28	33.31	2.33	33.88	2.35	35.87	2.42	37.44	2.46
					73	26.51	2.29	31.53	2.34	32.57	2.38	33.17	2.41	35.24	2.47	36.86	2.51
					77	26.51	2.35	30.78	2.40	31.88	2.44	32.50	2.46	34.65	2.53	36.32	2.57
					81	26.51	2.41	30.08	2.46	31.23	2.50	31.87	2.52	34.10	2.59	35.82	2.63
					84	26.51	2.47	29.42	2.52	30.61	2.56	31.29	2.59	33.59	2.65	35.36	2.69
					88	26.51	2.53	28.79	2.58	30.05	2.63	30.74	2.65	33.12	2.71	34.95	2.75
					91	26.51	2.60	28.21	2.64	29.52	2.69	30.24	2.71	32.70	2.78	34.58	2.82
					95	26.51	2.66	27.68	2.71	29.03	2.75	30.00	2.77	32.32	2.84	34.24	2.88
					99	26.51	2.73	27.18	2.78	28.59	2.82	29.36	2.84	31.97	2.91	33.96	2.95
					102	26.51	2.80	26.72	2.85	28.18	2.89	28.98	2.91	31.68	2.97	33.71	3.01
					108	26.51	2.90	26.12	2.95	27.66	3.00	28.50	3.02	31.30	3.08	33.42	3.12
					111	26.51	2.98	25.77	3.02	27.36	3.07	28.22	3.09	31.11	3.15	33.27	3.19
					115	26.51	3.05	25.46	3.10	27.10	3.14	27.99	3.16	30.96	3.22	33.17	3.26

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	15		33	68	29.16	2.40	36.00	2.45	37.06	2.50	37.67	2.52	38.34	2.55	39.82	2.60
					70	29.16	2.43	35.55	2.48	36.64	2.53	37.27	2.55	37.94	2.58	39.46	2.63
					73	29.16	2.49	34.68	2.54	35.83	2.59	36.48	2.62	37.19	2.64	38.76	2.69
					77	29.16	2.55	33.86	2.60	35.07	2.65	35.75	2.68	36.48	2.70	38.11	2.75
					81	29.16	2.62	33.09	2.67	34.35	2.72	35.06	2.74	35.82	2.77	37.51	2.81
					84	29.16	2.68	32.36	2.74	33.68	2.78	34.42	2.81	35.21	2.83	36.95	2.88
					88	29.16	2.75	31.67	2.80	33.05	2.85	33.82	2.88	34.64	2.90	36.43	2.95
					91	29.16	2.82	31.04	2.87	32.47	2.92	33.26	2.95	34.11	2.97	35.97	3.02
					95	29.16	2.89	30.44	2.94	31.93	2.99	33.00	3.01	33.64	3.04	35.55	3.09
					99	29.16	2.97	29.90	3.02	31.44	3.07	32.30	3.09	33.20	3.11	35.17	3.16
					102	29.16	3.04	29.40	3.09	31.00	3.14	31.88	3.16	32.82	3.19	34.84	3.23
					108	29.16	3.16	28.73	3.21	30.42	3.25	31.35	3.28	32.32	3.30	34.43	3.35
9	9	18		36	111	29.16	3.23	28.35	3.28	30.09	3.33	31.05	3.36	32.05	3.38	34.22	3.42
					115	29.16	3.32	28.01	3.36	29.81	3.41	30.79	3.44	31.83	3.46	34.05	3.50
					68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
9	12	12		33	108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64
					68	29.16	2.40	36.00	2.45	37.06	2.50	37.67	2.52	39.82	2.60	41.52	2.64
					70	29.16	2.43	35.55	2.48	36.64	2.53	37.27	2.55	39.46	2.63	41.18	2.67
					73	29.16	2.49	34.68	2.54	35.83	2.59	36.48	2.62	38.76	2.69	40.54	2.73
					77	29.16	2.55	33.86	2.60	35.07	2.65	35.75	2.68	38.11	2.75	39.95	2.79
					81	29.16	2.62	33.09	2.67	34.35	2.72	35.06	2.74	37.51	2.81	39.40	2.86
					84	29.16	2.68	32.36	2.74	33.68	2.78	34.42	2.81	36.95	2.88	38.90	2.92
					88	29.16	2.75	31.67	2.80	33.05	2.85	33.82	2.88	36.43	2.95	38.44	2.99
					91	29.16	2.82	31.04	2.87	32.47	2.92	33.26	2.95	35.97	3.02	38.03	3.06
					95	29.16	2.89	30.44	2.94	31.93	2.99	33.00	3.01	35.55	3.09	37.67	3.13
					99	29.16	2.97	29.90	3.02	31.44	3.07	32.30	3.09	35.17	3.16	37.35	3.20
					102	29.16	3.04	29.40	3.09	31.00	3.14	31.88	3.16	34.84	3.23	37.08	3.28
					108	29.16	3.16	28.73	3.21	30.42	3.25	31.35	3.28	34.43	3.35	36.76	3.39
					111	29.16	3.23	28.35	3.28	30.09	3.33	31.05	3.36	34.22	3.42	36.60	3.47
					115	29.16	3.32	28.01	3.36	29.81	3.41	30.79	3.44	34.05	3.50	36.49	3.55

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	15		36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	\	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60
9	12	18		39	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64
9	18	18		45	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	12		36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64
12	12	18		42	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60
12	18	18		48	68	34.93	2.47	36.44	2.52	37.98	2.56	38.76	2.59	39.54	2.61	41.13	2.66
					70	34.60	2.50	36.12	2.55	37.66	2.60	38.44	2.62	39.22	2.64	40.80	2.69
					73	33.94	2.56	35.47	2.61	37.01	2.66	37.79	2.69	38.57	2.71	40.16	2.76
					77	33.29	2.63	34.81	2.68	36.36	2.73	37.14	2.75	37.93	2.78	39.52	2.82
					81	32.64	2.70	34.17	2.74	35.72	2.79	36.50	2.82	37.29	2.84	38.88	2.89
					84	31.99	2.76	33.52	2.81	35.07	2.86	35.86	2.89	36.65	2.91	38.24	2.96
					88	31.34	2.83	32.87	2.88	34.43	2.93	35.22	2.96	36.01	2.98	37.61	3.03
					91	30.70	2.90	32.23	2.95	33.79	3.00	34.58	3.03	35.37	3.05	36.97	3.10
					95	30.05	2.97	31.59	3.02	33.15	3.07	34.00	3.09	34.73	3.12	36.34	3.17
					99	29.41	3.04	30.95	3.09	32.51	3.14	33.30	3.17	34.10	3.19	35.71	3.24
					102	28.77	3.12	30.31	3.17	31.88	3.22	32.67	3.24	33.47	3.27	35.08	3.32
					108	27.81	3.23	29.36	3.28	30.93	3.33	31.72	3.35	32.52	3.38	34.14	3.43
					111	27.17	3.30	28.72	3.35	30.30	3.40	31.09	3.43	31.89	3.46	33.51	3.51
					115	26.54	3.38	28.09	3.43	29.67	3.48	30.46	3.51	31.26	3.53	32.89	3.59

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	9	36	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64
9	9	9	12	39	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	41.03	2.66	42.78	2.71
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	40.65	2.69	42.43	2.74
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	39.94	2.76	41.77	2.80
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	39.27	2.82	41.16	2.87
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	38.64	2.89	40.59	2.93
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	38.07	2.96	40.08	3.00
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	37.54	3.02	39.61	3.07
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	37.06	3.10	39.19	3.14
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	36.62	3.17	38.81	3.21
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	36.24	3.24	38.48	3.29
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	35.90	3.32	38.20	3.36
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	35.48	3.44	37.87	3.48
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	35.26	3.52	37.71	3.56
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	35.08	3.60	37.59	3.64
9	9	9	18	45	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	12	42	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60
9	9	12	18	48	68	34.93	2.47	36.44	2.52	37.98	2.56	38.76	2.59	39.54	2.61	41.13	2.66
					70	34.60	2.50	36.12	2.55	37.66	2.60	38.44	2.62	39.22	2.64	40.80	2.69
					73	33.94	2.56	35.47	2.61	37.01	2.66	37.79	2.69	38.57	2.71	40.16	2.76
					77	33.29	2.63	34.81	2.68	36.36	2.73	37.14	2.75	37.93	2.78	39.52	2.82
					81	32.64	2.70	34.17	2.74	35.72	2.79	36.50	2.82	37.29	2.84	38.88	2.89
					84	31.99	2.76	33.52	2.81	35.07	2.86	35.86	2.89	36.65	2.91	38.24	2.96
					88	31.34	2.83	32.87	2.88	34.43	2.93	35.22	2.96	36.01	2.98	37.61	3.03
					91	30.70	2.90	32.23	2.95	33.79	3.00	34.58	3.03	35.37	3.05	36.97	3.10
					95	30.05	2.97	31.59	3.02	33.15	3.07	34.00	3.09	34.73	3.12	36.34	3.17
					99	29.41	3.04	30.95	3.09	32.51	3.14	33.30	3.17	34.10	3.19	35.71	3.24
					102	28.77	3.12	30.31	3.17	31.88	3.22	32.67	3.24	33.47	3.27	35.08	3.32
					108	27.81	3.23	29.36	3.28	30.93	3.33	31.72	3.35	32.52	3.38	34.14	3.43
					111	27.17	3.30	28.72	3.35	30.30	3.40	31.09	3.43	31.89	3.46	33.51	3.51
					115	26.54	3.38	28.09	3.43	29.67	3.48	30.46	3.51	31.26	3.53	32.89	3.59
9	12	12	12	45	68	30.05	2.46	37.09	2.51	38.19	2.57	38.82	2.59	39.50	2.62	41.03	2.66
					70	30.05	2.49	36.63	2.54	37.75	2.60	38.40	2.62	39.09	2.65	40.65	2.69
					73	30.05	2.55	35.73	2.61	36.92	2.66	37.59	2.68	38.32	2.71	39.94	2.76
					77	30.05	2.62	34.89	2.67	36.13	2.72	36.83	2.75	37.59	2.77	39.27	2.82
					81	30.05	2.69	34.09	2.74	35.39	2.79	36.12	2.82	36.91	2.84	38.64	2.89
					84	30.05	2.75	33.34	2.81	34.70	2.86	35.46	2.88	36.27	2.91	38.07	2.96
					88	30.05	2.83	32.63	2.88	34.05	2.93	34.84	2.95	35.69	2.98	37.54	3.02
					91	30.05	2.90	31.98	2.95	33.45	3.00	34.27	3.02	35.15	3.05	37.06	3.10
					95	30.05	2.97	31.37	3.02	32.90	3.07	34.00	3.09	34.65	3.12	36.62	3.17
					99	30.05	3.05	30.80	3.10	32.40	3.15	33.28	3.17	34.21	3.20	36.24	3.24
					102	30.05	3.12	30.29	3.17	31.94	3.22	32.85	3.25	33.81	3.27	35.90	3.32
					108	30.05	3.24	29.60	3.29	31.34	3.34	32.30	3.37	33.30	3.39	35.48	3.44
					111	30.05	3.32	29.21	3.37	31.01	3.42	31.99	3.45	33.02	3.47	35.26	3.52
					115	30.05	3.40	28.86	3.45	30.72	3.50	31.73	3.53	32.79	3.55	35.08	3.60

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	12	12	48	68	34.93	2.47	36.44	2.52	37.98	2.56	38.76	2.59	39.54	2.61	41.13	2.66
					70	34.60	2.50	36.12	2.55	37.66	2.60	38.44	2.62	39.22	2.64	40.80	2.69
					73	33.94	2.56	35.47	2.61	37.01	2.66	37.79	2.69	38.57	2.71	40.16	2.76
					77	33.29	2.63	34.81	2.68	36.36	2.73	37.14	2.75	37.93	2.78	39.52	2.82
					81	32.64	2.70	34.17	2.74	35.72	2.79	36.50	2.82	37.29	2.84	38.88	2.89
					84	31.99	2.76	33.52	2.81	35.07	2.86	35.86	2.89	36.65	2.91	38.24	2.96
					88	31.34	2.83	32.87	2.88	34.43	2.93	35.22	2.96	36.01	2.98	37.61	3.03
					91	30.70	2.90	32.23	2.95	33.79	3.00	34.58	3.03	35.37	3.05	36.97	3.10
					95	30.05	2.97	31.59	3.02	33.15	3.07	34.00	3.09	34.73	3.12	36.34	3.17
					99	29.41	3.04	30.95	3.09	32.51	3.14	33.30	3.17	34.10	3.19	35.71	3.24
					102	28.77	3.12	30.31	3.17	31.88	3.22	32.67	3.24	33.47	3.27	35.08	3.32
					108	27.81	3.23	29.36	3.28	30.93	3.33	31.72	3.35	32.52	3.38	34.14	3.43
					111	27.17	3.30	28.72	3.35	30.30	3.40	31.09	3.43	31.89	3.46	33.51	3.51
					115	26.54	3.38	28.09	3.43	29.67	3.48	30.46	3.51	31.26	3.53	32.89	3.59

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
- Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 48.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0**BNHDCH/AA or AC0**BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7				7	68	5.60	0.51	7.47	0.55	7.80	0.59	7.97	0.60	8.47	0.63	8.81	0.64
					70	5.60	0.52	7.41	0.56	7.74	0.59	7.90	0.61	8.40	0.64	8.74	0.65
					73	5.60	0.54	7.28	0.58	7.61	0.61	7.77	0.62	8.27	0.65	8.60	0.66
					77	5.60	0.57	7.15	0.60	7.48	0.63	7.64	0.64	8.13	0.67	8.47	0.67
					81	5.60	0.59	7.03	0.62	7.35	0.65	7.51	0.66	8.00	0.68	8.33	0.69
					84	5.60	0.61	6.90	0.64	7.22	0.67	7.38	0.68	7.87	0.70	8.20	0.70
					88	5.60	0.63	6.77	0.66	7.09	0.68	7.25	0.69	7.74	0.71	8.06	0.71
					91	5.60	0.65	6.65	0.68	6.97	0.70	7.13	0.71	7.61	0.73	7.93	0.73
					95	5.60	0.67	6.52	0.70	6.84	0.72	7.00	0.72	7.48	0.74	7.80	0.74
					99	5.60	0.70	6.40	0.72	6.71	0.74	6.87	0.75	7.34	0.76	7.66	0.76
					102	5.60	0.72	6.28	0.74	6.59	0.76	6.74	0.77	7.21	0.78	7.53	0.77
					108	5.53	0.75	6.09	0.78	6.40	0.79	6.55	0.80	7.02	0.80	7.33	0.80
					111	5.25	0.78	5.97	0.80	6.27	0.81	6.43	0.82	6.89	0.82	7.20	0.81
					115	5.11	0.80	5.85	0.82	6.15	0.83	6.30	0.84	6.76	0.84	7.07	0.83
9				9	68	7.20	0.57	9.60	0.61	10.03	0.65	10.24	0.67	10.89	0.70	11.32	0.71
					70	7.20	0.58	9.52	0.62	9.95	0.66	10.16	0.67	10.80	0.71	11.23	0.72
					73	7.20	0.61	9.36	0.65	9.78	0.68	9.99	0.69	10.63	0.72	11.06	0.73
					77	7.20	0.63	9.20	0.67	9.61	0.70	9.82	0.71	10.46	0.74	10.89	0.75
					81	7.20	0.65	9.03	0.69	9.45	0.72	9.66	0.73	10.29	0.76	10.71	0.76
					84	7.20	0.68	8.87	0.71	9.28	0.74	9.49	0.75	10.12	0.77	10.54	0.78
					88	7.20	0.70	8.71	0.73	9.12	0.76	9.33	0.77	9.95	0.79	10.37	0.79
					91	7.20	0.72	8.55	0.76	8.96	0.78	9.16	0.79	9.78	0.81	10.20	0.81
					95	7.20	0.75	8.39	0.78	8.79	0.80	9.00	0.80	9.61	0.83	10.02	0.83
					99	7.20	0.77	8.23	0.80	8.63	0.82	8.83	0.83	9.44	0.84	9.85	0.84
					102	7.20	0.80	8.07	0.83	8.47	0.85	8.67	0.85	9.28	0.86	9.68	0.86
					108	7.11	0.84	7.83	0.86	8.23	0.88	8.42	0.88	9.03	0.89	9.43	0.88
					111	6.75	0.86	7.67	0.89	8.07	0.90	8.26	0.91	8.86	0.91	9.26	0.90
					115	6.57	0.89	7.52	0.91	7.90	0.93	8.10	0.93	8.69	0.93	9.09	0.92
12				12	68	9.60	0.78	12.81	0.84	13.37	0.89	13.66	0.91	14.52	0.95	15.09	0.97
					70	9.60	0.79	12.70	0.85	13.26	0.90	13.54	0.92	14.40	0.96	14.98	0.98
					73	9.60	0.82	12.48	0.88	13.04	0.93	13.32	0.94	14.17	0.99	14.75	1.00
					77	9.60	0.86	12.26	0.91	12.82	0.95	13.10	0.97	13.95	1.01	14.51	1.02
					81	9.60	0.89	12.04	0.94	12.60	0.98	12.88	1.00	13.72	1.03	14.28	1.04
					84	9.60	0.92	11.83	0.97	12.38	1.01	12.66	1.02	13.49	1.05	14.05	1.06
					88	9.60	0.95	11.61	1.00	12.16	1.04	12.43	1.05	13.27	1.08	13.82	1.08
					91	9.60	0.99	11.40	1.03	11.94	1.06	12.21	1.08	13.04	1.10	13.59	1.10
					95	9.60	1.02	11.19	1.06	11.72	1.09	12.00	1.09	12.81	1.12	13.37	1.12
					99	9.60	1.05	10.97	1.09	11.51	1.12	11.78	1.13	12.59	1.15	13.14	1.15
					102	9.60	1.09	10.76	1.13	11.29	1.15	11.56	1.16	12.37	1.17	12.91	1.17
					108	9.48	1.14	10.44	1.17	10.97	1.20	11.23	1.21	12.03	1.21	12.57	1.21
					111	9.00	1.18	10.23	1.21	10.75	1.23	11.02	1.24	11.81	1.24	12.35	1.23
					115	8.76	1.21	10.02	1.24	10.54	1.26	10.80	1.27	11.59	1.27	12.12	1.25

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15				15	68	12.00	1.01	16.01	1.08	16.71	1.15	17.07	1.17	17.43	1.20	18.15	1.23
					70	12.00	1.03	15.87	1.10	16.58	1.16	16.93	1.19	17.29	1.21	18.00	1.25
					73	12.00	1.07	15.60	1.14	16.30	1.20	16.65	1.22	17.01	1.24	17.72	1.27
					77	12.00	1.11	15.33	1.18	16.02	1.23	16.37	1.25	16.72	1.27	17.43	1.30
					81	12.00	1.15	15.06	1.21	15.75	1.27	16.10	1.29	16.45	1.31	17.15	1.33
					84	12.00	1.19	14.79	1.25	15.47	1.30	15.82	1.32	16.17	1.34	16.86	1.36
					88	12.00	1.23	14.52	1.29	15.20	1.34	15.54	1.36	15.89	1.37	16.58	1.39
					91	12.00	1.28	14.25	1.33	14.93	1.38	15.27	1.39	15.61	1.41	16.30	1.42
					95	12.00	1.32	13.98	1.37	14.66	1.41	15.00	1.41	15.33	1.44	16.02	1.45
					99	12.00	1.36	13.71	1.41	14.38	1.45	14.72	1.47	15.06	1.48	15.74	1.49
					102	12.00	1.41	13.45	1.46	14.11	1.49	14.45	1.50	14.78	1.51	15.46	1.52
					108	11.85	1.48	13.05	1.52	13.71	1.55	14.04	1.56	14.37	1.57	15.04	1.57
					111	11.25	1.52	12.79	1.56	13.44	1.59	13.77	1.60	14.10	1.60	14.76	1.60
					115	10.95	1.57	12.53	1.61	13.17	1.63	13.50	1.64	13.83	1.64	14.49	1.64
18				18	68	13.68	1.06	18.25	1.14	19.05	1.20	19.46	1.23	20.69	1.29	21.51	1.32
					70	13.68	1.08	18.09	1.16	18.90	1.22	19.30	1.25	20.52	1.31	21.34	1.33
					73	13.68	1.12	17.78	1.20	18.58	1.26	18.98	1.28	20.20	1.34	21.01	1.36
					77	13.68	1.16	17.47	1.23	18.27	1.29	18.67	1.32	19.87	1.37	20.68	1.38
					81	13.68	1.21	17.16	1.27	17.95	1.33	18.35	1.35	19.55	1.40	20.35	1.41
					84	13.68	1.25	16.86	1.32	17.64	1.37	18.03	1.39	19.22	1.43	20.03	1.44
					88	13.68	1.29	16.55	1.36	17.33	1.41	17.72	1.42	18.90	1.46	19.70	1.47
					91	13.68	1.34	16.24	1.40	17.02	1.44	17.41	1.46	18.58	1.49	19.37	1.50
					95	13.68	1.38	15.94	1.44	16.71	1.48	17.10	1.48	18.26	1.53	19.05	1.53
					99	13.68	1.43	15.63	1.48	16.40	1.52	16.78	1.54	17.94	1.56	18.72	1.56
					102	13.68	1.48	15.33	1.53	16.09	1.56	16.47	1.58	17.62	1.59	18.40	1.59
					108	13.51	1.55	14.88	1.60	15.63	1.63	16.01	1.64	17.15	1.65	17.92	1.64
					111	12.83	1.60	14.58	1.64	15.32	1.67	15.70	1.68	16.83	1.68	17.59	1.67
					115	12.48	1.65	14.28	1.69	15.02	1.71	15.39	1.72	16.52	1.72	17.27	1.70
24				24	68	17.60	1.46	23.48	1.57	24.51	1.67	25.04	1.71	26.61	1.79	27.67	1.83
					70	17.60	1.49	23.28	1.60	24.31	1.69	24.83	1.73	26.40	1.81	27.46	1.84
					73	17.60	1.55	22.88	1.66	23.91	1.74	24.42	1.78	25.98	1.85	27.03	1.88
					77	17.60	1.61	22.48	1.71	23.50	1.79	24.01	1.82	25.57	1.89	26.61	1.92
					81	17.60	1.67	22.08	1.77	23.10	1.84	23.61	1.87	25.15	1.94	26.19	1.96
					84	17.60	1.73	21.69	1.82	22.69	1.89	23.20	1.92	24.73	1.98	25.76	1.99
					88	17.60	1.79	21.29	1.88	22.29	1.95	22.80	1.97	24.32	2.02	25.34	2.03
					91	17.60	1.85	20.90	1.94	21.89	2.00	22.39	2.03	23.91	2.07	24.92	2.07
					95	17.60	1.92	20.51	2.00	21.49	2.06	22.00	2.05	23.49	2.11	24.50	2.12
					99	17.60	1.98	20.12	2.06	21.10	2.11	21.59	2.13	23.08	2.16	24.09	2.16
					102	17.60	2.05	19.73	2.12	20.70	2.17	21.19	2.18	22.67	2.21	23.67	2.20
					108	17.38	2.15	19.14	2.21	20.11	2.25	20.59	2.27	22.06	2.28	23.05	2.27
					111	16.50	2.21	18.76	2.27	19.72	2.31	20.20	2.32	21.66	2.33	22.64	2.31
					115	16.06	2.28	18.37	2.34	19.32	2.37	19.80	2.38	21.25	2.38	22.22	2.36

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7			14	68	12.37	0.91	15.27	0.93	15.72	0.95	15.98	0.96	16.89	0.98	17.61	1.00
					70	12.37	0.92	15.08	0.94	15.54	0.96	15.81	0.97	16.74	0.99	17.47	1.01
					73	12.37	0.94	14.71	0.96	15.20	0.98	15.48	0.99	16.44	1.02	17.20	1.03
					77	12.37	0.97	14.37	0.99	14.88	1.01	15.17	1.01	16.17	1.04	16.95	1.06
					81	12.37	0.99	14.04	1.01	14.57	1.03	14.87	1.04	15.91	1.07	16.72	1.08
					84	12.37	1.02	13.73	1.04	14.29	1.05	14.60	1.06	15.67	1.09	16.50	1.11
					88	12.37	1.04	13.44	1.06	14.02	1.08	14.35	1.09	15.46	1.12	16.31	1.13
					91	12.37	1.07	13.17	1.09	13.77	1.11	14.11	1.12	15.26	1.14	16.14	1.16
					95	12.37	1.10	12.92	1.12	13.55	1.13	14.00	1.14	15.08	1.17	15.98	1.19
					99	12.37	1.12	12.68	1.14	13.34	1.16	13.70	1.17	14.92	1.20	15.85	1.21
					102	12.37	1.15	12.47	1.17	13.15	1.19	13.53	1.20	14.78	1.22	15.73	1.24
					108	12.37	1.20	12.19	1.21	12.91	1.23	13.30	1.24	14.61	1.27	15.59	1.28
					111	12.37	1.23	12.03	1.24	12.77	1.26	13.17	1.27	14.52	1.30	15.53	1.31
					115	12.37	1.26	11.88	1.27	12.65	1.29	13.06	1.30	14.45	1.33	15.48	1.34
7	9			16	68	14.14	1.00	17.45	1.02	17.97	1.04	18.27	1.05	19.31	1.08	20.13	1.10
					70	14.14	1.01	17.24	1.03	17.77	1.05	18.07	1.06	19.13	1.09	19.97	1.11
					73	14.14	1.03	16.82	1.06	17.37	1.08	17.69	1.09	18.79	1.12	19.66	1.13
					77	14.14	1.06	16.42	1.08	17.00	1.10	17.33	1.11	18.48	1.14	19.37	1.16
					81	14.14	1.09	16.04	1.11	16.65	1.13	17.00	1.14	18.18	1.17	19.10	1.19
					84	14.14	1.11	15.69	1.14	16.33	1.16	16.69	1.17	17.91	1.20	18.86	1.21
					88	14.14	1.14	15.36	1.16	16.02	1.18	16.40	1.19	17.67	1.22	18.64	1.24
					91	14.14	1.17	15.05	1.19	15.74	1.21	16.13	1.22	17.44	1.25	18.44	1.27
					95	14.14	1.20	14.76	1.22	15.48	1.24	16.00	1.25	17.23	1.28	18.26	1.30
					99	14.14	1.23	14.50	1.25	15.25	1.27	15.66	1.28	17.05	1.31	18.11	1.33
					102	14.14	1.26	14.25	1.28	15.03	1.30	15.46	1.31	16.89	1.34	17.98	1.36
					108	14.14	1.31	13.93	1.33	14.75	1.35	15.20	1.36	16.70	1.39	17.82	1.41
					111	14.14	1.34	13.74	1.36	14.59	1.38	15.05	1.39	16.59	1.42	17.74	1.44
					115	14.14	1.38	13.58	1.40	14.45	1.42	14.93	1.43	16.51	1.46	17.69	1.47
7	12			19	68	16.79	1.16	20.73	1.19	21.34	1.21	21.69	1.22	22.93	1.26	23.90	1.28
					70	16.79	1.18	20.47	1.20	21.10	1.23	21.46	1.24	22.72	1.27	23.71	1.30
					73	16.79	1.21	19.97	1.23	20.63	1.26	21.01	1.27	22.32	1.30	23.34	1.32
					77	16.79	1.24	19.50	1.26	20.19	1.29	20.58	1.30	21.94	1.33	23.00	1.36
					81	16.79	1.27	19.05	1.29	19.78	1.32	20.19	1.33	21.59	1.36	22.69	1.39
					84	16.79	1.30	18.63	1.33	19.39	1.35	19.81	1.36	21.27	1.40	22.40	1.42
					88	16.79	1.33	18.24	1.36	19.03	1.38	19.47	1.40	20.98	1.43	22.13	1.45
					91	16.79	1.37	17.87	1.39	18.69	1.42	19.15	1.43	20.71	1.46	21.90	1.48
					95	16.79	1.40	17.53	1.43	18.39	1.45	19.00	1.46	20.47	1.50	21.69	1.52
					99	16.79	1.44	17.21	1.46	18.10	1.49	18.60	1.50	20.25	1.53	21.51	1.55
					102	16.79	1.48	16.93	1.50	17.85	1.52	18.36	1.53	20.06	1.57	21.35	1.59
					108	16.79	1.53	16.54	1.56	17.52	1.58	18.05	1.59	19.83	1.62	21.16	1.64
					111	16.79	1.57	16.32	1.59	17.33	1.62	17.88	1.63	19.70	1.66	21.07	1.68
					115	16.79	1.61	16.13	1.63	17.16	1.66	17.73	1.67	19.61	1.70	21.01	1.72

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15			22	68	19.44	1.33	24.00	1.36	24.71	1.39	25.12	1.40	25.56	1.41	26.55	1.44
					70	19.44	1.35	23.70	1.38	24.43	1.40	24.84	1.42	25.30	1.43	26.30	1.46
					73	19.44	1.38	23.12	1.41	23.89	1.44	24.32	1.45	24.79	1.46	25.84	1.49
					77	19.44	1.42	22.57	1.44	23.38	1.47	23.83	1.49	24.32	1.50	25.41	1.53
					81	19.44	1.45	22.06	1.48	22.90	1.51	23.37	1.52	23.88	1.54	25.00	1.56
					84	19.44	1.49	21.57	1.52	22.45	1.55	22.94	1.56	23.47	1.57	24.63	1.60
					88	19.44	1.53	21.12	1.56	22.03	1.58	22.54	1.60	23.09	1.61	24.29	1.63
					91	19.44	1.57	20.69	1.59	21.65	1.62	22.18	1.63	22.74	1.65	23.98	1.67
					95	19.44	1.61	20.30	1.63	21.29	1.66	22.00	1.67	22.42	1.69	23.70	1.71
					99	19.44	1.65	19.93	1.67	20.96	1.70	21.53	1.71	22.14	1.73	23.45	1.75
					102	19.44	1.69	19.60	1.72	20.67	1.74	21.26	1.76	21.88	1.77	23.23	1.79
					108	19.44	1.75	19.16	1.78	20.28	1.81	20.90	1.82	21.55	1.83	22.96	1.86
					111	19.44	1.79	18.90	1.82	20.06	1.85	20.70	1.86	21.37	1.88	22.81	1.90
					115	19.44	1.84	18.67	1.87	19.87	1.89	20.53	1.91	21.22	1.92	22.70	1.94
7	18			25	68	21.30	1.43	26.29	1.46	27.07	1.49	27.51	1.51	29.08	1.55	30.32	1.58
					70	21.30	1.45	25.96	1.48	26.76	1.51	27.22	1.53	28.82	1.57	30.07	1.60
					73	21.30	1.49	25.33	1.52	26.17	1.55	26.64	1.56	28.31	1.61	29.61	1.63
					77	21.30	1.53	24.73	1.56	25.61	1.59	26.11	1.60	27.83	1.64	29.17	1.67
					81	21.30	1.56	24.16	1.60	25.08	1.63	25.60	1.64	27.39	1.68	28.77	1.71
					84	21.30	1.60	23.63	1.64	24.59	1.67	25.13	1.68	26.98	1.72	28.41	1.75
					88	21.30	1.65	23.13	1.68	24.14	1.71	24.70	1.72	26.61	1.76	28.08	1.79
					91	21.30	1.69	22.67	1.72	23.71	1.75	24.29	1.76	26.27	1.80	27.78	1.83
					95	21.30	1.73	22.23	1.76	23.32	1.79	24.10	1.80	25.96	1.85	27.51	1.87
					99	21.30	1.77	21.83	1.80	22.96	1.83	23.59	1.85	25.69	1.89	27.28	1.91
					102	21.30	1.82	21.47	1.85	22.64	1.88	23.28	1.89	25.45	1.93	27.08	1.96
					108	21.30	1.89	20.98	1.92	22.22	1.95	22.89	1.96	25.15	2.00	26.84	2.03
					111	21.30	1.93	20.70	1.96	21.98	1.99	22.67	2.01	24.99	2.05	26.73	2.07
					115	21.30	1.98	20.45	2.01	21.77	2.04	22.49	2.05	24.87	2.10	26.65	2.12
7	24			31	68	25.63	2.17	31.64	2.21	32.57	2.26	33.11	2.28	35.00	2.35	36.49	2.39
					70	25.63	2.19	31.24	2.24	32.20	2.29	32.75	2.31	34.67	2.37	36.19	2.41
					73	25.63	2.25	30.48	2.30	31.49	2.34	32.06	2.36	34.06	2.43	35.63	2.47
					77	25.63	2.31	29.76	2.35	30.82	2.40	31.42	2.42	33.49	2.48	35.11	2.52
					81	25.63	2.36	29.08	2.41	30.19	2.46	30.81	2.48	32.96	2.54	34.62	2.58
					84	25.63	2.43	28.43	2.47	29.59	2.52	30.24	2.54	32.47	2.60	34.18	2.64
					88	25.63	2.49	27.83	2.53	29.04	2.58	29.72	2.60	32.02	2.66	33.78	2.70
					91	25.63	2.55	27.27	2.60	28.53	2.64	29.23	2.66	31.61	2.73	33.42	2.76
					95	25.63	2.61	26.75	2.66	28.06	2.71	29.00	2.72	31.24	2.79	33.10	2.83
					99	25.63	2.68	26.27	2.73	27.63	2.77	28.38	2.79	30.91	2.85	32.82	2.89
					102	25.63	2.75	25.83	2.79	27.24	2.84	28.02	2.86	30.62	2.92	32.58	2.96
					108	25.63	2.85	25.25	2.90	26.74	2.94	27.55	2.96	30.26	3.02	32.30	3.06
					111	25.63	2.92	24.91	2.97	26.45	3.01	27.28	3.03	30.07	3.09	32.16	3.13
					115	25.63	3.00	24.61	3.04	26.20	3.08	27.06	3.11	29.92	3.17	32.06	3.20

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9			18	68	15.91	1.07	19.64	1.10	20.22	1.12	20.55	1.13	21.72	1.16	22.65	1.18
					70	15.91	1.09	19.39	1.11	19.99	1.13	20.33	1.15	21.52	1.18	22.46	1.20
					73	15.91	1.12	18.92	1.14	19.54	1.16	19.90	1.17	21.14	1.20	22.11	1.22
					77	15.91	1.14	18.47	1.17	19.13	1.19	19.50	1.20	20.79	1.23	21.79	1.25
					81	15.91	1.17	18.05	1.20	18.74	1.22	19.12	1.23	20.46	1.26	21.49	1.28
					84	15.91	1.20	17.65	1.23	18.37	1.25	18.77	1.26	20.15	1.29	21.22	1.31
					88	15.91	1.23	17.28	1.26	18.03	1.28	18.45	1.29	19.87	1.32	20.97	1.34
					91	15.91	1.27	16.93	1.29	17.71	1.31	18.14	1.32	19.62	1.35	20.75	1.37
					95	15.91	1.30	16.61	1.32	17.42	1.34	18.00	1.35	19.39	1.38	20.55	1.40
					99	15.91	1.33	16.31	1.35	17.15	1.38	17.62	1.39	19.18	1.42	20.37	1.44
					102	15.91	1.36	16.03	1.39	16.91	1.41	17.39	1.42	19.01	1.45	20.22	1.47
					108	15.91	1.42	15.67	1.44	16.59	1.46	17.10	1.47	18.78	1.50	20.05	1.52
					111	15.91	1.45	15.46	1.47	16.42	1.49	16.93	1.51	18.67	1.54	19.96	1.56
					115	15.91	1.49	15.28	1.51	16.26	1.53	16.80	1.54	18.57	1.57	19.90	1.59
9	12			21	68	18.56	1.24	22.91	1.27	23.59	1.30	23.97	1.31	25.34	1.35	26.42	1.37
					70	18.56	1.26	22.62	1.28	23.32	1.31	23.71	1.32	25.11	1.36	26.21	1.38
					73	18.56	1.29	22.07	1.32	22.80	1.34	23.22	1.36	24.67	1.39	25.80	1.42
					77	18.56	1.32	21.55	1.35	22.32	1.38	22.75	1.39	24.25	1.42	25.42	1.45
					81	18.56	1.36	21.05	1.38	21.86	1.41	22.31	1.42	23.87	1.46	25.07	1.48
					84	18.56	1.39	20.59	1.42	21.43	1.44	21.90	1.46	23.51	1.49	24.75	1.52
					88	18.56	1.43	20.16	1.45	21.03	1.48	21.52	1.49	23.19	1.53	24.46	1.55
					91	18.56	1.46	19.75	1.49	20.66	1.51	21.17	1.53	22.89	1.56	24.20	1.59
					95	18.56	1.50	19.37	1.53	20.32	1.55	21.00	1.56	22.62	1.60	23.97	1.62
					99	18.56	1.54	19.03	1.56	20.01	1.59	20.55	1.60	22.38	1.64	23.77	1.66
					102	18.56	1.58	18.71	1.60	19.73	1.63	20.29	1.64	22.17	1.68	23.60	1.70
					108	18.56	1.64	18.28	1.66	19.36	1.69	19.95	1.70	21.91	1.73	23.39	1.76
					111	18.56	1.68	18.04	1.70	19.15	1.73	19.76	1.74	21.78	1.77	23.29	1.80
					115	18.56	1.72	17.82	1.74	18.97	1.77	19.60	1.78	21.67	1.82	23.22	1.84
9	15			24	68	21.21	1.24	29.92	1.27	30.49	1.31	30.83	1.32	31.20	1.33	32.08	1.36
					70	21.21	1.27	29.10	1.31	29.71	1.34	30.07	1.35	30.47	1.37	31.39	1.39
					73	21.21	1.31	28.32	1.34	28.97	1.37	29.36	1.38	29.78	1.40	30.73	1.43
					77	21.21	1.34	27.58	1.37	28.27	1.40	28.67	1.42	29.11	1.43	30.11	1.46
					81	21.21	1.37	26.86	1.40	27.59	1.43	28.02	1.45	28.48	1.46	29.52	1.49
					84	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	27.88	1.50	28.96	1.53
					88	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	27.60	1.52	28.70	1.54
					91	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	27.05	1.55	28.19	1.58
					95	21.21	1.50	24.63	1.53	25.50	1.56	24.00	1.77	26.53	1.59	27.72	1.62
					99	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	26.05	1.63	27.28	1.65
					102	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	25.60	1.67	26.87	1.69
					108	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	25.19	1.71	26.50	1.73
					111	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	24.81	1.75	26.16	1.77
					115	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	24.46	1.79	25.85	1.81

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	18			27	68	23.07	1.80	28.47	1.84	29.31	1.88	29.80	1.90	31.50	1.95	32.84	1.98
					70	23.07	1.82	28.12	1.86	28.98	1.90	29.47	1.92	31.21	1.97	32.57	2.01
					73	23.07	1.87	27.43	1.91	28.34	1.95	28.86	1.96	30.66	2.02	32.06	2.05
					77	23.07	1.92	26.78	1.96	27.73	1.99	28.27	2.01	30.14	2.06	31.60	2.10
					81	23.07	1.96	26.17	2.00	27.17	2.04	27.73	2.06	29.66	2.11	31.16	2.15
					84	23.07	2.01	25.59	2.05	26.63	2.09	27.22	2.11	29.22	2.16	30.77	2.20
					88	23.07	2.07	25.05	2.10	26.14	2.14	26.75	2.16	28.82	2.21	30.41	2.25
					91	23.07	2.12	24.55	2.16	25.68	2.19	26.31	2.21	28.45	2.26	30.08	2.30
					95	23.07	2.17	24.08	2.21	25.26	2.25	26.10	2.26	28.11	2.32	29.79	2.35
					99	23.07	2.23	23.65	2.27	24.87	2.30	25.54	2.32	27.82	2.37	29.54	2.40
					102	23.07	2.28	23.25	2.32	24.52	2.36	25.22	2.38	27.56	2.43	29.33	2.46
					108	23.07	2.37	22.73	2.41	24.06	2.44	24.79	2.46	27.23	2.51	29.07	2.54
					111	23.07	2.43	22.42	2.47	23.80	2.50	24.56	2.52	27.07	2.57	28.95	2.60
					115	23.07	2.49	22.15	2.53	23.58	2.56	24.35	2.58	26.93	2.63	28.86	2.66
9	24			33	68	27.40	2.29	33.82	2.34	34.82	2.39	35.39	2.41	37.41	2.48	39.00	2.53
					70	27.40	2.32	33.40	2.37	34.42	2.42	35.01	2.44	37.07	2.51	38.69	2.56
					73	27.40	2.38	32.58	2.43	33.66	2.48	34.27	2.50	36.41	2.57	38.08	2.61
					77	27.40	2.44	31.81	2.49	32.94	2.54	33.58	2.56	35.80	2.63	37.53	2.67
					81	27.40	2.50	31.08	2.55	32.27	2.60	32.93	2.62	35.23	2.69	37.01	2.73
					84	27.40	2.57	30.40	2.62	31.64	2.66	32.33	2.69	34.71	2.75	36.54	2.80
					88	27.40	2.63	29.75	2.68	31.05	2.73	31.77	2.75	34.23	2.82	36.11	2.86
					91	27.40	2.70	29.15	2.75	30.50	2.80	31.25	2.82	33.79	2.89	35.73	2.93
					95	27.40	2.77	28.60	2.82	30.00	2.86	31.00	2.88	33.39	2.95	35.39	2.99
					99	27.40	2.84	28.09	2.89	29.54	2.93	30.34	2.96	33.04	3.02	35.09	3.06
					102	27.40	2.91	27.62	2.96	29.12	3.00	29.95	3.03	32.73	3.09	34.83	3.13
					108	27.40	3.02	26.99	3.07	28.58	3.11	29.45	3.14	32.35	3.20	34.53	3.24
					111	27.40	3.10	26.63	3.14	28.27	3.19	29.17	3.21	32.15	3.28	34.38	3.32
					115	27.40	3.17	26.31	3.22	28.01	3.27	28.93	3.29	31.99	3.35	34.28	3.39
12	12			24	68	21.21	1.41	26.18	1.44	26.96	1.47	27.40	1.48	28.96	1.53	30.19	1.55
					70	21.21	1.43	25.85	1.46	26.65	1.49	27.10	1.50	28.70	1.54	29.95	1.57
					73	21.21	1.46	25.22	1.49	26.06	1.52	26.53	1.54	28.19	1.58	29.48	1.61
					77	21.21	1.50	24.63	1.53	25.50	1.56	26.00	1.58	27.72	1.62	29.05	1.64
					81	21.21	1.54	24.06	1.57	24.98	1.60	25.50	1.61	27.28	1.65	28.66	1.68
					84	21.21	1.58	23.53	1.61	24.49	1.64	25.03	1.65	26.87	1.69	28.29	1.72
					88	21.21	1.62	23.03	1.65	24.04	1.68	24.59	1.69	26.50	1.73	27.96	1.76
					91	21.21	1.66	22.57	1.69	23.61	1.72	24.19	1.73	26.16	1.77	27.66	1.80
					95	21.21	1.70	22.14	1.73	23.22	1.76	24.00	1.77	25.85	1.81	27.40	1.84
					99	21.21	1.74	21.74	1.77	22.87	1.80	23.49	1.82	25.58	1.86	27.16	1.88
					102	21.21	1.79	21.38	1.82	22.55	1.85	23.19	1.86	25.34	1.90	26.97	1.93
					108	21.21	1.86	20.90	1.89	22.13	1.91	22.80	1.93	25.04	1.97	26.73	1.99
					111	21.21	1.90	20.62	1.93	21.89	1.96	22.58	1.97	24.89	2.01	26.62	2.04
					115	21.21	1.95	20.37	1.98	21.68	2.01	22.39	2.02	24.76	2.06	26.54	2.09

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15			27	68	23.86	1.89	29.45	1.94	30.32	1.98	30.82	2.00	31.37	2.01	32.58	2.05
					70	23.86	1.92	29.09	1.96	29.98	2.00	30.49	2.02	31.05	2.04	32.28	2.08
					73	23.86	1.97	28.38	2.01	29.32	2.05	29.85	2.07	30.43	2.09	31.71	2.12
					77	23.86	2.02	27.70	2.06	28.69	2.10	29.25	2.12	29.85	2.14	31.18	2.17
					81	23.86	2.07	27.07	2.11	28.10	2.15	28.68	2.17	29.31	2.19	30.69	2.22
					84	23.86	2.12	26.47	2.16	27.55	2.20	28.16	2.22	28.81	2.24	30.23	2.28
					88	23.86	2.18	25.91	2.22	27.04	2.26	27.67	2.27	28.34	2.29	29.81	2.33
					91	23.86	2.23	25.39	2.27	26.57	2.31	27.22	2.33	27.91	2.35	29.43	2.38
					95	23.86	2.29	24.91	2.33	26.13	2.37	27.00	2.38	27.52	2.40	29.08	2.44
					99	23.86	2.35	24.46	2.39	25.73	2.42	26.43	2.44	27.17	2.46	28.78	2.50
					102	23.86	2.40	24.05	2.44	25.37	2.48	26.09	2.50	26.85	2.52	28.51	2.56
					108	23.86	2.50	23.51	2.54	24.89	2.57	25.65	2.59	26.45	2.61	28.17	2.65
					111	23.86	2.56	23.19	2.60	24.62	2.64	25.40	2.65	26.22	2.67	28.00	2.71
					115	23.86	2.62	22.92	2.66	24.39	2.70	25.19	2.72	26.04	2.74	27.86	2.77
12	18			30	68	25.72	2.04	31.75	2.08	32.68	2.13	33.22	2.15	35.12	2.21	36.61	2.25
					70	25.72	2.06	31.35	2.11	32.31	2.15	32.86	2.17	34.79	2.23	36.31	2.27
					73	25.72	2.12	30.58	2.16	31.60	2.20	32.17	2.22	34.18	2.28	35.75	2.32
					77	25.72	2.17	29.86	2.21	30.92	2.26	31.52	2.28	33.61	2.34	35.23	2.38
					81	25.72	2.23	29.18	2.27	30.29	2.31	30.92	2.33	33.07	2.39	34.74	2.43
					84	25.72	2.28	28.53	2.33	29.70	2.37	30.35	2.39	32.58	2.45	34.30	2.49
					88	25.72	2.34	27.93	2.38	29.14	2.43	29.82	2.45	32.13	2.51	33.90	2.54
					91	25.72	2.40	27.37	2.44	28.63	2.49	29.33	2.51	31.72	2.56	33.54	2.60
					95	25.72	2.46	26.85	2.50	28.16	2.55	29.10	2.56	31.35	2.62	33.22	2.66
					99	25.72	2.52	26.36	2.57	27.73	2.61	28.48	2.63	31.02	2.69	32.94	2.72
					102	25.72	2.59	25.92	2.63	27.34	2.67	28.11	2.69	30.72	2.75	32.70	2.79
					108	25.72	2.68	25.34	2.73	26.83	2.77	27.64	2.79	30.37	2.85	32.41	2.88
					111	25.72	2.75	25.00	2.79	26.54	2.83	27.38	2.85	30.18	2.91	32.27	2.95
					115	25.72	2.82	24.70	2.86	26.29	2.90	27.15	2.92	30.03	2.98	32.18	3.02
12	24			36	68	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	41.03	2.95	42.78	3.00
					70	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	40.65	2.98	42.43	3.03
					73	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	39.94	3.05	41.77	3.10
					77	30.05	2.90	34.89	2.96	36.13	3.02	36.83	3.04	39.27	3.12	41.16	3.17
					81	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	38.64	3.20	40.59	3.25
					84	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	38.07	3.27	40.08	3.32
					88	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	37.54	3.35	39.61	3.40
					91	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	37.06	3.43	39.19	3.48
					95	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.42	36.62	3.51	38.81	3.56
					99	30.05	3.37	30.80	3.43	32.40	3.48	33.28	3.51	36.24	3.59	38.48	3.64
					102	30.05	3.46	30.29	3.51	31.94	3.57	32.85	3.60	35.90	3.67	38.20	3.72
					108	30.05	3.59	29.60	3.64	31.34	3.70	32.30	3.72	35.48	3.80	37.87	3.85
					111	30.05	3.68	29.21	3.73	31.01	3.79	31.99	3.81	35.26	3.89	37.71	3.94
					115	30.05	3.77	28.86	3.82	30.72	3.88	31.73	3.90	35.08	3.98	37.59	4.03

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	68	26.51	2.17	32.73	2.22	33.69	2.27	34.25	2.29	34.85	2.31	36.20	2.35
					70	26.51	2.20	32.32	2.25	33.31	2.29	33.88	2.32	34.49	2.34	35.87	2.38
					73	26.51	2.26	31.53	2.30	32.57	2.35	33.17	2.37	33.81	2.39	35.24	2.44
					77	26.51	2.31	30.78	2.36	31.88	2.41	32.50	2.43	33.17	2.45	34.65	2.49
					81	26.51	2.37	30.08	2.42	31.23	2.47	31.87	2.49	32.57	2.51	34.10	2.55
					84	26.51	2.43	29.42	2.48	30.61	2.53	31.29	2.55	32.01	2.57	33.59	2.61
					88	26.51	2.50	28.79	2.54	30.05	2.59	30.74	2.61	31.49	2.63	33.12	2.67
					91	26.51	2.56	28.21	2.61	29.52	2.65	30.24	2.67	31.01	2.69	32.70	2.74
					95	26.51	2.62	27.68	2.67	29.03	2.71	30.00	2.73	30.58	2.76	32.32	2.80
					99	26.51	2.69	27.18	2.74	28.59	2.78	29.36	2.80	30.18	2.82	31.97	2.86
					102	26.51	2.76	26.72	2.80	28.18	2.85	28.98	2.87	29.83	2.89	31.68	2.93
					108	26.51	2.86	26.12	2.91	27.66	2.95	28.50	2.97	29.39	2.99	31.30	3.04
					111	26.51	2.93	25.77	2.98	27.36	3.02	28.22	3.04	29.14	3.07	31.11	3.11
					115	26.51	3.01	25.46	3.05	27.10	3.10	27.99	3.12	28.93	3.14	30.96	3.18
15	18			33	68	28.37	2.32	35.02	2.37	36.05	2.42	36.65	2.44	37.29	2.46	38.74	2.51
					70	28.37	2.35	34.58	2.40	35.64	2.45	36.25	2.47	36.91	2.49	38.38	2.54
					73	28.37	2.41	33.74	2.46	34.85	2.50	35.49	2.53	36.18	2.55	37.70	2.60
					77	28.37	2.47	32.94	2.52	34.11	2.57	34.77	2.59	35.49	2.61	37.07	2.66
					81	28.37	2.53	32.18	2.58	33.41	2.63	34.10	2.65	34.85	2.67	36.48	2.72
					84	28.37	2.59	31.47	2.64	32.76	2.69	33.48	2.72	34.25	2.74	35.94	2.78
					88	28.37	2.66	30.81	2.71	32.15	2.76	32.89	2.78	33.69	2.80	35.44	2.85
					91	28.37	2.73	30.19	2.78	31.58	2.83	32.36	2.85	33.18	2.87	34.99	2.92
					95	28.37	2.80	29.61	2.85	31.06	2.89	32.10	2.91	32.72	2.94	34.58	2.98
					99	28.37	2.87	29.08	2.92	30.59	2.96	31.42	2.99	32.30	3.01	34.21	3.05
					102	28.37	2.94	28.60	2.99	30.16	3.04	31.01	3.06	31.92	3.08	33.89	3.13
					108	28.37	3.05	27.95	3.10	29.59	3.15	30.49	3.17	31.44	3.19	33.50	3.24
					111	28.37	3.13	27.57	3.18	29.27	3.22	30.20	3.25	31.18	3.27	33.29	3.31
					115	28.37	3.20	27.24	3.25	29.00	3.30	29.95	3.32	30.96	3.34	33.12	3.39
15	24			39	68	30.05	2.40	42.39	2.46	43.19	2.52	43.67	2.55	44.21	2.58	45.44	2.63
					70	30.05	2.46	41.23	2.52	42.09	2.58	42.60	2.61	43.17	2.64	44.47	2.69
					73	30.05	2.53	40.13	2.59	41.05	2.64	41.59	2.67	42.18	2.70	43.54	2.75
					77	30.05	2.59	39.07	2.65	40.05	2.71	40.62	2.74	41.24	2.76	42.65	2.82
					81	30.05	2.65	38.06	2.71	39.09	2.77	39.69	2.80	40.35	2.83	41.82	2.88
					84	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	39.50	2.90	41.03	2.95
					88	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	39.09	2.93	40.65	2.98
					91	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	38.32	3.00	39.94	3.05
					95	30.05	2.90	34.89	2.96	36.13	3.02	34.00	3.42	37.59	3.07	39.27	3.12
					99	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	36.91	3.14	38.64	3.20
					102	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	36.27	3.22	38.07	3.27
					108	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	35.69	3.30	37.54	3.35
					111	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	35.15	3.37	37.06	3.43
					115	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.43	34.65	3.45	36.62	3.51

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
18	18			36	68	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	41.03	2.95	42.78	3.00
					70	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	40.65	2.98	42.43	3.03
					73	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	39.94	3.05	41.77	3.10
					77	30.05	2.90	34.89	2.96	36.13	3.02	36.83	3.04	39.27	3.12	41.16	3.17
					81	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	38.64	3.20	40.59	3.25
					84	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	38.07	3.27	40.08	3.32
					88	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	37.54	3.35	39.61	3.40
					91	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	37.06	3.43	39.19	3.48
					95	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.42	36.62	3.51	38.81	3.56
					99	30.05	3.37	30.80	3.43	32.40	3.48	33.28	3.51	36.24	3.59	38.48	3.64
					102	30.05	3.46	30.29	3.51	31.94	3.57	32.85	3.60	35.90	3.67	38.20	3.72
					108	30.05	3.59	29.60	3.64	31.34	3.70	32.30	3.72	35.48	3.80	37.87	3.85
					111	30.05	3.68	29.21	3.73	31.01	3.79	31.99	3.81	35.26	3.89	37.71	3.94
					115	30.05	3.77	28.86	3.82	30.72	3.88	31.73	3.90	35.08	3.98	37.59	4.03
18	24			42	68	30.05	2.72	37.09	2.78	38.19	2.84	38.82	2.87	39.50	2.90	41.03	2.95
					70	30.05	2.76	36.63	2.82	37.75	2.87	38.40	2.90	39.09	2.93	40.65	2.98
					73	30.05	2.83	35.73	2.89	36.92	2.94	37.59	2.97	38.32	3.00	39.94	3.05
					77	30.05	2.90	34.89	2.96	36.13	3.02	36.83	3.04	37.59	3.07	39.27	3.12
					81	30.05	2.97	34.09	3.03	35.39	3.09	36.12	3.12	36.91	3.14	38.64	3.20
					84	30.05	3.05	33.34	3.11	34.70	3.16	35.46	3.19	36.27	3.22	38.07	3.27
					88	30.05	3.13	32.63	3.19	34.05	3.24	34.84	3.27	35.69	3.30	37.54	3.35
					91	30.05	3.21	31.98	3.26	33.45	3.32	34.27	3.35	35.15	3.37	37.06	3.43
					95	30.05	3.29	31.37	3.35	32.90	3.40	34.00	3.42	34.65	3.45	36.62	3.51
					99	30.05	3.37	30.80	3.43	32.40	3.48	33.28	3.51	34.21	3.54	36.24	3.59
					102	30.05	3.46	30.29	3.51	31.94	3.57	32.85	3.60	33.81	3.62	35.90	3.67
					108	30.05	3.59	29.60	3.64	31.34	3.70	32.30	3.72	33.30	3.75	35.48	3.80
					111	30.05	3.68	29.21	3.73	31.01	3.79	31.99	3.81	33.02	3.84	35.26	3.89
					115	30.05	3.77	28.86	3.82	30.72	3.88	31.73	3.90	32.79	3.93	35.08	3.98
24	24			48	68	38.23	2.40	39.73	2.45	41.25	2.50	42.03	2.53	42.80	2.55	44.37	2.60
					70	37.57	2.46	39.07	2.52	40.60	2.57	41.37	2.59	42.15	2.62	43.72	2.67
					73	36.90	2.53	38.41	2.58	39.94	2.63	40.71	2.66	41.49	2.68	43.07	2.74
					77	36.24	2.60	37.75	2.65	39.29	2.70	40.06	2.73	40.84	2.75	42.42	2.80
					81	35.58	2.66	37.10	2.72	38.63	2.77	39.41	2.80	40.19	2.82	41.77	2.87
					84	34.93	2.73	36.44	2.79	37.98	2.84	38.76	2.87	39.54	2.89	41.13	2.94
					88	34.60	2.77	36.12	2.82	37.66	2.87	38.44	2.90	39.22	2.93	40.80	2.98
					91	33.94	2.84	35.47	2.89	37.01	2.95	37.79	2.97	38.57	3.00	40.16	3.05
					95	33.29	2.91	34.81	2.96	36.36	3.02	34.00	3.42	37.93	3.07	39.52	3.13
					99	32.64	2.98	34.17	3.04	35.72	3.09	36.50	3.12	37.29	3.15	38.88	3.20
					102	31.99	3.06	33.52	3.11	35.07	3.17	35.86	3.19	36.65	3.22	38.24	3.28
					108	31.34	3.13	32.87	3.19	34.43	3.24	35.22	3.27	36.01	3.30	37.61	3.35
					111	30.70	3.21	32.23	3.27	33.79	3.32	34.58	3.35	35.37	3.38	36.97	3.43
					115	30.05	3.29	31.59	3.34	33.15	3.40	33.94	3.43	34.73	3.46	36.34	3.51

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7		21	68	18.56	1.34	22.91	1.37	23.59	1.39	23.97	1.41	25.34	1.45	26.42	1.47
					70	18.56	1.35	22.62	1.38	23.32	1.41	23.71	1.43	25.11	1.47	26.21	1.49
					73	18.56	1.39	22.07	1.42	22.80	1.45	23.22	1.46	24.67	1.50	25.80	1.52
					77	18.56	1.42	21.55	1.45	22.32	1.48	22.75	1.49	24.25	1.53	25.42	1.56
					81	18.56	1.46	21.05	1.49	21.86	1.52	22.31	1.53	23.87	1.57	25.07	1.60
					84	18.56	1.50	20.59	1.53	21.43	1.55	21.90	1.57	23.51	1.61	24.75	1.63
					88	18.56	1.54	20.16	1.56	21.03	1.59	21.52	1.61	23.19	1.64	24.46	1.67
					91	18.56	1.57	19.75	1.60	20.66	1.63	21.17	1.64	22.89	1.68	24.20	1.71
					95	18.56	1.61	19.37	1.64	20.32	1.67	21.00	1.68	22.62	1.72	23.97	1.75
					99	18.56	1.66	19.03	1.68	20.01	1.71	20.55	1.72	22.38	1.76	23.77	1.79
					102	18.56	1.70	18.71	1.73	19.73	1.75	20.29	1.77	22.17	1.80	23.60	1.83
					108	18.56	1.76	18.28	1.79	19.36	1.82	19.95	1.83	21.91	1.87	23.39	1.89
					111	18.56	1.81	18.04	1.83	19.15	1.86	19.76	1.87	21.78	1.91	23.29	1.94
					115	18.56	1.85	17.82	1.88	18.97	1.90	19.60	1.92	21.67	1.96	23.22	1.98
7	7	9		23	68	20.33	1.46	25.09	1.50	25.83	1.53	26.26	1.54	27.76	1.59	28.94	1.61
					70	20.33	1.48	24.78	1.52	25.54	1.55	25.97	1.56	27.50	1.60	28.70	1.63
					73	20.33	1.52	24.17	1.55	24.97	1.58	25.43	1.60	27.02	1.64	28.26	1.67
					77	20.33	1.56	23.60	1.59	24.44	1.62	24.92	1.64	26.56	1.68	27.84	1.71
					81	20.33	1.60	23.06	1.63	23.94	1.66	24.44	1.68	26.14	1.72	27.46	1.75
					84	20.33	1.64	22.55	1.67	23.47	1.70	23.99	1.72	25.75	1.76	27.11	1.79
					88	20.33	1.68	22.08	1.71	23.03	1.74	23.57	1.76	25.39	1.80	26.79	1.83
					91	20.33	1.72	21.63	1.76	22.63	1.79	23.18	1.80	25.07	1.84	26.51	1.87
					95	20.33	1.77	21.22	1.80	22.26	1.83	23.00	1.84	24.78	1.89	26.25	1.91
					99	20.33	1.81	20.84	1.84	21.92	1.87	22.51	1.89	24.51	1.93	26.03	1.96
					102	20.33	1.86	20.49	1.89	21.61	1.92	22.22	1.93	24.28	1.98	25.84	2.00
					108	20.33	1.93	20.03	1.96	21.20	1.99	21.85	2.00	24.00	2.05	25.62	2.07
					111	20.33	1.98	19.76	2.01	20.98	2.04	21.64	2.05	23.85	2.09	25.51	2.12
					115	20.33	2.03	19.52	2.06	20.78	2.09	21.46	2.10	23.73	2.14	25.43	2.17
7	7	12		26	68	22.98	1.66	28.36	1.69	29.20	1.73	29.68	1.74	31.38	1.79	32.71	1.82
					70	22.98	1.68	28.01	1.71	28.87	1.75	29.36	1.76	31.09	1.81	32.45	1.85
					73	22.98	1.72	27.33	1.76	28.23	1.79	28.75	1.81	30.54	1.86	31.94	1.89
					77	22.98	1.76	26.68	1.80	27.63	1.83	28.17	1.85	30.03	1.90	31.47	1.93
					81	22.98	1.81	26.07	1.84	27.06	1.88	27.62	1.90	29.55	1.94	31.04	1.97
					84	22.98	1.85	25.49	1.89	26.53	1.92	27.11	1.94	29.11	1.99	30.65	2.02
					88	22.98	1.90	24.95	1.94	26.04	1.97	26.64	1.99	28.71	2.04	30.29	2.07
					91	22.98	1.95	24.45	1.99	25.58	2.02	26.21	2.04	28.34	2.08	29.97	2.11
					95	22.98	2.00	23.99	2.03	25.16	2.07	26.00	2.08	28.01	2.13	29.68	2.16
					99	22.98	2.05	23.56	2.08	24.77	2.12	25.45	2.14	27.71	2.18	29.43	2.21
					102	22.98	2.10	23.16	2.14	24.43	2.17	25.12	2.19	27.45	2.23	29.21	2.26
					108	22.98	2.18	22.64	2.22	23.97	2.25	24.70	2.27	27.13	2.31	28.96	2.34
					111	22.98	2.24	22.33	2.27	23.71	2.30	24.46	2.32	26.96	2.37	28.84	2.40
					115	22.98	2.29	22.07	2.33	23.49	2.36	24.26	2.37	26.83	2.42	28.75	2.45

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	15		29	68	25.63	1.85	31.64	1.89	32.57	1.93	33.11	1.95	33.69	1.96	35.00	2.00
					70	25.63	1.87	31.24	1.91	32.20	1.95	32.75	1.97	33.34	1.99	34.67	2.02
					73	25.63	1.92	30.48	1.96	31.49	2.00	32.06	2.02	32.68	2.03	34.06	2.07
					77	25.63	1.97	29.76	2.01	30.82	2.05	31.42	2.06	32.06	2.08	33.49	2.12
					81	25.63	2.02	29.08	2.06	30.19	2.10	30.81	2.11	31.48	2.13	32.96	2.17
					84	25.63	2.07	28.43	2.11	29.59	2.15	30.24	2.17	30.94	2.18	32.47	2.22
					88	25.63	2.12	27.83	2.16	29.04	2.20	29.72	2.22	30.44	2.24	32.02	2.27
					91	25.63	2.17	27.27	2.21	28.53	2.25	29.23	2.27	29.98	2.29	31.61	2.32
					95	25.63	2.23	26.75	2.27	28.06	2.31	29.00	2.32	29.56	2.34	31.24	2.38
					99	25.63	2.29	26.27	2.33	27.63	2.36	28.38	2.38	29.18	2.40	30.91	2.43
					102	25.63	2.34	25.83	2.38	27.24	2.42	28.02	2.44	28.84	2.46	30.62	2.49
					108	25.63	2.43	25.25	2.47	26.74	2.51	27.55	2.53	28.41	2.54	30.26	2.58
					111	25.63	2.49	24.91	2.53	26.45	2.57	27.28	2.59	28.17	2.60	30.07	2.64
					115	25.63	2.56	24.61	2.59	26.20	2.63	27.06	2.65	27.97	2.67	29.92	2.70
7	7	18		32	68	28.28	2.04	34.91	2.08	35.94	2.13	36.53	2.15	38.62	2.21	40.26	2.25
					70	28.28	2.06	34.47	2.11	35.53	2.15	36.14	2.17	38.26	2.23	39.93	2.27
					73	28.28	2.12	33.63	2.16	34.75	2.20	35.38	2.22	37.59	2.28	39.31	2.32
					77	28.28	2.17	32.84	2.21	34.00	2.26	34.67	2.28	36.96	2.34	38.74	2.38
					81	28.28	2.23	32.08	2.27	33.31	2.31	34.00	2.33	36.37	2.39	38.21	2.43
					84	28.28	2.28	31.38	2.33	32.66	2.37	33.37	2.39	35.83	2.45	37.72	2.49
					88	28.28	2.34	30.71	2.38	32.05	2.43	32.79	2.45	35.33	2.51	37.28	2.54
					91	28.28	2.40	30.09	2.44	31.48	2.49	32.26	2.51	34.88	2.56	36.88	2.60
					95	28.28	2.46	29.52	2.50	30.97	2.55	32.00	2.56	34.47	2.62	36.53	2.66
					99	28.28	2.52	28.99	2.57	30.49	2.61	31.32	2.63	34.11	2.69	36.22	2.72
					102	28.28	2.59	28.51	2.63	30.06	2.67	30.92	2.69	33.79	2.75	35.96	2.79
					108	28.28	2.68	27.86	2.73	29.50	2.77	30.40	2.79	33.39	2.85	35.64	2.88
					111	28.28	2.75	27.49	2.79	29.18	2.83	30.11	2.85	33.18	2.91	35.49	2.95
					115	28.28	2.82	27.16	2.86	28.91	2.90	29.86	2.92	33.02	2.98	35.38	3.02
7	7	24		38	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9		25	68	22.09	1.59	27.27	1.63	28.08	1.66	28.54	1.68	30.17	1.72	31.45	1.75
					70	22.09	1.61	26.93	1.65	27.76	1.68	28.23	1.70	29.89	1.74	31.20	1.77
					73	22.09	1.65	26.27	1.69	27.14	1.72	27.64	1.74	29.36	1.78	30.71	1.81
					77	22.09	1.70	25.65	1.73	26.57	1.76	27.08	1.78	28.87	1.83	30.26	1.86
					81	22.09	1.74	25.07	1.77	26.02	1.81	26.56	1.82	28.41	1.87	29.85	1.90
					84	22.09	1.78	24.51	1.82	25.51	1.85	26.07	1.87	27.99	1.91	29.47	1.94
					88	22.09	1.83	23.99	1.86	25.04	1.90	25.62	1.91	27.60	1.96	29.12	1.99
					91	22.09	1.87	23.51	1.91	24.60	1.94	25.20	1.96	27.25	2.00	28.81	2.03
					95	22.09	1.92	23.06	1.96	24.19	1.99	25.00	2.00	26.93	2.05	28.54	2.08
					99	22.09	1.97	22.65	2.00	23.82	2.04	24.47	2.05	26.65	2.10	28.30	2.13
					102	22.09	2.02	22.27	2.05	23.49	2.09	24.15	2.10	26.40	2.15	28.09	2.18
					108	22.09	2.10	21.77	2.13	23.05	2.16	23.75	2.18	26.09	2.22	27.85	2.25
					111	22.09	2.15	21.48	2.18	22.80	2.21	23.52	2.23	25.92	2.28	27.73	2.30
					115	22.09	2.20	21.22	2.24	22.58	2.27	23.33	2.28	25.80	2.33	27.64	2.36
7	9	12		28	68	24.74	1.78	30.55	1.82	31.45	1.86	31.97	1.88	33.79	1.93	35.23	1.97
					70	24.74	1.81	30.16	1.84	31.09	1.88	31.62	1.90	33.48	1.95	34.94	1.99
					73	24.74	1.85	29.43	1.89	30.40	1.93	30.96	1.95	32.89	2.00	34.40	2.03
					77	24.74	1.90	28.73	1.94	29.75	1.98	30.33	1.99	32.34	2.05	33.90	2.08
					81	24.74	1.95	28.07	1.99	29.14	2.02	29.75	2.04	31.82	2.09	33.43	2.13
					84	24.74	2.00	27.45	2.04	28.57	2.07	29.20	2.09	31.35	2.14	33.01	2.18
					88	24.74	2.05	26.87	2.09	28.04	2.12	28.69	2.14	30.91	2.19	32.62	2.23
					91	24.74	2.10	26.33	2.14	27.55	2.17	28.22	2.19	30.52	2.24	32.27	2.28
					95	24.74	2.15	25.83	2.19	27.10	2.23	28.00	2.24	30.16	2.30	31.96	2.33
					99	24.74	2.21	25.37	2.25	26.68	2.28	27.40	2.30	29.84	2.35	31.69	2.38
					102	24.74	2.26	24.94	2.30	26.30	2.34	27.05	2.35	29.56	2.41	31.46	2.44
					108	24.74	2.35	24.38	2.39	25.81	2.42	26.60	2.44	29.22	2.49	31.19	2.52
					111	24.74	2.41	24.05	2.44	25.53	2.48	26.34	2.50	29.04	2.55	31.05	2.58
					115	24.74	2.47	23.76	2.50	25.30	2.54	26.13	2.56	28.89	2.61	30.96	2.64
7	9	15		31	68	27.40	1.97	33.82	2.02	34.82	2.06	35.39	2.08	36.01	2.10	37.41	2.14
					70	27.40	2.00	33.40	2.04	34.42	2.08	35.01	2.10	35.64	2.12	37.07	2.16
					73	27.40	2.05	32.58	2.09	33.66	2.13	34.27	2.15	34.94	2.17	36.41	2.21
					77	27.40	2.10	31.81	2.15	32.94	2.19	33.58	2.21	34.27	2.23	35.80	2.26
					81	27.40	2.16	31.08	2.20	32.27	2.24	32.93	2.26	33.65	2.28	35.23	2.32
					84	27.40	2.21	30.40	2.25	31.64	2.29	32.33	2.31	33.07	2.33	34.71	2.37
					88	27.40	2.27	29.75	2.31	31.05	2.35	31.77	2.37	32.54	2.39	34.23	2.43
					91	27.40	2.32	29.15	2.37	30.50	2.41	31.25	2.43	32.05	2.45	33.79	2.48
					95	27.40	2.38	28.60	2.43	30.00	2.47	31.00	2.48	31.60	2.51	33.39	2.54
					99	27.40	2.44	28.09	2.49	29.54	2.53	30.34	2.55	31.19	2.57	33.04	2.60
					102	27.40	2.51	27.62	2.55	29.12	2.59	29.95	2.61	30.83	2.63	32.73	2.66
					108	27.40	2.60	26.99	2.64	28.58	2.68	29.45	2.70	30.36	2.72	32.35	2.76
					111	27.40	2.67	26.63	2.71	28.27	2.75	29.17	2.77	30.11	2.78	32.15	2.82
					115	27.40	2.73	26.31	2.77	28.01	2.81	28.93	2.83	29.90	2.85	31.99	2.89

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	18		34	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	9	24		40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	12	12		31	68	27.40	1.97	33.82	2.02	34.82	2.06	35.39	2.08	37.41	2.14	39.00	2.18
					70	27.40	2.00	33.40	2.04	34.42	2.08	35.01	2.10	37.07	2.16	38.69	2.20
					73	27.40	2.05	32.58	2.09	33.66	2.13	34.27	2.15	36.41	2.21	38.08	2.25
					77	27.40	2.10	31.81	2.15	32.94	2.19	33.58	2.21	35.80	2.26	37.53	2.30
					81	27.40	2.16	31.08	2.20	32.27	2.24	32.93	2.26	35.23	2.32	37.01	2.35
					84	27.40	2.21	30.40	2.25	31.64	2.29	32.33	2.31	34.71	2.37	36.54	2.41
					88	27.40	2.27	29.75	2.31	31.05	2.35	31.77	2.37	34.23	2.43	36.11	2.46
					91	27.40	2.32	29.15	2.37	30.50	2.41	31.25	2.43	33.79	2.48	35.73	2.52
					95	27.40	2.38	28.60	2.43	30.00	2.47	31.00	2.48	33.39	2.54	35.39	2.58
					99	27.40	2.44	28.09	2.49	29.54	2.53	30.34	2.55	33.04	2.60	35.09	2.64
					102	27.40	2.51	27.62	2.55	29.12	2.59	29.95	2.61	32.73	2.66	34.83	2.70
					108	27.40	2.60	26.99	2.64	28.58	2.68	29.45	2.70	32.35	2.76	34.53	2.79
					111	27.40	2.67	26.63	2.71	28.27	2.75	29.17	2.77	32.15	2.82	34.38	2.86
					115	27.40	2.73	26.31	2.77	28.01	2.81	28.93	2.83	31.99	2.89	34.28	2.92

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	15		34	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	12	18		37	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	12	24		43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15	15		37	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	15	18		40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	15	24		46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	18	18	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
9	9	9	27	68	23.86	1.72	29.45	1.76	30.32	1.79	30.82	1.81	32.58	1.86	33.97	1.89	
				70	23.86	1.74	29.09	1.78	29.98	1.82	30.49	1.83	32.28	1.88	33.69	1.92	
				73	23.86	1.79	28.38	1.82	29.32	1.86	29.85	1.88	31.71	1.93	33.17	1.96	
				77	23.86	1.83	27.70	1.87	28.69	1.90	29.25	1.92	31.18	1.97	32.68	2.00	
				81	23.86	1.88	27.07	1.92	28.10	1.95	28.68	1.97	30.69	2.02	32.24	2.05	
				84	23.86	1.93	26.47	1.96	27.55	2.00	28.16	2.02	30.23	2.07	31.83	2.10	
				88	23.86	1.97	25.91	2.01	27.04	2.05	27.67	2.06	29.81	2.11	31.45	2.15	
				91	23.86	2.02	25.39	2.06	26.57	2.10	27.22	2.11	29.43	2.16	31.12	2.20	
				95	23.86	2.08	24.91	2.11	26.13	2.15	27.00	2.16	29.08	2.21	30.82	2.25	
				99	23.86	2.13	24.46	2.17	25.73	2.20	26.43	2.22	28.78	2.27	30.56	2.30	
				102	23.86	2.18	24.05	2.22	25.37	2.25	26.09	2.27	28.51	2.32	30.34	2.35	
				108	23.86	2.26	23.51	2.30	24.89	2.34	25.65	2.35	28.17	2.40	30.07	2.43	
9	9	12	30	68	26.51	1.91	32.73	1.95	33.69	1.99	34.25	2.01	36.20	2.07	37.74	2.11	
				70	26.51	1.93	32.32	1.98	33.31	2.02	33.88	2.04	35.87	2.09	37.44	2.13	
				73	26.51	1.98	31.53	2.03	32.57	2.07	33.17	2.09	35.24	2.14	36.86	2.18	
				77	26.51	2.03	30.78	2.08	31.88	2.12	32.50	2.14	34.65	2.19	36.32	2.23	
				81	26.51	2.09	30.08	2.13	31.23	2.17	31.87	2.19	34.10	2.24	35.82	2.28	
				84	26.51	2.14	29.42	2.18	30.61	2.22	31.29	2.24	33.59	2.30	35.36	2.33	
				88	26.51	2.19	28.79	2.24	30.05	2.27	30.74	2.29	33.12	2.35	34.95	2.38	
				91	26.51	2.25	28.21	2.29	29.52	2.33	30.24	2.35	32.70	2.40	34.58	2.44	
				95	26.51	2.31	27.68	2.35	29.03	2.39	30.00	2.40	32.32	2.46	34.24	2.50	
				99	26.51	2.37	27.18	2.41	28.59	2.44	29.36	2.46	31.97	2.52	33.96	2.55	
				102	26.51	2.42	26.72	2.47	28.18	2.50	28.98	2.52	31.68	2.58	33.71	2.61	
				108	26.51	2.52	26.12	2.56	27.66	2.60	28.50	2.61	31.30	2.67	33.42	2.70	
111	26.51	2.58	25.77	2.62	27.36	2.66	28.22	2.68	31.11	2.73	33.27	2.76					
115	26.51	2.64	25.46	2.68	27.10	2.72	27.99	2.74	30.96	2.79	33.17	2.83					

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	15		33	68	29.16	2.10	36.00	2.15	37.06	2.19	37.67	2.21	38.34	2.23	39.82	2.28
					70	29.16	2.13	35.55	2.17	36.64	2.22	37.27	2.24	37.94	2.26	39.46	2.30
					73	29.16	2.18	34.68	2.23	35.83	2.27	36.48	2.29	37.19	2.32	38.76	2.36
					77	29.16	2.24	33.86	2.28	35.07	2.33	35.75	2.35	36.48	2.37	38.11	2.41
					81	29.16	2.30	33.09	2.34	34.35	2.38	35.06	2.41	35.82	2.43	37.51	2.47
					84	29.16	2.35	32.36	2.40	33.68	2.44	34.42	2.46	35.21	2.48	36.95	2.53
					88	29.16	2.41	31.67	2.46	33.05	2.50	33.82	2.52	34.64	2.54	36.43	2.58
					91	29.16	2.47	31.04	2.52	32.47	2.56	33.26	2.58	34.11	2.60	35.97	2.64
					95	29.16	2.54	30.44	2.58	31.93	2.63	33.00	2.64	33.64	2.67	35.55	2.71
					99	29.16	2.60	29.90	2.65	31.44	2.69	32.30	2.71	33.20	2.73	35.17	2.77
					102	29.16	2.67	29.40	2.71	31.00	2.75	31.88	2.78	32.82	2.80	34.84	2.84
					108	29.16	2.77	28.73	2.81	30.42	2.85	31.35	2.88	32.32	2.90	34.43	2.94
					111	29.16	2.84	28.35	2.88	30.09	2.92	31.05	2.94	32.05	2.96	34.22	3.00
					115	29.16	2.91	28.01	2.95	29.81	2.99	30.79	3.01	31.83	3.03	34.05	3.07
9	9	18		36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
9	9	24		42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12		33	68	29.16	2.10	36.00	2.15	37.06	2.19	37.67	2.21	39.82	2.28	41.52	2.32
					70	29.16	2.13	35.55	2.17	36.64	2.22	37.27	2.24	39.46	2.30	41.18	2.34
					73	29.16	2.18	34.68	2.23	35.83	2.27	36.48	2.29	38.76	2.36	40.54	2.40
					77	29.16	2.24	33.86	2.28	35.07	2.33	35.75	2.35	38.11	2.41	39.95	2.45
					81	29.16	2.30	33.09	2.34	34.35	2.38	35.06	2.41	37.51	2.47	39.40	2.51
					84	29.16	2.35	32.36	2.40	33.68	2.44	34.42	2.46	36.95	2.53	38.90	2.56
					88	29.16	2.41	31.67	2.46	33.05	2.50	33.82	2.52	36.43	2.58	38.44	2.62
					91	29.16	2.47	31.04	2.52	32.47	2.56	33.26	2.58	35.97	2.64	38.03	2.68
					95	29.16	2.54	30.44	2.58	31.93	2.63	33.00	2.64	35.55	2.71	37.67	2.75
					99	29.16	2.60	29.90	2.65	31.44	2.69	32.30	2.71	35.17	2.77	37.35	2.81
					102	29.16	2.67	29.40	2.71	31.00	2.75	31.88	2.78	34.84	2.84	37.08	2.87
					108	29.16	2.77	28.73	2.81	30.42	2.85	31.35	2.88	34.43	2.94	36.76	2.97
					111	29.16	2.84	28.35	2.88	30.09	2.92	31.05	2.94	34.22	3.00	36.60	3.04
					115	29.16	2.91	28.01	2.95	29.81	2.99	30.79	3.01	34.05	3.07	36.49	3.11
9	12	15		36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	12	18		39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	24	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
9	15	15	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
9	15	18	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15	24	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34	
				70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37	
				73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43	
				77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49	
				81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55	
				84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61	
				88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67	
				91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73	
				95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79	
				99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86	
				102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92	
				108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02	
				111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09	
				115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16	
9	18	18	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	12	12	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	12	15	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	12	18	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	12	24	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34	
				70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37	
				73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43	
				77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49	
				81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55	
				84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61	
				88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67	
				91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73	
				95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79	
				99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86	
				102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92	
				108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02	
				111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09	
				115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15	15	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	15	18	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35	
				70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37	
				73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43	
				77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48	
				81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54	
				84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60	
				88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66	
				91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73	
				95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79	
				99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85	
				102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92	
				108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02	
				111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09	
				115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17	
12	18	18	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34	
				70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37	
				73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43	
				77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49	
				81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55	
				84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61	
				88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67	
				91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73	
				95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79	
				99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86	
				102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92	
				108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02	
				111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09	
				115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15	15		45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
15	15	18		48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16
7	7	7	7	28	68	24.74	1.78	30.55	1.82	31.45	1.86	31.97	1.88	33.79	1.93	35.23	1.97
					70	24.74	1.81	30.16	1.84	31.09	1.88	31.62	1.90	33.48	1.95	34.94	1.99
					73	24.74	1.85	29.43	1.89	30.40	1.93	30.96	1.95	32.89	2.00	34.40	2.03
					77	24.74	1.90	28.73	1.94	29.75	1.98	30.33	1.99	32.34	2.05	33.90	2.08
					81	24.74	1.95	28.07	1.99	29.14	2.02	29.75	2.04	31.82	2.09	33.43	2.13
					84	24.74	2.00	27.45	2.04	28.57	2.07	29.20	2.09	31.35	2.14	33.01	2.18
					88	24.74	2.05	26.87	2.09	28.04	2.12	28.69	2.14	30.91	2.19	32.62	2.23
					91	24.74	2.10	26.33	2.14	27.55	2.17	28.22	2.19	30.52	2.24	32.27	2.28
					95	24.74	2.15	25.83	2.19	27.10	2.23	28.00	2.24	30.16	2.30	31.96	2.33
					99	24.74	2.21	25.37	2.25	26.68	2.28	27.40	2.30	29.84	2.35	31.69	2.38
					102	24.74	2.26	24.94	2.30	26.30	2.34	27.05	2.35	29.56	2.41	31.46	2.44
					108	24.74	2.35	24.38	2.39	25.81	2.42	26.60	2.44	29.22	2.49	31.19	2.52
					111	24.74	2.41	24.05	2.44	25.53	2.48	26.34	2.50	29.04	2.55	31.05	2.58
					115	24.74	2.47	23.76	2.50	25.30	2.54	26.13	2.56	28.89	2.61	30.96	2.64

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	9	30	68	26.51	1.91	32.73	1.95	33.69	1.99	34.25	2.01	36.20	2.07	37.74	2.11
					70	26.51	1.93	32.32	1.98	33.31	2.02	33.88	2.04	35.87	2.09	37.44	2.13
					73	26.51	1.98	31.53	2.03	32.57	2.07	33.17	2.09	35.24	2.14	36.86	2.18
					77	26.51	2.03	30.78	2.08	31.88	2.12	32.50	2.14	34.65	2.19	36.32	2.23
					81	26.51	2.09	30.08	2.13	31.23	2.17	31.87	2.19	34.10	2.24	35.82	2.28
					84	26.51	2.14	29.42	2.18	30.61	2.22	31.29	2.24	33.59	2.30	35.36	2.33
					88	26.51	2.19	28.79	2.24	30.05	2.27	30.74	2.29	33.12	2.35	34.95	2.38
					91	26.51	2.25	28.21	2.29	29.52	2.33	30.24	2.35	32.70	2.40	34.58	2.44
					95	26.51	2.31	27.68	2.35	29.03	2.39	30.00	2.40	32.32	2.46	34.24	2.50
					99	26.51	2.37	27.18	2.41	28.59	2.44	29.36	2.46	31.97	2.52	33.96	2.55
					102	26.51	2.42	26.72	2.47	28.18	2.50	28.98	2.52	31.68	2.58	33.71	2.61
					108	26.51	2.52	26.12	2.56	27.66	2.60	28.50	2.61	31.30	2.67	33.42	2.70
					111	26.51	2.58	25.77	2.62	27.36	2.66	28.22	2.68	31.11	2.73	33.27	2.76
					115	26.51	2.64	25.46	2.68	27.10	2.72	27.99	2.74	30.96	2.79	33.17	2.83
7	7	7	12	33	68	29.16	2.10	36.00	2.15	37.06	2.19	37.67	2.21	39.82	2.28	41.52	2.32
					70	29.16	2.13	35.55	2.17	36.64	2.22	37.27	2.24	39.46	2.30	41.18	2.34
					73	29.16	2.18	34.68	2.23	35.83	2.27	36.48	2.29	38.76	2.36	40.54	2.40
					77	29.16	2.24	33.86	2.28	35.07	2.33	35.75	2.35	38.11	2.41	39.95	2.45
					81	29.16	2.30	33.09	2.34	34.35	2.38	35.06	2.41	37.51	2.47	39.40	2.51
					84	29.16	2.35	32.36	2.40	33.68	2.44	34.42	2.46	36.95	2.53	38.90	2.56
					88	29.16	2.41	31.67	2.46	33.05	2.50	33.82	2.52	36.43	2.58	38.44	2.62
					91	29.16	2.47	31.04	2.52	32.47	2.56	33.26	2.58	35.97	2.64	38.03	2.68
					95	29.16	2.54	30.44	2.58	31.93	2.63	33.00	2.64	35.55	2.71	37.67	2.75
					99	29.16	2.60	29.90	2.65	31.44	2.69	32.30	2.71	35.17	2.77	37.35	2.81
					102	29.16	2.67	29.40	2.71	31.00	2.75	31.88	2.78	34.84	2.84	37.08	2.87
					108	29.16	2.77	28.73	2.81	30.42	2.85	31.35	2.88	34.43	2.94	36.76	2.97
					111	29.16	2.84	28.35	2.88	30.09	2.92	31.05	2.94	34.22	3.00	36.60	3.04
					115	29.16	2.91	28.01	2.95	29.81	2.99	30.79	3.01	34.05	3.07	36.49	3.11
7	7	7	15	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	18	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	7	7	24	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	9	9	32	68	28.28	2.04	34.91	2.08	35.94	2.13	36.53	2.15	38.62	2.21	40.26	2.25
					70	28.28	2.06	34.47	2.11	35.53	2.15	36.14	2.17	38.26	2.23	39.93	2.27
					73	28.28	2.12	33.63	2.16	34.75	2.20	35.38	2.22	37.59	2.28	39.31	2.32
					77	28.28	2.17	32.84	2.21	34.00	2.26	34.67	2.28	36.96	2.34	38.74	2.38
					81	28.28	2.23	32.08	2.27	33.31	2.31	34.00	2.33	36.37	2.39	38.21	2.43
					84	28.28	2.28	31.38	2.33	32.66	2.37	33.37	2.39	35.83	2.45	37.72	2.49
					88	28.28	2.34	30.71	2.38	32.05	2.43	32.79	2.45	35.33	2.51	37.28	2.54
					91	28.28	2.40	30.09	2.44	31.48	2.49	32.26	2.51	34.88	2.56	36.88	2.60
					95	28.28	2.46	29.52	2.50	30.97	2.55	32.00	2.56	34.47	2.62	36.53	2.66
					99	28.28	2.52	28.99	2.57	30.49	2.61	31.32	2.63	34.11	2.69	36.22	2.72
					102	28.28	2.59	28.51	2.63	30.06	2.67	30.92	2.69	33.79	2.75	35.96	2.79
					108	28.28	2.68	27.86	2.73	29.50	2.77	30.40	2.79	33.39	2.85	35.64	2.88
					111	28.28	2.75	27.49	2.79	29.18	2.83	30.11	2.85	33.18	2.91	35.49	2.95
					115	28.28	2.82	27.16	2.86	28.91	2.90	29.86	2.92	33.02	2.98	35.38	3.02

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	12	35	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	7	9	15	38	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	9	18	41	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdo Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	24	47	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	7	12	12	38	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	7	12	15	41	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	12	18	44	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
7	7	15	15	44	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
7	7	15	18	47	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17					

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	9	34	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	9	9	12	37	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	9	9	15	40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	18	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
7	9	12	12	40	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20
7	9	12	15	43	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	12	18	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
7	9	15	15	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
7	9	15	15	46	111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
					68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
7	12	12	12	43	102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	12	12	15	46	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
9	9	9	9	36	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
9	9	9	12	39	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	41.03	2.35	42.78	2.39
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	40.65	2.37	42.43	2.41
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	39.94	2.43	41.77	2.47
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	39.27	2.48	41.16	2.52
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	38.64	2.54	40.59	2.58
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	38.07	2.60	40.08	2.64
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	37.54	2.66	39.61	2.70
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	37.06	2.73	39.19	2.76
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	36.62	2.79	38.81	2.83
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	36.24	2.85	38.48	2.89
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	35.90	2.92	38.20	2.96
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	35.48	3.02	37.87	3.06
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	35.26	3.09	37.71	3.13					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	35.08	3.17	37.59	3.20					

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	15	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17					
9	9	9	18	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17					
9	9	12	12	42	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09					
115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17					

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	15	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
9	9	12	18	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
9	9	15	15	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09					
115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16					

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Cooling(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, WB)											
						57.2		60.8		64.4		67		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	12	12	45	68	30.05	2.17	37.09	2.21	38.19	2.26	38.82	2.28	39.50	2.30	41.03	2.35
					70	30.05	2.19	36.63	2.24	37.75	2.29	38.40	2.31	39.09	2.33	40.65	2.37
					73	30.05	2.25	35.73	2.30	36.92	2.34	37.59	2.36	38.32	2.39	39.94	2.43
					77	30.05	2.31	34.89	2.35	36.13	2.40	36.83	2.42	37.59	2.44	39.27	2.48
					81	30.05	2.36	34.09	2.41	35.39	2.46	36.12	2.48	36.91	2.50	38.64	2.54
					84	30.05	2.43	33.34	2.47	34.70	2.52	35.46	2.54	36.27	2.56	38.07	2.60
					88	30.05	2.49	32.63	2.53	34.05	2.58	34.84	2.60	35.69	2.62	37.54	2.66
					91	30.05	2.55	31.98	2.60	33.45	2.64	34.27	2.66	35.15	2.68	37.06	2.73
					95	30.05	2.61	31.37	2.66	32.90	2.71	34.00	2.72	34.65	2.75	36.62	2.79
					99	30.05	2.68	30.80	2.73	32.40	2.77	33.28	2.79	34.21	2.81	36.24	2.85
					102	30.05	2.75	30.29	2.79	31.94	2.84	32.85	2.86	33.81	2.88	35.90	2.92
					108	30.05	2.85	29.60	2.90	31.34	2.94	32.30	2.96	33.30	2.98	35.48	3.02
					111	30.05	2.92	29.21	2.97	31.01	3.01	31.99	3.03	33.02	3.05	35.26	3.09
					115	30.05	3.00	28.86	3.04	30.72	3.08	31.73	3.11	32.79	3.13	35.08	3.17
9	12	12	15	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16
12	12	12	12	48	68	34.93	2.17	36.44	2.22	37.98	2.26	38.76	2.28	39.54	2.30	41.13	2.34
					70	34.60	2.20	36.12	2.24	37.66	2.29	38.44	2.31	39.22	2.33	40.80	2.37
					73	33.94	2.26	35.47	2.30	37.01	2.34	37.79	2.36	38.57	2.39	40.16	2.43
					77	33.29	2.31	34.81	2.36	36.36	2.40	37.14	2.42	37.93	2.44	39.52	2.49
					81	32.64	2.37	34.17	2.42	35.72	2.46	36.50	2.48	37.29	2.50	38.88	2.55
					84	31.99	2.43	33.52	2.48	35.07	2.52	35.86	2.54	36.65	2.56	38.24	2.61
					88	31.34	2.49	32.87	2.54	34.43	2.58	35.22	2.60	36.01	2.62	37.61	2.67
					91	30.70	2.55	32.23	2.60	33.79	2.64	34.58	2.66	35.37	2.69	36.97	2.73
					95	30.05	2.62	31.59	2.66	33.15	2.70	34.00	2.72	34.73	2.75	36.34	2.79
					99	29.41	2.68	30.95	2.72	32.51	2.77	33.30	2.79	34.10	2.81	35.71	2.86
					102	28.77	2.74	30.31	2.79	31.88	2.83	32.67	2.85	33.47	2.88	35.08	2.92
					108	27.81	2.84	29.36	2.89	30.93	2.93	31.72	2.95	32.52	2.98	34.14	3.02
					111	27.17	2.91	28.72	2.95	30.30	3.00	31.09	3.02	31.89	3.04	33.51	3.09
					115	26.54	2.97	28.09	3.02	29.67	3.06	30.46	3.09	31.26	3.11	32.89	3.16

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 48.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9			9	-13	14.25	3.47	12.24	2.96	10.64	2.62	7.62	1.95	6.77	1.66	4.82	1.17	
				5	11.91	2.21	11.62	2.23	11.34	2.25	10.90	2.38	10.77	2.30	10.49	2.32	
				17	11.36	1.88	11.21	1.91	11.01	1.92	10.90	2.05	10.82	1.97	10.61	1.99	
				32	11.51	1.41	11.34	1.42	11.17	1.44	10.90	1.52	10.82	1.46	10.65	1.48	
				47	11.83	1.03	11.42	1.00	11.27	1.01	10.90	1.07	10.81	1.00	10.19	0.95	
				50	12.64	1.08	12.26	1.13	11.90	1.10	11.90	1.11	11.61	1.13	11.44	1.14	
				59	13.71	1.12	13.49	1.16	13.21	1.11	13.11	1.14	12.86	1.17	12.69	1.18	
				12	-13	18.30	4.18	15.72	3.57	13.67	3.16	9.79	2.35	8.70	2.00	6.19	1.41
					5	15.29	2.66	14.93	2.69	14.56	2.71	14.00	2.87	13.83	2.78	13.47	2.80
					17	14.59	2.27	14.40	2.30	14.15	2.32	14.00	2.47	13.89	2.37	13.63	2.40
					32	14.79	1.69	14.57	1.71	14.34	1.73	14.00	1.83	13.90	1.76	13.68	1.78
					47	15.20	1.24	14.67	1.20	14.47	1.21	14.00	1.29	13.88	1.20	13.09	1.14
			50		16.24	1.30	15.75	1.36	15.28	1.33	15.28	1.34	14.91	1.36	14.70	1.37	
			59	17.61	1.35	17.32	1.39	16.96	1.34	16.84	1.38	16.52	1.41	16.29	1.43		
			15	-13	23.53	5.93	20.22	5.06	17.57	4.48	12.59	3.33	11.18	2.84	7.96	2.00	
				5	19.66	3.77	19.20	3.81	18.73	3.85	18.00	4.07	17.79	3.94	17.32	3.97	
				17	18.75	3.22	18.52	3.26	18.19	3.29	18.00	3.50	17.86	3.36	17.52	3.41	
				32	19.01	2.40	18.73	2.42	18.44	2.46	18.00	2.60	17.87	2.49	17.58	2.53	
47	19.54	1.76		18.86	1.71	18.61	1.72	18.00	1.83	17.85	1.71	16.83	1.62				
50	20.88	1.84		20.25	1.93	19.65	1.89	19.65	1.89	19.17	1.93	18.90	1.94				
			59	22.64	1.91	22.27	1.98	21.81	1.90	21.65	1.95	21.24	2.00	20.95	2.02		
			18	-13	26.14	6.03	22.46	5.14	19.52	4.55	13.99	3.38	12.42	2.89	8.85	2.03	
				5	21.85	3.83	21.33	3.88	20.81	3.91	20.00	4.14	19.76	4.00	19.24	4.04	
				17	20.84	3.28	20.58	3.32	20.21	3.34	20.00	3.56	19.84	3.42	19.47	3.47	
				32	21.13	2.44	20.81	2.46	20.49	2.50	20.00	2.64	19.86	2.54	19.54	2.57	
				47	21.71	1.79	20.95	1.74	20.67	1.75	20.00	1.86	19.83	1.74	18.70	1.64	
				50	23.20	1.87	22.50	1.96	21.83	1.92	21.83	1.93	21.30	1.96	21.00	1.98	
			59	25.16	1.94	24.74	2.01	24.23	1.93	24.06	1.98	23.60	2.04	23.28	2.06		
			24	-13	35.29	7.71	30.32	6.58	26.35	5.83	18.88	4.33	16.77	3.69	11.94	2.60	
				5	29.50	4.91	28.79	4.96	28.09	5.00	27.00	5.30	26.68	5.12	25.98	5.17	
				17	28.13	4.19	27.78	4.25	27.28	4.28	27.00	4.56	26.79	4.37	26.28	4.44	
				32	28.52	3.13	28.09	3.15	27.66	3.20	27.00	3.38	26.80	3.24	26.38	3.29	
47	29.31	2.28		28.28	2.22	27.91	2.24	27.00	2.38	26.77	2.22	25.25	2.10				
50	31.32	2.39		30.37	2.51	29.47	2.45	29.47	2.46	28.75	2.50	28.35	2.53				
			59	33.96	2.49	33.40	2.57	32.71	2.47	32.48	2.54	31.86	2.61	31.42	2.63		
			18	-13	24.54	6.86	20.52	5.44	19.69	5.52	15.24	4.02	13.51	3.35	9.63	2.17	
				5	23.84	4.62	23.27	4.67	22.69	4.74	21.80	4.92	21.55	4.84	20.98	4.88	
				17	23.23	4.00	22.83	4.04	22.43	4.08	21.80	4.23	21.63	4.17	21.22	4.21	
				32	23.04	2.97	22.69	3.00	22.34	3.03	21.80	3.14	21.65	3.08	21.30	3.11	
				47	23.10	2.09	22.83	2.11	22.53	2.13	21.80	2.21	21.92	2.17	21.62	2.19	
50	25.08	2.22		24.47	2.25	24.01	2.28	23.79	2.30	23.22	2.34	22.89	2.36				
			59	27.46	2.31	26.94	2.34	26.45	2.38	26.23	2.39	25.62	2.43	25.26	2.45		
			21	-13	28.02	7.33	23.44	5.81	22.49	5.90	17.41	4.29	15.44	3.58	11.00	2.32	
				5	27.23	4.94	26.58	4.99	25.92	5.06	24.90	5.25	24.62	5.16	23.96	5.22	
				17	26.53	4.27	26.07	4.32	25.61	4.36	24.90	4.52	24.70	4.45	24.24	4.50	
				32	26.32	3.18	25.92	3.21	25.52	3.24	24.90	3.35	24.73	3.29	24.33	3.32	
				47	26.39	2.23	26.08	2.25	25.74	2.27	24.90	2.36	25.04	2.31	24.69	2.34	
50	28.65	2.37		27.95	2.41	27.42	2.44	27.18	2.45	26.52	2.50	26.14	2.52				
			59	31.37	2.47	30.77	2.50	30.21	2.54	29.95	2.55	29.26	2.60	28.86	2.62		

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)													
						57		60.8		64.4		69.98		71.6		75.2			
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)		
9	15		24	-13	32.53	7.58	27.21	6.01	26.10	6.10	20.21	4.44	17.92	3.70	12.77	2.40			
				5	31.60	5.11	30.85	5.16	30.08	5.23	28.90	5.43	28.57	5.34	27.81	5.39			
				17	30.79	4.42	30.26	4.46	29.73	4.51	28.90	4.67	28.67	4.60	28.14	4.65			
				32	30.55	3.28	30.09	3.31	29.62	3.34	28.90	3.46	28.70	3.41	28.24	3.44			
				47	30.63	2.31	30.27	2.33	29.87	2.35	28.90	2.44	29.06	2.39	28.66	2.42			
				50	33.25	2.45	32.44	2.49	31.83	2.52	31.54	2.54	30.78	2.58	30.34	2.60			
				59	36.41	2.55	35.71	2.59	35.07	2.62	34.77	2.64	33.96	2.68	33.49	2.71			
				9	18	27	-13	34.78	8.17	29.09	6.47	27.90	6.57	21.61	4.78	19.16	3.99	13.66	2.58
							5	33.79	5.50	32.98	5.56	32.17	5.64	30.90	5.85	30.55	5.75	29.74	5.81
							17	32.92	4.76	32.36	4.81	31.79	4.86	30.90	5.03	30.66	4.96	30.08	5.01
							32	32.66	3.54	32.17	3.57	31.67	3.61	30.90	3.73	30.69	3.67	30.19	3.70
							47	32.75	2.49	32.36	2.51	31.94	2.53	30.90	2.63	31.07	2.58	30.64	2.61
50	35.55	2.64	34.68				2.68	34.03	2.72	33.72	2.74	32.91	2.78	32.44	2.81				
				59	38.93	2.75	38.18	2.79	37.49	2.83	37.17	2.84	36.31	2.89	35.81	2.92			
				9	24	33	-13	38.27	9.16	32.01	7.26	30.70	7.37	23.78	5.36	21.08	4.47	15.03	2.90
							5	37.18	6.17	36.29	6.23	35.39	6.32	34.00	6.56	33.62	6.45	32.72	6.52
							17	36.23	5.34	35.60	5.40	34.98	5.45	34.00	5.65	33.73	5.57	33.10	5.62
							32	35.94	3.97	35.40	4.01	34.85	4.04	34.00	4.19	33.77	4.12	33.22	4.15
							47	36.03	2.79	35.61	2.82	35.14	2.84	34.00	2.95	34.19	2.89	33.72	2.92
50	39.12	2.96	38.16				3.01	37.44	3.05	37.11	3.07	36.21	3.12	35.70	3.15				
				59	42.83	3.08	42.01	3.13	41.25	3.17	40.90	3.19	39.95	3.24	39.40	3.28			
				12	12	24	-13	31.51	7.76	26.36	6.15	25.29	6.25	19.58	4.55	17.36	3.79	12.37	2.46
							5	30.62	5.23	29.89	5.28	29.15	5.36	28.00	5.56	27.68	5.47	26.94	5.53
							17	29.83	4.52	29.32	4.57	28.80	4.62	28.00	4.78	27.78	4.72	27.26	4.76
							32	29.59	3.37	29.15	3.40	28.70	3.43	28.00	3.55	27.81	3.49	27.36	3.52
							47	29.68	2.37	29.33	2.39	28.94	2.41	28.00	2.50	28.15	2.45	27.77	2.48
50	32.22	2.51	31.43				2.55	30.83	2.58	30.56	2.60	29.82	2.64	29.40	2.67				
				59	35.27	2.61	34.60	2.65	33.97	2.69	33.68	2.70	32.90	2.75	32.45	2.78			
				12	15	27	-13	36.02	9.35	30.13	7.41	28.90	7.52	22.38	5.47	19.84	4.56	14.14	2.96
							5	34.99	6.30	34.16	6.36	33.31	6.45	32.00	6.70	31.64	6.59	30.79	6.65
							17	34.10	5.45	33.51	5.50	32.92	5.56	32.00	5.76	31.75	5.68	31.16	5.73
							32	33.82	4.05	33.31	4.09	32.80	4.13	32.00	4.27	31.78	4.20	31.27	4.24
							47	33.91	2.85	33.52	2.87	33.07	2.90	32.00	3.01	32.17	2.95	31.73	2.98
50	36.82	3.02	35.92				3.07	35.24	3.11	34.93	3.13	34.08	3.18	33.60	3.21				
				59	40.31	3.15	39.54	3.19	38.83	3.24	38.50	3.26	37.60	3.31	37.08	3.34			
				12	18	30	-13	38.27	9.16	32.01	7.26	30.70	7.37	23.78	5.36	21.08	4.47	15.03	2.90
							5	37.18	6.17	36.29	6.23	35.39	6.32	34.00	6.56	33.62	6.45	32.72	6.52
							17	36.23	5.34	35.60	5.40	34.98	5.45	34.00	5.65	33.73	5.57	33.10	5.62
							32	35.94	3.97	35.40	4.01	34.85	4.04	34.00	4.19	33.77	4.12	33.22	4.15
							47	36.03	2.79	35.61	2.82	35.14	2.84	34.00	2.95	34.19	2.89	33.72	2.92
50	39.12	2.96	38.16				3.01	37.44	3.05	37.11	3.07	36.21	3.12	35.70	3.15				
				59	42.83	3.08	42.01	3.13	41.25	3.17	40.90	3.19	39.95	3.24	39.40	3.28			
				12	24	36	-13	38.94	9.16	32.57	7.26	31.25	7.37	24.20	5.36	21.45	4.47	15.29	2.90
							5	37.84	6.17	36.93	6.23	36.02	6.32	34.60	6.56	34.21	6.45	33.30	6.52
							17	36.87	5.34	36.23	5.40	35.59	5.45	34.60	5.65	34.33	5.57	33.69	5.62
							32	36.57	3.97	36.02	4.01	35.46	4.04	34.60	4.19	34.36	4.12	33.81	4.15
							47	36.67	2.79	36.24	2.82	35.76	2.84	34.60	2.95	34.79	2.89	34.31	2.92
50	39.81	2.96	38.84				3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15				
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28			

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	18			33	-13	38.27	9.16	32.01	7.26	30.70	7.37	23.78	5.36	21.08	4.47	15.03	2.90
					5	37.18	6.17	36.29	6.23	35.39	6.32	34.00	6.56	33.62	6.45	32.72	6.52
					17	36.23	5.34	35.60	5.40	34.98	5.45	34.00	5.65	33.73	5.57	33.10	5.62
					32	35.94	3.97	35.40	4.01	34.85	4.04	34.00	4.19	33.77	4.12	33.22	4.15
					47	36.03	2.79	35.61	2.82	35.14	2.84	34.00	2.95	34.19	2.89	33.72	2.92
					50	39.12	2.96	38.16	3.01	37.44	3.05	37.11	3.07	36.21	3.12	35.70	3.15
					59	42.83	3.08	42.01	3.13	41.25	3.17	40.90	3.19	39.95	3.24	39.40	3.28
18	18			36	-13	38.94	9.16	32.57	7.26	31.25	7.37	24.20	5.36	21.45	4.47	15.29	2.90
					5	37.84	6.17	36.93	6.23	36.02	6.32	34.60	6.56	34.21	6.45	33.30	6.52
					17	36.87	5.34	36.23	5.40	35.59	5.45	34.60	5.65	34.33	5.57	33.69	5.62
					32	36.57	3.97	36.02	4.01	35.46	4.04	34.60	4.19	34.36	4.12	33.81	4.15
					47	36.67	2.79	36.24	2.82	35.76	2.84	34.60	2.95	34.79	2.89	34.31	2.92
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
9	9	9		27	-13	26.23	4.90	25.01	4.94	24.30	5.01	22.87	5.07	22.15	5.14	20.72	5.14
					5	35.32	6.00	34.56	6.06	33.57	6.14	32.70	6.21	31.96	6.27	31.34	6.32
					17	34.83	5.15	34.19	5.21	33.40	5.28	32.70	5.34	32.09	5.39	31.56	5.44
					32	34.68	3.82	34.08	3.86	33.35	3.92	32.70	3.96	32.13	4.00	31.63	4.04
					47	34.54	2.69	33.98	2.72	33.31	2.76	32.70	2.79	32.16	2.82	31.69	2.85
					50	37.63	2.80	36.70	2.85	36.01	2.88	35.69	2.90	34.83	2.95	34.33	2.98
					59	41.20	2.92	40.40	2.96	39.68	3.00	39.34	3.02	38.42	3.07	37.90	3.10
9	9	12		30	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
9	9	15		33	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
9	9	18		36	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
9	12	12		33	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F,DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	12	15	36	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
9	12	18	39	59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
9	18	18	45	50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
9	18	18	45	47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
12	12	12	36	32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
				5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
12	12	18	42	17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
				-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43	
12	18	18	48	5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68	
				17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75	
				32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27	
				47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01	
				50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15	
				59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28	
9	9	9	9	36	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	9	12	39	-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
9	9	9	18	45	59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
9	9	12	12	42	50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
9	9	12	18	48	47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
					17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
9	12	12	12	45	32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43
					5	37.37	6.34	36.57	6.41	35.52	6.49	34.60	6.56	33.82	6.63	33.17	6.68
12	12	12	12	48	17	36.85	5.45	36.18	5.51	35.34	5.58	34.60	5.65	33.95	5.70	33.40	5.75
					32	36.69	4.04	36.06	4.09	35.29	4.14	34.60	4.19	33.99	4.23	33.47	4.27
					47	36.55	2.84	35.95	2.88	35.24	2.92	34.60	2.95	34.03	2.98	33.53	3.01
					50	39.81	2.96	38.84	3.01	38.10	3.05	37.76	3.07	36.85	3.12	36.33	3.15
					59	43.59	3.08	42.75	3.13	41.98	3.17	41.62	3.19	40.66	3.24	40.10	3.28
					-13	27.75	5.18	26.46	5.23	25.71	5.29	24.20	5.36	23.44	5.43	21.93	5.43

- Cooling capacity is based on 80°FDB(26.7°CDB) / 80°FDB(19.4°CWB) (indoor temperature), 95°FDB(35°CDB) (outdoor temperature).
- Heating capacity is based on 70°FDB(21.1°CDB) (indoor temperature), 47°FDB(8.33°CDB) / 43°FDB(6.11°CWB) (outdoor temperature).
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 24.6ft(7.5m) / - Level difference : 0m
- The total combination Index of connected a indoor unit is up to 48.
- At least two indoor units must be connected for operation.
- Ducted combination means mixing AC***BNZDCH/AA (MPAH) and AC***BNLDCH/AA (Slim Duct) units on the same system.
- If AJ0***BNHDCH/AA or AC0***BNZDCH/AA (MPAH) is included in the combination, the combination criteria noted on page 31 must be followed.
- This data is reference data for temperature capacity trend.

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7			7	-13	9.80	2.72	8.42	2.32	7.32	2.06	5.24	1.53	4.66	1.30	3.32	0.92	
				5	8.19	1.73	8.00	1.75	7.80	1.77	7.50	1.87	7.41	1.81	7.22	1.82	
				17	7.81	1.48	7.72	1.50	7.58	1.51	7.50	1.61	7.44	1.54	7.30	1.57	
				32	7.92	1.10	7.80	1.11	7.68	1.13	7.50	1.19	7.45	1.15	7.33	1.16	
				47	8.14	0.81	7.86	0.78	7.75	0.79	7.50	0.84	7.44	0.78	7.01	0.74	
				50	8.70	0.84	8.44	0.89	8.19	0.87	8.19	0.87	7.99	0.88	7.87	0.89	
				59	9.43	0.88	9.28	0.91	9.09	0.87	9.02	0.90	8.85	0.92	8.73	0.93	
9			9	-13	14.25	3.47	12.24	2.96	10.64	2.62	7.62	1.95	6.77	1.66	4.82	1.17	
				5	11.91	2.21	11.62	2.23	11.34	2.25	10.90	2.38	10.77	2.30	10.49	2.32	
				17	11.36	1.88	11.21	1.91	11.01	1.92	10.90	2.05	10.82	1.97	10.61	1.99	
				32	11.51	1.41	11.34	1.42	11.17	1.44	10.90	1.52	10.82	1.46	10.65	1.48	
				47	11.83	1.03	11.42	1.00	11.27	1.01	10.90	1.07	10.81	1.00	10.19	0.95	
				50	12.64	1.08	12.26	1.13	11.90	1.10	11.90	1.11	11.61	1.13	11.44	1.14	
				59	13.71	1.12	13.49	1.16	13.21	1.11	13.11	1.14	12.86	1.17	12.69	1.18	
12			12	-13	18.30	4.18	15.72	3.57	13.67	3.16	9.79	2.35	8.70	2.00	6.19	1.41	
				5	15.29	2.66	14.93	2.69	14.56	2.71	14.00	2.87	13.83	2.78	13.47	2.80	
				17	14.59	2.27	14.40	2.30	14.15	2.32	14.00	2.47	13.89	2.37	13.63	2.40	
				32	14.79	1.69	14.57	1.71	14.34	1.73	14.00	1.83	13.90	1.76	13.68	1.78	
				47	15.20	1.24	14.67	1.20	14.47	1.21	14.00	1.29	13.88	1.20	13.09	1.14	
				50	16.24	1.30	15.75	1.36	15.28	1.33	15.28	1.34	14.91	1.36	14.70	1.37	
				59	17.61	1.35	17.32	1.39	16.96	1.34	16.84	1.38	16.52	1.41	16.29	1.43	
15			15	-13	23.53	5.93	20.22	5.06	17.57	4.48	12.59	3.33	11.18	2.84	7.96	2.00	
				5	19.66	3.77	19.20	3.81	18.73	3.85	18.00	4.07	17.79	3.94	17.32	3.97	
				17	18.75	3.22	18.52	3.26	18.19	3.29	18.00	3.50	17.86	3.36	17.52	3.41	
				32	19.01	2.40	18.73	2.42	18.44	2.46	18.00	2.60	17.87	2.49	17.58	2.53	
				47	19.54	1.76	18.86	1.71	18.61	1.72	18.00	1.83	17.85	1.71	16.83	1.62	
				50	20.88	1.84	20.25	1.93	19.65	1.89	19.65	1.89	19.17	1.93	18.90	1.94	
				59	22.64	1.91	22.27	1.98	21.81	1.90	21.65	1.95	21.24	2.00	20.95	2.02	
18			18	-13	26.14	6.03	22.46	5.14	19.52	4.55	13.99	3.38	12.42	2.89	8.85	2.03	
				5	21.85	3.83	21.33	3.88	20.81	3.91	20.00	4.14	19.76	4.00	19.24	4.04	
				17	20.84	3.28	20.58	3.32	20.21	3.34	20.00	3.56	19.84	3.42	19.47	3.47	
				32	21.13	2.44	20.81	2.46	20.49	2.50	20.00	2.64	19.86	2.54	19.54	2.57	
				47	21.71	1.79	20.95	1.74	20.67	1.75	20.00	1.86	19.83	1.74	18.70	1.64	
				50	23.20	1.87	22.50	1.96	21.83	1.92	21.83	1.93	21.30	1.96	21.00	1.98	
				59	25.16	1.94	24.74	2.01	24.23	1.93	24.06	1.98	23.60	2.04	23.28	2.06	
24			24	-13	33.33	7.71	28.64	6.58	24.89	5.83	17.83	4.33	15.84	3.69	11.28	2.60	
				5	27.86	4.91	27.19	4.96	26.53	5.00	25.50	5.30	25.20	5.12	24.53	5.17	
				17	26.57	4.19	26.23	4.25	25.77	4.28	25.50	4.56	25.30	4.37	24.82	4.44	
				32	26.94	3.13	26.53	3.15	26.13	3.20	25.50	3.38	25.32	3.24	24.91	3.29	
				47	27.68	2.28	26.71	2.22	26.36	2.24	25.50	2.38	25.28	2.22	23.84	2.10	
				50	29.58	2.39	28.68	2.51	27.84	2.45	27.83	2.46	27.16	2.50	26.77	2.53	
				59	32.08	2.49	31.55	2.57	30.90	2.47	30.68	2.54	30.09	2.61	29.68	2.63	
7	7		14	-13	16.88	3.91	14.12	3.10	13.55	3.15	10.49	2.29	9.30	1.91	6.63	1.24	
				5	16.40	2.64	16.01	2.66	15.61	2.70	15.00	2.80	14.83	2.76	14.43	2.78	
				17	15.98	2.28	15.71	2.30	15.43	2.33	15.00	2.41	14.88	2.38	14.60	2.40	
				32	15.85	1.70	15.62	1.71	15.37	1.73	15.00	1.79	14.90	1.76	14.66	1.77	
				47	15.90	1.19	15.71	1.20	15.50	1.21	15.00	1.26	15.08	1.23	14.87	1.25	
				50	17.26	1.27	16.84	1.29	16.52	1.30	16.37	1.31	15.97	1.33	15.75	1.34	
				59	18.90	1.32	18.53	1.34	18.20	1.35	18.05	1.36	17.63	1.39	17.38	1.40	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)																
						57		60.8		64.4		69.98		71.6		75.2						
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)					
7	9		16	-13	20.71	4.66	17.32	3.69	16.62	3.75	12.87	2.73	11.41	2.27	8.13	1.47						
				5	20.12	3.14	19.64	3.17	19.15	3.21	18.40	3.34	18.19	3.28	17.71	3.32						
				17	19.61	2.71	19.27	2.74	18.93	2.77	18.40	2.87	18.25	2.83	17.91	2.86						
				32	19.45	2.02	19.16	2.04	18.86	2.06	18.40	2.13	18.27	2.09	17.98	2.11						
				47	19.50	1.42	19.27	1.43	19.02	1.45	18.40	1.50	18.50	1.47	18.25	1.49						
				50	21.17	1.51	20.65	1.53	20.26	1.55	20.08	1.56	19.60	1.59	19.32	1.60						
				59	23.18	1.57	22.73	1.59	22.33	1.61	22.14	1.62	21.62	1.65	21.32	1.67						
				7	12		19	-13	24.20	5.19	20.24	4.11	19.42	4.17	15.03	3.04	13.33	2.53	9.50	1.64		
								5	23.51	3.49	22.95	3.53	22.38	3.58	21.50	3.72	21.26	3.65	20.69	3.69		
								17	22.91	3.02	22.51	3.05	22.12	3.08	21.50	3.20	21.33	3.15	20.93	3.18		
								32	22.72	2.25	22.38	2.27	22.04	2.29	21.50	2.37	21.35	2.33	21.01	2.35		
								47	22.79	1.58	22.52	1.59	22.22	1.61	21.50	1.67	21.62	1.64	21.32	1.66		
50	24.74	1.68	24.13					1.70	23.68	1.73	23.47	1.74	22.90	1.77	22.57	1.78						
						59	27.09	1.75	26.56	1.77	26.09	1.80	25.86	1.81	25.26	1.84	24.92	1.85				
						7	15		22	-13	28.70	6.18	24.01	4.90	23.03	4.97	17.83	3.62	15.81	3.02	11.27	1.96
										5	27.88	4.16	27.22	4.21	26.54	4.26	25.50	4.43	25.21	4.35	24.54	4.40
										17	27.17	3.60	26.70	3.64	26.23	3.67	25.50	3.81	25.30	3.76	24.83	3.79
										32	26.95	2.68	26.55	2.70	26.14	2.73	25.50	2.83	25.32	2.78	24.91	2.80
										47	27.03	1.88	26.71	1.90	26.36	1.92	25.50	1.99	25.64	1.95	25.29	1.97
50	29.34	2.00	28.62	2.03	28.08					2.06	27.83	2.07	27.16	2.10	26.77	2.12						
						59	32.13	2.08	31.51	2.11	30.94	2.14	30.68	2.15	29.96	2.19	29.55	2.21				
						7	18		25	-13	30.95	6.24	25.89	4.95	24.83	5.02	19.23	3.65	17.05	3.05	12.15	1.98
										5	30.07	4.21	29.35	4.25	28.63	4.31	27.50	4.47	27.19	4.40	26.46	4.44
										17	29.30	3.64	28.80	3.68	28.29	3.71	27.50	3.85	27.28	3.79	26.77	3.83
										32	29.07	2.71	28.63	2.73	28.19	2.76	27.50	2.85	27.31	2.81	26.87	2.83
										47	29.15	1.90	28.80	1.92	28.42	1.94	27.50	2.01	27.65	1.97	27.27	1.99
50	31.64	2.02	30.87	2.05	30.28					2.08	30.01	2.09	29.29	2.13	28.87	2.15						
						59	34.64	2.10	33.98	2.13	33.37	2.16	33.08	2.17	32.31	2.21	31.87	2.23				
						7	24		31	-13	37.14	7.48	31.07	5.93	29.80	6.02	23.08	4.38	20.46	3.65	14.58	2.37
										5	36.09	5.04	35.22	5.09	34.35	5.17	33.00	5.36	32.63	5.27	31.76	5.33
										17	35.16	4.36	34.56	4.41	33.95	4.45	33.00	4.61	32.74	4.55	32.13	4.59
										32	34.88	3.24	34.35	3.27	33.82	3.30	33.00	3.42	32.77	3.36	32.24	3.39
										47	34.97	2.28	34.56	2.30	34.11	2.32	33.00	2.41	33.18	2.36	32.72	2.39
50	37.97	2.42	37.04	2.46	36.34					2.49	36.02	2.51	35.14	2.55	34.65	2.57						
						59	41.57	2.52	40.77	2.56	40.04	2.59	39.70	2.61	38.78	2.65	38.24	2.68				
						9	9		18	-13	24.54	5.31	20.52	4.21	19.69	4.27	15.24	3.11	13.51	2.59	9.63	1.68
										5	23.84	3.58	23.27	3.61	22.69	3.66	21.80	3.80	21.55	3.74	20.98	3.78
										17	23.23	3.09	22.83	3.13	22.43	3.16	21.80	3.27	21.63	3.23	21.22	3.26
										32	23.04	2.30	22.69	2.32	22.34	2.34	21.80	2.43	21.65	2.39	21.30	2.41
										47	23.10	1.62	22.83	1.63	22.53	1.65	21.80	1.71	21.92	1.68	21.62	1.69
50	25.08	1.72	24.47	1.74	24.01					1.77	23.79	1.78	23.22	1.81	22.89	1.82						
						59	27.46	1.79	26.94	1.81	26.45	1.84	26.23	1.85	25.62	1.88	25.26	1.90				
						9	12		21	-13	28.02	5.78	23.44	4.58	22.49	4.65	17.41	3.38	15.44	2.82	11.00	1.83
										5	27.23	3.89	26.58	3.93	25.92	3.99	24.90	4.14	24.62	4.07	23.96	4.11
										17	26.53	3.37	26.07	3.40	25.61	3.43	24.90	3.56	24.70	3.51	24.24	3.54
										32	26.32	2.50	25.92	2.53	25.52	2.55	24.90	2.64	24.73	2.60	24.33	2.62
										47	26.39	1.76	26.08	1.78	25.74	1.79	24.90	1.86	25.04	1.82	24.69	1.84
50	28.65	1.87	27.95	1.90	27.42					1.92	27.18	1.93	26.52	1.97	26.14	1.99						
						59	31.37	1.94	30.77	1.97	30.21	2.00	29.95	2.01	29.26	2.05	28.86	2.07				

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15		24	-13	32.53	6.55	27.21	5.19	26.10	5.27	20.21	3.84	17.92	3.20	12.77	2.07	
				5	31.60	4.42	30.85	4.46	30.08	4.52	28.90	4.69	28.57	4.62	27.81	4.66	
				17	30.79	3.82	30.26	3.86	29.73	3.90	28.90	4.04	28.67	3.98	28.14	4.02	
				32	30.55	2.84	30.09	2.87	29.62	2.89	28.90	3.00	28.70	2.95	28.24	2.97	
				47	30.63	2.00	30.27	2.02	29.87	2.03	28.90	2.11	29.06	2.07	28.66	2.09	
				50	33.25	2.12	32.44	2.15	31.83	2.18	31.54	2.19	30.78	2.23	30.34	2.25	
				59	36.41	2.20	35.71	2.24	35.07	2.27	34.77	2.28	33.96	2.32	33.49	2.34	
9	18		27	-13	34.78	7.02	29.09	5.56	27.90	5.65	21.61	4.11	19.16	3.42	13.66	2.22	
				5	33.79	4.73	32.98	4.78	32.17	4.84	30.90	5.03	30.55	4.94	29.74	4.99	
				17	32.92	4.09	32.36	4.13	31.79	4.17	30.90	4.33	30.66	4.27	30.08	4.30	
				32	32.66	3.04	32.17	3.07	31.67	3.10	30.90	3.21	30.69	3.15	30.19	3.18	
				47	32.75	2.14	32.36	2.16	31.94	2.18	30.90	2.26	31.07	2.21	30.64	2.24	
				50	35.55	2.27	34.68	2.30	34.03	2.34	33.72	2.35	32.91	2.39	32.44	2.41	
				59	38.93	2.36	38.18	2.40	37.49	2.43	37.17	2.44	36.31	2.49	35.81	2.51	
9	24		33	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51	
				5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64	
				17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86	
				32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59	
				47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	12		24	-13	31.51	6.37	26.36	5.05	25.29	5.12	19.58	3.73	17.36	3.11	12.37	2.01	
				5	30.62	4.29	29.89	4.33	29.15	4.39	28.00	4.56	27.68	4.49	26.94	4.53	
				17	29.83	3.71	29.32	3.75	28.80	3.79	28.00	3.92	27.78	3.87	27.26	3.90	
				32	29.59	2.76	29.15	2.78	28.70	2.81	28.00	2.91	27.81	2.86	27.36	2.89	
				47	29.68	1.94	29.33	1.96	28.94	1.97	28.00	2.05	28.15	2.01	27.77	2.03	
				50	32.22	2.06	31.43	2.09	30.83	2.12	30.56	2.13	29.82	2.17	29.40	2.19	
				59	35.27	2.14	34.60	2.17	33.97	2.20	33.68	2.22	32.90	2.25	32.45	2.28	
12	15		27	-13	36.02	7.27	30.13	5.76	28.90	5.85	22.38	4.25	19.84	3.55	14.14	2.30	
				5	34.99	4.90	34.16	4.95	33.31	5.02	32.00	5.21	31.64	5.12	30.79	5.17	
				17	34.10	4.23	33.51	4.28	32.92	4.32	32.00	4.48	31.75	4.42	31.16	4.46	
				32	33.82	3.15	33.31	3.18	32.80	3.21	32.00	3.32	31.78	3.27	31.27	3.30	
				47	33.91	2.22	33.52	2.23	33.07	2.25	32.00	2.34	32.17	2.29	31.73	2.32	
				50	36.82	2.35	35.92	2.39	35.24	2.42	34.93	2.43	34.08	2.47	33.60	2.50	
				59	40.31	2.45	39.54	2.48	38.83	2.52	38.50	2.53	37.60	2.57	37.08	2.60	
12	18		30	-13	38.27	7.73	32.01	6.13	30.70	6.22	23.78	4.53	21.08	3.77	15.03	2.45	
				5	37.18	5.21	36.29	5.26	35.39	5.34	34.00	5.54	33.62	5.45	32.72	5.50	
				17	36.23	4.51	35.60	4.55	34.98	4.60	34.00	4.77	33.73	4.70	33.10	4.74	
				32	35.94	3.35	35.40	3.38	34.85	3.41	34.00	3.54	33.77	3.48	33.22	3.51	
				47	36.03	2.36	35.61	2.38	35.14	2.40	34.00	2.49	34.19	2.44	33.72	2.47	
				50	39.12	2.50	38.16	2.54	37.44	2.57	37.11	2.59	36.21	2.63	35.70	2.66	
				59	42.83	2.60	42.01	2.64	41.25	2.68	40.90	2.69	39.95	2.74	39.40	2.77	
12	24		36	-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51	
				5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64	
				17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86	
				32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59	
				47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
15	15			30	-13	38.27	7.92	32.01	6.28	30.70	6.37	23.78	4.64	21.08	3.86	15.03	2.51
					5	37.18	5.34	36.29	5.39	35.39	5.47	34.00	5.67	33.62	5.58	32.72	5.64
					17	36.23	4.61	35.60	4.66	34.98	4.71	34.00	4.88	33.73	4.81	33.10	4.86
					32	35.94	3.43	35.40	3.46	34.85	3.50	34.00	3.62	33.77	3.56	33.22	3.59
					47	36.03	2.41	35.61	2.44	35.14	2.46	34.00	2.55	34.19	2.50	33.72	2.53
					50	39.12	2.56	38.16	2.60	37.44	2.64	37.11	2.65	36.21	2.70	35.70	2.72
					59	42.83	2.66	42.01	2.70	41.25	2.74	40.90	2.76	39.95	2.80	39.40	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	41.19	7.92	34.46	6.28	33.05	6.37	25.59	4.64	22.69	3.86	16.18	2.51
					5	40.02	5.34	39.07	5.39	38.10	5.47	36.60	5.67	36.19	5.58	35.22	5.64
					17	39.00	4.61	38.33	4.66	37.65	4.71	36.60	4.88	36.31	4.81	35.63	4.86
					32	38.68	3.43	38.10	3.46	37.51	3.50	36.60	3.62	36.35	3.56	35.76	3.59
					47	38.79	2.41	38.33	2.44	37.83	2.46	36.60	2.55	36.80	2.50	36.29	2.53
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	18.05	3.22	17.21	3.24	16.72	3.28	15.73	3.33	15.24	3.37	14.26	3.37
					5	24.30	3.93	23.78	3.97	23.10	4.03	22.50	4.07	21.99	4.11	21.57	4.14
					17	23.97	3.38	23.53	3.42	22.98	3.46	22.50	3.50	22.08	3.54	21.72	3.57
					32	23.86	2.51	23.45	2.53	22.95	2.57	22.50	2.60	22.10	2.63	21.76	2.65
					47	23.77	1.76	23.38	1.78	22.92	1.81	22.50	1.83	22.13	1.85	21.81	1.87
					50	25.89	1.84	25.25	1.87	24.78	1.89	24.56	1.90	23.96	1.93	23.62	1.95
					59	28.35	1.91	27.80	1.94	27.30	1.97	27.07	1.98	26.44	2.01	26.07	2.03

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	23	-13	20.77	3.55	19.81	3.58	19.24	3.63	18.11	3.67	17.55	3.72	16.41	3.72	
				5	27.98	4.34	27.37	4.39	26.59	4.44	25.90	4.49	25.31	4.54	24.83	4.57	
				17	27.59	3.73	27.08	3.77	26.46	3.82	25.90	3.87	25.41	3.91	25.00	3.94	
				32	27.47	2.77	26.99	2.80	26.42	2.83	25.90	2.87	25.45	2.90	25.05	2.92	
				47	27.36	1.95	26.91	1.97	26.38	2.00	25.90	2.02	25.47	2.04	25.10	2.06	
				50	29.80	2.03	29.07	2.06	28.52	2.09	28.27	2.10	27.58	2.14	27.19	2.16	
				59	32.63	2.11	32.00	2.14	31.43	2.17	31.16	2.18	30.43	2.22	30.01	2.24	
7	7	12	26	-13	23.26	3.55	22.18	3.58	21.55	3.63	20.28	3.67	19.65	3.72	18.38	3.72	
				5	31.33	4.34	30.65	4.39	29.77	4.44	29.00	4.49	28.34	4.54	27.80	4.57	
				17	30.89	3.73	30.32	3.77	29.62	3.82	29.00	3.87	28.46	3.91	27.99	3.94	
				32	30.76	2.77	30.22	2.80	29.58	2.83	29.00	2.87	28.49	2.90	28.05	2.92	
				47	30.63	1.95	30.13	1.97	29.54	2.00	29.00	2.02	28.52	2.04	28.10	2.06	
				50	33.37	2.03	32.55	2.06	31.94	2.09	31.65	2.10	30.88	2.14	30.45	2.16	
				59	36.53	2.11	35.83	2.14	35.19	2.17	34.89	2.18	34.08	2.22	33.61	2.24	
7	7	15	29	-13	26.47	4.04	25.24	4.07	24.52	4.13	23.08	4.18	22.36	4.24	20.91	4.24	
				5	35.65	4.94	34.88	4.99	33.88	5.06	33.00	5.12	32.25	5.17	31.63	5.21	
				17	35.15	4.25	34.51	4.29	33.71	4.35	33.00	4.40	32.38	4.45	31.85	4.49	
				32	35.00	3.15	34.39	3.19	33.66	3.23	33.00	3.27	32.42	3.30	31.92	3.33	
				47	34.86	2.22	34.29	2.24	33.61	2.27	33.00	2.30	32.46	2.32	31.98	2.35	
				50	37.97	2.31	37.04	2.35	36.34	2.38	36.02	2.39	35.14	2.43	34.65	2.45	
				59	41.57	2.40	40.77	2.44	40.04	2.47	39.70	2.49	38.78	2.53	38.24	2.55	
7	7	18	32	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
7	7	24	38	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
7	9	9	25	-13	23.50	3.59	22.41	3.61	21.77	3.66	20.49	3.71	19.85	3.76	18.57	3.76	
				5	31.65	4.38	30.97	4.43	30.08	4.49	29.30	4.54	28.64	4.58	28.09	4.62	
				17	31.21	3.77	30.64	3.81	29.93	3.86	29.30	3.90	28.75	3.94	28.28	3.98	
				32	31.07	2.79	30.54	2.83	29.88	2.86	29.30	2.90	28.79	2.93	28.34	2.95	
				47	30.95	1.97	30.45	1.99	29.84	2.02	29.30	2.04	28.82	2.06	28.40	2.08	
				50	33.71	2.05	32.89	2.08	32.27	2.11	31.98	2.12	31.20	2.16	30.76	2.18	
				59	36.91	2.13	36.20	2.16	35.55	2.19	35.25	2.21	34.43	2.24	33.96	2.27	
7	9	12	28	-13	25.99	3.97	24.78	4.00	24.07	4.06	22.66	4.11	21.95	4.16	20.53	4.16	
				5	35.00	4.86	34.24	4.91	33.26	4.97	32.40	5.03	31.67	5.08	31.06	5.12	
				17	34.51	4.17	33.88	4.22	33.10	4.28	32.40	4.33	31.79	4.37	31.27	4.41	
				32	34.36	3.10	33.77	3.13	33.05	3.17	32.40	3.21	31.83	3.24	31.34	3.27	
				47	34.23	2.18	33.67	2.20	33.00	2.23	32.40	2.26	31.87	2.28	31.40	2.31	
				50	37.28	2.27	36.37	2.30	35.68	2.34	35.36	2.35	34.51	2.39	34.02	2.41	
				59	40.82	2.36	40.03	2.40	39.31	2.43	38.98	2.44	38.07	2.49	37.55	2.51	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	15	31	-13	29.19	4.46	27.84	4.50	27.05	4.56	25.45	4.62	24.66	4.68	23.07	4.68	
				5	39.32	5.46	38.47	5.52	37.37	5.59	36.40	5.65	35.58	5.71	34.89	5.75	
				17	38.77	4.69	38.06	4.74	37.18	4.81	36.40	4.86	35.72	4.91	35.13	4.95	
				32	38.60	3.48	37.94	3.52	37.13	3.56	36.40	3.61	35.76	3.64	35.21	3.68	
				47	38.45	2.45	37.82	2.48	37.07	2.51	36.40	2.54	35.80	2.57	35.28	2.59	
				50	41.88	2.55	40.86	2.59	40.09	2.63	39.73	2.64	38.77	2.69	38.22	2.71	
7	9	18	34	59	45.86	2.65	44.97	2.69	44.17	2.73	43.79	2.75	42.77	2.79	42.18	2.82	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
7	9	24	40	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
7	12	12	31	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	28.47	4.34	27.15	4.38	26.38	4.43	24.83	4.49	24.05	4.55	22.50	4.55	
				5	38.35	5.31	37.52	5.36	36.44	5.43	35.50	5.50	34.70	5.55	34.03	5.59	
				17	37.81	4.56	37.12	4.61	36.26	4.67	35.50	4.73	34.83	4.78	34.26	4.82	
7	12	15	34	32	37.65	3.38	37.00	3.42	36.21	3.47	35.50	3.51	34.88	3.54	34.34	3.58	
				47	37.50	2.38	36.89	2.41	36.16	2.44	35.50	2.47	34.92	2.50	34.40	2.52	
				50	40.85	2.48	39.85	2.52	39.09	2.55	38.75	2.57	37.81	2.61	37.27	2.64	
				59	44.72	2.58	43.86	2.62	43.07	2.66	42.71	2.67	41.71	2.72	41.14	2.74	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
7	12	18	37	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
7	12	24	43	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	15	15	37	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
7	15	18	40	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
7	15	24	46	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
7	18	18	43	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
9	9	9	27	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	26.23	4.01	25.01	4.04	24.30	4.09	22.87	4.15	22.15	4.20	20.72	4.20	
				5	35.32	4.90	34.56	4.95	33.57	5.02	32.70	5.07	31.96	5.12	31.34	5.16	
9	9	12	30	17	34.83	4.21	34.19	4.26	33.40	4.31	32.70	4.36	32.09	4.41	31.56	4.45	
				32	34.68	3.12	34.08	3.16	33.35	3.20	32.70	3.24	32.13	3.27	31.63	3.30	
				47	34.54	2.20	33.98	2.22	33.31	2.25	32.70	2.28	32.16	2.30	31.69	2.33	
				50	37.63	2.29	36.70	2.33	36.01	2.36	35.69	2.37	34.83	2.41	34.33	2.43	
				59	41.20	2.38	40.40	2.42	39.68	2.45	39.34	2.47	38.42	2.51	37.90	2.53	
				-13	28.71	4.38	27.38	4.41	26.60	4.47	25.03	4.53	24.25	4.59	22.69	4.59	
9	9	15	33	5	38.67	5.35	37.84	5.41	36.75	5.48	35.80	5.54	34.99	5.59	34.32	5.64	
				17	38.13	4.60	37.44	4.65	36.57	4.71	35.80	4.77	35.13	4.81	34.55	4.86	
				32	37.97	3.41	37.31	3.45	36.51	3.49	35.80	3.54	35.17	3.57	34.63	3.60	
				47	37.82	2.40	37.20	2.43	36.46	2.46	35.80	2.49	35.21	2.52	34.69	2.54	
				50	41.19	2.50	40.18	2.54	39.42	2.57	39.07	2.59	38.13	2.63	37.59	2.66	
				59	45.10	2.60	44.23	2.64	43.44	2.68	43.07	2.69	42.07	2.74	41.49	2.77	
9	9	15	33	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
9	9	15	33	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	18	36	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
9	9	24	42	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
9	9	24	42	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
9	12	12	33	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
9	12	15	36	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
9	12	18	39	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
9	12	24	45	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
9	12	15	39	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
9	12	15	39	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
				-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	15	18	42	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
9	15	24	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
9	18	18	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	12	12	36	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	12	15	39	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	12	18	42	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	12	24	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
12	15	15	42	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	15	18	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
12	18	18	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
15	15	15	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
15	15	18	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70	
				5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77	
				17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97	
				32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69	
				47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60	
				50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72	
				59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83	
7	7	7	28	-13	24.06	3.85	22.95	3.88	22.29	3.93	20.98	3.98	20.32	4.03	19.01	4.03	
				5	32.41	4.71	31.71	4.76	30.80	4.82	30.00	4.87	29.32	4.92	28.76	4.96	
				17	31.95	4.04	31.37	4.09	30.64	4.14	30.00	4.19	29.44	4.23	28.96	4.27	
				32	31.82	3.00	31.27	3.03	30.60	3.07	30.00	3.11	29.47	3.14	29.02	3.17	
				47	31.69	2.11	31.17	2.14	30.56	2.16	30.00	2.19	29.51	2.21	29.07	2.23	
				50	34.52	2.20	33.67	2.23	33.04	2.26	32.74	2.28	31.95	2.32	31.50	2.34	
				59	37.79	2.29	37.07	2.32	36.40	2.35	36.09	2.37	35.25	2.41	34.77	2.43	
7	7	9	30	-13	26.79	4.29	25.55	4.32	24.82	4.38	23.36	4.44	22.63	4.49	21.17	4.49	
				5	36.08	5.24	35.30	5.30	34.29	5.37	33.40	5.43	32.64	5.48	32.02	5.53	
				17	35.58	4.51	34.93	4.56	34.12	4.62	33.40	4.67	32.77	4.72	32.24	4.76	
				32	35.42	3.34	34.81	3.38	34.07	3.42	33.40	3.46	32.81	3.50	32.31	3.53	
				47	35.28	2.35	34.71	2.38	34.02	2.41	33.40	2.44	32.85	2.47	32.37	2.49	
				50	38.43	2.45	37.49	2.49	36.78	2.52	36.45	2.54	35.57	2.58	35.07	2.60	
				59	42.08	2.55	41.27	2.59	40.53	2.62	40.18	2.64	39.25	2.68	38.71	2.71	

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	7	12	33	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	7	7	15	36	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
7	7	7	18	39	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
7	7	7	24	45	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
7	7	9	9	32	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
7	7	9	12	35	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
7	7	9	15	38	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	7	9	18	41	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	7	9	24	47	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
7	7	9	24	47	50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
7	7	12	12	38	47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
7	7	12	15	41	32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
7	7	12	18	44	17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
7	7	15	15	44	5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
7	7	15	18	47	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	7	15	18	47	59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
					-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	9	9	34	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	9	12	37	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	9	15	40	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	9	18	43	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	12	40	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	15	43	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	9	12	18	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5</												

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
7	9	15	15	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	12	12	12	43	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
7	12	12	15	46	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
9	9	9	9	36	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
9	9	9	12	39	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
9	9	9	15	42	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
9	9	9	18	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72

Capacity Table

JXH36S4B(AJ036BXS4CH/AA)

Heating(Non Ducted)

Combination (Capacity Index)				Combination (Total)	Outdoor Temperature (°F,DB)	Indoor Temperature(°F, DB)											
						57		60.8		64.4		69.98		71.6		75.2	
						TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)	TC(kbtu)	PI(kW)
9	9	12	12	42	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	9	12	15	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	9	12	18	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	9	15	15	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	12	12	12	45	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
9	12	12	15	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83
12	12	12	12	48	-13	29.35	4.48	27.99	4.52	27.19	4.58	25.59	4.64	24.79	4.70	23.19	4.70
					5	39.54	5.48	38.68	5.54	37.57	5.61	36.60	5.67	35.77	5.73	35.08	5.77
					17	38.99	4.71	38.27	4.76	37.39	4.82	36.60	4.88	35.91	4.93	35.33	4.97
					32	38.82	3.49	38.15	3.53	37.33	3.58	36.60	3.62	35.96	3.66	35.40	3.69
					47	38.66	2.46	38.03	2.49	37.28	2.52	36.60	2.55	36.00	2.58	35.47	2.60
					50	42.11	2.56	41.08	2.60	40.31	2.64	39.95	2.65	38.98	2.70	38.43	2.72
					59	46.11	2.66	45.22	2.70	44.41	2.74	44.03	2.76	43.01	2.80	42.41	2.83

1. Cooling capacity is based on 80°F (26.7°C) DB, 67°F (19.4°C) WB (indoor temperature), 95°F (35°C) DB (outdoor temperature).

2. Heating capacity is based on 70°F (21.1°C) DB (indoor temperature), 47°F (8.3°C) DB, 43°F (6.1°C) WB (outdoor temperature).

3. The above values are based on connection of non-ducted indoor units.

4. Capacities are based on the following conditions:

- Refrigerant piping length: 16.4 ft (5m) / Height difference: 0 ft (0m)

5. The total combination index of connected indoor units is up to 48.

6. Single unit data in the table above is provided for capacity estimation purposes only. At least two (2) indoor units must be connected.

Single indoor unit connection is not allowed.

7. This reference data is based on temperature and capacity trend.



2023.09
Ver.1.4