160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws, $0.8 \times 4 \times 100 \text{ mm}$

Kraftform Plus - Series 100 VDE







EAN: 4013288160102 **Size:** 198x33x33 mm

Part number:05006441001Weight:52 gArticle number:160 iSCountry of origin:CZ

Customs tariff 82054000

number:











- Insulated blades for secure work at 1,000 volts
- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Take it easy tool finder: colour coding according to profile and size
- · Hexagonal anti-roll feature against rolling away
- · Reduced shaft diameter


Reduced blade diameter with integrated insulation protection so that even low-lying screw and spring elements can be accessed and actuated. Kraftform Plus handle for pleasant, ergonomic working that makes blisters and calluses a thing of the past. Hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. "Take it easy" tool finder with colour coding according to profiles and size stamp — for simple and rapid accessing of the required tool. The hexagonal anti-roll feature prevents any bothersome rolling away at the workplace.

160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws, $0.8 \times 4 \times 100 \text{ mm}$

Kraftform Plus - Series 100 VDE



VDE-insulated screwdriver with reduced blade diameter



Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

Individually tested



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Impact strength test



Impact strength tested at -40° C, guaranteeing safety even under extreme conditions.

Multicomponent Kraftform handle

to 1,000 volts.

Our screwdrivers are tested for

dielectric strength under a 10,000

volt load to make sure that their

most important property, their

insulation, has been exhaustively

tested. Each individual Wera VDE

screwdriver is subjected to this test to guarantee safe working up



Wera produces the Kraftform handle out of several materials with different properties. resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces - resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any "sticking" of the hand to the handle, making rapid repositioning of the hand possible.

Prevents hand injuries



The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.

"Take it easy" Tool Finder



Screwdrivers with "Take it easy" tool finder: colour coding according to profile and size stamp.

Web link

https://products.wera.de/en/tools_for_electricians_kraftform_plus__series_100_vde_160_is.html

Wera - 160 iS 05006441001 - 4013288160102

160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws, 0.8 x 4 x 100 mm $\,$

Kraftform Plus - Series 100 VDE



Further versions in this product family:

			_ ^ _	A v		
	mm	mm	mm	mm	inch	inch
05006440001	0.6	3.5	100	81	9/64	4
05006441001	0.8	4.0	100	98	5/32	4
05006442001	1.0	5.5	125	98	7/32	5