

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 1 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

### SECTION 1: Identification

#### Product identifier

**Product name:** Epoxy Putty Stick - Under Water Cure - Part A

**Product code:** 8277, 8277H



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Not determined or not applicable.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

J-B Weld Company, LLC

400 CMH Road

Sulphur Springs, TX 75482

903-885-7696

info@jbweld.com

#### Emergency telephone number:

##### United States

InfoTrac

Transportation Emergencies (24 hour): 800-535-5053

Poison Control Centers (24 hour): medical emergencies 800-222-1222

### SECTION 2: Hazard(s) identification

#### GHS classification:

Eye irritation, category 2A

Skin irritation, category 2

Skin sensitization, category 1

#### Label elements

##### Hazard pictograms:



**Signal word:** Warning

#### Hazard statements:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

#### Precautionary statements:

P264 Wash skin and eyes thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 2 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P501 Dispose of contents/container in accordance with local regulations.

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14807-96-6	Talc Powder	<15
CAS number: 13463-67-7	Titanium Dioxide	<10
CAS number: 65997-17-3	Glass, oxide, chemicals	<25
CAS number: 3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	<1
CAS number: 25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	<30

### Additional Information:

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 3 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

Wash with plenty of lukewarm, gently flowing water  
Get medical advice if skin irritation occurs or you feel unwell

### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes  
If symptoms develop or persist, seek medical attention  
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open  
Remove contact lenses, if present and easy to do so  
Continue rinsing for 15-20 minutes  
Get medical advice if eye irritation persists

### After swallowing:

Rinse mouth thoroughly  
Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

#### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion  
Heating causes a rise in pressure, risk of bursting and combustion

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation  
Ensure air handling systems are operational  
Wear protective eye wear, gloves and clothing

### Environmental precautions:

Should not be released into the environment

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 4 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Sweep or scoop up solid material while minimizing dust generation

Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing dust.

Do not eat, drink, smoke or use personal products when handling chemical substances.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Keep container dry.

Store in a cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc Powder	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Titanium Dioxide	13463-67-7	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
ACGIH	Talc Powder	14807-96-6	ACGIH TLV TWA 2 mg/m <sup>3</sup> ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Titanium Dioxide	13463-67-7	ACGIH TLV TWA 10 mg/m <sup>3</sup>
	Glass, oxide, chemicals	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm <sup>3</sup>
NIOSH	Talc Powder	14807-96-6	NIOSH REL TWA 2.0 mg/m <sup>3</sup>
	Titanium Dioxide	13463-67-7	IDLH: 5,000 mg/m <sup>3</sup>
	Glass, oxide, chemicals	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm <sup>3</sup>

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 5 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	White (solid)
<b>Odor</b>	Not determined or not available.
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flash point (closed cup)</b>	135°C (275°F)
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	1.98 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not determined or not available.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Not determined or not available.
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 6 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

### Other information

#### SECTION 10: Stability and reactivity

##### Reactivity:

Does not react under normal conditions of use and storage.

##### Chemical stability:

Stable under normal conditions of use and storage.

##### Possibility of hazardous reactions:

None under normal conditions of use and storage.

##### Conditions to avoid:

None known.

##### Incompatible materials:

None known.

##### Hazardous decomposition products:

None known.

#### SECTION 11: Toxicological information

##### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

##### Skin corrosion/irritation

###### Assessment:

Causes skin irritation

###### Product data:

No data available.

###### Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Causes skin irritation.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Causes skin irritation

##### Serious eye damage/irritation

###### Assessment:

Causes serious eye irritation

###### Product data:

No data available.

###### Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Causes serious eye irritation.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Causes serious eye damage

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 7 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

### Respiratory or skin sensitization

**Assessment:**

May cause an allergic skin reaction

**Product data:**

No data available.

**Substance data:**

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	May cause an allergic skin reaction.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Result : May cause sensitisation by skin contact.

### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans
Glass, oxide, chemicals	Group 2B
Titanium Dioxide	Group 2B

### National Toxicology Program (NTP):

Name	Classification
Glass, oxide, chemicals	Reasonably anticipated to be human carcinogens

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 8 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	EC50 - Scenedesmus capricornutum - 9 mg/L - 48 h

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 9 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

### SECTION 14: Transport information

#### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

#### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

#### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

#### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

### SECTION 15: Regulatory information

#### United States regulations

##### Inventory listing (TSCA):

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Listed
3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Glass, oxide, chemicals	Listed
13463-67-7	Titanium Dioxide	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 10 of 11

## Epoxy Putty Stick - Under Water Cure - Part A

**SARA Section 302 extremely hazardous substances:** Not determined.

**SARA Section 313 toxic chemicals:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Not Listed
14807-96-6	Talc Powder	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed
13463-67-7	Titanium Dioxide	Not Listed

**CERCLA:** Not determined.

**RCRA:** Not determined.

**Section 112(r) of the Clean Air Act (CAA):** Not determined.

**Massachusetts Right to Know:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Not Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Glass, oxide, chemicals	Listed
13463-67-7	Titanium Dioxide	Listed

**New Jersey Right to Know:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Not Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Glass, oxide, chemicals	Listed
13463-67-7	Titanium Dioxide	Listed

**New York Right to Know:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Not Listed
14807-96-6	Talc Powder	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed
13463-67-7	Titanium Dioxide	Listed

**Pennsylvania Right to Know:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
3101-60-8	P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Not Listed

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 11 of 11

### Epoxy Putty Stick - Under Water Cure - Part A

14807-96-6	Talc Powder	Listed
65997-17-3	Glass, oxide, chemicals	Listed
13463-67-7	Titanium Dioxide	Listed

**California Proposition 65:** None of the ingredients are listed.

### SECTION 16: Other information

**Abbreviations and Acronyms:** None

**Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-0-0

**HMIS:** 2-0-0

Initial preparation date: 07.24.2018

**End of Safety Data Sheet**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 1 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

### SECTION 1: Identification

#### Product identifier

**Product name:** Epoxy Putty Stick - Under Water Cure - Part B

**Product code:** 8277 & 8277H



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Not determined or not applicable.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

J-B Weld Company, LLC

400 CMH Road

Sulphur Springs, TX 75482

903-885-7696

info@jbweld.com

#### Emergency telephone number:

##### United States

InfoTrac

Transportation Emergencies (24 hour): 800-535-5053

Poison Control Centers (24 hour): medical emergencies 800-222-1222

### SECTION 2: Hazard(s) identification

#### GHS classification:

Eye irritation, category 2A

Skin irritation, category 2

Skin sensitization, category 1

#### Label elements

##### Hazard pictograms:



**Signal word:** Warning

#### Hazard statements:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

#### Precautionary statements:

P264 Wash skin and eyes thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 2 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P501 Dispose of contents/container in accordance with local regulations.

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14807-96-6	Talc Powder	<20
CAS number: 112-24-3	Amine Mix	<1
CAS number: 13463-67-7	Titanium Dioxide	<2
CAS number: 65997-17-3	Glass Powder	<15
CAS number: 7727-43-7	Barium Sulphate	<15
CAS number: 68479-04-9	Amine complex	<1
CAS number: 26950-63-0	Polyamine	<5
CAS number: 57-55-6	Diluent	<1
CAS number: 72244-98-5	Curing Agent	<20
CAS number: 186898-76-0	Amine complex	<5

### Additional Information:

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

## SECTION 4: First aid measures

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 3 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

#### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

#### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 4 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

### Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion  
Heating causes a rise in pressure, risk of bursting and combustion

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation  
Ensure air handling systems are operational  
Wear protective eye wear, gloves and clothing

### Environmental precautions:

Should not be released into the environment  
Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing  
Sweep or scoop up solid material while minimizing dust generation  
Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation.  
Avoid breathing dust.  
Do not eat, drink, smoke or use personal products when handling chemical substances.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.  
Keep container dry.  
Store in a cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
WEEL	Diluent	57-55-6	WEEL TWA 10.0 mg/m <sup>3</sup>
	Amine Mix	112-24-3	WEEL TWA 1.0 ppm
United States (OSHA)	Talc Powder	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Titanium Dioxide	13463-67-7	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Barium Sulphate	7727-43-7	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Barium Sulphate	7727-43-7	OSHA PEL TWA 5 mg/m <sup>3</sup> (Respirable fraction)
ACGIH	Barium Sulphate	7727-43-7	ACGIH TLV TWA 5.0 mg/m <sup>3</sup> (inhalable fraction, particulate containing no asbestos and <1% crystalline silica)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 5 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Talc Powder	14807-96-6	ACGIH TLV TWA 2 mg/m <sup>3</sup> ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Titanium Dioxide	13463-67-7	ACGIH TLV TWA 10 mg/m <sup>3</sup>
	Glass Powder	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm <sup>3</sup>
NIOSH	Barium Sulphate	7727-43-7	NIOSH TWA 5.0 mg/m <sup>3</sup> (Respirable fraction)
	Talc Powder	14807-96-6	NIOSH REL TWA 2.0 mg/m <sup>3</sup>
	Barium Sulphate	7727-43-7	NIOSH TWA 10.0 mg/m <sup>3</sup> (Total dust)
	Titanium Dioxide	13463-67-7	IDLH: 5,000 mg/m <sup>3</sup>
	Glass Powder	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm <sup>3</sup>

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 6 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

<b>Appearance</b>	Very thick light yellow paste (solid)
<b>Odor</b>	Not determined or not available.
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flash point (closed cup)</b>	107.78°C (226°F)
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	1.96 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not determined or not available.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Not determined or not available.
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

### Other information

#### SECTION 10: Stability and reactivity

**Reactivity:**

Does not react under normal conditions of use and storage.

**Chemical stability:**

Stable under normal conditions of use and storage.

**Possibility of hazardous reactions:**

None under normal conditions of use and storage.

**Conditions to avoid:**

None known.

**Incompatible materials:**

None known.

**Hazardous decomposition products:**

None known.

#### SECTION 11: Toxicological information

**Acute toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 7 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

**Product data:** No data available.

**Substance data:** No data available.

### Skin corrosion/irritation

**Assessment:**

Causes skin irritation

**Product data:**

No data available.

**Substance data:**

Name	Result
Amine complex	Causes severe skin burns and eye damage.
Polyamine	Corrosive to the skin.
Amine Mix	Causes severe skin burns and eye damage.

### Serious eye damage/irritation

**Assessment:**

Causes serious eye irritation

**Product data:**

No data available.

**Substance data:**

Name	Result
Polyamine	Corrosive effect on the eyes.

### Respiratory or skin sensitization

**Assessment:**

May cause an allergic skin reaction

**Product data:**

No data available.

**Substance data:**

Name	Result
Curing Agent	May cause an allergic skin reaction.
Polyamine	Sensitization possible through skin contact.
Amine Mix	May cause an allergic skin reaction.

### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Glass Powder	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Glass Powder	Group 2B
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 8 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

Name	Classification
Titanium Dioxide	Group 2B

### National Toxicology Program (NTP):

Name	Classification
Glass Powder	Reasonably anticipated to be human carcinogens

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Amine complex	Harmful if swallowed.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:**

Harmful to aquatic life

**Product data:** No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 9 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

### Substance data:

Name	Result
Amine Mix	LC50 - Daphnia magna (Water flea) - 33.9 mg/L - 48 h

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Result
Curing Agent	NOEC - Daphnia magna (Water flea) - 3.5 mg/L - 21 d

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 10 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

<b>UN number</b>	Not Regulated
<b>UN proper shipping name</b>	Not Regulated
<b>UN transport hazard class(es)</b>	None
<b>Packing group</b>	None
<b>Environmental hazards</b>	None
<b>Special precautions for user</b>	None

<b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	
<b>Bulk Name</b>	None
<b>Ship type</b>	None
<b>Pollution category</b>	None

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

186898-76-0	Amine complex	Not Listed
57-55-6	Diluent	Listed
68479-04-9	Amine complex	Listed
72244-98-5	Curing Agent	Listed
26950-63-0	Polyamine	Listed
112-24-3	Amine Mix	Listed
65997-17-3	Glass Powder	Listed
14807-96-6	Talc Powder	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

#### SARA Section 313 toxic chemicals:

186898-76-0	Amine complex	Not Listed
57-55-6	Diluent	Not Listed
68479-04-9	Amine complex	Not Listed
72244-98-5	Curing Agent	Not Listed
26950-63-0	Polyamine	Not Listed
112-24-3	Amine Mix	Not Listed

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 11 of 12

### Epoxy Putty Stick - Under Water Cure - Part B

65997-17-3	Glass Powder	Not Listed
14807-96-6	Talc Powder	Not Listed
13463-67-7	Titanium Dioxide	Not Listed
7727-43-7	Barium Sulphate	Listed

**CERCLA:** Not determined.

**RCRA:** Not determined.

**Section 112(r) of the Clean Air Act (CAA):** Not determined.

#### Massachusetts Right to Know:

186898-76-0	Amine complex	Not Listed
57-55-6	Diluent	Not Listed
68479-04-9	Amine complex	Not Listed
72244-98-5	Curing Agent	Not Listed
26950-63-0	Polyamine	Not Listed
112-24-3	Amine Mix	Listed
65997-17-3	Glass Powder	Listed
14807-96-6	Talc Powder	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

#### New Jersey Right to Know:

186898-76-0	Amine complex	Not Listed
57-55-6	Diluent	Listed
68479-04-9	Amine complex	Not Listed
72244-98-5	Curing Agent	Not Listed
26950-63-0	Polyamine	Not Listed
112-24-3	Amine Mix	Listed
65997-17-3	Glass Powder	Listed
14807-96-6	Talc Powder	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

#### New York Right to Know:

186898-76-0	Amine complex	Not Listed
-------------	---------------	------------

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.24.2018

Page 12 of 12

## Epoxy Putty Stick - Under Water Cure - Part B

57-55-6	Diluent	Not Listed
68479-04-9	Amine complex	Not Listed
72244-98-5	Curing Agent	Not Listed
26950-63-0	Polyamine	Not Listed
112-24-3	Amine Mix	Listed
65997-17-3	Glass Powder	Not Listed
14807-96-6	Talc Powder	Not Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Not Listed

### Pennsylvania Right to Know:

186898-76-0	Amine complex	Not Listed
57-55-6	Diluent	Listed
68479-04-9	Amine complex	Not Listed
72244-98-5	Curing Agent	Not Listed
26950-63-0	Polyamine	Not Listed
112-24-3	Amine Mix	Listed
65997-17-3	Glass Powder	Listed
14807-96-6	Talc Powder	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

**California Proposition 65:** None of the ingredients are listed.

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-0-0

**HMIS:** 2-0-0

**Initial preparation date:** 07.24.2018

**End of Safety Data Sheet**