

FFAL-A15Z-CFV-072

HFO, R-448A, 60Hz, 1- Phase, 208/230 V

COPELAND™**Availability :** Custom US OEM Or Wholesaler**Mechanical**

Unit Height (in):	19.1
Unit Length (in):	24.9
Unit Width (in):	20.4
Ship Weight (lbs):	127.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	18.4
Compressor:	ZF06KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	68.0
Compressor LRA - Half winding:	
Compressor RLA:	13.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	21-Oct-2020	Return Gas Temp. (°F):	40	
Compressor:	ZF06KAE-PFV-118 x 1	Subcooling (°F):	5	
Performance No:	19395	Air Flow Rate (CFM)	1216	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	3,640	102.8	12.8	2.4
-35	4,190	103.4	13.4	2.7
-30	4,790	104.1	14.1	3.0
-25	5,460	104.9	14.9	3.4
-20	6,200	105.7	15.7	3.7
-15	7,010	106.6	16.6	4.1
-10	7,890	107.6	17.6	4.4
-5	8,850	108.8	18.8	4.8
0	9,900	110.0	20.0	5.2