

# FFAL-A26Z-CFV-072

HFC , R-407A, 60Hz, 1- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	19.3
Unit Length (in):	34.0
Unit Width (in):	25.1
Ship Weight (lbs):	208.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	43.00

## Electrical

Max Fuse Size:	45
Min Circuit Ampacity:	28.0
Compressor:	ZF11K4E-PFV-231
Compressor LRA - Low:	
Compressor LRA - High:	109.0
Compressor LRA - Half winding:	
Compressor RLA:	20.8
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	21-Oct-2020	Return Gas Temp. (°F):	40	
Compressor:	ZF11K4E-PFV-231 x 1	Subcooling (°F):	5	
Performance No:	19658	Air Flow Rate (CFM)	1490	
<b>90°F Ambient Air Temperature</b>				
<b><u>Evap Temp</u></b> <b><u>(°F)</u></b>	<b><u>Unit Capacity</u></b> <b><u>(Btu/hr)</u></b>	<b><u>Cond. Temp.</u></b> <b><u>(°F)</u></b>	<b><u>Temp. Diff.</u></b> <b><u>(°F)</u></b>	<b><u>EER</u></b> <b><u>(Btu/Wh):</u></b>
-40	5,760	102.5	12.5	2.5
-35	6,750	103.4	13.4	2.7
-30	7,820	104.5	14.5	3.0
-25	8,990	105.5	15.5	3.4
-20	10,300	106.6	16.6	3.8
-15	11,800	107.9	17.9	4.2
-10	13,400	109.4	19.4	4.6
-5	15,300	111.0	21.0	5.1
0	17,300	112.8	22.8	5.6