

FFAL-A26Z-CFV-072

HFO, R-448A, 60Hz, 1- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

NOTE : APPLICATION APPROVAL REQUIRED

Mechanical

Unit Height (in):	19.3
Unit Length (in):	34.0
Unit Width (in):	25.1
Ship Weight (lbs):	208.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	43.00

Electrical

Max Fuse Size:	45
Min Circuit Ampacity:	28.0
Compressor:	ZF11K4E-PFV-231
Compressor LRA - Low:	
Compressor LRA - High:	109.0
Compressor LRA - Half winding:	
Compressor RLA:	20.8
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	21-Oct-2020	Return Gas Temp. (°F):	40
Compressor:	ZF11K4E-PFV-231 x 1	Subcooling (°F):	5
Performance No:	19659	Air Flow Rate (CFM)	1490

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-40	6,910	105.3	15.3	2.9
-35	7,830	106.3	16.3	3.1
-30	8,860	107.3	17.3	3.4
-25	9,990	108.4	18.4	3.7
-20	11,200	109.5	19.5	4.0
-15	12,600	110.8	20.8	4.3
-10	14,100	112.2	22.2	4.7
-5	15,600	113.7	23.7	5.0
0	17,300	115.3	25.3	5.3