

Availability : Custom US OEM Or Wholesaler

NOTE :APPLICATION APPROVAL REQUIRED

Mechanical

Unit Height (in):	20.0
Unit Length (in):	34.1
Unit Width (in):	25.0
Ship Weight (lbs):	195.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	60.00

Electrical

Max Fuse Size:	45
Min Circuit Ampacity:	29.5
Compressor:	ZF15K4E-TF5-251
Compressor LRA - Low:	
Compressor LRA - High:	123.0
Compressor LRA - Half winding:	
Compressor RLA:	21.4
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	21-Oct-2020	Return Gas Temp. (°F):	40	
Compressor:	ZF15K4E-TF5-251 x 1	Subcooling (°F):	5	
Performance No:	19558	Air Flow Rate (CFM)	2170	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	9,920	106.9	16.9	2.3
-35	11,200	107.9	17.9	2.5
-30	12,700	108.9	18.9	2.8
-25	14,400	110.0	20.0	3.2
-20	16,200	111.2	21.2	3.5
-15	18,200	112.5	22.5	3.9
-10	20,300	114.0	24.0	4.2
-5	22,600	115.6	25.6	4.6
0	25,000	117.4	27.4	4.9