

# FFAP-A17Z-TFC-072

HFC, R-407C, 60Hz, 3- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.4
Ship Weight (lbs):	109.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

## Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	14.4
Compressor:	ZS11KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	10.4
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	17950	Air Flow Rate (CFM)	1070

**90°F Ambient Air Temperature**

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	5,800	106.0	16.0	4.1
0	6,820	107.3	17.3	4.8
5	7,860	108.7	18.7	5.4
10	8,940	110.1	20.1	6.0
15	10,000	111.6	21.6	6.5
20	11,200	113.2	23.2	7.1
25	12,400	114.8	24.8	7.7