

# FFAP-A20Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	18.9
Unit Length (in):	34.1
Unit Width (in):	25.0
Ship Weight (lbs):	174.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

## Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	16.8
Compressor:	ZS13KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	56.0
Compressor LRA - Half winding:	
Compressor RLA:	12.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	0.6
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS13KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	17992	Air Flow Rate (CFM)	1927

**90°F Ambient Air Temperature**

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	5,020	100.4	10.4	4.9
0	5,750	100.4	10.4	5.5
5	6,530	100.4	10.4	6.1
10	7,390	100.4	10.4	6.7
15	8,280	101.4	11.4	7.4
20	9,230	102.6	12.6	8.0
25	10,200	104.0	14.0	8.6