

FFAP-A20Z-CFV-072

HFC, R-407C, 60Hz, 1- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	18.9
Unit Length (in):	34.1
Unit Width (in):	25.0
Ship Weight (lbs):	174.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	16.8
Compressor:	ZS13KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	56.0
Compressor LRA - Half winding:	
Compressor RLA:	12.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS13KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	17998	Air Flow Rate (CFM)	1927

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	6,670	105.1	15.1	4.1
0	7,840	106.4	16.4	4.8
5	9,040	107.7	17.7	5.4
10	10,300	109.0	19.0	6.0
15	11,600	110.4	20.4	6.6
20	12,900	111.9	21.9	7.2
25	14,300	113.3	23.3	7.8