

FFAP-A20Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V

COPELAND™

Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	18.9
Unit Length (in):	34.1
Unit Width (in):	25.0
Ship Weight (lbs):	174.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.9
Compressor:	ZS13KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	9.7
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40	
Compressor:	ZS13KAE-TF5-118 x 1	Subcooling (°F):	5	
Performance No:	18016	Air Flow Rate (CFM)	1927	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	5,020	100.4	10.4	4.9
0	5,750	100.4	10.4	5.5
5	6,530	100.4	10.4	6.1
10	7,390	100.4	10.4	6.7
15	8,280	101.4	11.4	7.4
20	9,230	102.6	12.6	8.0
25	10,200	104.0	14.0	8.6