

FFAP-A22Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	19.0
Unit Length (in):	34.1
Unit Width (in):	25.1
Ship Weight (lbs):	174.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	16.0
Compressor:	ZS15KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	10.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	17656	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	6,060	100.4	10.4	4.3
0	6,930	100.4	10.4	4.8
5	7,870	100.4	10.4	5.4
10	8,910	100.4	10.4	6.0
15	10,000	100.4	10.4	6.6
20	11,300	100.4	10.4	7.4
25	12,600	100.5	10.5	8.1