

FFAP-A22Z-TFC-072

HFC , R-407A, 60Hz, 3- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	19.0
Unit Length (in):	34.1
Unit Width (in):	25.1
Ship Weight (lbs):	174.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	16.0
Compressor:	ZS15KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	10.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	17659	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-25	5,740	100.5	10.5	3.3
-20	6,770	101.1	11.1	3.8
-15	7,810	101.8	11.8	4.2
-10	8,860	102.5	12.5	4.7
-5	9,960	103.1	13.1	5.1
0	11,100	103.9	13.9	5.6
5	12,400	104.6	14.6	6.1
10	13,700	105.4	15.4	6.6
15	15,100	106.3	16.3	7.2
20	16,700	107.3	17.3	7.8
25	18,400	108.3	18.3	8.4