

# FFAP-A22Z-TFC-072

HFO, R-448A, 60Hz, 3- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	19.0
Unit Length (in):	34.1
Unit Width (in):	25.1
Ship Weight (lbs):	174.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

## Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	16.0
Compressor:	ZS15KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	10.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	17663	Air Flow Rate (CFM)	2170

### 90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-25	5,250	101.4	11.4	3.2
-20	6,130	102.0	12.0	3.5
-15	7,050	102.6	12.6	3.8
-10	8,010	103.2	13.2	4.2
-5	9,040	103.9	13.9	4.5
0	10,200	104.6	14.6	5.0
5	11,400	105.3	15.3	5.5
10	12,700	106.1	16.1	6.0
15	14,100	107.0	17.0	6.5
20	15,800	107.9	17.9	7.2
25	17,500	108.9	18.9	7.8