

# FFAP-A30Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	19.0
Unit Length (in):	34.1
Unit Width (in):	25.1
Ship Weight (lbs):	186.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

## Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.9
Compressor:	ZS19KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	73.0
Compressor LRA - Half winding:	
Compressor RLA:	13.7
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS19KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	17728	Air Flow Rate (CFM)	2170

**90°F Ambient Air Temperature**

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	7,140	100.4	10.4	4.7
0	8,120	100.4	10.4	5.2
5	9,190	100.4	10.4	5.8
10	10,300	100.4	10.4	6.3
15	11,600	100.4	10.4	7.1
20	12,900	100.9	10.9	7.7
25	14,300	101.9	11.9	8.3