

# FFAP-A40Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	26.6
Unit Length (in):	44.1
Unit Width (in):	28.3
Ship Weight (lbs):	247.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	1.12 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	34.00

## Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	22.9
Compressor:	ZS26KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	93.0
Compressor LRA - Half winding:	
Compressor RLA:	15.5
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

## Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS26KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	18089	Air Flow Rate (CFM)	4240

**90°F Ambient Air Temperature**

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	10,200	100.4	10.4	4.6
0	11,700	100.4	10.4	5.2
5	13,200	100.4	10.4	5.7
10	15,000	100.4	10.4	6.4
15	16,900	100.4	10.4	7.1
20	18,900	100.4	10.4	7.9
25	21,100	101.1	11.1	8.6