

FFAP-A40Z-TFC-072

HFC , R-407A, 60Hz, 3- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	26.6
Unit Length (in):	44.1
Unit Width (in):	28.3
Ship Weight (lbs):	247.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	1.12 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	34.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	22.9
Compressor:	ZS26KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	93.0
Compressor LRA - Half winding:	
Compressor RLA:	15.5
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019	Return Gas Temp. (°F):	40
Compressor:	ZS26KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	18092	Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-25	9,120	100.9	10.9	3.1
-20	10,600	101.4	11.4	3.5
-15	12,100	102.1	12.1	3.9
-10	13,800	102.7	12.7	4.3
-5	15,700	103.5	13.5	4.8
0	17,700	104.2	14.2	5.3
5	19,900	105.1	15.1	5.8
10	22,200	106.0	16.0	6.4
15	24,700	107.0	17.0	6.9
20	27,500	108.0	18.0	7.6
25	30,400	109.1	19.1	8.2