

**Product**

**AutoSnap® Steel Flange Mount for TracPipe and CounterStrike**

**Project Information**

Job Name:		Date Submitted:	
Location:		Submitted By:	
Engineer:		Approved By:	
Contractor:		Manufacturer's Rep:	

**Installation**

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

**Mounting**

Termination fitting between TracPipe or CounterStrike Tubing and NPT thread.  
Fitting thread is Male NPT. For use indoor, outdoor, and concealed location applications.

**Technical Data**

Materials

Nut, Adapter, and Snap Ring	Yellow Brass
Mounting Flange	Steel

Pressure Ratings (used with tubing)

Specification Operating Pressure	25 PSIG
CSA International Evaluation Report - Max Operating Pressure, 3/8" through 1-1/4"	125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range	-20 to 200 Deg F
-----------------------------	------------------



**Codes**

ICC Codes (IFGC, IRC, IMC, IPC), NFPA 54, UPC, CAN/CSA B149.1, NFPA 58

**Standards**

ANSI LC1 / CSA 6.26, ANSI Z223.1

**Listings**

CSA

**Dimensional Information**

✓	Size	P/N	Diameter across flats (Nom. in.)	Fitting length (Nom. in.)	TracPipe or CounterStrike Size	Weight (lbs)
<input type="checkbox"/>	3/8"	FGP-SRFG-375	15/16"	2-3/8"	3/8" X 3/8"	0.3
<input type="checkbox"/>	1/2"	FGP-SRFG-500	1-1/8"	2-3/4"	1/2" X 1/2"	0.5
<input type="checkbox"/>	3/4"	FGP-SRFG-750	1-3/8"	2-7/8"	3/4" X 3/4"	0.7
<input type="checkbox"/>	1"	FGP-SRFG-1000	1-3/4"	3-1/8"	1" X 1"	0.9
<input type="checkbox"/>	1-1/4"	FGP-SRFG-1250	2"	3-1/2"	1-1/4" X 1-1/4"	2.0

Omega Flex, Inc. \* 451 Creamery Way\* Exton, PA 19341

Tel: 610-524-7272 \* Toll Free: 800-671-8622 \* Fax: 610-524-7282

www.omegaflex.com