





Product

PS-II Coupling Assembly

rroject information							
Job Name:		Date Submitted:					
Location:		Submitted By:					
Engineer:	Engineer: Approved By:						
Contractor:		Manufacturer's Rep:					

Installation

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Connection of identical sizes of PS-II.

Technical Data

Materials

Nut, Adapter, Flange and Split Rings Yellow Brass Insert and 1" Split Ring Stainless Steel

Pressure Ratings (used with tubing)

Specification Operating Pressure 25 PSIG Max Test Pressure 40 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range -20 to 200 Deg F

Codes

ICC Codes (IFGC, IRC, IMC, IPC), NFPA 54, UPC, CAN/CSA B149.1, NFPA 58

Standards

ANSI LC1 / CSA 6.26, ANSI Z223.1

Listings

CSA, ICC PMG 1046 / 1052, IAPMO (UPC) File No. 4665

Dimensional Information

/			Diameter	Fitting	TracPipe or	
\ \			across flats	length	CounterStrike	
	Size	P/N	(Nom. in.)	(Nom. in.)	Size	Weight (lbs)
	3/8"	FGP-UGC-375	1"	6"	3/8"	0.65
	1/2"	FGP-UGC-500	1-1/8"	6-1/4"	1/2"	0.70
	3/4"	FGP-UGC-750	1-3/8"	7-1/8"	3/4"	1.05
	1"	FGP-UGC-1000	1-5/8"	7-5/8"	1"	1.40
	1-1/4"	FGP-UGC-1250	2-5/8"	8-3/8"	1-1/4"	2.50
	1-1/2"	FGP-UGC-1500	3"	10-1/8"	1-1/2"	4.25
	2"	FGP-UGC-2000	3-1/16"	10-5/8"	2"	6.90

Omega Flex, Inc. * 451 Creamery Way* Exton, PA 19341 Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282

www.omegaflex.com