

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.4
Ship Weight (lbs):	73.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.5 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	13.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.8
Compressor:	RRT73C1E-IAV-104
Compressor LRA - Low:	
Compressor LRA - High:	33.7
Compressor LRA - Half winding:	
Compressor RLA:	8.5
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-May-2017	Return Gas Temp. (°F):	65	
Compressor:	RRT73C1E-IAV-104 x 1	Subcooling (°F):	5	
Performance No:	11598	Air Flow Rate (CFM)	680	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	3,040	102.2	12.2	4.5
0	3,510	104.0	14.0	4.8
5	3,990	105.8	15.8	5.2
10	4,500	107.7	17.7	5.5
15	5,040	109.7	19.7	5.9
20	5,590	111.7	21.7	6.3
25	6,170	113.9	23.9	6.6
30	6,780	116.1	26.1	6.9
35	7,400	118.5	28.5	7.1
40	8,050	121.0	31.0	7.3
45	8,710	123.7	33.7	7.4