

Availability : **Standard US OEM**
Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.4
Ship Weight (lbs):	80.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.62 SWEAT
Discharge Line Size (in):	0.37
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	20.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.0
Compressor:	RRT10K1E-PFA-150
Compressor LRA - Low:	
Compressor LRA - High:	78.0
Compressor LRA - Half winding:	
Compressor RLA:	13.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	12-Jan-2017	Return Gas Temp. (°F):	65	
Compressor:	RRT10K1E-PFA-150 x 1	Subcooling (°F):	5	
Performance No:	12490	Air Flow Rate (CFM)	680	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	3,370	104.5	14.5	4.7
0	3,870	106.5	16.5	5.1
5	4,410	108.6	18.6	5.5
10	4,980	110.8	20.8	5.8
15	5,580	113.1	23.1	6.2
20	6,210	115.6	25.6	6.5
25	6,860	118.1	28.1	6.8
30	7,540	120.6	30.6	7.1
35	8,230	123.3	33.3	7.4
40	8,940	126.0	36.0	7.6
45	9,660	128.7	38.7	7.8