

Availability : Standard US OEM

NOTE :APPLICATION APPROVAL REQUIRED

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.4
Ship Weight (lbs):	80.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.62 SWEAT
Discharge Line Size (in):	0.37
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	20.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.0
Compressor:	RRT10K1E-PFA-150
Compressor LRA - Low:	
Compressor LRA - High:	78.0
Compressor LRA - Half winding:	
Compressor RLA:	13.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-May-2017	Return Gas Temp. (°F):	65
Compressor:	RRT10K1E-PFA-150 x 1	Subcooling (°F):	5
Performance No:	11630	Air Flow Rate (CFM)	680

90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	3,980	106.4	16.4	4.4
0	4,520	108.5	18.5	4.8
5	5,110	110.8	20.8	5.1
10	5,730	113.1	23.1	5.4
15	6,370	115.6	25.6	5.7
20	7,050	118.2	28.2	6.1
25	7,760	120.9	30.9	6.3
30	8,490	123.7	33.7	6.6
35	9,240	126.5	36.5	6.8
40	10,000	129.5	39.5	7.1
45	10,800	132.5	42.5	7.3