

Availability : Standard US OEM

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.4
Ship Weight (lbs):	85.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.62 SWEAT
Discharge Line Size (in):	0.37
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	20.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.2
Compressor:	RRT10K1E-PFV-150
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	01-Dec-2016	Return Gas Temp. (°F):	65	
Compressor:	RRT10K1E-PFV-150 x 1	Subcooling (°F):	5	
Performance No:	12491	Air Flow Rate (CFM)	680	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-5	3,430	105.2	15.2	4.4
0	3,970	107.3	17.3	4.8
5	4,520	109.4	19.4	5.2
10	5,080	111.6	21.6	5.6
15	5,650	113.8	23.8	5.9
20	6,250	116.1	26.1	6.2
25	6,860	118.4	28.4	6.5
30	7,500	120.9	30.9	6.8
35	8,160	123.4	33.4	7.1
40	8,850	126.0	36.0	7.4
45	9,560	128.7	38.7	7.6