

Availability : Standard US OEM

Mechanical

Unit Height (in):	16.2
Unit Length (in):	24.0
Unit Width (in):	18.3
Ship Weight (lbs):	85.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.62 SWEAT
Discharge Line Size (in):	0.37
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	20.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.4
Compressor:	RRT10K1E-PFV-150
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	01-Dec-2016	Return Gas Temp. (°F):	65	
Compressor:	RRT10K1E-PFV-150 x 1	Subcooling (°F):	5	
Performance No:	12494	Air Flow Rate (CFM)	1070	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-10	3,110	96.6	6.6	3.9
-5	3,690	97.7	7.7	4.4
0	4,290	98.7	8.7	4.9
5	4,900	99.8	9.8	5.4
10	5,550	100.9	10.9	5.9
15	6,230	102.1	12.1	6.3
20	6,950	103.3	13.3	6.8
25	7,710	104.6	14.6	7.3
30	8,520	106.0	16.0	7.8
35	9,380	107.5	17.5	8.3
40	10,300	109.0	19.0	8.8
45	11,300	110.7	20.7	9.4