

Availability : **Standard US OEM****Mechanical**

Unit Height (in):	16.2
Unit Length (in):	24.0
Unit Width (in):	18.3
Ship Weight (lbs):	85.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.62 SWEAT
Discharge Line Size (in):	0.37
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	20.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.4
Compressor:	RRT10K1E-PFV-150
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	22-Jun-2018	Return Gas Temp. (°F):	65	
Compressor:	RRT10K1E-PFV-150 x 1	Subcooling (°F):	5	
Performance No:	15624	Air Flow Rate (CFM)	1070	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-10	3,660	96.6	6.6	4.1
-5	4,210	97.6	7.6	4.5
0	4,820	98.7	8.7	4.9
5	5,480	99.8	9.8	5.3
10	6,190	101.1	11.1	5.7
15	6,960	102.4	12.4	6.2
20	7,770	103.8	13.8	6.6
25	8,640	105.3	15.3	7.1
30	9,560	106.8	16.8	7.6
35	10,500	108.5	18.5	8.0
40	11,600	110.2	20.2	8.6
45	12,600	112.0	22.0	9.0