

Samsung "Quantum 2.0", wall mounted evaporator

Job Name \_\_\_\_\_  
 Purchaser \_\_\_\_\_  
 Submitted to \_\_\_\_\_  
 Unit Designation \_\_\_\_\_

Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Reference \_\_\_\_\_ Approval \_\_\_\_\_ Construction \_\_\_\_\_  
 Schedule # \_\_\_\_\_

**Specifications**

Model	US Code		RNS24YBT
	Model Number		AR24TSFYBWKNCV
Performance	Nominal Capacity	Cooling (Btu/h)	22,000
		Heating (Btu/h)	24,000
Power	Voltage	Ø / V / Hz	
		1 / 208-230 / 60	
	Operating Current (Max.)	Cooling (A)	0.5
		Heating (A)	0.5
Evaporator Fan	Type		BLDC motor with cross-flow fan
	Consumption	Watts	27 X 1
	FLA	Amps	0.12
Airflow	Air Volume (L/M/H/Turbo)	Cooling (CFM)	465 / 525 / 584 / 623
		Heating (CFM)	470 / 529 / 589 / 629
Refrigerant	Type		R410A
	Control Method		Electronic Expansion Valve (at outdoor unit)
Pipe Connections	Indoor & Outdoor	High side (flare)	1/4"
		Low side (flare)	5/8"
Dimensions	W X H X D (in.)	Indoor Unit	41 1/2 X 11 13/16 X 8 7/16
	Weight (lbs.)	Indoor Unit	25.4
	Condensate Connection		11/16" OD
Sound Pressure Level	Low / High	dB(A)	30 / 45
Accessories	Wired Controllers <sup>1</sup>	Advanced	MWR-WG00UN
		Simple Touch	MWR-SH11UN
	Wired Controller Sub-PCB		MIM-A00UN
	Condensate Pump	Aspen Mini Orange	ASP-MO-UNIV 110-250
		Blue Diamond	BD-BLUE-230
	External Temperature Sensor		MRW-TA
	External Contact Control Interface Module <sup>2</sup>		MIM-B14
Line sets - insulated and flared, interconnect cables included		25' - ILS2509	
		50' - ILS5009	
Safety Certifications			ETL (UL 1995)



**General Information**

- The indoor unit shall have Wi-Fi capability as standard
- The indoor unit shall be powered by the outdoor unit

**Construction**

- Indoor unit chassis shall be UL94 V0 with a galvanized steel mounting bracket
- The indoor unit shall have easy-access to wire, pipe, and drain connections via access panel on the bottom of the unit for simple installation and service

**Heat Exchanger**

- The heat exchangers shall be mechanically bonded fin to copper tube

**Indoor Fan**

- The indoor fan shall be a single, antibacterial cross-flow type
- Three fan speed settings and auto setting
- Automatic (motorized) vertical swing (up/down) louver and manual horizontal swing (left/right) louvers.

**Controls**

- The system shall have a built in Wi-Fi adapter as standard to allow control and monitoring using the Samsung SmartThings app (Android, iOS)
- Dual set temperature support when connected to MWR-WG00UN Advanced Wired Controller.
- The indoor unit shall have a simple connection for overflow detection devices or any other normally closed contact for simple unit shutdown
- The indoor unit shall ship with a wireless controller, holder, and batteries
- Wired controller options available

**Convenience**

- System energy consumption can be viewed using the Samsung SmartThings mobile app or on the indoor unit display using the included wireless controller (not revenue grade, for reference only)
- Auto Clean Function
- 7-segment digital display on front of unit to display temperature and unit status
- Auto changeover
- Good sleep mode
- Quiet mode
- Dry mode
- Simple ON/OFF time function – Using the wireless controller specify the ON and/or OFF times
- Electro-static, washable, main filter as standard accessible from the top of unit
- Filter cleaning reminder

**Compatibility**

Will only operate with Samsung outdoor unit model numbers:  
 AR24TSFYBWKXCV (RXS24YBT), AJ036TXJ4CH/AA (JXH36J4T),  
 AJ048TXJ5CH/AA (JXH48J5T), AJ030TXS4CH/AA (JXH30S4T),  
 AJ036TXS4CH/AA (JXH36S4T)

<sup>1</sup> Sub-PCB model MIM-A00UN is required when connecting optional wired controllers

<sup>2</sup> When applying MIM-B14 external contact control interface module, MIM-A00UN wired controller sub-PCB is required.

Samsung HVAC maintains a policy of ongoing development, specifications are subject to change without notice. Refer to [www.AHRIdirectory.org](http://www.AHRIdirectory.org) for current reference numbers.



Samsung "Quantum 2.0", wall mounted evaporator  
Indoor unit dimensional drawing

Unit: inches

