



Submittal Data Sheet

Daikin ENTRA R-32 -- 1.5-Ton Wall Mounted Unit with Heat Pump
FTXC18AXVJU- RXC18AXVJU

FEATURES

- Daikin Swing Compressor with Inverter
- Coil Fin Coating
- Indoor Unit quiet operation
- Auto Defrost, Auto Fan speed and Auto Restart (after Power Failure)
- Program Dry Function
- Power-airflow Flap
- Wide Angle Louvers and Vertical Auto-Swing (Up and Down)
- Programme Dry Function
- Energy Saving Function
- Sleep Mode
- Indoor Unit ON/OFF Button
- R/C with Backlight
- Catechin Filter / Green Tea Filter
- Titanium Apatite Air-Purifying Filter
- 24-hour ON/OFF Timer
- Self-diagnosis

INDOOR UNIT



BENEFITS

- 10 Year limited parts and compressor warranty
- Included Handheld Remote
- Precharged for up to 33'
- Simple Maintenance
- Whisper Quiet operation with specially designed airflow pattern
- Reduced power consumption
- Affordable cost saving solution
- Compact and quiet outdoor unit.
- Blue fin protection increases life span of outdoor unit
- R-32 Easy, Proven, Efficient, Available

OUTDOOR UNIT





Submittal Data Sheet

Daikin ENTRA R-32 -- 1.5-Ton Wall Mounted Unit with Heat Pump

FTXC18AXVJU- RXC18AXVJU

SYSTEM PERFORMANCE

| | | | |
|------------------------------------|----------------|----------------------------------|---|
| Indoor Unit Model No. | FTXC18AXVJU | Indoor Unit Name: | Daikin Entra R-32 - 18K Indoor High Wall Unit |
| Outdoor Unit Model No. | RXC18AXVJU | Outdoor Unit Name: | Daikin Entra R-32 Heat Pump Ductless ODU 1.5 Ton |
| Rated Cooling Capacity (Btu/hr): | 18,100 | Rated Cooling Conditions: | Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75 |
| Sensible Capacity (Btu/hr): | 14,120 | Rated Piping Length(ft): | 25 |
| Max/Min Cooling Capacity (Btu/hr): | 20,000 / 6,900 | Rated Height Difference (ft): | 0.00 |
| Cooling Input Power (kW): | 1.720 | Heating Input Power (kW): | 1.60 |
| SEER2 (Non-Ducted/Ducted): | 18.00 / | HSPF2 (Non-Ducted/Ducted): | 9.0 / |
| EER2 (Non-Ducted/Ducted): | 10.50 / | Heating COP (Non-Ducted/Ducted): | 3.3 / |
| Rated Heating Capacity (Btu/hr): | 18,000 | Rated Heating Conditions: | Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43 |

SYSTEM DETAILS

| | | | |
|--|------|-----------------------------------|----------|
| Refrigerant Type: | R-32 | Cooling Operation Range (°F DB): | 50 - 114 |
| Holding Refrigerant Charge (lbs): | 3.31 | Heating Operation Range (°F WB): | 5 - 65 |
| Additional Charge (oz/ft): | 0.18 | Max. Pipe Length (Vertical) (ft): | 33 |
| Pre-charge Piping (Length) (ft): | 33 | Cooling Range w/Baffle (°F DB): | - |
| Max. Pipe Length (Total) (ft): | 99 | | |
| Max Height Separation (Ind to Ind ft): | 0 | | |



Submittal Data Sheet


Daikin ENTRA R-32 -- 1.5-Ton Wall Mounted Unit with Heat Pump
FTXC18AXVJU- RXC18AXVJU

INDOOR UNIT DETAILS

| | | | |
|--|-----------------------------|----------------------------------|---------------------|
| Power Supply (V/Hz/Ph): | 208-230 / 60 / 1 | Airflow Rate (HH/HM/L/SL) (CFM): | 754/716/605/467/395 |
| Power Supply Connections: | L1, L2, L3, Ground | Moisture Removal (Gal/hr): | 0.6 |
| Min. Circuit Amps MCA (A): | | Gas Pipe Connection (inch): | 1/2 |
| Max Overcurrent Protection (MOP) (A): | | Liquid Pipe Connection (inch): | 1/4 |
| Dimensions (HxWxD) (in): | 11-11/16 x 39-9/16 x 11-1/3 | Condensate Connection (inch): | 5/8 |
| Net Weight (lb): | 30.5 | Sound Pressure (H/M/L/SL) (dBA): | 48/43/37/33 |
| Ext. Static Pressure (Rated/Max) (inWg): | / | Sound Power Level (dBA): | |

DIMENSIONAL DRAWING - INDOOR UNIT

Model : FTXC18/24A



Submittal Data Sheet


Daikin ENTRA R-32 -- 1.5-Ton Wall Mounted Unit with Heat Pump
FTXC18AXVJU- RXC18AXVJU

OUTDOOR UNIT DETAILS

| | | | |
|---------------------------------------|------------------------------|--------------------------------|----------|
| Power Supply (V/Hz/Ph): | 208-230 / 60 / 1 | Compressor Stage: | Inverter |
| Power Supply Connections: | L1, L2, L3, Ground | Capacity Control Range (%): | - |
| Min. Circuit Amps MCA (A): | 16.34 | Airflow Rate (H) (CFM): | 1879 |
| Max Overcurrent Protection (MOP) (A): | 20 | Gas Pipe Connection (inch): | 1/2 |
| Max Starting Current MSC(A): | | Liquid Pipe Connection (inch): | 1/4 |
| Rated Load Amps RLA(A): | | Sound Pressure (H) (dBA): | 53 |
| Dimensions (HxWxD) (in): | 27-13/32 x 36-5/8 x 13-13/16 | Sound Power Level (dBA): | |
| Net Weight (lb): | 101 | | |

DIMENSIONAL DRAWING - OUTDOOR UNIT

Model : RXC18/24A





Submittal Data Sheet

Daikin ENTRA R-32 -- 1.5-Ton Wall Mounted Unit with Heat Pump
FTXC18AXVJU- RXC18AXVJU

INDOOR ACCESSORIES

| PART NUMBER | DESCRIPTION | INCLUDED |
|-------------|-------------|----------|
|-------------|-------------|----------|

| | | |
|-------------|---|----|
| AZAI6WSCDKB | DKN Residential Cloud Wi-Fi Adaptor for Single- and Multi-Zone System (S21) | No |
|-------------|---|----|

| | | |
|-------------|--------------------|----|
| AZAI6WSPDKC | DKN Plus Interface | No |
|-------------|--------------------|----|

| | | |
|----------|-----------------------------|----|
| BRC51D61 | Wired Remote Controller Kit | No |
|----------|-----------------------------|----|

| | | |
|----------|-------------------------|----|
| BRC944B2 | Wired Remote Controller | No |
|----------|-------------------------|----|

| | | |
|------------|---------------------------|----|
| DACA-CP1-1 | Mini Aqua Condensate Pump | No |
|------------|---------------------------|----|

| | | |
|------------|------------------------------|----|
| DACA-CP4-1 | MINI WHITE PUMP KIT 100-250V | No |
|------------|------------------------------|----|

| | | |
|---------------|---|----|
| DTST-LTE-LA-A | Daikin One Lite (with Translation Adaptor for S21 only) | No |
|---------------|---|----|

| | | |
|----------------|---|----|
| DTST-ONE-ADA-A | Daikin One+ Smart Thermostat for VRV, SkyAir, Single- and Multi-Zone System | No |
|----------------|---|----|

| | | |
|----------------|---|----|
| DTST-TOU-ADA-A | Daikin One Touch Smart Thermostat (with Translation Adaptor for S21 and P1P2) | No |
|----------------|---|----|

OUTDOOR ACCESSORIES

| PART NUMBER | DESCRIPTION | INCLUDED |
|-------------|-------------|----------|
|-------------|-------------|----------|