

SUBMITTAL - 15KZAH1

Job Name: _____

Date: _____

Location: _____

R32

Indoor Unit: **ASUH15KZAS**

Outdoor Unit: **AOUH15KZAH1**



XLTH

FEATURES

INDOOR UNIT:

- Compact wall-mounted indoor unit providing superior comfort.
- Indoor unit with ProCore™ (High Corrosion Resistant Copper) coils for long-lasting protection against corrosion
- Whisper-quiet operation with sound levels as low as 26dB
- Multiple fan speed options: Auto, High, Med-High, Med, Med-Low, Low, and Quiet.
- Special Operation modes available:
 - Economy Mode / Energy Saving Mode / Powerful Mode / Minimum Heat Mode / Automatic defrosting operation / Auto-restart function
- Enhanced controls platform for seamless, intuitive operation:
 - Backlit wireless remote controller included with the indoor unit
 - Built-in Wi-Fi connectivity for remote monitoring & control via the Airstage Mobile App
 - Occupancy sensor for enhanced energy savings
 - Extended connectivity with support for third-party interface options
 - Compatible with BACnet and Modbus protocols for seamless integration with building management and Home Automation Systems
- Advanced scheduling and timer options offer greater control over unit operation:
 - Weekly Timer / 24-hr Timer / Sleep Function
- Dual-action Filtration: Apple-Catechin Filter & Ion Deodorizing Filter
- Additional premium features include, but are not limited to:
 - Built-in external input and output for interlocking systems with 3rd party devices (Ex: Fire Alarm, Door Switch, Humidifier, Aux. Heat & more)
 - Multiple Auxiliary Heat logic for optimized heating performance
 - Service monitoring functionality via compatible accessories (UTY-RVRU & UTY-RNRUZ-series)

OUTDOOR UNIT:

- Low GWP R-32 systems for reduced environmental impact
- INVERTER-driven compressor that offers superior performance, comfort, and energy savings
- Base pan heater designed for the extreme cold climate region
- Compact outdoor unit with extended line set lengths up to 98ft (30m)
- Up to 24% higher rated heating capacity than nominal capacity
 - 18000 Btu/h Rated Heating Capacity for 15000 Btu/h system
 - Up to 26% higher heating capacity @ -5°F
- Low-noise outdoor unit operation mode
- Hydro Fin-coated heat exchanger for improved corrosion resistance and coil durability



7 Year Compressor, 5 Year Parts out-of-the-box Warranty.



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence.



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence and installed by a Fujitsu Elite contractor.



Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://connect.fujitsugeneral.com>

Version: 20250409A

-1 of 6-

SUBMITTAL - 15KZAH1

SPECIFICATIONS:

Indoor Unit					ASUH15KZAS			
Outdoor Unit					AOUH15KZAH1			
System Name					15KZAH1			
AHRI Number					214888804			
SEER2		Cooling			Btu/hW	27.5		
EER2						14.8		
HSPF 2 (IV) / HSPF 2 (V)		Heating			kW/kW	12.7 / 10.1		
COP2						4.6		
Outdoor Operation Range		Cooling ⁸			°F (°C)	14 to 122 (-10 to 50)		
		Heating				-15 to 75 (-26 to 24)		
Indoor Capacity		Cooling		Rated	Btu/h	14500		
				Min.—Max.		3,100—19,000		
		Heating	47°FDB (Outdoor temp.)			Rated	18000	
			17°FDB (Outdoor temp.) ¹			Min.—Max.	4,150—25,000	
						Rated	11400	
			5°FDB (Outdoor temp.) ²			Max.	22000	
		Rated				21000		
		Max.						
Outdoor Connection pipe	Size	Liquid			in (mm)	Ø1/4 (Ø6.35)		
		Gas				Ø1/2 (Ø12.70)		
	Method					FLARE		
	Pre-charge length				ft (m)	49 (15)		
	Min. length					10 (3)		
	Max. length					98 (30)		
Max. height difference				82 (25)				
Indoor Dimensions (H × W × D)		Net			in (mm)	11 × 38-9/16 × 9-7/16 (280 × 980 × 240)		
		Gross				12-11/16 × 42-7/16 × 13-5/8 (322 × 1,078 × 346)		
Indoor Weight		Net			lb (kg)	28 (12.5)		
		Gross				36 (16.5)		
Outdoor Dimensions (H × W × D)		Net			in (mm)	24-7/8 × 31-7/16 × 11-7/16 (632 × 799 × 290)		
		Gross				27-1/4 × 37 × 14-3/4 (692 × 940 × 375)		
Outdoor Weight		Net			lb (kg)	86 (39)		
		Gross				95 (43)		
Indoor Fan	Airflow rate	Cooling	High	CFM (m³/h)	553 (940)			
			Med—High		494 (840)			
			Med		441 (750)			
			Med—Low		371 (630)			
			Low		300 (510)			
			Quiet		230 (390)			
		Heating	High		594 (1,010)			
			Med—High		530 (900)			
			Med		465 (790)			
			Med—Low		371 (630)			
			Low		300 (510)			
			Quiet		230 (390)			
		Type × Qty					CROSSFLOW FAN × 1	
		Outdoor Fan	Airflow rate		Motor output			W
Cooling				CFM (m³/h)	1,218 (2,070)			
Heating					1,348 (2,290)			
Type × Qty					PROPELLER FAN × 1			
Indoor Sound Pressure Level ⁴		Motor output			W	49		
						Cooling	High	dB (A)
		Med—High	43					
		Med	40					
		Med—Low	36					
		Low	31					
		Quiet	26					
		Heating	High	46				
			Med—High	44				
			Med	41				
			Med—Low	35				
			Low	31				
Quiet	26							
Outdoor Sound Pressure Level ⁴		Cooling			49			
		Heating			50			

SUBMITTAL - 15KZAH1

SPECIFICATIONS:

Outdoor Refrigerant		Type		R32
		Charge	lb oz	2 lb 10 oz
g	1200			
Additional Charge Calculation			oz/ft	0.22
			g/m	20
Outdoor Refrigerant Oil		Type		RMM68AF
		Amount	in ³ (cm ³)	24.4 (400)
Indoor Moisture removal			pints/h (L/h)	5.3 (2.5)
Indoor Drain hose		Material		POLYPROPYLENE + HIGH-DENSITY POLYETHYLENE
		Tip Diameter	in (mm)	Ø17/32 (Ø13.8) (I.D.), Ø19/32 to 21/32 (Ø15.0 to 16.8) (O.D.)
Indoor Operation range		Cooling	°F (°C)	64 to 90 (18 to 32)
			%RH	80 or less
		Heating	°F (°C)	60 to 86 (16 to 30)
Power Supply				208/230 V~ 60 Hz
Available Voltage Range				187—253
System power supply		Voltage		208/230
		Frequency		60
		Available voltage range		187—253
Indoor Current	Cooling		A	4.8
	Heating			5.2
Maximum Operating Current* ³		Cooling		9.9
		Heating		14.4
Outdoor Starting Current				5.2
MCA* ⁵				17.5
Wiring spec.* ⁶		MAX. CKT. BKR* ⁷		20
Indoor Input Power	Cooling			Rated
			Min.—Max.	0.15—1.70
	Heating	47°FDB (Outdoor temp.)	Rated	1.15
		17°FDB (Outdoor temp.)* ¹	Min.—Max.	0.24—2.25
			Rated	0.97
		5°FDB (Outdoor temp.)* ²	Max.	2.74
			Rated	2.93
		Indoor Power Factor	Cooling	
Heating			96.2	
Energy Star* ⁹				ES, ESCC, ESME

NOTES

- Cooling: Indoor temperature of 80°F (26.67°CDB)/67°FWB (19.44°CWB), and outdoor temperature of 95°FDB (35°CDB)/75°FWB (23.9°CWB).
 —Heating: Indoor temperature of 70°FDB (21.11°CDB)/60°FWB (15.56°CWB), and outdoor temperature of 47°FDB (8.33°CDB)/43°FWB (6.11°CWB).
 17°FDB (Outdoor temp.) —*1: Heating (17°F): Indoor temperature of 70°FDB (21.11°CDB)/60°FWB (15.56°CWB), and outdoor temperature of 17°FDB (-8.33°CDB)/15°FWB (-9.44°CWB).
 5°FDB (Outdoor temp.) —*2: Heating (5°F): Indoor temperature of 70°FDB (21.11°CDB)/60°FWB (15.56°CWB), and outdoor temperature of 5°FDB (-15.0°CDB)/4°FWB (-15.56°CWB).
 —Test conditions are based on AHRI 210/240 2023.
 —*4:
 Indoor Sound Pressure Level —Measured values in manufacturer's anechoic chamber.
 Outdoor Sound Pressure Level —Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.
 —*3:
 Maximum Operating Current —Maximum current is maximum value when operated within the operation range.
 —The total current of indoor unit and outdoor unit.
 MCA —*5: Minimum Circuit Ampacity (Calculation based on UL60335-2-40)
 —*6: Selected sample based on Japan Electrotechnical Standards and Codes Committee ED005.
 Wiring spec. As the regulations of wire size and circuit breaker differ in each country or region, select appropriate devices complied to the regional standard.
 MAX. CKT. BKR —*7: Maximum Circuit Breaker
 Operation Range —*8: Suction temperature of the outdoor unit.
 Energy Star ® *9 : ES = Energy Star, ESCC = Energy Star Cold Climate, ESME = Energy Star Most Efficient.
 System continues to operate below rated outdoor operation temperature range, subject to varying conditions. System has no low temperature cut out. Capacity is not tested outside of the rated temperature range.

SUBMITTAL - 15KZAH1

ACCESSORIES:

Model Number	Description
UTY-RVRU ^{*1}	KAGAMI - Touch Panel Wired Controller
UTY-RNRUZ5 ^{*1}	Touch Panel Wired Remote Controller
UTY-RHRY ^{*1}	Simple Wired Remote (Without Mode Function) - Hospitality
UTY-RSRY ^{*1}	Simple Wired Remote (With Mode Function)
UTY-TWRXZ2	Communication Kit - Wall Mount
FJ-AC-WIFI-1	Intesis Wi-Fi Device: Wired Module
FJ-IR-WIFI-1NA	Intesis IR Wireless AC Cloud Control Interface (Intesis Home app)
BM101WA	Cielo - Breez Max IR Controller w/ WiFi (Black)
BM102WA	Cielo - Breez Max IR Controller w/ WiFi (White)
UTY-VMSX	Modbus Converter
UTY-VTGX ^{*1}	Network Converter - Convert H-Series Comm. Protocol to V/J-Series Comm.
FJ-AC-485-1	Intesis - BACnet MSTP & Modbus RTU Gateway
UTY-TERX ^{*1}	External Switch Controller
UTY-TTRXZ1 ^{*1, 2}	24V Thermostat Interface
TTRXZ1-KIT ^{*1, 2}	24V Thermostat Interface Kit (UTY-TTRXZ1, UTY-WiFi Plug & 24V Transformer)
UTY-XCSXZ2	External input and output PCB
UTY-XWZXZ5	External Connect Kit
UTY-DSGYZ2 ^{*3}	Airstage Edge Controller
UTZ-DUHGG3A	Hail Guard
UTZ-DUSHG3A	Snowhood
UTZ-DUWBG3A	Wind Baffle

NOTES:


*1 -Requires Communication kit UTY-TWRXZ2 to connect this device to IDU.

*2 -This device may not be used with any other type of controls (central controller, wire/wireless RC, WiFi adapter, BMS interface).

*3 -Connection to AIRSTAGE Cloud requires a compatible AIRSTAGE Mobile adapter connected to the IDU.

SUBMITTAL - 15KZAH1


INDOOR UNIT DIMENSIONS:




SUBMITTAL - 15KZAH1

OUTDOOR UNIT DIMENSIONS:


Unit: in (mm)




Top view




Side view




Front view



Side view



Bottom view



Side view (Valve part)

The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2025 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.