

SUBMITTAL - 12KMAS1

Job Name: _____

Date: _____

Location: _____

R32

Indoor Unit: **ASUH12KMAS**

Outdoor Unit: **AOUH12KMAS1**



FEATURES

INDOOR UNIT:

- Compact wall-mounted indoor unit delivering superior comfort and energy-efficient performance
- Indoor unit with ProCore™ (High Corrosion Resistant Copper) coils for long-lasting protection against corrosion
- Whisper-quiet operation with sound levels as low as 19dB
- Multiple fan speed options; Auto, High, Med, Low, and Quiet
- Special Operation modes available:
 - Economy Mode/ Energy Saving Mode / Powerful Mode / Minimum Heat Mode / Automatic defrosting operation / Auto-restart function
- Enhanced controls platform for seamless, intuitive operation:
 - Wireless Remote Controller provided with the indoor unit
 - Built-in Wi-Fi connectivity with remote monitoring via the Airstage Mobile App
 - Extended connectivity with support for third-party interface options
 - Compatible with BACnet and Modbus protocols for seamless integration with building management and Home Automation Systems
- Advanced scheduling and timer options offer greater control over unit operation:
 - Weekly Timer / 24-hr Timer / Sleep Function
- Dual-action Filtration: Apple-Catechin Filter & Ion Deodorizing Filter
- Additional premium features include, but are not limited to:
 - Built-in external input and output for interlocking systems with 3rd party devices (Ex: Fire Alarm, Door Switch, Humidifier, Aux. Heat & more)
 - Multiple Auxiliary Heat logic for optimized heating performance
 - Service monitoring functionality via compatible accessories (UTY-RVRU & UTY-RNRUZ-series)

OUTDOOR UNIT:

- Low GWP R-32 systems for reduced environmental impact
- INVERTER-driven compressor that offers superior performance, comfort, and energy savings
- Compact outdoor unit with extended line set lengths up to 66ft (20m)
- Up to 16% higher rated heating capacity than nominal capacity
- Low-noise outdoor unit operation mode
- Hydro Fin-coated heat exchanger for improved corrosion resistance and coil durability



7 Year Compressor, 5 Year Parts out-of-the-box Warranty.



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence.



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence and installed by a Fujitsu Elite contractor.



Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://connect.fujitsugeneral.com>

Version: 20250409A

-1 of 6-

SUBMITTAL - 12KMAS1

SPECIFICATIONS:

Indoor Unit				ASUH12KMAS			
Outdoor Unit				AOUH12KMAS1			
System Name				12KMAS1			
AHRI Number				214390708			
SEER2	Cooling			Btu/hW	27.5		
EER2					13.5		
HSPF 2 (IV) / HSPF 2 (V)	Heating			kW/kW	11.2 / 8.5		
COP2					4.32		
Outdoor Operation Range		Cooling		°F (°C)	14 to 122 (-10 to 50)		
		Heating			5 to 75 (-15 to 24)		
Indoor Capacity		Cooling		Rated	12000		
				Min.—Max.	3,100—13,800		
		Heating	47°FDB (Outdoor temp.)	Rated	14000		
				Min.—Max.	2,800—19,800		
			17°FDB (Outdoor temp.) ^{*1}	Rated	8700		
				Max.	13200		
			5°FDB (Outdoor temp.) ^{*2}	Rated	10600		
				Max.			
Outdoor Connection pipe	Size	Liquid		in (mm)	Ø1/4 (Ø6.35)		
		Gas			Ø3/8 (Ø9.52)		
	Method				FLARE		
	Pre-charge length			ft (m)	49 (15)		
	Min. length				10 (3)		
	Max. length				66 (20)		
	Max. height difference				49 (15)		
Indoor Dimensions (H × W × D)		Net		in (mm)	10-5/8 × 32-13/16 × 8-3/4 (270 × 834 × 222)		
		Gross			10-7/8 × 36 × 13-1/16 (277 × 914 × 332)		
Indoor Weight		Net		lb (kg)	22 (10)		
		Gross			28 (12.5)		
Outdoor Dimensions (H × W × D)		Net		in (mm)	21-5/16 × 31-7/16 × 11-7/16(542 × 799 × 290)		
		Gross			23-11/16 × 37 × 14-3/4(602 × 940 × 375)		
Outdoor Weight		Net		lb (kg)	71 (32)		
		Gross			77 (35)		
Indoor Fan	Airflow rate	Cooling	High	CFM (m³/h)	400 (680)		
			Med		324 (550)		
			Low		253 (430)		
		Heating	Quiet		153 (260)		
			High		441 (750)		
			Med		371 (630)		
			Low		300 (510)		
			Quiet		188 (320)		
		Type × Qty				CROSSFLOW FAN × 1	
		Motor output			W	49	
Outdoor Fan	Airflow rate	Cooling		CFM (m³/h)	1,042 (1,770)		
		Heating			1,065 (1,810)		
	Type × Qty				PROPELLER FAN × 1		
	Motor output			W	23		
Indoor Sound Pressure Level ^{*4}		Cooling	High	dB (A)	40		
			Med		35		
			Low		30		
			Quiet		19		
		Heating	High		42		
			Med		38		
			Low		33		
			Quiet		21		
Outdoor Sound Pressure Level ^{*4}		Cooling			48		
		Heating			50		

SUBMITTAL - 12KMAS1

SPECIFICATIONS:

Outdoor Refrigerant		Type		R32		
		Charge	lb oz	1 lb 14 oz		
			g	850		
Additional Charge Calculation				oz/ft	0.22	
				g/m	20	
Outdoor Refrigerant Oil		Type		RB68A		
		Amount	in ³ (cm ³)	20.7 (340)		
Indoor Moisture removal			pints/h (L/h)	3.7 (1.73)		
Indoor Drain hose		Material		POLYVINYL CHLORIDE		
		Tip Diameter		in (mm) Ø17/32 (Ø13.8) (I.D.), Ø19/32 to 21/32 (Ø15 to 16.8) (O.D.)		
Indoor Operation range		Cooling	°F (°C)	64 to 90 (18 to 32)		
			%RH	80 or less		
		Heating	°F (°C)	60 to 86 (16 to 30)		
Power Supply				208/230 V ~ 60 Hz		
Available Voltage Range				187—253		
System power supply		Voltage		V	208/230	
		Frequency		Hz	60	
		Available voltage range		V	187—253	
Indoor Current	Cooling		Rated	A	4.3	
	Heating				4.6	
Maximum Operating Current ^{*3}			Cooling		6.9	
			Heating		9.4	
Outdoor Starting Current					4.6	
MCA ^{*5}					11.5	
Wiring spec. ^{*6}		MAX. CKT. BKR ^{*7}			15	
Indoor Input Power		Cooling	Rated	kW	0.89	
			Min.—Max.		0.13—1.24	
		Heating	47°FDB (Outdoor temp.)		Rated	0.95
					Min.—Max.	0.14—1.76
			17°FDB (Outdoor temp.) ^{*1}		Rated	0.82
					Max.	1.46
	5°FDB (Outdoor temp.) ^{*2}	Rated	1.3			
		Max.				
Indoor Power Factor		Cooling		%	90	
		Heating			89.8	
Energy Star ^{*8}				ES, ESCE, ESME		

NOTES

- Cooling: Indoor temperature of 80°F (26.7°CDB)/67°FDB (19.4°CQWB), and outdoor temperature of 95°FDB (35°CDB)/75°FDB (23.9°CQWB).
- Heating: Indoor temperature of 70°FDB (21.1°CDB)/60°FDB (15.6°CQWB), and outdoor temperature of 47°FDB (8.3°CDB)/43°FDB (6.1°CQWB).
- 17°FDB (Outdoor temp.), —*1: Heating (17°F): Indoor temperature of 70°FDB (21.1°CDB)/60°FDB (15.6°CQWB), and outdoor temperature of 17°FDB (–8.3°CDB)/15°FDB (–9.4°CQWB).
- 5°FDB (Outdoor temp.) —*2: Heating (5°F): Indoor temperature of 70°FDB (21.1°CDB)/60°FDB (15.6°CQWB), and outdoor temperature of 5°FDB (–15.0°CDB)/4°FDB (–15.6°CQWB).
- Test conditions are based on AHRI 210/240 2023.
- *4: Indoor Sound Pressure Level, Outdoor Sound Pressure Level —Measured values in manufacturer's anechoic chamber.
- Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.
- *3: Maximum Operating Current —Maximum current is maximum value when operated within the operation range.
- The total current of indoor unit and outdoor unit.
- MCA —*5: Minimum Circuit Ampacity (Calculation based on UL60335-2-40)
- *6: Selected sample based on Japan Electrotechnical Standards and Codes Committee E0005.
- Wiring spec. As the regulations of wire size and circuit breaker differ in each country or region, select appropriate devices complied to the regional standard.
- MAX. CKT. BKR —*7: Maximum Circuit Breaker
- Energy Star ® *8 : ES = Energy Star, ESCE = Energy Star Cold Climate, ESME= Energy Star Most Efficient.

System continues to operate below rated outdoor operation temperature range, subject to varying conditions. System has no low temperature cut out. Capacity is not tested outside of the rated temperature range.

SUBMITTAL - 12KMAS1

ACCESSORIES:

Model Number	Description
UTY-RVRU ^{*1}	KAGAMI - Touch Panel Wired Controller
UTY-RNRUZ5 ^{*1}	Touch Panel Wired Remote Controller
UTY-RHRY ^{*1}	Simple Wired Remote (Without Mode Function) - Hospitality
UTY-RSRY ^{*1}	Simple Wired Remote (With Mode Function)
UTY-TWRXZ2	Communication Kit - Wall Mount
FJ-AC-WIFI-1	Intesis Wi-Fi Device: Wired Module
FJ-IR-WIFI-1NA	Intesis IR Wireless AC Cloud Control Interface (Intesis Home app)
BM101WA	Cielo - Breez Max IR Controller w/ WiFi (Black)
BM102WA	Cielo - Breez Max IR Controller w/ WiFi (White)
UTY-VMSX	Modbus Converter
UTY-VTGX ^{*1}	Network Converter - Convert H-Series Comm. Protocol to V/J-Series Comm.
FJ-AC-485-1	Intesis - BACnet MSTP & Modbus RTU Gateway
UTY-TERX ^{*1}	External Switch Controller
UTY-TTRXZ1 ^{*1, 2}	24V Thermostat Interface
TTRXZ1-KIT ^{*1, 2}	24V Thermostat Interface Kit (UTY-TTRXZ1, UTY-WiFi Plug & 24V Transformer)
UTY-XCSXZ2	External input and output PCB
UTY-XWZX	External Wire Kit
UTY-XWZXZ5	External Connect Kit
UTY-DSGYZ2 ^{*3}	Airstage Edge Controller
UTZ-DUHGG2A	Hail Guard
UTZ-DUSHG2A	Snowhood
UTZ-DUWBG2A	Wind Baffle

NOTES:

*1 -Requires Communication kit UTY-TWRXZ2 to connect this device to IDU.


*2 -This device may not be used with any other type of controls (central controller, wire/wireless RC, WiFi adapter, BMS interface).

*3 -Connection to AIRSTAGE Cloud requires a compatible AIRSTAGE Mobile adapter connected to the IDU.

SUBMITTAL - 12KMAS1

INDOOR UNIT DIMENSIONS:


Unit: in (mm)




SUBMITTAL - 12KMAS1

OUTDOOR UNIT DIMENSIONS:

Unit: in (mm)




Top view




Side view

Front view

Side view



Bottom view



Side view (Valve part)

The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2025 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Version: 20250409A

-6 of 6-