



Submittal Data Sheet

Daikin Entra HP Ductless IDU 2 Ton

FTXB24BXVJU

FEATURES

- Titanium apatite photocatalytic air purifying filter
- Daikin Swing Compressor
- Inverter Compressor

BENEFITS

- 10 year limited parts and compressor warranty with online registration

INDOOR UNIT



OUTDOOR UNIT





Submittal Data Sheet

Daikin Entra HP Ductless IDU 2 Ton

FTXB24BXVJU

EFFICIENCY:

COOLING:		HEATING:	
SEER		HSPF	
EER		COP	

PERFORMANCE:

COOLING (Btu/Hr):		HEATING (Btu/Hr):	
Rated:(Min/Max):	21,200 (/)	47° Rated:(Min/Max):	21,200 (/)
Sensible AHRI:		17° Rated:	Add MSS
Moisture Removal (Gal/Hr):	0.7	5° Max:	Add MSS
Standard Operating Range:	50°F - 115°F	Operating Range:	5°F - 64°F
Extended Operating Range:	°F - °F	47° Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Cooling Conditions:	Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75	17° Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43

ELECTRICAL

PIPING

Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.	*208-230 / 60 / 1	Gas Connection (in):	5/8
System MCA:		Liquid Connection (in):	1/4
System MFA:		Drain Connection (in):	5/8
Compressor RLA:		Max. Interunit Piping Length (ft):	99
Outdoor fan motor FLA:		Max. Interunit Height Difference (ft):	
Outdoor fan motor W:	39.0	Refrigerant Pre-Charged Pipe Length (ft):	
Indoor fan motor FLA:		Additional Charge of Refrigerant (oz/ft):	
Indoor fan motor W:	39.0		
MCA: Min.circuit amps	MFA: Max.fuse amps	RLA: Rated load amps	
		FLA: Full load amps	W: Rated output watts



Submittal Data Sheet

Daikin Entra HP Ductless IDU 2 Ton


FTXB24BXVJU

INDOOR SPECIFICATIONS

COOLING - Airflow Rate (cfm):				HEATING - Airflow Rate (cfm):			
High:	716	Med:	605	High:	716	Med:	605
Low:	467	SuperLow:	395	Low:	467	SuperLow:	395
Sound Pressure (H/M/L/SL) (dBA): 51/44/38/34				Sound Pressure (H/M/L/SL) (dBA): 48/42/37/34			
Dimensions (HxWxD) (in):			11-11/16 x 39-9/16 x 10-3/4	Net Weight (lb):		31	

DIMENSIONAL DRAWING - INDOOR UNIT

Model : FTXB18/24B





Submittal Data Sheet


Daikin Entra HP Ductless IDU 2 Ton
FTXB24BXVJU

OUTDOOR SPECIFICATIONS

COOLING - Airflow Rate (cfm):		HEATING - Airflow Rate (cfm):	
High:	716	High:	716
SuperLow:	395	SuperLow:	395
Compressor Stage:		Refrigerant Type:	R-410A
Factory Charge (Lbs):		Refrigerant Oil:	
Sound Pressure Level (dBA):	51		
Dimensions (HxWxD) (in):	11-11/16 x 39-9/16 x 10-3/4	Net Weight (lb):	31

DIMENSIONAL DRAWING - OUTDOOR UNIT

Model : FTXB18/24B





Submittal Data Sheet

Daikin Entra HP Ductless IDU 2 Ton
FTXB24BXVJU