

Item # FRA13NY18AJ1NA, Endeavor® Line F-Series™ Series 1 1/2 ton 13.4 SEER2 Single-Stage iM Air Conditioner-208/230/1/60

- Cooling Efficiency: 13.4 SEER2 / 9 EER2
- Refrigerant Type: R-454B
- Nominal Sizes: 1.5 to 5 Tons [TBD kW]
- Cooling Capacities: 17.1 to 55.5 kBTU
- Sound Ranking¹: As low as 68 dB
- EcoNet® Enabled: No
- Compressor Type²: Single Stage
- Condenser Coil Type³: 7mm
- PlusOnes:
 - PlusOne® Expanded Valve Space: Provides a minimum working area of 27-sqaure inches
 - PlusOne Triple Service Access : 15 in. wide industry leading corner service access, two fastener removeable corner and easily removeable individual louver


[more](#)

[Specifications](#) | [Electrical Data](#) | [Outdoor Coil](#) | [Outdoor Fan](#) | [Cooling Performance](#) | [Dimensions](#) | [Features](#)

Specifications

Type	Heat Pump
Nominal Capacity	18000 Btu/h 5.28 kW 1.5 TR

Refrigerant Type	R-454B
Refrigerant Furnished oz.	64
Compressor Type	Scroll
Sound Level	70 dB
Weight	141 lb

Electrical Data

-

Voltage	208 to 230 V
Number of Phases	1
Frequency	60 Hz
Maximum Overcurrent Protection	15 A
Minimum Circuit Ampacity	12 A
Compressor - Rated Load Amps	8.3 A
Compressor - Locked Rotor Amps	45 A
Condenser Fan Motor - Full Load Amps	0.8 A
Condenser Fan Motor - Locked Rotor Amps	1.5 A

Outdoor Coil

-

Net Face Area - Outer Coil	10.9 ft ²
Tube Diameter	0.276 in
Number of Rows	1

Fins per Inch	24
----------------------	----

Outdoor Fan

Outdoor Fan Diameter	20 in
Number of Blades	2
Motor HP	1/7 hp
CFM	1765 ft ³ /min
RPM	1075
Watts	154 W

Cooling Performance

Air Handler	RCFY2417STAN
Total Capacity	17100 Btu/h 5 kW
Net Sensible Capacity	13100 Btu/h 3.8 kW
Net Latent Capacity	4000 Btu/h 1.2 kW
SEER2	13.4
EER2	9.0
Indoor CFM	1600 ft ³ /min 283.2 L/s

Dimensions

Depth	29.75 in 756 mm
--------------	--------------------

Width	29.75 in 756 mm
Height	25.00 in 635 mm
Shipping Depth	32.38 in 822 mm
Liquid Line O.D.	3/8 in
Suction Line O.D.	3/4 in

Features

- **7mm Condenser Copper Coil:** Requires less refrigerant allowing for a smaller and lighter footprint while enhancing reliability
- **PlusOne® Expanded Valve Space:** 3 in. – 4 in. – 5 in. service valve space – provides a minimum working area of 27-square inches for easier access
- **PlusOne® Triple Service Access:** 15 in. wide, industry leading corner service access, two fastener, removeable corner and individual louver panels – makes repairs easier and faster
- **Designing for Sustainability with Low GWP:** For 2025, the Environmental Protection Agency (EPA) has set a global warming potential (GWP) limit of 700 for refrigerant used in heating and cooling systems. This new requirement will result in a 78%2 lower GWP than previous-generation refrigerants — with only minimal changes to system installation. For us, this is another step toward our continued sustainability goal of reducing greenhouse gas emissions, while still delivering an exceptional level of energy efficient, dependable comfort
- **PlusOne® Refrigerant Detection System™3:** An integrated one-box, patented design featuring the A2L sensor and mitigation board, offering easier commissioning with a single component and simplified wiring configuration, compatibility with any 24V thermostat application and system protection by automatically pausing outdoor unit operation — if excess refrigerant is detected