

Job Name

Purchaser

Submitted to

Unit Designation

Location

Engineer

Reference

Schedule #

Approval

Construction

Specifications			
Model	US Code		RNS07CPC
	Model Number		AR07CSKCPWKNCV
Performance	Nominal Capacity	Cooling (Btu/h)	7,000
		Heating (Btu/h)	7,500
Power	Voltage	ø / V / Hz	1 / 208-230 / 60
	Operating Current (Max.)	Cooling (A)	0.3
		Heating (A)	0.3
	Type	BLDC motor with cross-flow fan	
Evaporator Fan	Consumption	Watts	27
	FLA	Amps	0.12
Airflow	Air Volume (L/M/H/Turbo)	Cooling (CFM)	309 / 322 / 336 / 350
		Heating (CFM)	340 / 354 / 368 / 381
Refrigerant	Type	R410A	
	Control Method	Electronic Expansion Valve	
Pipe Connections	Indoor & Outdoor	High side (flare)	1/4"
		Low side (flare)	3/8"
	Condensate Connection		11/16" OD
Dimensions	W X H X D (in.)	Indoor Unit	32-5/16 x 13-9/16 x 8-7/16
	Weight (lbs.)	Indoor Unit	20.1
Sound Pressure Level	Low / High	dB(A)	23 / 37
Accessories	Wired Controllers	Advanced	MWR-WG00UN
		Simple Touch	MWR-SH11UN
	Wired Controller Sub-PCB		MIM-A00UN
	24VAC Thermostat Adapter		MIM-A60UN
	Condensate Pump	Aspen Mini Orange	ASP-MO-UNIV 110-250
		Blue Diamond	BD-BLUE-230
	External Temperature Sensor		MRW-TA
	External Contact Control Card Interface		MIM-B14
Safety	Certifications	UL 60335-2-40	



- General Information
- The indoor unit shall feature WindFree™ mode. In cooling mode, as room temperature nears set temperature, the unit will close its louver and will disperse air into the space through thousands of micro-holes on the front of the indoor unit preventing cold air drafts on occupants.
 - The indoor unit shall be capable of sensing dust particulate matter in the air stream, and displaying the appropriate measured data on the unit's display.
 - The indoor unit shall have Wi-Fi capability as standard.
 - The indoor unit shall be powered by the outdoor unit.

- Construction
- Indoor unit chassis shall be UL94 V0 with a galvanized steel mounting bracket
 - The indoor unit shall have easy-access to wire, pipe, and drain connections via access panel on the bottom of the unit for simple installation and service
 - The indoor unit shall include a factory installed electrostatic precipitator capable of breaking down dust and particulate matter as small as 0.3 microns.

- Heat Exchanger
- The heat exchanger shall be mechanically bonded fin to copper tube

- Indoor Fan
- The indoor fan shall be a single, antibacterial cross-flow type
 - Three fan speed settings and auto setting
 - Automatic (motorized) vertical swing (up/down) and horizontal swing (left/right) louvers

- Controls
- The system shall have a built in Wi-Fi adapter as standard to allow control and monitoring using the Samsung SmartThings app (Android, iOS)
 - Dual set temperature support when connected to MWR-WG00UN Advanced Wired Controller.
 - The indoor unit shall have a simple connection for overflow detection devices or any other normally closed contact for simple unit shutdown
 - The indoor unit shall ship with a wireless controller, holder, and batteries
 - Wired controller options available
 - Interconnect control wire between outdoor and indoor unit shall be 16AWG X 2

- Convenience
- System energy consumption can be viewed using the Samsung SmartThings mobile app or on the indoor unit display using the included wireless controller**
 - Measured indoor-air-quality can viewed using the Samsung SmartThings mobile app, allowing the AI Purify mode to automatically run the Purify mode when indoor air quality is low.
 - Auto Clean Function
 - 7-segment digital display on front of unit to display temperature and unit status
 - Auto changeover
 - Good Sleep mode
 - Quiet mode
 - Dry mode
 - Purify mode
 - Simple ON/OFF time function – Using the wireless controller specify the ON and/or OFF times
 - Electro-static, washable, main filter as standard accessible from the top of unit
 - Filter cleaning reminder

- Compatibility
- Refer to the FJM outdoor unit submittal data or technical data book for complete compatibility listings.

*The WindFree™ unit delivers an air current that is under 0.15 m/s while in WindFree™ mode. Air velocity that is below 0.15 m/s is considered "still air" as defined by ASHRAE (American Society of Heating, Refrigerating, and Air Conditioning Engineers).

**For reference only; not revenue grade.

¹Sub-PCB model MIM-A00UN is required when connecting optional wired controllers or MIM-A60UM 24VAC thermostat adapter.

²When applying MIM-B14 external contact control interface module, MIM-A00UN wired controller sub-PCB is required.

Samsung HVAC maintains a policy of ongoing development. Specifications are subject to change without notice. Refer to www.AHRIdirectory.org for current reference numbers.

Unit: inches

